

Department of Electronics & Telecommunication Engineering

CLASS : B.E. E &TC SUBJECT: DIVP

EXPT. NO. : 6 DATE:27-11-2020

TITLE : TO PERFORM IMAGE COMPRESSION USING DCT/DWT

CO 1:	Apply the fundamentals of digital image processing to perform various
	operations on an image-enhancement in spatial domain/ frequency domain,
	image-restoration, image compression, video filtering and video compression
	on a given gray image. Examine the effect of varying the mask size and density
	of noise in an image and comment on the obtained results.
CO4:	Carry out experiments as an individual and in a team, comprehend and write a
	laboratory record and draw conclusions at a technical level.

AIM:

- 1. To apply Discrete Cosine Transform (DCT) on an image.
- 2. Reconstruct the image by taking Inverse Discrete Cosine Transform (IDCT).
- 3. Perform DCT based quantization on given 8X8 Matrix.

SOFTWARE REQUIREMENT: Matlab 7.0 or above, python

6.1THEORY:

6.1.1 Discrete Cosine Transform

In transform coding, a reversible, linear transform like DFT or the discrete cosine transform (DCT) is used to map an image into a set of transform coefficients, which are then quantized and coded for most natural images, a significant number of



Department of Electronics & Telecommunication Engineering

coefficient have small magnitudes and can be coarsely quantized with a little image distortion.

DCT is a child of DFT, only cosine terms are taken.

• 1D DCT is given by,

$$C(u) = \begin{array}{c} N\text{-}1 \\ C(u) = \alpha(u) \ \Sigma \ f(x) \ . \ cos[(2x+1)u \ \Pi/2N] \\ x{=}0 \end{array}$$

• 1D IDCT is given by,

$$\begin{array}{c} N\text{-}1 \\ f(x) = \ \alpha(u) \ \ \Sigma \ C(u) \ . \ cos[(2x+1)u \ \Pi/2N] \\ u = 0 \end{array}$$

where,
$$\alpha$$
 (u) = sqrt(1/N)for u = 0
= sqrt(2/N)for u = 1,2,...,N-1

Image is a two dimensional signal f(x, y), hence in order to find DCT of an image DCT must be applied in the 2 directions x and y.

• 2D DCT is given by,

$$C(u,v) = \begin{array}{ccc} & N\text{-}1 & N\text{-}1 \\ C(u,v) = & \alpha(u) & \alpha(v) & \sum \Sigma & f(x,\,y) \;.\; cos[(2x+1)u \;\Pi/2N] \;.\; cos[(2y+1)v\Pi/2N] \\ & & x\text{=}0 & y\text{=}0 \end{array}$$

• 2D IDCT is given by,

$$f(x,y) = \begin{array}{c} N\text{-}1 & N\text{-}1 \\ \Sigma & \Sigma & \alpha(u) \ . \ \alpha(v) \ . \ C(u,\,v) \ . \ cos[(2x+1)u\ \Pi/2N] \ . \ cos[(2y+1)v\ \Pi/2N] \\ u=0 & v=0 \\ \end{array}$$
 where,

$$\alpha(u) = \text{sqrt}(1/N) \dots \text{for } u = 0$$

= $\text{sqrt}(2/N) \dots \text{for } u = 1,2,\dots,N-1$
 $\alpha(v) = \text{sqrt}(1/N) \dots \text{for } v = 0$
= $\text{sqrt}(2/N) \dots \text{for } v = 1,2,\dots,N-1$



Department of Electronics & Telecommunication Engineering

Consider an image f(x, y) of size $M \times N$, it is subdivided into sub-images of sub-size $n \times n$ and DCT of these sub-images is found out. The DCT of the sub-image is obtained by using the above formula.

6.1.2 Quantization:

Our 8*8 block of DCT coefficients is now ready for compression by quantization. A remarkable and highly useful feature of the JPEG process is that in every step, varying levels of image compression and quality are obtainable through selection of specific quantization matrices. This enables the user to decide on quality levels ranging from 1 to 100, where 1 gives the poorest image quality and highest compression. As a result, the quality/compression ratio can be tailored to suit different needs. Subjective experiments involving the human visual system have resulted in the JPEG standard quantization matrix. With a quality level of 0, this matrix renders both high compression and excellent decompressed image quality.

6.1.3 Advantages:

- Transform co-efficient are relatively uncorrelated.
- Energy is highly compacted.
- Reasonable robust relative to channel error.
- There is no loss in the data.

6.1.4 Disadvantages:

While the DCT-based image coders perform very well at moderate bit rates, at higher compression ratios, image quality degrades because of the artifacts resulting fro the block based DCT scheme.



6.1.5 Applications:

The DCT is used in JPEG image compression, MPEG, DV and Theora video compression. DCT is also widely used in signal and image processing, especially for lossy data compression, because it has a strong energy function.

6.2 Algorithm:

6.2.1 Algorithm for part A:

- 1. Start.
- 2. Read an image and divide it in 8x8 blocks.
- 3. Apply 2D DCT formula on each block, resultant image is DCT of image.
- 4. Divide DCT image into 8x8 blocks.
- 5. Apply 2D IDCT formula on each block, resultant image is recovered image.
- 6. Stop.

6.2.2 Algorithm for part B:

- 1. Start.
- 2. Take 8X8 Matrix.
- 3. Leveled off the matrix by subtracting 128 from each entry. (Matrix M)
- 4. Obtain DCT of above matrix by using the 2D DCT formula. (Matrix D)
 - a. Obtain the coefficient matrix by using formula

$$T_{i,j} = \left\{ \begin{array}{ll} \frac{1}{\sqrt{N}} & \text{if } i = 0\\ \sqrt{\frac{2}{N}} \cos \left[\frac{(2j+1)i\pi}{2N} \right] & \text{if } i > 0 \end{array} \right\}$$
 (Matrix T).

- b. Obtain DCT Matrix, D = TMT'.
- 5. Select Quantization level, and initialize standard Q matrix. (Matrix Q)
- 6. Obtain Quantization by dividing each element in the transformed image matrix D



Department of Electronics & Telecommunication Engineering

by the corresponding element in the Q matrix. And rounding off to the nearest integer value. (This is quantized matrix can be further coded).

$$C(i,j) = \text{round}(D(i,j) / Q(i,j));$$

- 7. For Decompression, $R(i, j) = Q(I, j) \times C(i, j)$
- 8. Obtain the IDCT of above matrix, and round off it to the nearest integer value.
- 9. Add 128 to each element.
- 10. Compare original and recover image.

(Note: If the M x N size image has to be compressed, divide the image into 8x8 blocks and repeat the above procedure for each block.)



Department of Electronics & Telecommunication Engineering

6.3 Conclusion:

- The discrete cosine transform (DCT) is lossless technique which helps to separate the image into parts (or spectral sub-bands) of differing importance (with respect to the image's visual quality
- The DCT can be used to convert the signal (spatial information) into numeric data ("frequency" or "spectral" information) so that the image's information exists in a quantitative form that can be manipulated for compression.
- DCT is majorly used for compression of data.
- With higher bit rates, image quality gets degraded with DCT.

6.4 References:

- i. Gonzalez R, Woods R, "Digital image processing", Pearson Prentice Hall, 2008.
- ii. Gonzalez R, Woods R, Steven E, "Digital Image Processing Using MATLAB®", McGraw Hill Education, 2010.
- Jayaraman S, Esakkirajan S and Veerakumar T, "Digital Image Processing" Tata McGraw Hill,
 2010
- iv. Joshi, Madhuri A. "Digital Image Processing: an algorithm approach", PHI Learning Pvt. Ltd., 2006.
- v. Pictures taken from:
 http://www.imageprocessingplace.com/root_files_V3/image_databases.html

(Course Teacher)



Department of Electronics & Telecommunication Engineering

CLASS : B.E (E &TC) COURSE : DIVP

AY : 2020-21 (SEM- I) DATE : 27-11-2020

EXPT. NO. : 6 CLASS & ROLL NO : BE VIII 42428

TITLE : TO PERFORM IMAGE COMPRESSION USING DCT/DWT


I. CODE:

plt.show()


```
from cv2 import cv2
import numpy as np
from matplotlib import pyplot as plt
# Reading the input image
img = cv2.imread('Images/hibiscus.tif', 0)
imf = np.float32(img)/255.0 # float conversion/scale
dct1 = cv2.dct(imf)
                            # the dct
dct = np.uint8(dct1*255.0) # convert back to int
idct = cv2.idct(dct1)
                          # take idct
error = imf - idct
idct = np.uint8(idct*255.0) #convert back to int
error = np.uint8(error*255.0)
plt.subplot(2, 3, 1),plt.imshow(img, 'gray'),plt.title('Original Image')
plt.subplot(2, 3, 2),plt.imshow(dct, 'gray'),plt.title('DCT of Image')
plt.subplot(2, 3, 3),plt.imshow(idct, 'gray'),plt.title('IDCT of Image')
plt.subplot(2, 3, 4), plt.hist(img.ravel(),256,[0,256]),plt.title('Histogram of Original Image')
plt.subplot(2, 3, 5), plt.hist(dct.ravel(),256,[0,256]),plt.title('Histogram of DCT of Image')
plt.subplot(2, 3, 6), plt.hist(idct.ravel(),256,[0,256]),plt.title('Histogram of IDCT of Image')
plt.show()
plt.imshow(error, cmap=plt.cm.gray)
plt.title("Error between original and after taking IDCT")
```




II. RESULTS:




Histogram of Original Image



















ERROR

