

Activity 1:

List three tasks you perform regularly that involve repetition. For each:

1. What is being repeated?
2. What determines when it stops?

Algorithm :

1. Start the program.
2. Create a Scanner object to accept user input.
3. Prompt the user: "Enter how many minutes you want to brush your teeth:"
4. Read the input value and store it in totalMinutes.
5. Initialize minutesBrushed to 0.
6. While minutesBrushed is less than totalMinutes:
7. Display: "Brushing teeth... minute (minutesBrushed + 1)"
8. Increment minutesBrushed by 1.
9. After the loop ends, display "Done brushing!".
10. End the program

Pseudo code :

```
START
Prompt the user to enter the number of minutes to brush
Read the user input and store it as totalMinutes
Set minutesBrushed = 0
WHILE minutesBrushed < totalMinutes DO
    Display "Brushing teeth... minute (minutesBrushed + 1)"
    Increment minutesBrushed by 1
END WHILE
Display "Done brushing!"
END
```

Code :

```
import java.util.Scanner;
```

```

public class BrushingTeeth {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        System.out.print("Enter how many minutes you want to brush your teeth: ");
        int totalMinutes = scanner.nextInt();

        int minutesBrushed = 0 ;

        while (minutesBrushed < totalMinutes) {
            System.out.println("Brushing teeth... minute " + (minutesBrushed + 1));
            minutesBrushed++;
        }

        System.out.println("Done brushing!");
    }
}

```

```

TC2 : public class TypingPractice {
    public static void main(String[] args) {
        int linesTyped = 0;
        int maxLines = 10;

        while (linesTyped < maxLines) {
            System.out.println("Typing practice line " + (linesTyped + 1));
            linesTyped++;
        }

        System.out.println("Typing practice complete!");
    }
}

```

| Test cases | Input | Expected Out put |
|------------|--------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TC1 | Enter how many minutes you want to brush your teeth: 2 | <div>Output</div> <pre> Enter how many minutes you want to brush your teeth: 2 Brushing teeth... minute 1 Brushing teeth... minute 2 Done brushing! </pre> |

| | | |
|-----|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TC2 | Enter how many mails : 5 | <div>Output</div> <pre> Reading email 5 Reading email 4 Reading email 3 Reading email 2 Reading email 1 All emails read! </pre> |
| TC3 | | <div>Output</div> <pre> Typing practice line 1 Typing practice line 2 Typing practice line 3 Typing practice line 4 Typing practice line 5 Typing practice line 6 Typing practice line 7 Typing practice line 8 Typing practice line 9 Typing practice line 10 Typing practice complete! </pre> |

Observation : This program simulates the real-life task of brushing teeth based on user-defined duration. It uses a while loop to repeat the brushing action for the number of minutes specified. The user can input any valid integer to customize the brushing duration. The output shows each minute of brushing and ends with a confirmation message. This demonstrates the use of loops, user input, and counters in Java programming.

Activity 2:

Write a Java program that prints the word "Hello!" ten times without using a loop.
After writing the code, reflect on:

What would happen if you had to print "Hello!" 1000 times instead?
Would you still write every line manually?

Algorithm :

Start the program.

Use `System.out.println()` to print "Hello!" ten times.

End the program

Pseudo code :

START
Print "Hello!"
END

Code :

```
public class HelloPrinter {  
    public static void main(String[] args) {  
        System.out.println("Hello!");  
    }  
}
```

For loop :

```
import java.util.Scanner;
```

```
public class HelloPrinter {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
  
        System.out.print("Enter how many times to print 'Hello!': ");  
        int times = scanner.nextInt();  
        if (times <= 0) {  
            System.out.println("Please enter a positive number.");  
        } else {
```

```
        for (int i = 1; i <= times; i++) {
            System.out.println("Hello!");
        }
    }

    scanner.close(); // Close scanner
}
}
```

[illegible]

Observation : The code successfully prints "Hello! " ten times without using loops.

However, the code becomes repetitive and long.

If the task was to print 100 or 1000 times, writing each line manually would be:

Time-consuming

Hard to read and maintain

Not scalable

In real-world scenarios, we should use loops (for, while) to handle such repetition efficiently. This activity highlights why loops are important in programming to avoid code duplication.

SECTION 1

Problem Statement 1:

Print numbers from 10 to 1, then print "Blastoff!"

Algorithm :

Start the program.

Initialize a loop variable *i* with value 10.

Repeat while *i* is greater than or equal to 1:

- a. Print the value of *i*.
- b. Decrease *i* by 1.

After the loop ends, print "Blastoff!".

End the program.

Pseudo code :

```
START
FOR i from 10 down to 1 DO
PRINT i
END FOR
PRINT "Blastoff!"
END
```

Code :

```
public class Countdown {
    public static void main(String[] args) {
        for (int i = 10; i >= 1; i--) {
            System.out.println(i);
        }
        System.out.println("Blastoff!");
    }
}
```

| Test cases | Input | Expected Out put |
|------------|-----------------|----------------------------------------------------|
| TC1 | Input : from 10 | <pre> Output 10 9 8 7 6 5 4 3 2 1 Blastoff! </pre> |
| TC2 | Input : 5 | <pre> Output 5 4 3 2 1 Blastoff! </pre> |
| TC3 | Input : 0 | <pre> Output Blastoff! </pre> |

Observation : The program uses a for loop to print numbers from 10 to 1 in descending order. After the countdown, it prints "Blastoff!" to simulate a rocket launch. This demonstrates control flow using loops, particularly counting in reverse. The program is simple and effective for teaching loop decrementing (`i--`).

Problem Statement 2 :

Ask the user to enter numbers repeatedly. Keep adding them until the user enters 0. Then print the total sum.

Algorithm :

1. Start the program.
2. Declare variables sum and number.
3. Set sum = 0.
4. Use a do-while loop:
5. Prompt the user to enter a number.
6. Read the number into number.
7. Add the number to sum.
8. Repeat the loop until the number is 0.
9. After exiting the loop, display the value of sum.
10. End the program.

Pseudo code :

```
START
Initialize sum = 0
REPEAT
Prompt user to enter a number (0 to stop)
Read number
Add number to sum
UNTIL number is 0
Display total sum
END
```

Code :

```
import java.util.Scanner;

public class SumUntilZero {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int number, sum = 0;
```

```

do {
    System.out.print("Enter a number (0 to stop): ");
    number = scanner.nextInt();
    sum += number;
} while (number != 0);

System.out.println("Total sum: " + sum);
}
}

```

| Test cases | Input | Expected Out put |
|------------|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TC1 | Enter a number (0 to stop): 5 Enter a number (0 to stop): 2 Enter a number (0 to stop): 5 Enter a number (0 to stop): 0 | <div>Output</div> <pre> Enter a number (0 to stop): 5 Enter a number (0 to stop): 2 Enter a number (0 to stop): 5 Enter a number (0 to stop): 0 Total sum: 12 </pre> |
| TC2 | Enter a number (0 to stop): -10 Enter a number (0 to stop): 10 Enter a number (0 to stop): 0 | <div>Output</div> <pre> Enter a number (0 to stop): -10 Enter a number (0 to stop): 10 Enter a number (0 to stop): 0 Total sum: 0 </pre> |
| TC3 | Enter a number (0 to stop): 0 | <div>Output</div> <pre> Enter a number (0 to stop): 0 Total sum: 0 </pre> |

Observation :

The program accepts numbers from the user continuously. The loop runs at least once, which is why `do-while` is appropriate. When the user enters 0, the loop stops. The program then displays the sum of all numbers entered (excluding the zero). This demonstrates: Input handling, Use of loops, Basic accumulator pattern

Problem Statement 3 :

Generate a random number between 1 and 10. Ask user to guess until correct.

Algorithm :

Start the program.

Create a Scanner object to read user input.

Ask User 1 to enter a secret number between 1 and 10

Display a message to pass the game to User 2.

Start a loop:

- Ask User 2 to guess the number.
- If the guess is lower than the secret number, print "Too low!"
- If the guess is higher than the secret number, print "Too high!"
- If the guess is equal, print "Correct!"

Repeat until the correct number is guessed

End the program.

Pseudo code :

START

Create scanner

Prompt user to enter secret number

Store it in secretNumber

PRINT "Pass to your friend"

REPEAT

 Prompt user to guess number

 Read guess

 IF guess < secretNumber

 PRINT "Too low!"

 ELSE IF guess > secretNumber

 PRINT "Too high!"

 ELSE

```
PRINT "Correct!"
UNTIL guess == secretNumber
END
```

Code :

```
import java.util.Scanner;

public class GuessNumber {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        System.out.print("Enter the secret number (1 to 10): ");
        int secretNumber = scanner.nextInt();

        System.out.println("\nNow pass the game to your friend to guess!\n");
        int userGuess;
        do {
            System.out.print("Guess the number (1 to 10): ");
            userGuess = scanner.nextInt();

            if (userGuess < secretNumber) {
                System.out.println("Too low!");
            } else if (userGuess > secretNumber) {
                System.out.println("Too high!");
            } else {
                System.out.println("Correct! ");
            }
        } while (userGuess != secretNumber);
    }
}
```

| Test cases | Input | Expected Out put |
|------------|----------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TC1 | Enter a number (0 to stop): 5 Enter a number (0 to stop): 2 Enter a number (0 to stop): 5 Enter a number (0 to stop): 0 | <pre> Output Enter the secret number (1 to 10): 5 Now pass the game to your friend to guess! Guess the number (1 to 10): 4 Too low! Guess the number (1 to 10): 6 Too high! Guess the number (1 to 10): 5 Correct! ? </pre> |
| TC2 | Enter a number (0 to stop): -10 Enter a number (0 to stop): 10 Enter a number (0 to stop): 0 | <pre> Output Enter the secret number (1 to 10): -10 Now pass the game to your friend to guess! Guess the number (1 to 10): 20 Too high! Guess the number (1 to 10): 0 Too high! Guess the number (1 to 10): -1 Too high! Guess the number (1 to 10): -11 Too low! Guess the number (1 to 10): -10 Correct! </pre> |
| TC3 | Enter a number (0 to stop): 2 | <pre> Output Enter the secret number (1 to 10): 2 Now pass the game to your friend to guess! Guess the number (1 to 10): 2 Correct! </pre> |

Observation :

This is a two-player guessing game: Player 1 sets the number. Player 2 tries to guess it. The loop continues until the guess is correct. It uses a do-while loop because at least one guess is required. This version is great for practicing: Input/output, Loops, Conditional statements

Problem Statement 4 :

Infinite loop debugging : analyze and fix

```
Int count = 0;
```

```
While (count < 5)
```

```
{
```

```
system.out.print ln("Hello");
```

```
}
```

Algorithm :

- Start the program.
- Create a Scanner object to read input.
- Ask the user: "How many times do you want to print 'Hello'?"
- Store the input in variable times
- Initialize counter to 0
- While counter is less than times:
 Print "Hello"
 Increase counter by 1
 After loop ends, close the Scanner.
- End the program.

Pseudo code :

START

Create Scanner for input

Prompt user for number of times to print "Hello"

Read the number and store in variable 'times'

Set counter to 0

WHILE counter is less than times

 PRINT "Hello"

 INCREMENT counter

CLOSE Scanner

END

Code :

```
import java.util.Scanner;

public class UserInputLoop {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        System.out.print("How many times do you want to print 'Hello': ");
        int times = scanner.nextInt();

        if (times < 0) {
            System.out.println("Invalid input!");
        } else {
            int counter = 0;

            while (counter < times) {
                System.out.println("Hello");
                counter++;
            }
        }

        scanner.close();
    }
}
```

| Test cases | Input | Expected Out put |
|------------|------------------------------------------------|-------------------------------------------------------------------------------------------------|
| TC1 | How many times do you want to print 'Hello': 2 | <div>Output How many times do you want to print 'Hello': 2 Hello Hello</div> |

| | | |
|-----|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| TC2 | How many times do you want to print 'Hello': -1 | <pre> Output How many times do you want to print 'Hello': -1 Invalid input! Please enter a positive number. </pre> |
| TC3 | How many times do you want to print 'Hello': 0 | <pre> Output How many times do you want to print 'Hello': 0 </pre> |

Observation :

This program prints "Hello" a user-defined number of times. It uses a while loop, which checks the condition before each execution. The use of counter++ is important to avoid an infinite loop. Demonstrates basic programming concepts: User input (Scanner), Loops (while), Condition checking. The program is dynamic: the user controls how many times the output is printed. If the user enters 0, the loop won't run at all.

Section 2:

Problem Statement 5 :

Print even numbers from 2 to 20 using a for loop.

Algorithm :

Start the program.

Create a Scanner object to take input from the user.

Ask the user to enter a maximum number (should be ≥ 2).

Store the input in a variable called max.

Check if max is less than 2:

- If true, print "Invalid input!"
- Else, do the following:
 - Print a message: "Even numbers from 2 to max:"
 - Use a for loop starting from 2 up to max with step size 2.
 - Print each value of i during the loop.

Close the Scanner.

End the program.

Pseudo code :

START

Create a scanner to read user input

Prompt user to enter a maximum number (≥ 2)

Read the number into variable 'max'

IF max < 2 THEN

 PRINT "Invalid input!"

ELSE

 PRINT "Even numbers from 2 to max"

 FOR i from 2 to max, incrementing by 2

 PRINT i

 END IF

Close scanner
END

Code :

```
import java.util.Scanner;

public class EvenNumbers {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        System.out.print("Enter the maximum number (>= 2): ");
        int max = scanner.nextInt();

        if (max < 2) {
            System.out.println("Invalid input! Please enter a number greater than or equal to 2.");
        } else {
            System.out.println("Even numbers from 2 to " + max + ":");
            for (int i = 2; i <= max; i += 2) {
                System.out.println(i);
            }
        }

        scanner.close();
    }
}
```

| Test cases | Input | Expected Out put |
|------------|-------|------------------|
|------------|-------|------------------|

| | | |
|-----|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| TC1 | Enter the maximum number (>= 2): 20 | <div>Output</div> <pre> Enter the maximum number (>= 2): 20 Even numbers from 2 to 20: 2 4 6 8 10 12 14 16 18 20 </pre> |
| TC2 | Enter the maximum number (>= 2): 14 | <div>Output</div> <pre> Enter the maximum number (>= 2): 14 Even numbers from 2 to 14: 2 4 6 8 10 12 14 </pre> |
| TC3 | Enter the maximum number (>= 2): -15 | <div>Output</div> <pre> Enter the maximum number (>= 2): -15 Invalid input! Please enter a number greater than or equal to 2. </pre> |

Observation :

This program demonstrates input validation for numeric limits. It ensures the user cannot proceed with a number less than 2. The use of a for loop with `i += 2` makes it efficient to directly print even numbers without additional condition checks. The program is simple and interactive, suitable for beginners learning loops and conditions. If the user enters a valid number (e.g. 10), it prints: 2 4 6 8 10. If the user enters a number like 1 or -5, it immediately responds with an error message.

Problem Statement 6 :

Calculate $n!$ for a user-input number n . Handle the edge case when $n == 0$ (since $0! = 1$).

Algorithm :

1. Start the program.
2. Create a Scanner object to read user input.
3. Ask the user to enter a number.
4. Store the number in variable n .
5. Check if n is less than 0:
 - a. If yes, print: "Factorial is not defined for negative numbers."
 - b. If no:
 - i. Initialize a variable `factorial` to 1.
 - ii. Loop from $i = 1$ to $i \leq n$, multiply `factorial` by i on each iteration.
 - iii. After the loop ends, print the value of `factorial`.
6. Close the scanner.
7. End the program.

Pseudo code :

```
START
Create a scanner to read user input
Prompt user to enter a maximum number ( $\geq 2$ )
Read the number into variable 'max'
IF max < 2 THEN
    PRINT "Invalid input!"
ELSE
    PRINT "Even numbers from 2 to max"
    FOR i from 2 to max, incrementing by 2
        PRINT i
    END IF
Close scanner
END
```

Code :

```
import java.util.Scanner;

public class FactorialCalculator {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        System.out.print("Enter a number to calculate its factorial: ");
        int n = scanner.nextInt();
        if (n < 0) {
            System.out.println("Factorial is not defined for negative numbers.");
        } else {
            long factorial = 1;
            for (int i = 1; i <= n; i++) {
                factorial *= i;
            }

            System.out.println("Factorial of " + n + " is: " + factorial);
        }

        scanner.close();
    }
}
```

| Test cases | Input | Expected Out put |
|------------|----------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| TC1 | Enter a number to calculate its factorial: 3 | <div>Output</div> <div>Enter a number to calculate its factorial: 3 Factorial of 3 is: 6</div> |
| TC2 | Enter a number to calculate its factorial: 0 | <div>Output</div> <div>Enter a number to calculate its factorial: 0 Factorial of 0 is: 1</div> |

| | | |
|-----|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| TC3 | Enter a number to calculate its factorial: -1 | Output Enter a number to calculate its factorial: -1 Factorial is not defined for negative numbers. |
|-----|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------|

Observation :

This program calculates the factorial ($n!$) of a non-negative integer using a for loop. It correctly handles edge cases: For $n = 0$, the result is 1 (as $0! = 1$). For $n < 0$, it prints an error message. The result is stored in a long variable to support larger outputs. It's a good example of: Input handling, Looping, Conditional logic, Basic error checking

If the user enters 5, the output will be:

Factorial of 5 is: 120

Problem Statement 7 :

Ask for a string input. Count how many times 'a' or 'A' appears.

Algorithm :

8. Start the program.
9. Create a Scanner object to take string input from the user.
10. Prompt the user to enter a string and store it in a variable called input.
11. Initialize a variable count to 0.
12. Use a for loop to iterate through each character in the string:
13. Extract the character at the current position.
14. Check if the character is 'a' or 'A'.
15. If yes, increment count by 1.
16. After the loop ends, print the total count of 'a' and 'A'.
17. Close the scanner.
18. End the program.

Pseudo code :

```
START
Create Scanner to read user input
PRINT "Enter a string:"
READ string into variable 'input'
SET count = 0
FOR i from 0 to length of input - 1
SET ch = character at position i
IF ch == 'a' OR ch == 'A'
INCREMENT count by 1
END FOR
PRINT "Number of 'a' or 'A' in the string: " + count
CLOSE scanner
END
```

Code :

```
import java.util.Scanner;

public class CountA {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        System.out.print("Enter a string: ");
        String input = scanner.nextLine();

        int count = 0;

        for (int i = 0; i < input.length(); i++) {
            char ch = input.charAt(i);

            if (ch == 'a' || ch == 'A') {
                count++;
            }
        }

        System.out.println("Number of 'a' or 'A' in the string: " + count);

        scanner.close();
    }
}
```

| Test cases | Input | Expected Out put |
|------------|---------------------|---------------------------------------------------------------------------------------------------|
| TC1 | Enter a string: raj | <div>Output</div> <div>Enter a string: raj Number of 'a' or 'A' in the string: 1</div> |

| | | |
|-----|--------------------------|------------------------------------------------------------------------------------|
| TC2 | Enter a string: hgajky12 | <pre> Output Enter a string: hgajky12 Number of 'a' or 'A' in the string: 1 </pre> |
| TC3 | Enter a string: data | <pre> Output Enter a string: data Number of 'a' or 'A' in the string: 2 </pre> |

Observation :

This program counts how many times the letter 'a' or 'A' appears in a user-entered string. It works by: Looping through each character in the string. Using `charAt(i)` to access each character. Comparing each character to 'a' and 'A'. It uses case-insensitive checking for just one letter. The logic is efficient for small and large strings.

Problem Statement 8 :

Print a single line with five stars (*), using one for loop.

Algorithm :

- Start the program.
- Create a Scanner object to read user input.
- Prompt the user to enter the number of stars (n).
- Store the input in variable n.
- Check if $n \leq 0$
- If true, print "Invalid input! Please enter a positive number."
- Else:
- Run a for loop from $i = 1$ to $i \leq n$:
In each iteration, print a * on the same line.
After the loop, print a newline to finish the output nicely.
- Close the scanner.
End the program.

Pseudo code :

START

Create Scanner to take input from user

PRINT "Enter the number of stars to print: "

READ integer n

IF $n \leq 0$ THEN

PRINT "Invalid input! Please enter a positive number."

ELSE

FOR i from 1 to n

PRINT "*" (on same line)

END FOR

PRINT newline

END IF

Code :

```
import java.util.Scanner;

public class StarPattern {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        System.out.print("Enter the number of stars to print: ");
        int n = scanner.nextInt();

        if (n <= 0) {
            System.out.println("Invalid input! Please enter a positive number.");
        } else {
            for (int i = 1; i <= n; i++) {
                System.out.print("*");
            }
            System.out.println(); // Move to next line after printing stars
        }

        scanner.close();
    }
}
```

| Test cases | Input | Expected Out put |
|------------|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| TC1 | Enter the number of stars to print: 2 | <div>Output</div> <div>Enter the number of stars to print: 2 **</div> |
| TC2 | Enter the number of stars to print: 0 | <div>Output</div> <div>Enter the number of stars to print: 0 Invalid input! Please enter a positive number.</div> |

| | | |
|-----|----------------------------------------|-----------------------------------------------------------------------------------------------------------|
| TC3 | Enter the number of stars to print: -1 | Output Enter the number of stars to print: -1 Invalid input! Please enter a positive number. |
|-----|----------------------------------------|-----------------------------------------------------------------------------------------------------------|

Observation :

The program prints n number of asterisks (*) on the same line. It performs input validation: Only accepts positive integers if a negative number or 0 is entered, it prints an error message. Useful concepts demonstrated: Scanner for input, if-else for input validation, for loop for repetition, System.out.print() vs System.out.println()

Section 3 :

Problem Statement 9 :

Check if a number is prime using a loop and break

Algorithm :

Start the program.

Create a Scanner object to read user input.

Prompt the user to enter the number of stars (n).

Store the input in variable n.

Check if $n \leq 0$:

If true, print "Invalid input! Please enter a positive number."

Else:

Run a for loop from $i = 1$ to $i \leq n$:

In each iteration, print a * on the same line

After the loop, print a newline to finish the output nicely.

Close the scanner.

End the program

Pseudo code :

START

Create Scanner to take input from user

PRINT "Enter the number of stars to print: "

READ integer n

IF $n \leq 0$ THEN

PRINT "Invalid input! Please enter a positive number."

ELSE

FOR i from 1 to n

PRINT "*" (on same line)

END FOR

PRINT newline

END IF

CLOSE scanner

END

Code :

```
import java.util.Scanner;

public class SimplePrimeCheck {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        System.out.print("Enter a number: ");
        int num = scanner.nextInt();
        boolean isPrime = true;

        if (num <= 1) {
            isPrime = false;
        } else {
            for (int i = 2; i < num; i++) {
                if (num % i == 0) {
                    isPrime = false;
                    break;
                }
            }
        }

        if (isPrime) {
            System.out.println(num + " is a prime number.");
        } else {
            System.out.println(num + " is not a prime number.");
        }

        scanner.close();
    }
}
```


| Test cases | Input | Expected Out put |
|------------|--------------------|---------------------------------------------------------------------------|
| TC1 | Enter a number: 5 | <div>Output</div> <pre>Enter a number: 5 5 is a prime number.</pre> |
| TC2 | Enter a number: -1 | <div>Output</div> <pre>Enter a number: -1 -1 is not a prime number.</pre> |
| TC3 | Enter a number: 6 | <div>Output</div> <pre>Enter a number: 6 6 is not a prime number.</pre> |

Observation :

The program prints n number of asterisks (*) on the same line.

It performs input validation:

Only accepts positive integers.

If a negative number or 0 is entered, it prints an error message.

Useful concepts demonstrated:

Scanner for input

if-else for input validation

for loop for repetition

Problem Statement 10:

Input 5 numbers, use continue to skip negative ones and sum the rest

Algorithm :

- Start
- Initialize sum = 0
- Repeat steps 4–7 for i = 1 to 5
- Prompt: "Enter number i"
- Read number → num
- If num < 0, skip to next iteration (continue)
- Else, add num to sum
- After loop ends, print sum
- End

Pseudo code :

Start

Initialize sum as 0

Print "Enter 5 numbers"

Repeat for i = 1 to 5:

 Prompt user to enter number i

 Read number

 If number is negative:

 Skip this number (continue loop)

 Add number to sum

Print sum of non-negative numbers

End

Code :

```
import java.util.Scanner;

public class SkipNegativeNumbers {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int sum = 0;
        System.out.println("Enter 5 number:");

        for (int i = 1; i <= 5; i++) {
            System.out.print("Num " + i + ": ");
            int num = scanner.nextInt();
            if (num < 0) {

                continue;
            }

            sum += num;
        }

        System.out.println("Sum of non-negative numbers: " + sum);

        scanner.close();
    }
}
```

| Test cases | Input | Expected Out put |
|------------|-------|------------------|
|------------|-------|------------------|

| | | |
|-----|--------------------|--------------------------------------------------------------------------------------------------------------------|
| TC1 | Enter a number: 5 | <pre> Output Enter 5 number: Num 1: 2 Num 2: -5 Num 3: 6 Num 4: 8 Num 5: -5 Sum of non-negative numbers: 16 </pre> |
| TC2 | Enter a number: -1 | <pre> Output Enter 5 number: Num 1: -5 Num 2: -1 Num 3: 2 Num 4: 0 Num 5: 0 Sum of non-negative numbers: 2 </pre> |
| TC3 | Enter a number: 6 | <pre> Output Enter 5 number: Num 1: -5 Num 2: 4 Num 3: -5 Num 4: 0 Num 5: 0 Sum of non-negative numbers: 4 </pre> |

Observation :

The program demonstrates the use of loop control (continue) to skip unwanted input. Negative numbers are not processed or added to the sum. Input is taken 5 times regardless of whether the number is valid or not. It's an efficient way to filter out unwanted values during input. continue helps in maintaining code clarity and avoiding nested if-else structures.

Problem Statement 11:

Rectangle Pattern . input rows and cols, print a rectangle of *

Algorithm :

- Start
- Input the number of rows and store in variable rows
- Input the number of columns and store in variable cols
- Repeat the following steps for i = 1 to rows
- For each i, repeat the following for j = 1 to cols:
 - Print "*" without moving to the next line
- After inner loop ends, print a newline to move to the next row
- End

Pseudo code :

Start

Prompt user to enter number of rows

Read rows

Prompt user to enter number of columns

Read columns

For i = 1 to rows:

 For j = 1 to columns:

 Print "**", staying on the same line

 Move to next line after printing one row

End

Code :

```
import java.util.Scanner;
```

```
public class RectanglePattern {
```

```

public static void main(String[] args) {
    Scanner scanner = new Scanner(System.in);


    System.out.print("Enter number of rows: ");
    int rows = scanner.nextInt();

    System.out.print("Enter number of columns: ");
    int cols = scanner.nextInt();

    for (int i = 1; i <= rows; i++) {
        for (int j = 1; j <= cols; j++) {
            System.out.print("**");
        }
        System.out.println();
    }

    scanner.close();
}

```

| Test cases | Input | Expected Out put |
|------------|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TC1 | Enter a number: 2,3 |  <pre> Output Enter number of rows: 2 Enter number of columns: 2 ** ** </pre> |

| | | |
|-----|----------------------|---------------------------------------------------------------------------------------------------|
| TC2 | Enter a number: 3,5 | <div>Output</div> <pre>Enter number of rows: 3 Enter number of columns: 5 ***** ***** *****</pre> |
| TC3 | Enter a number: -1,5 | <div>Output</div> <pre>Enter number of rows: -1 Enter number of columns: 2</pre> |

Observation :

The program uses nested loops: The outer loop controls rows, and the inner loop controls columns. It prints a solid rectangle of asterisks (*). Each row contains the same number of asterisks equal to the number of columns. The shape and size of the rectangle depend entirely on the user input.

Problem Statement 12:

Triangle Pattern input height , print right angled triangle with*

Algorithm :

- Start
- Prompt the user: "Enter the height of the triangle"
- Read the input and store it in variable height
- Repeat for i = 1 to height (inclusive)
- Repeat for j = 1 to i (inclusive)
 - Print * (without newline)
- Print newline (System.out.println()) to move to next row
- End

Pseudo code :

Start

Prompt user to enter height of the triangle

Read height

For i = 1 to height:

 For j = 1 to i:

 Print "*", staying on same line

 Move to the next line

End

Code :

```
import java.util.Scanner;
```

```
public class TrianglePattern {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
        System.out.print("Enter the height of the triangle: ");  
        int height = scanner.nextInt();  
        for (int i = 1; i <= height; i++) {  
            for (int j = 1; j <= i; j++) {  
                System.out.print("*");  
            }  
            System.out.println();  
        }  
  
        scanner.close();  
    }  
}
```



```
}  
}
```

| Test cases | Input | Expected Out put |
|------------|--------------------|---------------------------------------------------------------------------------------------------------------------|
| TC1 | Enter a number: 3 | <div>Output</div> <div>Enter the height of the triangle: 3 * ** ***</div> |
| TC2 | Enter a number: 5 | <div>Output</div> <div>Enter the height of the triangle: 5 * ** *** **** *****</div> |
| TC3 | Enter a number: -1 | <div>Output</div> <div>Enter the height of the triangle: -1 === Code Execution Successful ===</div> |

Observation :

This program prints a right-angled triangle using asterisks (*).The number of rows (height of the triangle) is taken from user input.The pattern grows by one * per row from top to bottom.It uses nested loops:The outer loop controls the number of rows.The inner loop controls how many * to print in each row

Problem Statement 13:

Pyramid Pattern Challenge input height print centered pyramid

Algorithm :

- Start
- Prompt the user: "Enter the height of the pyramid"
- Read input → store in variable height
- Repeat steps 5–7 for $i = 1$ to height
- Print height - i spaces
- Print $2 * i - 1$ stars (*)
- Move to next line (`System.out.println()`)
- After loop ends, close the scanner
- End

Pseudo code :

Start

Prompt user to enter height of the pyramid

Read height

For $i = 1$ to height:

 Print (height - i) spaces

 Print ($2 * i - 1$) stars

 Move to next line

End

Code :

```
import java.util.Scanner;
```

```
public class PyramidPattern {
```

```
    public static void main(String[] args) {
```

```
        Scanner scanner = new Scanner(System.in);
```

```
        System.out.print("Enter the height of the pyramid: ");
```

```
        int height = scanner.nextInt();
```

```
        for (int i = 1; i <= height; i++) {
```

```
            for (int space = 1; space <= height - i; space++) {
```

```




        System.out.print(" ");
    }

    for (int star = 1; star <= 2 * i - 1; star++) {
        System.out.print("*");
    }

    System.out.println();
}

scanner.close();
}
}

```

| Test cases | Input | Expected Out put |
|------------|-------------------|---------------------------------------------------------------------------------------|
| TC1 | Enter a number: 5 |  |
| TC2 | Enter a number: 3 |  |
| TC3 | Enter a number: 0 |  |

Observation :

The program prints a center-aligned pyramid made of stars *.The height of the pyramid (number of rows) is taken as user input.For each row:
First, it prints some spaces to center-align the stars.Then, it prints odd number of stars, increasing in each row