

## **Installing Jenkins on AWS EC2-Instance Redhat system :**

### **Launch AWS EC2-Instance Process:**

1. We have to login AWS console.
2. Then we have to select RedHat ec2 instance.
3. In Choose AMI Tab we have to select RedHat enterprise linux needs to be select
4. In Choose Instance type we have to select t2.micro General purpose.
5. Then click on Review and Launch Button
6. Then click on Launch Button.
7. When click on launch we have to download key pair with selecting option called new keypair.
8. Then click on Launch Instances button.

### **Connect to AWS EC2 Instance now:**

Now Redhat ec2 instance has been created so we have to go to EC2 instance dash board and we have to provide name for new instance. Like "Jenkins master server".

1. Select just now created EC2 instance and click on connect button above one.
2. Then copy the ssh command which is available under example one.
3. We have to open terminal and go to Downloads folder location since our pem file is available there.  
Cd Downloads
4. And enter copied ssh command
5. And says yes and enter
6. Now we can see we have been connected successfully to AWS instance with ec2 user.

Now we have to follow the installation steps to install Jenkins on this instance.

1. `sudo yum install wget`
2. `sudo wget -O /etc/yum.repos.d/jenkins.repo http://pkg.jenkins-ci.org/redhat/jenkins.repo`
3. `sudo rpm --import https://jenkins-ci.org/redhat/jenkins-ci.org.key`
4. `sudo yum install jenkins`
5. `sudo yum install java`
6. `sudo service Jenkins start`
7. `sudo chkconfig Jenkins on`

Success Jenkins is installed now and running fine.

Now Access Jenkins from a web browser.

For this Enable TCP/IP connections for the RHEL instance that we just know launched.

How to Enable TCP/IP connections to instance.

Now go to AWS RED HAT instance and find the security wizard used. Go to security groups . Select the security wizard ... Actions -> Edit inbound Rules -> Allow all TCP/IP or Allow all traffic and select anywhere not custom as source tab.

And now go to browser and type public ip:8080.

Unlock Jenkins using initial admin password, copy the location shown on the screen and go to instance and get the password using below command

```
sudo cat /var/lib/Jenkins/secrets/initialAdminPassword
```

And copy the password and paste into the browser and click on enter.

And select plugins installation button.

And try to create a new user or else continue with admin user.

Now our Jenkins installation setup is done on AWS redhat ec2 instance successfully.

---

Install GIT and GIT HUB tools and plug ins in Jenkins as well.

So here we are going to run a simple maven project.

So We have to install Maven here and configure in Global tool configuration tab under manage Jenkins tab and maven plug in in Jenkins as well.

We need to install Java as well

```
sudo yum install java*
```

We need to install MAVEN and we have to set up MAVEN like windows for this please follow below steps,

<http://www.techoism.com/install-apache-maven-on-centos-765/>

### **What does Maven do ?**

- Maven describes how the software is built.
- Maven describes the project's dependencies.

### Configure Jenkins for our Maven – Based project.

We have to go Manage Jenkins and Global tool configuration tab.

# Maven pom.xml file

- Describe the software project being built, including
  - The dependencies on other external modules.
  - The directory structures.
  - The required plugins.
  - The predefined targets for performing certain tasks such as compilation and packaging.

## Different Phases in Maven Build Lifecycle

- validate** Validate the project is correct and all necessary information is available.
- compile** Compile the source code of the project.
- test** Test the compiled source code using a suitable unit testing framework.
- package** Take the compiled code and package it in its distributable format.
- verify** Run any checks on results of integration tests to ensure quality criteria are met.
- install** Install the package into the local repository, for use as a dependency in other projects locally.
- deploy** Copy the final package to the remote repository for sharing with other developers and projects.

# Maven Build Phases

- These lifecycle phases are executed sequentially to complete the default lifecycle.
- We want to specify the maven **package** command, this command would execute each default life cycle phase in order including **validate**, **compile**, **test** before executing **package**.
- We only need to call the last build phase to be executed.

## Configure Jenkins for our Maven – Based project.

- Click on New Item and give project name as maven\_project
- Configure github repo
- Configure build step as invoke maven based job
- And give goal as **clean package**

And click on save and click on build now.

It can be successful build.

Now we can make same Maven build automatic way using poll scm

# Set up SSH keys for Github Account

- SSH keys are a way to identify trusted computers without involving password.
- Generate a SSH key pair and save the private SSH key in your local box and add the public key to your GitHub account.
- Then you can directly push your changes to github repository without typing password.

## How to check if SSH public key files are available on your local box?

The SSH public key file usually sits under `~/.ssh/` directory and ends with `.pub` extension.

### Checking for existing SSH keys:

<https://help.github.com/articles/checking-for-existing-ssh-keys/>

### Generating a new SSH key and adding it to the ssh-agent:

<https://help.github.com/articles/generating-a-new-ssh-key-and-adding-it-to-the-ssh-agent/>

### Adding a new SSH key to your GitHub account:

<https://help.github.com/articles/adding-a-new-ssh-key-to-your-github-account/>

After doing above steps when we want to push changes from our system to github no need to provide any password. This way we can do pull scm when we can have new files in git hub account repository.

Now Other build type,

# Other Build Triggers of Jenkins



# Jenkins

**Build Triggers**

☒ Trigger builds remotely (e.g., from scripts) ?

Authentication Token

Use the following URL to trigger build remotely: `JENKINS_URL/job/maven-project/build?token=TOKEN_NAME` or `/buildWithParameters?token=TOKEN_NAME`  
Optionally append `&cause=Cause+Text` to provide text that will be included in the recorded build cause.

☐ Build after other projects are built ?

☐ Build periodically ?

☐ Build when a change is pushed to GitHub ?

☐ Build when another project is promoted ?

☒ Poll SCM ?

Schedule \*\*\*\*\* ?

**Build Triggers**

☒ Trigger builds remotely (e.g., from scripts) ?

Authentication Token **TOKEN**

Use the following URL to trigger build remotely: `JENKINS_URL/job/Maven_Project/build?token=TOKEN_NAME` or `/buildWithParameters?token=TOKEN_NAME`  
Optionally append `&cause=Cause+Text` to provide text that will be included in the recorded build cause.

Using this option we can generate builds from outside using TOKENS.

Lets take a example here for my maven project I have selected Trigger builds remotely option and I have provided token name as “TOKEN” only.

Now I have copied below link and saved the build.

Now went to new browser window and paste the copied link and given token name as “TOKEN” and I did press enter. Now the build has been run you can go to that build history and check new build has been run. Below is the example link for new browser.

[http://13.126.253.76:8080/job/Maven\\_Project/build?token=TOKEN](http://13.126.253.76:8080/job/Maven_Project/build?token=TOKEN)

We have to replace with actual ip or localhost:8080 with Jenkins URL in above copied link.

Next is Build project other builds are built: this will come when we have to make builds are in pipeline.

Next one build is periodically.

## **When to use scheduled build(build periodically option)?**

- Very long running build jobs, where quick feedback is less critical.
- Some intensive load and performance tests which may take several hours to run.

### **Jenkins project with code quality metrics report:**

**Checkstyle** is a **code static analysis** tool to help programmers to write Java code that adheres to a coding standard such as

- Avoiding multiple blank lines;
- Removing unused variables;
- Enforcing correct indentations;

For this we have to install checkstyle plugin into Jenkins.

Filter:

Updates Available Installed Advanced

Install ↓ Name

☒ **Checkstyle Plug-in**  
This plug-in generates the trend report for Checkstyle, an open source static code analysis program.

[Static Analysis Collector Plug-in](#)  
☐ This plug-in is an add-on for the plug-ins Checkstyle, Dry, FindBugs, PMD, Tasks, and Warnings: the plug-in collects the different analysis results and shows the results in a combined trend graph. Additionally, the plug-in provides health reporting and build stability based on the combined results.

[Box UK - JSLint](#)  
☐ Lint JavaScript files using a sensible ruleset - outputs to checkstyle format

[Report Info Plugin](#)  
☐ A view with some information from Surefire, PMD, Findbugs and Checkstyle reports.

**Install without restart** **Download now and install after restart** Update information obtained: 3 hr 17 min ago **Check now**

For doing checkstyle plugin we need to enter goal name as checkstyle:checkstyle like below

**Build**

Invoke top-level Maven targets



Goals

Advanced...

Add build step ▾

And now I want to publish the results outcome of checkstyle plugin. For that we have to add one more step on job page cluster in post build actions like below





So here we can leave it as empty Jenkins will take care about that.

Now iam going to trigger a new build by clicking on buld now option.

After running the please click on build number example please look at below figure.

Jenkins > Maven\_Project > #8

Back to Project
 **Status**
 Changes
 Console Output
 Edit Build Information
 Delete Build
 Git Build Data
 No Tags
 **Checkstyle Warnings**
 Previous Build

**Build #8** (1)
 No changes.
 Started by user j
 Revision: 04c7a
 refs/remo
 Checkstyle: [5 wa](#)

- [5 new wa](#)

Now we are able to see new option called checkstyle warnings on home page of build number 8.

Just click on that

Jenkins > Maven\_Project > #8 > Checkstyle Warnings

Back to Project
 Status
 Changes
 Console Output
 Edit Build Information
 Delete Build
 Git Build Data
 No Tags
 **Checkstyle Warnings**
 Previous Build

### CheckStyle Result

#### Warnings Trend

| All Warnings | New Warnings      | Fixed Warnings |
|--------------|-------------------|----------------|
| 5            | <a href="#">5</a> | 0              |

#### Summary

| Total | High Priority     | Normal Priority | Low Priority |
|-------|-------------------|-----------------|--------------|
| 5     | <a href="#">5</a> | 0               | 0            |

#### Details

| People  | Categories | Types | Warnings | Origin       | Details | New |
|---|------------|-------|----------|--------------|---------|-----|
| Author  |            | Total |          | Distribution |         |     |
| <a href="#">Unknown authors</a>                             |            | 1     |          | <div></div>  |         |     |
| <a href="#">James Lee &lt;jameleetutorial@gmail.com&gt;</a> |            | 4     |          | <div></div>  |         |     |
| Total   |            | 5     |          |              |         |     |

We are able to see there are 5 failures with error lines and click on that it will take us to exact line of code .All of them high priority.

How to fix those now,

## CheckStyle Result




### Warnings Trend

| All Warnings | New Warnings      |
|--------------|-------------------|
| 5            | <a href="#">5</a> |

### Summary

| Total | High Priority     | Normal Priority |
|-------|-------------------|-----------------|
| 5     | <a href="#">5</a> | 0               |

### Details

| Categories              | Types | Warnings | Details | New  |
|-------------------------|-------|----------|---------|--|
| Category                |       |          | Total   | Distribution   |
| <a href="#">Checks</a>  |       |          | 2       |  |
| <a href="#">Design</a>  |       |          | 1       |  |
| <a href="#">Javadoc</a> |       |          | 2       |  |
| Total                   |       |          | 5       |  |



Go to Checks category.

## Checkstyle Warnings - **Category Checks**

### Summary

| Total | High Priority     | Normal Priority |
|-------|-------------------|-----------------|
| 2     | <a href="#">2</a> | 0               |

### Details

| Types                                | Warnings | Details  |
|--------------------------------------|----------|--|
| Type                                 | Total    | Distribution   |
| <a href="#">FinalParametersCheck</a> | 1        |  |
| <a href="#">TodoCommentCheck</a>     | 1        |  |
| Total                                | 2        |  |

Click on FinalParametersCheck for exact warning.

## Category Checks - Type **FinalParametersCheck**

### Summary

| Total | High Priority | Normal Priority |
|-------|---------------|-----------------|
| 1     | 1             | 0               |

### Details

**Details**


**Greeter.java:16**, FinalParametersCheck, Priority: High

**Parameter someone should be final.**

Check that parameters for methods, constructors, and catch blocks are final. Interface, abstract, and native for interface, abstract, and native method parameters as there is no code that could modify the parameter.

Rationale: Changing the value of parameters during the execution of the method's algorithm can be confusing. To prevent this coding style is to declare parameters final.

There is a line number 16 we are having warning message here click on that it will take us exact line of code now.



Only thing we have to add final keyword in front string parameter. So one warning fixed it seems.

In check category we have to go to next warning and click on that

## Category Checks - Type **TodoCommentCheck**


### Summary

| Total | High Priority | Normal Priority |
|-------|---------------|-----------------|
| 1     | <u>1</u>      | 0               |

### Details

| Origin                 |          | Details  |                           |
|------------------------|----------|----------|---------------------------|
| File                   | Priority | Age      | Author                    |
| <b>Greeter.java:15</b> | High     | <u>1</u> | <a href="#">James Lee</a> |

Click on that



We have to remove that line

Third warning

| Checkstyle Warnings > Category Design  |               |                 |
|--|---------------|-----------------|
| Total  | High Priority | Normal Priority |
| 1  | 1             | 0               |
| Details  |               |                 |
| Details  |               |                 |
| Greeter.java:16, DesignForExtensionCheck, Priority: High                             |               |                 |
| Method 'greet' is not designed for extension - needs to be abstract, final or empty. |               |                 |

```
1 //
2 //
3 /**
4  * This is a class.
5  */
6 public class Greeter {
7
8  /**
9   * This is a constructor.
10  */
11  public Greeter() {
12
13  }
14
15
16  public final String greet(final String someone) {
17      return String.format("Hello, %s!", someone);
18  }
19
20 }
```

We have to add final word again in front string.

Fourth warning


## Checkstyle Warnings - Category Javadoc

### Summary

| Total | High Priority | Normal Priority |
|-------|---------------|-----------------|
| 2     | 2             | 0               |

### Details

| Types               | Warnings | Details      |
|---------------------|----------|--------------|
| Type                | Total    | Distribution |
| JavadocMethodCheck  | 1        | <div></div>  |
| JavadocPackageCheck | 1        | <div></div>  |
| Total               | 2        |              |



Comments has been missed so added between the methods

```
1 package com.example;  
2  
3 /**  
4  * This is a class.  
5  */  
6 public class Greeter {  
7  
8     /**  
9     * This is a constructor.  
10    */  
11    public Greeter() {  
12    }  
13  
14    /**  
15    * @param someone the name of a person  
16    * @return greeting string  
17    */  
18    public final String greet(final String someone) {  
19        return String.format("Hello, %s!", someone);  
20    }  
21 }  
22 }  
23
```

Fifth warning :



## Category Javadoc - Type JavadocPackageCheck

### Summary

| Total | High Priority | Normal Priority |
|-------|---------------|-----------------|
| 1     | 1             | 0               |

### Details

**Details**


[Greeter.java](#), JavadocPackageCheck, Priority: High

**Missing package-info.java file.**

Checks that each Java package has a Javadoc file used for commenting. By default it only allows a package-info.java file or package.html file.

An error will be reported if both files exist as this is not allowed by the Javadoc tool.

File has been missed there



So under example folder I have created a new file called package-info.java with above content. Now all warnings has been fixed so we can re run the build now.

Git status

Git add .

Git commit -m "message"

Git push origin master

And click on build now or configure poll scm for every minit.

Now we can go to home page of new build number and check for the checkstyle report now.

Back to Project
 Status
 Changes
 Console Output
 Edit Build Information
 Delete Build
 Polling Log
 Git Build Data
 No Tags
 Checkstyle Warnings
 Previous Build

**Build #4 (Sep 25, 20**

Changes
 1. fix checkstyle warnings ([detail](#)) /

[Started by an SCM change](#)

**Revision:** da06cce3597f76ec24de300
 

- refs/remotes/origin/master

Checkstyle: [1 warning](#) from one analys
 

- **1 new warning**
- **5 fixed warnings**

Now 5 warnings are fixed and new warning came into picture

## Summary

| Total | High Priority     | Normal |
|-------|-------------------|--------|
| 1     | <a href="#">1</a> | 0      |

## Details

Details

New

Fixed

[package-info.java:0](#), NewlineAtEndOfFileCheck, Priority: High


**File does not end with a newline.**

Checks whether files end with a line separator.


Rationale: Any source files and text files in general should end with a line sep
 previous lines as changed.

Example (line 36 should not be in diff):

Am going to newly created file after last code line am putting one enter means adding new line after last line of code.



Now again git add commit push and build will get run and check the report again.



There are other tools are available like checkstyle. They are PMD and FindBugs and many.

If you are intrested just go through the below links

### **PMD Jenkins plugin:**

<https://wiki.jenkins-ci.org/display/JENKINS/PMD+Plugin>

### **Findbugs Jenkins Plugin:**

<https://wiki.jenkins-ci.org/display/JENKINS/FindBugs+Plugin>

# Jenkins' support for other build systems (Ant, Gradle and shell scripts)



# Jenkins

## Apache Ant

- Widely-used and very well-known build scripting language for Java.
- Flexible, extensible, relatively low-level scripting language.
- An Ant build script is made up of a number of targets, each target performs a particular job in the build process.



# Gradle

- Gradle is a relatively new open source build tool for the Java Virtual Machine.
- Build scripts for Gradle are written in a Domain Specific Language based on Groovy.
- The concise nature of Groovy scripting lets you write very expressive build scripts with very little code.



## **Apache Ant:**

<http://ant.apache.org/>

## **Ant Targets:**

<http://ant.apache.org/manual/targets.html>

## **Gradle:**

<https://docs.gradle.org/current/dsl/index.html>


# Archive generated artifacts




# Jenkins

So far we have just seen about compile test and package preparation. Now are going to do archive the artifact and deploying into container.

## Continuous Integration Workflow



To archive the artifact we have to add one more step into post build action step like below




The screenshot shows the 'Post-build Actions' configuration page in Jenkins. It contains two actions:

- Publish Checkstyle analysis results**: Includes a text field for 'Checkstyle results' and a description: 'Fileset includes setting that specifies the generated raw CheckStyle XML report files, such as \*/checkstyle-result.xml. Basedir of the fileset is the workspace root. If no value is set, then the default \*/checkstyle-result.xml is used. Be sure not to include any non-report files into this pattern.' There is an 'Advanced...' button.
- Archive the artifacts**: Includes a text field for 'Files to archive' with the value '\*\*/\*.war'. There is an 'Advanced...' button.

At the bottom, there is a dropdown menu labeled 'Add post-build action' and two buttons: 'Save' and 'Apply'.

Here Jenkins is going to take all .war files to do archive. After running the build we can see archived artifact on build number home page.



The screenshot shows the Jenkins 'Build #9 (Nov)' page. The breadcrumb navigation is 'Jenkins > Maven\_Project > #9'.

**Left sidebar (Actions):**

- Back to Project
- Status
- Changes
- Console Output
- Edit Build Information
- Delete Build
- Git Build Data
- No Tags
- Previous Build

**Build #9 (Nov) details:**

- Build Artifacts**: Shows a box icon and the artifact **webapp.war**.
- Changes**: Shows a document icon and the text 'No changes.'
- Started by user**: Shows a person icon and the text 'Started by user admin'.
- Revision**: Shows a 'git' icon and the text 'Revision: 04c7a52eefdc' with a list item '• refs/remotes/origi'.

And you can go and check console output as well what process has been done.

## Install and configure Tomcat as a staging environment



# Jenkins

## Tomcat

Tomcat is an open-source web server and provides a "pure Java" HTTP web server environment in which Java code can run.



## Apache Tomcat

We have to install tomcat server and then we are able to deploy to this container.

## Change Tomcat Server Port

- Jenkins runs on port **8080**.
- The default port of Tomcat is also **8080**.



- Install *copy artifact* and *deploy to container* plugins
- Deploy our application to staging environment



# Jenkins

Here we have to install 2 plugins one is for copying artifact from previous build and another plugin is for deploying to container. And below configuration we have to do in build step and post build step.

**Build**

**Copy artifacts from another project** X

Project name

Which build

☐ Stable build only

Artifacts to copy

Artifacts not to copy

Target directory

Parameter filters

☐ Flatten directories ☐ Optional ☒ Fingerprint Artifacts

[Advanced...](#)

### Post-build Actions

Deploy war/ear to a container

WAR/EAR files

Context path

Containers

Tomcat 7.x

Manager user name

Manager password

Tomcat URL

Add Container


Deploy on failure ☐

Add post-build action

Save


Apply

So here I have to create 2 builds and one is for preparing package and the second one is for taking that artifact and it is able to deploy into staging area. And here we have to make these 2 builds like upstream and down stream projects in post build action tab.




When you run the first build it is going to have this output.

# Our Current Build Pipeline



## Build Pipeline Plugin



# Parallel Jenkins Build




# Jenkins

Linear Pipeline



# Parallel Pipeline



We are going to create 3 builds



Package will have goals to prepare war so in build actions tab we have to provide goal called clean and package no checkstyle goal.

Now second build is static analysis here we have to write checkstyle:checkstyle goal in build action tab.

So in Package build we are going to 2 bulds at a time like below screen shot

### Post-build Actions

Archive the artifacts

Files to archive

Build other projects

Projects to build

No such project 'sta'. Did you mean 'package'?

☒ Trigger only if build is stable


☐ Trigger even if the build is unstable

☐ Trigger even if the build fails

Add post-build action ▼

Save

Apply



So next one is we are going to setup deploy to production.


# Continuous Delivery

Deploy our app to production




# Jenkins

## Full Continuous Delivery Pipeline



# Full Continuous Delivery Pipeline




we are going to have 2 tomcats with 2 diff port numbers in 2 diff folders and in a same system.

So we have to start both the servlet containers then we can create above 4 builds and we can set up pipeline.


We have to create new job for prod env same like staging we have done like in build step we have to select copy artifact from package build and in same way we have to select deploy to container in post build actions tab.

And then this prod job calling we have to set up in staging deployment build in post build actions, since we have to do manually we have to select option called deploy other builds manually in post build actions of staging area build setup.





Last build we have to run manually only.



## Install Jenkins on ubuntu system :

### Install Jenkins on the Master Node

```
wget -q -O - http://pkg.jenkins-ci.org/debian/jenkins-ci.org.key | apt-key  
add -
```

```
echo deb http://pkg.jenkins-ci.org/debian binary/ >  
/etc/apt/sources.list.d/jenkins.list
```

```
apt-get update
```


```
apt-get install Jenkins
```

## Introduction to Distributed Jenkins Builds



# Jenkins

### Jenkins' Master and Slave Architecture




#### Master:

- Schedule build jobs.
- Dispatch builds to the slaves for the actual job execution.
- Monitor the slaves and record the build results.
- Can also execute build jobs directly.

#### Slave:

- Execute build jobs dispatched by the master.

# Jenkins Slave Agent



## Different ways to start slave agent

- The master can start the slave agents via SSH.
- Start the slave agent manually using Java Web Start.
- Install the slave agent as a Window service.
- Start the slave agent directly from the command line on the slave machine.

