

2011

Storage Class

(c)

November
Wednesday

23

There are four storage classes —

- ① Automatic
- ② Register
- ③ Static
- ④ External

① Automatic → Automatic variables are declared inside a particular function and they are created when the function is called and destroyed when the function exits. These are local to a function in which they are defined.

By default, all the variables declared without a storage specification is automatic.

The key to declare an automatic storage class is auto.

```
#include <stdio.h>
void main ()
```

```
{
    auto int i=1;
    auto int i=2;
```

```
{
    auto int i=3; printf ("%d", i);
```

```
} printf ("%d", i);
```

```
{
    printf ("%d", i);
}
```

T F S S M T W T F S S M T W T F S S M T W T F S DEC
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 2011

25 November
Friday

2011

② Register → A variable is usually stored in memory but it is also possible to store a variable in CPU register by defining it as register variable.

It is much faster than a memory access. The keyword to declare an register storage class is register.

```
register int i;
```

③ Static → The static storage class is declared with the keyword static.

26 November
Saturday

(a) The scope of variable is local. But the value of variable persists until the end of the program.

(b) When the program is compiled, it is never initialized again.

```
#include <stdio.h>
```

27 SUNDAY

```
void stat_func() {
```

```
    static int x;
```

```
    x++;
```

```
    printf("x = %d", x);
```

```
}
```

NOV 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 •

```
void main() {
```

```
    stat - func();
    stat - func();
    stat - func();
```

```
}
```

④ External → Variables which are common to all functions and accessible by all the functions of a program are external variables. It is declared outside of all functions.

(a) Its default value (initial) is 0.

(b) The scope of the external variables are global.

```
#include <stdio.h>
```

```
int i = 10;
```

```
void function1() {
```

```
    printf("%d", i); i++;
```

```
}
```

```
void function2() {
```

```
    printf("%d", i); i--;
```

```
}
```

```

void main () {
    printf ("%d", i);
    function1 ();
    function2 ();
    printf ("%d", i);
}

```

- ⑤ Extern → Global variables are usually declared in the beginning of the program before all the functions.

01

December
Thursday

However, C provides a facility to declare any variable as global. This is using by the keyword storage class extern.

eg. #include <stdio.h>

```

void function1 () {
    extern int i;
    i = 20;
    printf ("%d", i);
}

int i = 10;

```



```
void main()  
{  
    function1();  
    printf("%d", i);  
}
```

Table (Storage Class)

① Auto : — .

(a) Storage → Memory

(b) Default Value → Garbage Value

(c) Scope → Local to the block, in which the variable is declared.

(d) Lifetime → Till the control remains within the block in which it is defined.

15

August
Monday

2011

~~Notes~~~~Enumeration~~Enumeration Constants

(*) Enumeration is a user defined type with values ranging over a finite set of identifiers, called enumeration constants.

eg. enum color {red, blue, green};

↓ ↓ ↓

(values) 0 1 2

16

August
Tuesday

eg. enum weather {hot, warm=0, cold, we};

↓ ↓ ↓ ↓

0 0 1 2

interchangeably used.

eg. enum week {sun, mon, tue, wed, thu, fri, sat};

Difference between Character Constant and String Constant :-

'A' → Character Constant

(a) Occupying Single Byte.

"A" → String Constant

(a) Occupying Two Bytes

(b) All string terminates with a null character or '\0' with the value of 0.

August 18
Thursday

Logical Operators

(1) Logical AND →

$$a > b \ \&\& \ x == 10$$

(2) Logical OR →

$$a < m \ || \ a < n$$

19 August
Friday

2011

③ Logical Not →

! (x >= y)

Bitwise Operators

① Bitwise AND →

a = 13
b = 7

c = a & b

integer ↓
16 bits (2 bytes)

20 August
Saturday

a = 0000 0000 0000 1101

b = 0000 0000 0000 0111

a & b = 0000 0000 0000 0101

[each bit in c will be 1 only if the corresponding bits in both a and b are 1.]

21 SUNDAY

AUG 2011 M T W T F S S M T W T F S S M T W T F S S M T W
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31

② Bitwise OR \rightarrow

$$c = \frac{a}{b};$$

$$a = 0000\ 0000\ 0000\ 1101$$

$$b = 0000\ 0000\ 0000\ 0111$$

$$a/b = 0000\ 0000\ 0000\ 1111$$

[each bit in c will be 1 only if the corresponding one of the bits of a or b is 1]

Tuesday

③ Bitwise XOR \rightarrow

$$c = a^b$$

$$a = 0000\ 0000\ 0000\ 1101$$

$$b = 0000 \ 0000 \ 0000 \ 0111$$

0000 0000 0000 1010

c will be 1 whenever the corresponding bits in a and b differ.

24 August
Wednesday

④ Left-Shift →

$$c = a \ll 3$$

drop off ← 0000 0000 0000 1101 ← insert 0's
↓ using left shift $a \ll 3$

0000 0000 0110 1000 (*)

25 August
Thursday

⑤ Right-Shift →

$$c = a \gg 3$$

insert 0's → 0000 0000 0000 1101 → drop off
↓ using right shift $a \gg 3$

0000 0000 0000 0001 (**)

AUG	M	T	W	T	F	S	S	M	T	W	T	F	S	S	M	T	W	T	F	S	S	M	T	W	T	F	S	S	M	T	W
2011	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31

2011

August 26
Friday

(*) Shifting a variable to the left by one bit position is to multiply it by 2.

eg. here a is shifted by 3 positions.

ie/ a is multiplied by 2^3 .

ie/ initial value $a = 13$.

↓ $a \ll 3$.

$$a = 13 * 2^3 = 13 * 8 = 104.$$

(**) Shifting a variable to the right by one bit position is to divide by 2.

eg. here also a is shifted by 3 positions.

ie/ a is divided by 2^3 .

ie/ initial value $a = 13$

↓ $a \gg 3$

$$a = 13 / 8 = 10$$

August 27
Saturday

SUNDAY 28

29

August
Monday

2011

Shifting Negative Numbers

$$a = -3$$

i) Representation of 3 →

0000 0000 0000 0011

ii) 1's Complement →

1111 1111 1111 1100

iii) 2's Complement →

30

August

Tuesday

(add)

1111 1111 1111 1100

1

1111 1111 1111 1101



Representation of (-3).



2011

August 31
Wednesday

$$C = a \gg 2$$

ie) shift 2 bit positions to the right and insert two 1's to the left.

insert 1's \rightarrow 1111 1111 1111 1101 \rightarrow drop off

1111 1111 1111 1111

ie) 2's Complement \rightarrow .

0000 0000 0000 0000

1's complement

September

0000 0000 0000 0001

Thursday

2's complement


01

(magnitude is (-1)).

Note: — ① In case of unsigned integers, inserted left bit is always zero.

② Case of right shift —
left bit carries with the sign.

③ Case of left shift —
right bit carries with the sign.

02 September
FridayFormat Specifier03 September
SaturdayChart of Format SpecifiersInteger :-

- ① `%d` → Signed decimal integer
- ② `%i` → Signed decimal integer
- ③ `%o` → unsigned decimal integer.
- ④ `%x, %X` → unsigned hexadecimal int.
- ⑤ `%f, %e, %g` → Signed value of floating point
- ⑥ `%u` → unsigned decimal integer.

Qualified Data Types :-

- (1) %ld, %li long decimal int.
- (2) %lu unsigned long decimal int.
- (3) %hd, %hi short decimal int.
- (4) %hu unsigned short decimal int.
- (5) %le, %lf, %lg signed double.
- (6) %Le, %Lf, %Lg signed long double.
- (7) %lo octal long integer.
- (8) %lx hexadecimal long int.

Character Datatype :-

- (1) %c single character
- (2) %s sequence of character
- (3) %% prints the % character.