

SQL Server IS NULL Condition (Operator)

 javatpoint.com/sql-server-is-null-operator

The SQL Server IS NULL operator is used to test for a NULL value.

Syntax:

1. expression ISNULL

Parameter explanation

expression: It specifies a value whether it is NULL.

Note:


- If the expression is NULL value then the condition evaluates to TRUE.
- If expression is not a NULL value, the condition evaluates to FALSE.

IS NULL Operator with SELECT Statement

Example:

1. SELECT *
2. FROM [javatpoint].[dbo].[Employees]
3. WHERE salary ISNULL;

Output:




IS NULL Operator with INSERT Statement

Example:

1. INSERT INTO [javatpoint].[dbo].[Employees]

2. (id, name, salary)
3. SELECT id, name, Department
4. FROM [javatpoint].[dbo].[Employee2]
5. WHERE name IS NULL;

Output:



Note: This displays "0 rows affected" because there is no NULL value in name in the "Employees" table.


IS NULL Operator with UPDATE Statement

Example:


Update the salary of the employees in "Employees" table and set to 100000 where salary is NULL.

1. UPDATE Employees
2. SET salary = '100000'
3. WHERE salary IS NULL;

Output:



You can verify it by using SELECT query:




IS NULL Operator with DELETE Statement

Delete the employees from the "Employees" table where age is NULL.


Example:

1. DELETE FROM [javatpoint].[dbo].[Employees]
2. WHERE age IS NULL;

Output:



You can verify it by using SELECT query:



You can see that there is no NULL value in age in the above table.