pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe...

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class ShipwreckStoreServiceApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreServiceApplication.class, args);
    }

}
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe...

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class ShipwreckStoreServiceApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreServiceApplication.class, args);
    }

}
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe...

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class ShipwreckStoreServiceApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreServiceApplication.class, args);
    }

}
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe...

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class ShipwreckStoreServiceApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreServiceApplication.class, args);
    }

}
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe...

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class ShipwreckStoreServiceApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreServiceApplication.class, args);
    }

}
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe...

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class ShipwreckStoreServiceApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreServiceApplication.class, args);
    }

}
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe...

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class ShipwreckStoreServiceApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreServiceApplication.class, args);
    }

}
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe...

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class ShipwreckStoreServiceApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreServiceApplication.class, args);
    }

}
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe...

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class ShipwreckStoreServiceApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreServiceApplication.class, args);
    }

}
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe...

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class ShipwreckStoreServiceApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreServiceApplication.class, args);
    }

}
```

InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml | pom.xml | ShipwreckStoreAp... | ApplicationContr... | ServiceProxy.java | application.prop... | pom.xml | GatewayApplicati... | application.prop... | bootstrap.properties | pom.xml | RegistryApplicat... | application.prop...

```properties
server.port = 8761
```

1. 49. 5.

Assessment home

InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml | pom.xml | ShipwreckStoreAp... | ApplicationContr... | ServiceProxy.java | application.prop... | pom.xml | GatewayApplicati... | application.prop... | bootstrap.properties | pom.xml | RegistryApplicat...

```java
package com.example;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class RegistryApplication {

    public static void main(String[] args) {
        SpringApplication.run(RegistryApplication.class, args);
    }

}
```

1. 49. 19.

Assessment home

```jump_to_line
InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml | pom.xml | ShipwreckStoreAp... | ApplicationContr... | ServiceProxy.java | application.prop... | pom.xml | GatewayApplicati... | application.prop... | bootstrap.properties | pom.xml | RegistryApp
```

```java
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 https://maven.apache.org/xsd/maven-4.0.0.xsd">
    <modelVersion>4.0.0</modelVersion>

    <parent>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-parent</artifactId>
        <version>3.0.6</version>
        <relativePath/> <!-- lookup parent from repository -->
    </parent>
    <groupId>com.example</groupId>
    <artifactId>Registry</artifactId>
    <version>0.0.1-SNAPSHOT</version>
    <name>Registry</name>
    <description>Registry</description>
    <properties>
        <java.version>17</java.version>
        <spring-cloud.version>2022.0.2</spring-cloud.version>
    </properties>
    <dependencies>
        <dependency>
            <groupId>org.springframework.cloud</groupId>
            <artifactId>spring-cloud-starter-netflix-eureka-server</artifactId>
        </dependency>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-test</artifactId>
            <scope>test</scope>
        </dependency>
    </dependencies>
    <dependencyManagement>
        <dependencies>
            <dependency>
                <groupId>org.springframework.cloud</groupId>
                <artifactId>spring-cloud-dependencies</artifactId>
                <version>${spring-cloud.version}</version>
                <type>pom</type>
                <scope>import</scope>
            </dependency>
        </dependencies>
    </dependencyManagement>

    <build>
        <plugins>
            <plugin>
                <groupId>org.springframework.boot</groupId>
                <artifactId>spring-boot-maven-plugin</artifactId>
            </plugin>

        </plugins>
    </build>
    <repositories>
        <repository>
            <id>netflix-candidates</id>
            <name>Netflix Candidates</name>
            <url>https://artifactory-oss.prod.netflix.net/artifactory/maven-oss-candidates</url>
            <snapshots>
                <enabled>false</enabled>
            </snapshots>
        </repository>
    </repositories>

</project>
```

```jump_to_line
InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml | pom.xml | ShipwreckStoreAp... | ApplicationContr... | ServiceProxy.java | application.prop... | pom.xml | GatewayApplicati... | application.prop... | bootstrap.properties
```

```properties
spring.application.name=gateway
spring.cloud.gateway.discovery.locator.enabled=true
spring.cloud.consul.discovery.health-check-path=/actuator/health
```

```jump_to_line
InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml | pom.xml | ShipwreckStoreAp... | ApplicationContr... | ServiceProxy.java | application.prop... | pom.xml | GatewayApplicati... | application.prop...
```

```properties
server.port=8777
spring.application.name=gateway
```

```jump_to_line
InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml | pom.xml | ShipwreckStoreAp... | ApplicationContr... | ServiceProxy.java | application.prop... | pom.xml | GatewayApplicati...
```

```java
package com.example.demo;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class GatewayApplication {

    public static void main(String[] args) {
        SpringApplication.run(GatewayApplication.class, args);
    }

}
```

InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml | pom.xml | ShipwreckStoreAp... | ApplicationContr... | ServiceProxy.java | application.prop... | pom.xml

```xml
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 https://maven.apache.org/xsd/maven-4.0.0.xsd">
    <modelVersion>4.0.0</modelVersion>
    <parent>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-parent</artifactId>
        <version>3.0.6</version>
        <relativePath/> <!-- lookup parent from repository -->
    </parent>
    <groupId>com.example</groupId>
    <artifactId>Gateway</artifactId>
    <version>0.0.1-SNAPSHOT</version>
    <name>Gateway</name>
    <description>Gateway</description>
    <properties>
        <java.version>17</java.version>
        <spring-cloud.version>2022.0.2</spring-cloud.version>
    </properties>
    <dependencies>
        <dependency>
            <groupId>org.springframework.cloud</groupId>
            <artifactId>spring-cloud-starter-gateway</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.cloud</groupId>
            <artifactId>spring-cloud-starter-netflix-eureka-client</artifactId>

        </dependency>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-test</artifactId>
            <scope>test</scope>
        </dependency>

    <!-- Spring Boot Starter -->
    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter</artifactId>

    </dependency>





    </dependencies>
    <dependencyManagement>
        <dependencies>
            <dependency>
                <groupId>org.springframework.cloud</groupId>
                <artifactId>spring-cloud-dependencies</artifactId>
                <version>${spring-cloud.version}</version>
                <type>pom</type>
                <scope>import</scope>
            </dependency>
        </dependencies>
    </dependencyManagement>

    <build>
        <plugins>
            <plugin>
                <groupId>org.springframework.boot</groupId>
                <artifactId>spring-boot-maven-plugin</artifactId>
            </plugin>
        </plugins>
    </build>
    <repositories>
        <repository>
            <id>netflix-candidates</id>
            <name>Netflix Candidates</name>
            <url>https://artifactory-oss.prod.netflix.net/artifactory/maven-oss-candidates</url>
            <snapshots>
                <enabled>false</enabled>
            </snapshots>
        </repository>
    </repositories>

</project>
```

InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml | pom.xml | ShipwreckStoreAp... | ApplicationContr... | ServiceProxy.java | application.prop... | pom

```yaml
server.port=8090
```

InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml | pom.xml | ShipwreckStoreAp... | ApplicationContr... | ServiceProxy.java | a

```java
package com.shipwreckstore.proxy;


import org.springframework.web.bind.annotation.RequestMapping;

public interface ServiceProxy {

        public String greeting();
}
```

InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml | pom.xml | ShipwreckStoreAp... | ApplicationContr...

```java
package com.shipwreckstore.controller;

import org.springframework.web.bind.annotation.RestController;


@RestController
public class ApplicationController {



    public String retreiveInfo( ) {

        return null;

    }

    public String fallback(Exception e) {
        return "Sorry Service is unavailable";
    }

}
```

ExceptionRespons... | InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml | pom.xml | ShipwreckStoreAp...

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;


@SpringBootApplication

public class ShipwreckStoreApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreApplication.class, args);
    }

}
```

istomizedRespon... | ExceptionRespons... | InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml | pom.xml | ShipwreckStoreAp...

```xml
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 https://maven.apache.org/xsd/maven-4.0.0.xsd">
    <modelVersion>4.0.0</modelVersion>
    <parent>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-parent</artifactId>
        <version>3.0.6</version>
        <relativePath/> <!-- lookup parent from repository -->
    </parent>
    <groupId>com.shipwreckstore</groupId>
    <artifactId>ShipwreckStoreApplication</artifactId>
    <version>0.0.1-SNAPSHOT</version>
    <name>ShipwreckStoreApplication</name>
    <description>ShipwreckStoreApplication</description>
    <properties>
        <java.version>17</java.version>
        <spring-cloud.version>2022.0.2</spring-cloud.version>
    </properties>
    <dependencies>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-validation</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-web</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.cloud</groupId>
            <artifactId>spring-cloud-starter-circuitbreaker-resilience4j</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.cloud</groupId>
            <artifactId>spring-cloud-starter-netflix-eureka-client</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.cloud</groupId>
            <artifactId>spring-cloud-starter-openfeign</artifactId>
        </dependency>

        <dependency>
            <groupId>org.projectlombok</groupId>
            <artifactId>lombok</artifactId>
            <optional>true</optional>
        </dependency>
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-test</artifactId>
            <scope>test</scope>
        </dependency>

        <dependency>
            <groupId>org.springframework.restdocs</groupId>
            <artifactId>spring-restdocs-mockmvc</artifactId>
            <scope>test</scope>
        </dependency>

        <dependency>
            <groupId>junit</groupId>
            <artifactId>junit</artifactId>
            <version>4.12</version>
            <scope>test</scope>
        </dependency>

        <dependency>
    <groupId>org.springframework.cloud</groupId>
    <artifactId>spring-cloud-starter-loadbalancer</artifactId>
</dependency>

    </dependencies>
    <dependencyManagement>
        <dependencies>
            <dependency>
                <groupId>org.springframework.cloud</groupId>
                <artifactId>spring-cloud-dependencies</artifactId>
                <version>${spring-cloud.version}</version>
                <type>pom</type>
                <scope>import</scope>
            </dependency>
        </dependencies>
    </dependencyManagement>

    <build>
        <plugins>
            <plugin>
                <groupId>org.asciidoctor</groupId>
                <artifactId>asciidoctor-maven-plugin</artifactId>
                <version>2.2.1</version>
                <executions>
                    <execution>
                        <id>generate-docs</id>
```

ler.java | CustomizedRespon... | ExceptionRespons... | InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop... | logger.xml

```xml
<?xml version="1.0" encoding="UTF-8"?>
<configuration>
    <property name="HOME_LOG" value="log/mylogs.log"/>

    <appender name="CONSOLE" class="ch.qos.logback.core.ConsoleAppender">
        <layout class="ch.qos.logback.classic.PatternLayout">
            <Pattern>
                %d{HH:mm:ss.SSS} [%t] %-5level %logger{36} - %msg%n
            </Pattern>
        </layout>
    </appender>

    <appender name="FILE" class="ch.qos.logback.core.FileAppender">
        <file>${HOME_LOG}</file>

        <append>true</append>
        <encoder>
            <pattern>[%-5level] %d{dd-MM-yyyy hh:mm:ss.SSS a} [%thread]  %logger{50} - %msg%n</pattern>
        </encoder>
    </appender>


<!-- additivity as false appends only to file and not to console -->
    <logger name="com.shipwreckstore.service" level="info" additivity="false">
        <!-- <appender-ref ref="CONSOLE"/> -->
        <appender-ref ref="FILE"/>
    </logger>

    <logger name="com.shipwreckstore.exception" level="info" additivity="false">
        <!-- <appender-ref ref="CONSOLE"/> -->
        <appender-ref ref="FILE"/>
    </logger>

    <root level="debug">
        <appender-ref ref="CONSOLE"/>
    </root>
</configuration>
```

3... | ShipController.java | CustomizedRespon... | ExceptionRespons... | InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | application.prop...

```python
server.port=9090
logging.config=src/main/resources/logger.xml
```

nl | ShipwreckStoreSe... | ShipController.java | CustomizedRespon... | ExceptionRespons... | InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | ShipServiceImpl.java | ap

```java
package com.shipwreckstore.service;

import java.time.LocalDate;
import java.util.ArrayList;
import java.util.List;
import com.shipwreckstore.exception.*;
import com.shipwreckstore.model.*;

public class ShipServiceImpl implements IShipService{

private static List<Ship> shipList=new ArrayList<Ship>();

    public static List<Ship> getShipList() {
        return shipList;
    }

    public static void setShipList(List<Ship> shipList) {
        ShipServiceImpl.shipList = shipList;
    }


    // Implement the service methods as per the requirement

    public Ship updateDepth( String shipID,int depth)throws ShipNotAvailableException{
        return null;
    }

    public Ship addShip( Ship ship)  throws InvalidShipException{

            return null;

    }

    public Ship getShip(Ship b1) {

        return null;
}

    public List<Ship> getShipWithGoodCondition()  {


        return null;

    }

    public List<Ship> getShipWithFairCondition()  {

        return null;
    }


    public ShipServiceImpl() {
        populateShips();
    }
    public void populateShips() {

        //If needed, you can uncomment the below lines and use the objects to check your application


//      shiplist.add(new Ship("SHIP 1-455","Thistlegorm","British Merchant boat in the red sea","Good",80,34.56,67.75,LocalDate.now().minusYears(28)));
//      shiplist.add(new Ship("SHIP 9-789","SS Yongala","A luxury passenger ship wrecked on the great barrier reef","Fair",50,56.78,67.75,LocalDate.now().minusYears(28)));
//      shiplist.add(new Ship("SHIP 7-555","Javaship","Programming ship to develop secure applications","Fair",350,80.78,120.75,LocalDate.now().minusYears(31)));
//      shiplist.add(new Ship("SHIP 6-458","RMS Titanic","Famous ship for never making her destination","Good",80,70.78,120.75,LocalDate.now().minusYears(110)));
//      shiplist.add(new Ship("SHIP 3-623","MS Estonia","British Merchant boat in the Caribbean Sea","Good",280,80.78,90.75,LocalDate.now().minusYears(28)));
//      shiplist.add(new Ship("SHIP 5-222","HMS Victory","Now the property of British government under marine Laws","Fair",50,60.78,90.75,LocalDate.now().minusYears(14)));
//      shiplist.add(new Ship("SHIP 4-345","The Mary Rose","It was a warship in the navy of the Tudor King Henry VIII","Fair",220,80.78,120.75,LocalDate.now().minusYears(40)));

    }

}
```

mylogs.log | pom.xml | ShipwreckStoreSe... | ShipController.java | CustomizedRespon... | ExceptionRespons... | InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService.java | s

```java
package com.shipwreckstore.service;

import java.util.List;

import com.shipwreckstore.exception.*;
import com.shipwreckstore.model.*;

public interface IShipService {

    public Ship addShip(Ship ship)  throws InvalidShipException;
    public Ship updateDepth(String shipID,int depth)  throws ShipNotAvailableException;
    public List<Ship> getShipWithGoodCondition() ;
    public List<Ship> getShipWithFairCondition() ;

}
```

plication.prop... | mylogs.log | pom.xml | ShipwreckStoreSe... | ShipController.java | CustomizedRespon... | ExceptionRespons... | InvalidShipExcep... | ShipNotAvailable... | Ship.java

```java
package com.shipwreckstore.model;

import java.time.LocalDate;

public class Ship {

    private String shipID;
    private String shipName;
    private String description;
    private String condition;
    private Integer depth;
    private Double latitude;
    private Double longitude;
    private LocalDate yearDiscovered;

    public String getShipID() {
        return shipID;
    }
```

gControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe... | ShipController.java | CustomizedRespon... | ExceptionRespons... | InvalidShipExcep... | ShipNotAvailable...

```java
package com.shipwreckstore.exception;

public class ShipNotAvailableException extends Exception{

    String message;



}
```

ckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe... | ShipController.java | CustomizedRespon... | ExceptionRespons... | InvalidShipExcep...

```java
package com.shipwreckstore.exception;


public class InvalidShipException extends Exception{

    String message;


}
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe... | ShipController.java | CustomizedRespon... | ExceptionRespons...

```java
package com.shipwreckstore.exception;

import java.time.LocalDate;

public class ExceptionResponse {
      private LocalDate timestamp;
      private String message;
      private String details;
      private String httpCodeMessage;
    public LocalDate getTimestamp() {
        return timestamp;
    }
    public void setTimestamp(LocalDate timestamp) {
        this.timestamp = timestamp;
    }
    public String getMessage() {
        return message;
    }
    public void setMessage(String message) {
        this.message = message;
    }
    public String getDetails() {
        return details;
    }
    public void setDetails(String details) {
        this.details = details;
    }
    public String getHttpCodeMessage() {
        return httpCodeMessage;
    }
    public void setHttpCodeMessage(String httpCodeMessage) {
        this.httpCodeMessage = httpCodeMessage;
    }
    public ExceptionResponse(LocalDate timestamp, String message, String details, String httpCodeMessage) {
        super();
        this.timestamp = timestamp;
        this.message = message;
        this.details = details;
        this.httpCodeMessage = httpCodeMessage;
    }
    public ExceptionResponse() {

    }


}
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe... | ShipController.java | CustomizedRespon...

```java
package com.shipwreckstore.exception;

import org.springframework.http.HttpHeaders;
import org.springframework.http.HttpStatus;
import org.springframework.http.HttpStatusCode;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.MethodArgumentNotValidException;
import org.springframework.web.context.request.WebRequest;
import org.springframework.web.servlet.mvc.method.annotation.ResponseEntityExceptionHandler;


public class CustomizedResponseEntityExceptionHandler extends ResponseEntityExceptionHandler {


    public final ResponseEntity<Object> handleAllExceptions(Exception ex, WebRequest request)
    {
        return null;
    }


    public final ResponseEntity<ExceptionResponse> handleNotFoundException(ShipNotAvailableException ex, WebRequest request)
    {
        return null;
    }


    public final ResponseEntity<ExceptionResponse> handleInvalidException(InvalidShipException ex, WebRequest request)
    {

        return null;
    }

@Override
protected ResponseEntity<Object> handleMethodArgumentNotValid(MethodArgumentNotValidException ex,
        HttpHeaders headers, HttpStatusCode status, WebRequest request) {


        return null;
    }
}
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe... | ShipController.java

```java
package com.shipwreckstore.controller;

import java.util.List;
import com.shipwreckstore.exception.InvalidShipException;
import com.shipwreckstore.exception.ShipNotAvailableException;
import com.shipwreckstore.model.Ship;


public class ShipController {


        public Ship addShip(Ship ship) throws InvalidShipException {

            return null;
        }

        public Ship updateDepth(String shipID, int depth) throws ShipNotAvailableException {

            return null;
        }

        public List<Ship> getShipWithGoodCondition()  {
            return null;
        }

        public List<Ship> getShipWithFairCondition()  {
            return null;
        }

    }
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe...

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class ShipwreckStoreServiceApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreServiceApplication.class, args);
    }

}
```

```xml
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-test</artifactId>
            <scope>test</scope>
        </dependency>

        <dependency>
            <groupId>org.springframework.restdocs</groupId>
            <artifactId>spring-restdocs-mockmvc</artifactId>
            <scope>test</scope>
        </dependency>

        <dependency>
            <groupId>junit</groupId>
            <artifactId>junit</artifactId>
            <version>4.12</version>
            <scope>test</scope>
        </dependency>

    </dependencies>
    <dependencyManagement>
        <dependencies>
            <dependency>
                <groupId>org.springframework.cloud</groupId>
                <artifactId>spring-cloud-dependencies</artifactId>
                <version>${spring-cloud.version}</version>
                <type>pom</type>
                <scope>import</scope>
            </dependency>
        </dependencies>
    </dependencyManagement>

    <build>
        <plugins>
            <plugin>
                <groupId>org.asciidoctor</groupId>
                <artifactId>asciidoctor-maven-plugin</artifactId>
                <version>2.2.1</version>
                <executions>
                    <execution>
                        <id>generate-docs</id>
                        <phase>prepare-package</phase>
                        <goals>
                            <goal>process-asciidoc</goal>
                        </goals>
                        <configuration>
                            <backend>html</backend>
                            <doctype>book</doctype>
                        </configuration>
                    </execution>
                </executions>
                <dependencies>
                    <dependency>
                        <groupId>org.springframework.restdocs</groupId>
                        <artifactId>spring-restdocs-asciidoctor</artifactId>
                        <version>${spring-restdocs.version}</version>
                    </dependency>
                </dependencies>
            </plugin>
            <plugin>
                <groupId>org.springframework.boot</groupId>
                <artifactId>spring-boot-maven-plugin</artifactId>
                <configuration>
                    <excludes>
                        <exclude>
                            <groupId>org.projectlombok</groupId>
                            <artifactId>lombok</artifactId>
                        </exclude>
                    </excludes>
                </configuration>
            </plugin>
        </plugins>
    </build>
    <repositories>
        <repository>
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckSt

```xml
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 https://maven.apache.org/xsd/maven-4.0.0.xsd">
    <modelVersion>4.0.0</modelVersion>
    <parent>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-parent</artifactId>
        <version>3.0.6</version>
        <relativePath/> <!-- lookup parent from repository -->
    </parent>
    <groupId>com.shipwreckstore</groupId>
    <artifactId>ShipwreckStoreService</artifactId>
    <version>0.0.1-SNAPSHOT</version>
    <name>ShipwreckStoreService</name>
    <description>ShipwreckStoreService</description>
    <properties>
        <java.version>17</java.version>
        <spring-cloud.version>2022.0.2</spring-cloud.version>
    </properties>
    <dependencies>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-validation</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-web</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.cloud</groupId>
            <artifactId>spring-cloud-starter-circuitbreaker-resilience4j</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.cloud</groupId>
            <artifactId>spring-cloud-starter-netflix-eureka-client</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.cloud</groupId>
            <artifactId>spring-cloud-starter-openfeign</artifactId>
        </dependency>

        <dependency>
            <groupId>org.projectlombok</groupId>
            <artifactId>lombok</artifactId>
            <optional>true</optional>
        </dependency>
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-test</artifactId>
            <scope>test</scope>
        </dependency>

        <dependency>
            <groupId>org.springframework.restdocs</groupId>
            <artifactId>spring-restdocs-mockmvc</artifactId>
            <scope>test</scope>
        </dependency>

        <dependency>
            <groupId>junit</groupId>
            <artifactId>junit</artifactId>
            <version>4.12</version>
            <scope>test</scope>
        </dependency>

    </dependencies>
    <dependencyManagement>
        <dependencies>
            <dependency>
                <groupId>org.springframework.cloud</groupId>
                <artifactId>spring-cloud-dependencies</artifactId>
                <version>${spring-cloud.version}</version>
                <type>pom</type>
                <scope>import</scope>
            </dependency>
        </dependencies>
    </dependencyManagement>

    <build>
        <plugins>
            <plugin>
                <groupId>org.asciidoctor</groupId>
                <artifactId>asciidoctor-maven-plugin</artifactId>
                <version>2.2.1</version>
                <executions>
                    <execution>
                        <id>generate-docs</id>
                        <phase>prepare-package</phase>
                        <goals>
                            <goal>process-asciidoc</goal>
                        </goals>
                        <configuration>
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop...

```
server.port=8091
spring.application.name = ShipwreckStoreGreeting
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe... | ShipController.java | CustomizedRespon... | ExceptionRespons... | InvalidShipExcep... | ShipNotAvailable... | Ship.java | IShipService

```java
package com.shipwreckstore.controller;

import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.PathVariable;
import org.springframework.web.bind.annotation.ResponseBody;
import org.springframework.web.bind.annotation.RestController;

@RestController
public class GreetingController {


    @GetMapping(value="/welcome")
    public @ResponseBody String greeting( ) {

        return "Welcome to Shipwreck store. It is a store that specializes in equipment or supplies related to scuba diving or marine salvage, which are often used in the exploration and recovery of shipwrecks.Spread over an area of 2,600 sq ft.";

    }
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log

```java
package com.shipwreckstore.app;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.annotation.ComponentScan;

@SpringBootApplication
@ComponentScan(basePackages= {"com.shipwreckstore.controller"})
public class ShipwreckStoreGreetingApplication {

    public static void main(String[] args) {
        SpringApplication.run(ShipwreckStoreGreetingApplication.class, args);
    }

}
```

```
            <scope>test</scope>
        </dependency>


    </dependencies>
    <dependencyManagement>
        <dependencies>
            <dependency>
                <groupId>org.springframework.cloud</groupId>
                <artifactId>spring-cloud-dependencies</artifactId>
                <version>${spring-cloud.version}</version>
                <type>pom</type>
                <scope>import</scope>
            </dependency>
        </dependencies>
    </dependencyManagement>

    <build>
        <plugins>
            <plugin>
                <groupId>org.asciidoctor</groupId>
                <artifactId>asciidoctor-maven-plugin</artifactId>
                <version>2.2.1</version>
                <executions>
                    <execution>
                        <id>generate-docs</id>
                        <phase>prepare-package</phase>
                        <goals>
                            <goal>process-asciidoc</goal>
                        </goals>
                        <configuration>
                            <backend>html</backend>
                            <doctype>book</doctype>
                        </configuration>
                    </execution>
                </executions>
                <dependencies>
                    <dependency>
                        <groupId>org.springframework.restdocs</groupId>
                        <artifactId>spring-restdocs-asciidoctor</artifactId>
                        <version>${spring-restdocs.version}</version>
                    </dependency>
                </dependencies>
            </plugin>
            <plugin>
                <groupId>org.springframework.boot</groupId>
                <artifactId>spring-boot-maven-plugin</artifactId>
                <configuration>
                    <excludes>
                        <exclude>
                            <groupId>org.projectlombok</groupId>
                            <artifactId>lombok</artifactId>
                        </exclude>
                    </excludes>
                </configuration>
            </plugin>
        </plugins>
    </build>
    <repositories>
        <repository>
            <id>netflix-candidates</id>
            <name>Netflix Candidates</name>
            <url>https://artifactory-oss.prod.netflix.net/artifactory/maven-oss-candidates</url>
            <snapshots>
                <enabled>false</enabled>
            </snapshots>
        </repository>
    </repositories>

</project>
```

pom.xml | ShipwreckStoreGr... | GreetingControll... | application.prop... | mylogs.log | pom.xml | ShipwreckStoreSe

```java
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 https://maven.apache.org/xsd/maven-4.0.0.xsd">
    <modelVersion>4.0.0</modelVersion>
    <parent>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-parent</artifactId>
        <version>3.0.6</version>
        <relativePath/> <!-- lookup parent from repository -->
    </parent>
    <groupId>com.shipwreckstore</groupId>
    <artifactId>ShipwreckStoreGreeting</artifactId>
    <version>0.0.1-SNAPSHOT</version>
    <name>ShipwreckStoreGreeting</name>
    <description>ShipwreckStoreGreeting</description>
    <properties>
        <java.version>17</java.version>
        <spring-cloud.version>2022.0.2</spring-cloud.version>
    </properties>
    <dependencies>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-validation</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-web</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.cloud</groupId>
            <artifactId>spring-cloud-starter-circuitbreaker-resilience4j</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.cloud</groupId>
            <artifactId>spring-cloud-starter-netflix-eureka-client</artifactId>
        </dependency>
        <dependency>
            <groupId>org.springframework.cloud</groupId>
            <artifactId>spring-cloud-starter-openfeign</artifactId>
        </dependency>

        <dependency>
            <groupId>org.projectlombok</groupId>
            <artifactId>lombok</artifactId>
            <optional>true</optional>
        </dependency>
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-test</artifactId>
            <scope>test</scope>
        </dependency>

        <dependency>
            <groupId>org.springframework.restdocs</groupId>
            <artifactId>spring-restdocs-mockmvc</artifactId>
            <scope>test</scope>
        </dependency>

        <dependency>
            <groupId>junit</groupId>
            <artifactId>junit</artifactId>
            <version>4.12</version>
            <scope>test</scope>
        </dependency>


    </dependencies>
    <dependencyManagement>
        <dependencies>
            <dependency>
                <groupId>org.springframework.cloud</groupId>
                <artifactId>spring-cloud-dependencies</artifactId>
                <version>${spring-cloud.version}</version>
                <type>pom</type>
                <scope>import</scope>
            </dependency>
        </dependencies>
    </dependencyManagement>

    <build>
        <plugins>
            <plugin>
                <groupId>org.asciidoctor</groupId>
                <artifactId>asciidoctor-maven-plugin</artifactId>
                <version>2.2.1</version>
                <executions>
                    <execution>
                        <id>generate-docs</id>
                        <phase>prepare-package</phase>
                        <goals>
                            <goal>process-asciidoc</goal>
                        </goals>
                        <configuration>
                            <backend>html</backend>
                            <doctype>book</doctype>
                        </configuration>
                    </execution>
                </executions>
                <dependencies>
                    <dependency>
```

```
ShipwreckStoreGreeting
  pom.xml
  src
    main
      java
        com
          shipwreckstore
            app
              ShipwreckStoreGreetingApplication.java
            controller
              GreetingController.java
      resources
        application.properties
ShipwreckStoreService
  log
    mylogs.log
  pom.xml
  src
    main
      java
        com
          shipwreckstore
            app
              ShipwreckStoreServiceApplication.java
            controller
              ShipController.java
            exception
              CustomizedResponseEntityExceptionHandler.java
              ExceptionResponse.java
              InvalidShipException.java
              ShipNotAvailableException.java
            model
              Ship.java
            service
              IShipService.java
              ShipServiceImpl.java
      resources
        application.properties
        logger.xml
ShipwreckStoreApplication
  pom.xml
  src
    main
      java
        com
          shipwreckstore
            app
              ShipwreckStoreApplication.java
            controller
              ApplicationController.java
            proxy
              ServiceProxy.java
      resources
        application.properties
Gateway
  pom.xml
  src
    main
      java
        com
          example
            demo
              GatewayApplication.java
      resources
        application.properties
        bootstrap.properties
Registry
  pom.xml
  src
    main
      java
        com
          example
            RegistryApplication.java
      resources
        application.properties
```

ShipwreckStore - Boot with MicroServices - Cloud Gateway- Version Update

ShipwreckStore - Boot with MicroServices - Cloud Gateway- Version Update

scription

ShipwreckStore

o Credible is a well-established leading shipwreck Store and has many branches in the state of w York. They are in need of a separate online portal that should support the below business tivities.

Add Ship Details

Modify Ship Details

List All Ship Details

u need to implement the shipwreck module of the Shipwreck Management application. The client shes to have restful web services for adding ship details, modifying the details of ship information e ship name, description, depth, Latitude, Longitude and yearDiscovered. Display the ship ormation based on the requirement. Help them to automate the above process by developing Rest rvice using Maven and incorporate microservices for the same.