

Ambassador Flow — Gemini Enterprise Sethu

Generated: 2026-07-28

Project: *gemini-enterprise-sethu* (Tilicho Labs)

Overview

An **Ambassador** is a student who is granted the AMBASSADOR role by a College Admin. They get access to the **mobile cockpit app** to monitor and nudge their assigned cohort (department · year · section) towards Gemini Enterprise activation.

Key constraints:

- One ambassador per section (department · year · section)
 - Ambassador can only see and act on their own cohort
 - Authentication is via a **signed magic link** (no password)
 - Attribution: when an ambassador shares a `/go/` link via WhatsApp, any activation through that link is credited to them
-

Ambassador Lifecycle

```
College Admin assigns AMBASSADOR role to a student
      ↓
System creates a User row linked to that student
      ↓
Worker sends a signed sign-in link to ambassador's email/WhatsApp
      ↓
Ambassador taps link → JWT issued → cockpit app opens
      ↓
Ambassador views their cohort, stragglers, leaderboard
      ↓
Ambassador shares /go/ links with unactivated students
      ↓
Student activates → attributed to that ambassador
      ↓
War-room sees ambassador leaderboard + coverage metrics
      ↓
Close-out report includes ambassador rankings
```

Authentication Flow

1. Signed Link Login

- College Admin assigns role → worker sends magic link via email/WhatsApp
- Link format: `sethu://link?token=<signed-token>`
- Ambassador taps link → app calls **POST /auth/link/redeem**
- Server validates token → issues JWT with `role: AMBASSADOR` + `tenantId`

2. Self-Serve Link Request

- If link expires, ambassador taps "Request new link"
- App calls **POST /auth/link/request-new** with email
- Server always returns generic message (no user enumeration):
"If this email belongs to an ambassador, a new sign-in link was sent."

APIs

Auth

Method	Path	Auth	Description
POST	/api/v1/auth/link/redeem	Public	Redeem signed token → get JWT
POST	/api/v1/auth/link/request-new	Public	Self-serve: request a new sign-in link

Ambassador Cockpit (AMBASSADOR role required)

Method	Path	Auth	Description
GET	/api/v1/cohorts/mine	AMBASSADOR	Own cohort — students, stragglers, stats, next milestone
GET	/api/v1/cohorts/mine/stragglers	AMBASSADOR	Paginated unactivated students with /go/ links
GET	/api/v1/cohorts/mine/students/:studentId	AMBASSADOR	Single student detail (scoped to own cohort only)
GET	/api/v1/tenants/:id/leaderboard	AMBASSADOR, COLLEGE_ADMIN	Full leaderboard ranked by activation %; ambassador's row is highlighted with myRank

People Management (COLLEGE_ADMIN role required)

Method	Path	Auth	Description
GET	/api/v1/people	COLLEGE_ADMIN	List all people; filter by role (includes AMBASSADOR)
POST	/api/v1/people/assign-role	COLLEGE_ADMIN	Bulk-grant AMBASSADOR role to selected students
POST	/api/v1/people/revoke-role	COLLEGE_ADMIN	Remove AMBASSADOR role; reverts them to Student

GET	/api/v1/people/:studentId/touches	COLLEGE_ADMIN, SUPER_ADMIN	Touch timeline; includes ambassadorName field
-----	-----------------------------------	-------------------------------	--

War Room (COLLEGE_ADMIN / SUPER_ADMIN)

Method	Path	Auth	Description
GET	/api/v1/tenants/:id/war-room/people	Authenticated	Ambassador leaderboard + faculty list + coverage ratio

Attribution (COLLEGE_ADMIN / SUPER_ADMIN)

Method	Path	Auth	Description
GET	/api/v1/tenants/:id/attribution	SUPER_ADMIN, COLLEGE_ADMIN	Top ambassadors ranked by credited touches/conversions

Dev Only (local/staging)

Method	Path	Auth	Description
POST	/api/v1/dev/ambassador-token	Dev only	Mint a JWT for a dev ambassador without a signed link

Key API Response Shapes

GET /cohorts/mine

```
{
  "ambassador": { "name": "Sneha Reddy", "section": "CSE Sem 5 · Sec A" },
  "stats": { "activated": 12, "size": 60, "pct": 20 },
  "nextMilestone": { "target": 25, "reward": "..."},
  "stragglers": [...],
  "fullRoster": [...]
}
```

GET /cohorts/mine/stragglers (paginated)

```
{
  "data": [
    { "studentId": "...", "name": "...", "phone": "...", "waLink": "/go/<token>" }
  ],
  "total": 48, "page": 1, "limit": 20
}
```

GET /tenants/:id/leaderboard

```
{
  "data": [
    {
      "rank": 1, "ambassadorId": "...", "name": "Sneha Reddy",
      "cohortSection": "CSE Sem 5 · Sec A", "activated": 22, "size": 60,
      "pct": 36.7, "streakDays": 5, "idleDays": 0, "lastActive": "2026-07-27"
    }
  ],
  "myRank": 1
}
```

GET /tenants/:id/war-room/people

```
{
  "ambassadors": [
    {
      "rank": 1, "userId": "...", "name": "Sneha Reddy",
      "cohortSection": "CSE Sem 5 · Sec A", "activated": 22, "size": 60,
      "pct": 36.7, "streakDays": 5, "idleDays": 0, "lastActive": "2026-07-27"
    }
  ],
  "faculty": [...],
  "coverageRatio": { "covered": 8, "total": 10 }
}
```

POST /people/assign-role

```
// Request
{ "studentIds": ["id1", "id2"], "role": "AMBASSADOR" }

// Response (409 if section already has ambassador)
{ "success": true, "granted": 2, "conflicts": [] }
```

Mobile App Screens

Screen	File	Description
Login	app/login.tsx	Dev: calls /dev/ambassador-token; prod: not used
Link Auth	app/(auth)/link.tsx	Receives deep link sethu://link?token=..., redeems it
Link Expired	app/(auth)/link-expired.tsx	Self-serve new link request form
Cohort Dashboard	app/(cockpit)/cohort/index.tsx	Main screen: stats, milestone, stragglers count

Full Roster	app/(cockpit)/cohort/full.tsx	All cohort students with activation status
Stragglers	app/(cockpit)/cohort/stragglers.tsx	Unactivated students; share /go/ link via WhatsApp
Student Detail	app/(cockpit)/cohort/student/[id].tsx	Individual student — touch history, activation status
Leaderboard	app/(cockpit)/progress/leaderboard.tsx	All ambassadors ranked; own row highlighted
Progress	app/(cockpit)/progress/index.tsx	Own stats over time
Rewards	app/(cockpit)/rewards/index.tsx	Milestone rewards

Mobile Hooks

Hook	Query Key	API Called
useCohort	["ambassador", "cohort"]	GET /cohorts/mine
useStragglers	["ambassador", "stragglers", page]	GET /cohorts/mine/stragglers
useStudentDetail	["ambassador", "student", studentId]	GET /cohorts/mine/students/:id
useLeaderboard	["ambassador", "leaderboard"]	GET /tenants/:id/leaderboard
useRewards	["ambassador", "rewards"]	(rewards endpoint)

Web App Surfaces (War Room / Admin)

Page	File	Ambassador Relevance
People	people/people-view.tsx	Assign/revoke AMBASSADOR role; one-per-section enforcement UI
Dashboard	dashboard/page.tsx	Ambassador count; sections without ambassadors
War Room > People	war-room/people/page.tsx	Ambassador leaderboard table (rank, %, streak, idle)
War Room > Laggards	war-room/laggards/page.tsx	Filter laggards by ambassador; "no-ambassador" segment
War Room > Attribution	war-room/attribution/page.tsx	Top ambassadors ranked by credited conversions
War Room > Close-out	war-room/close-out/page.tsx	Ambassador rankings in close-out report

Data Model (Prisma)

Role

AMBASSADOR – student ambassador; cockpit app; own cohort only

User (Ambassador row)

id, role: AMBASSADOR, tenantId, studentId (→ Student), ambassadorTokens (GoToken[])

GoToken (the /go/ interstitial link)

studentId, ambassadorId (nullable – null = campaign link, set = ambassador link)
@unique([studentId, ambassadorId]) ← one token per student-ambassador pair

AttributionTouch

originalAmbassadorId ← who shared the link
creditedAmbassadorId ← who gets the credit (can change after dispute)
channel: WA_ME ← indicates ambassador-shared link (vs WABA campaign)

Business Rules

Rule	Detail
One ambassador per section	Enforced at assign-role; 409 CONFLICT if section already covered
Own cohort only	Ambassador cannot see other sections' students
GoToken uniqueness	At most one ambassador-shared /go/ link per student
Attribution channel	WA_ME = ambassador credit; WABA = campaign; SELF_SERVE = organic
No password auth	Ambassadors use magic link only (ADR-003)
Signed link TTL	7-day expiry; self-serve re-request always returns generic response
Idle detection	Ambassador idle after 3+ days without activity (shown in war-room)
Honest numbers	Activation count comes from Google's certified data only

Worker Jobs

Job	Queue	Trigger	Action
Send invite link	SEND_INVITE_LINK_QUEUE	Role assigned	Emails/WhatsApps sethu://link? token=... deeplink to ambassador
Attribution processing	(attribution lib)	Student activates	Maps GoToken ambassadorId → originalAmbassadorId on touch

Source File Index

API

- `apps/api/src/modules/auth/auth.routes.ts`
- `apps/api/src/modules/cohorts/cohorts.routes.ts`
- `apps/api/src/modules/cohorts/cohorts.service.ts`
- `apps/api/src/modules/cohorts/stragglers.service.ts`
- `apps/api/src/modules/war-room/war-room.routes.ts`
- `apps/api/src/modules/war-room/war-room.service.ts`
- `apps/api/src/modules/people/people.routes.ts`
- `apps/api/src/modules/people/people.service.ts`
- `apps/api/src/modules/attribution/attribution.routes.ts`
- `apps/api/src/modules/attribution/attribution.service.ts`
- `apps/api/src/modules/dev/dev.routes.ts`
- `apps/api/prisma/schema.prisma`

Mobile

- `apps/mobile/app/(auth)/link.tsx`
- `apps/mobile/app/(auth)/link-expired.tsx`
- `apps/mobile/app/(cockpit)/cohort/index.tsx`
- `apps/mobile/app/(cockpit)/cohort/stragglers.tsx`
- `apps/mobile/app/(cockpit)/cohort/full.tsx`
- `apps/mobile/app/(cockpit)/cohort/student/[id].tsx`
- `apps/mobile/hooks/useCohort.ts`
- `apps/mobile/hooks/useStragglers.ts`
- `apps/mobile/hooks/useStudentDetail.ts`
- `apps/mobile/hooks/useLeaderboard.ts`

Web

- `apps/web/src/app/people/people-view.tsx`
- `apps/web/src/app/dashboard/page.tsx`
- `apps/web/src/app/(warroom)/colleges/[id]/war-room/people/page.tsx`
- `apps/web/src/app/(warroom)/colleges/[id]/war-room/laggards/page.tsx`
- `apps/web/src/app/(warroom)/colleges/[id]/war-room/attribution/page.tsx`
- `apps/web/src/app/(warroom)/colleges/[id]/war-room/close-out/page.tsx`

Shared

- `packages/shared/src/types/index.ts`
- `packages/shared/src/schemas/cohorts.ts`
- `packages/shared/src/schemas/people.ts`
- `packages/shared/src/schemas/war-room.ts`
- `packages/shared/src/schemas/attribution.ts`

Worker

- `apps/worker/src/jobs/send-invite-link.ts`
- `apps/worker/src/lib/attribution.ts`