

# Intelligent Adaptive Systems: Assignment

Chanelle Lee

April 20, 2016

## 1 Introduction

### 1.1 Adaptive Neuro-Fuzzy Inference System (ANFIS)

ANFIS is a ‘fuzzy inference system implemented in the framework of adaptive networks’ developed in the early 1990s [1]. It is called a hybrid neuro-fuzzy technique as it uses the learning capabilities of neural networks to ‘tune’ the membership functions of a Sugeno-type Fuzzy Inference System.

### 1.2 The Task

The task of this assignment is to use ANFIS to derive a representation of the inverse kinematics of the Lynxmotion robotic arm. In order to investigate this, Matlab’s anfis toolbox will be used, with the main questions to be explored:

1. What is the ideal density of training data? A balance between efficiency and effectiveness is needed; as the more training data points the more accurate the results, but the longer the system takes.
2. How to generate the initial fuzzy inference system; should genfis1 or genfis2 be used? And what parameters should they take?
3. For how many epochs should ANFIS run?
4. What should be the spread of the training data? Should the training data points be uniform over the workspace or concentrated near singularities?

Due to time constraints, the simpler problem of a two link arm will be used to investigate the first three questions; as the data sets required to train the system are much smaller, and so more exploration of parameter settings of the ANFIS is achievable. Then, the best parameters found will be used to train for a three link arm and as the three link arm gives a planar representation of the Lynxmotion arm, the final question will be investigated. Finally, these findings will be implemented on the Lynxmotion arm and compared against analytical solutions.

## 2 Two Link Arm

For this section, the Lynxmotion arm will be reduced to the two link problem as described in Fig.1<sup>1</sup>.

---

<sup>1</sup>Altered to match findings in Section2.1




Figure 1: Two Link Robotic Arm

$\theta_3$ range	trnRMSE2	chkRMSE2	trnRMSE3	chkRMSE3	cartRMSE	cartMin	cartMax
$[-\pi/2, \pi/2]$	0.3792	0.3794	0.7387	0.7389	35.7034	0.0497	99.4345
$[-\pi/2, 0]$	0.0312	0.0311	0.0682	0.0687	5.5590	0.0651	111.7742

Table 1: Results from changing range of  $\theta_3$ .

dataPoints	Epochs	MFs	trnRMSE2	chkRMSE2	trnRMSE3	chkRMSE3	cartRMSE	cartMin	cartMax	time
100	50	2	0.0848	0.0847	0.1474	0.1477	8.9448	0.0728	63.0842	2.38
100	100	2	0.0358	0.0356	0.0795	0.0801	5.8968	0.0425	25.2959	4.38
100	500	2	0.0312	0.0311	0.0682	0.0687	5.5590	0.0651	111.7742	20.17
100	1000	2	0.0311	0.0309	0.0681	0.0687	5.5723	0.0184	111.7176	39.92

Table 2: Number of Epochs Experiment

## 2.1 Joint Angle Range Issues

When the experiments were first run there were very large errors in the Cartesian and joint space (Table.1)<sup>2</sup> and this was discovered to be because the range  $\theta_3$  was set to  $[-\pi/2, \pi/2]$ , This meant that for each point in Cartesian space there were two possible solutions in the joint space with either a positive or negative value for  $\theta_3$ . This corresponded to the fact that each point in Cartesian space can be reached by the end effector in one of two configurations; elbow up or elbow down. This was solved by limiting the range of  $\theta_3$  to only negative values, i.e. limiting the robotic arm to only elbow down configurations, which is much more realistic in terms of the Lynxmotion arm’s capabilities.

## 2.2 Number of Epochs

The number of epochs controls the length of time ANFIS spends tuning the membership functions of the Fuzzy Inference System (FIS) and setting this is a matter of comparing the accuracy attained against the time taken. In Fig.2<sup>3</sup> it is clear that if only the first fifty epochs are considered the training and validation errors of the joint angles are still falling and there is little evidence to show how far they might further fall, but when one thousand epochs are run there is clearly little improvement after five hundred epochs. Table.2 also shows that the Root-Mean-Squared-Error (RMSE) in the Cartesian space reduces by less than a tenth of a millimetre from five hundred to one thousand epochs despite it taking twice as long to run. Interestingly, there is also little change in the Cartesian RMSE between one hundred epochs and five hundred epochs.. In conclusion, the best number of epochs to use for further experiments is five hundred as confidence can be had that training and validation errors in the joint angles have stabilised by this epoch, but there is little point continuing as neither the error in the joint angles or the Cartesian RMSE appear to decrease enough to be beneficial.

## 2.3 Optimising Genfis1

To investigate the best parameters using Genfis1 to create the FIS two loops were used to explore:

<sup>2</sup>Genfis1 with two membership functions, 100 data points and 500 epochs.

<sup>3</sup>Genfis1 with two membership functions and 100 data points




Figure 2: Two Link Arm with run for 50 and 1000 Epochs




Figure 3: Example of Over-Fitting

- The number of membership functions between two and ten.
- The number of data points from ten, twenty, fifty, one hundred, two hundred and five hundred.

The results from this can be seen in Appendix 1, Table 4; the last half of the two hundred data

### 2.3.1 Number of Membership Functions

The number of membership functions is used by `genfis1` to set the number of membership functions of each variable in the FIS [2]. This is important to explore as more membership functions can lead to an increase in accuracy due to a greater capacity for complexity, much like increasing the degree of a polynomial line of best fit. However, too great a capacity for complexity can lead to over-fitting, where the system has been trained so well on the training data, that it is unable to generalise in the areas in between. To continue the polynomial line of best fit example, this would be analogous to increasing the degree of the line of best fit until it passes through every given data point, but in doing so losing the overall shape of the data being described. In order to check for over-fitting, validation data is used so that the error at points not in the training set can be monitored. Then over-fitting can be identified as where the error at training points drops to near zero, but the error at validation points begins to climb, see Figure.3. A countermeasure against over-fitting is to increase the density of the training data, as seen in Figure.4, where the behaviour with different numbers of membership functions varies greatly with the density of the training data.

Another repercussion of increasing membership functions is that this also increases the time the systems takes to train and so once again a balance needs to be struck between accuracy and efficiency. Considering the results from Table

MFs	Average cartRMSE	Average time
2	15.2	5.9
3	25.8	14.0
4	46.2	31.0
5	65.7	65.5
6	37.7	125.7
7	64.1	227.6
8	52.3	380.2
9	67.0	603.8
10	51.1	904.0

Table 3: The average Cartesian RMSE and time taken for each number of membership functions from Table 4

4 and displayed in Figure.4, it is clear that the most choosing the most efficient number of membership functions depends greatly on the density of the training data. Perhaps surprisingly, Table 3 shows that, for the training data densities experimented with, two membership functions performed the best in terms of Cartesian RMSE and time. This is mostly likely due to the negative effects of over-fitting at low training data densities.

### 2.3.2 Density of Training Data

A limitation of ANFIS is that it uses supervised learning and as such needs training input-output data, which can be difficult to source for problems and for this task in particular the density of the training data can be a problem.

## 2.4 Optimising Genfis2

Genfis2 uses subtractive clustering to generate a Sugeno-type FIS structure [3] and in this experiment a genetic algorithm is used to try and determine optimal radii inputs for each joint. A genetic algorithm was chosen here, over any other type of optimisation algorithm, as it was feared that there would be many local optima, e.g. the optimal radius for each cluster. For the sake of convenience, Matlab’s built in ga function was used for this experiment; with hard constraints set on the chromosome. However, as genfis2 only accepts radii to one decimal place and the population the ga produces is to four decimal places, the inputs are rounded before genfis2. As the aim of the genetic algorithm is to find the most efficient set of parameters, as opposed to the most accurate, the fitness function used to evaluate the performance of the chromosomes is the Cartesian RMSE mitigated by the time taken.

Time problems were experienced using the genetic algorithm, as the time taken for each generation is the length of time for fitness function (in this case genfis2 and anfis) to run, multiplied by the population size. As such only a small population size of ten was used for this experiment and as such the genetic algorithm converged in a short space of time on a result which may not be globally optimal. In terms of practicality, the length of time necessary to compute the fitness function should in future be taken into account when considering the use




Figure 4: Time and Cartesian RMSE vs Number of Membership Functions for Different Numbers of Data points (from Table 4)

of a genetic algorithm. Furthermore, the need to round the chromosomes from Matlab's built-in ga function, meant there was a lot of unnecessary variation within populations.

### 3 Three Link Arm

Need to have another constraint to balance the new variable, using the pitch.

More partitions lead to better results but longer time frame especially the more complicated the system becomes.




Figure 5: Cartesian RMSE in Joint Space

#### 4 Lynxmotion Arm

#### 5 Appendix 1 - Experiment Result Tables Overflow



dataPoints	Epochs	MFs	trnRMSE2	chkRMSE2	trnRMSE3	chkRMSE3	cartRMSE	cartMin	cartMax	time
10	500	2	0.0441	0.1769	0.0595	0.2102	35.0791	2.3860	151.5126	0.32
10	500	3	0.0075	0.6026	0.0186	1.5039	88.9466	1.7816	300.7353	0.44
10	500	4	0.0016	1.5343	0.0029	2.8815	168.6123	3.1412	464.0428	0.99
10	500	5	0.0005	2.3307	0.0001	1.6801	194.8358	8.2084	519.1364	2.03
10	500	6	0.0000	0.7692	0.0000	1.1000	106.5546	1.1282	342.4532	3.91
10	500	7	0.0000	1.0441	0.0000	1.5253	191.3857	6.1158	625.5818	7.09
10	500	8	0.0000	0.8198	0.0000	0.5227	164.0823	2.6072	624.2153	11.81
10	500	9	0.0000	0.8749	0.0000	0.7083	161.5942	7.4095	629.0190	18.56
10	500	10	0.0000	1.0498	0.0000	0.7715	199.8085	4.0177	629.9484	28.28
20	500	2	0.0487	0.0707	0.0747	0.1185	12.4193	0.4108	103.9274	0.74
20	500	3	0.0196	0.0490	0.0395	0.0945	5.5069	0.3025	24.1058	1.74
20	500	4	0.0204	0.0871	0.0407	0.1851	11.8301	0.1035	64.8913	3.95
20	500	5	0.0083	1.0060	0.0151	1.4404	65.1519	0.4279	462.7651	8.43
20	500	6	0.0037	0.1839	0.0074	0.3333	35.6708	0.2279	256.3560	15.52
20	500	7	0.0018	0.3554	0.0035	0.5666	61.4179	0.3654	572.2944	28.16
20	500	8	0.0013	0.2046	0.0025	0.3664	41.7306	0.2340	212.7630	48.13
20	500	9	0.0011	0.3528	0.0015	0.3827	102.7713	0.4082	488.5110	73.61
20	500	10	0.0007	0.3804	0.0015	0.6136	109.5996	1.7098	521.3018	111.39
50	500	2	0.0371	0.0362	0.0694	0.0769	7.7817	0.1222	98.5986	4.46
50	500	3	0.0248	0.0250	0.0451	0.0512	5.1415	0.1326	99.1554	10.80
50	500	4	0.0206	0.0221	0.0411	0.0435	2.2461	0.0248	13.0735	23.72
50	500	5	0.0164	0.0177	0.0326	0.0348	1.5393	0.0175	7.7383	50.42
50	500	6	0.0124	0.0572	0.0253	0.0767	7.5921	0.0401	209.7884	96.92
50	500	7	0.0112	0.0242	0.0220	0.0487	2.1075	0.0208	23.5713	175.22
50	500	8	0.0103	0.0217	0.0195	0.0383	2.1102	0.0155	22.4959	292.86
50	500	9	0.0087	0.0214	0.0171	0.0451	2.8006	0.0122	26.8913	468.32
50	500	10	0.0081	0.0197	0.0159	0.0394	2.8987	0.0078	45.3157	699.17
100	500	2	0.0312	0.0311	0.0682	0.0687	5.5590	0.0651	111.7742	18.10
100	500	3	0.0236	0.0235	0.0446	0.0458	3.6464	0.0521	29.4106	42.97
100	500	4	0.0200	0.0202	0.0396	0.0400	1.9688	0.0156	10.9047	95.06
100	500	5	0.0158	0.0160	0.0314	0.0318	1.4229	0.0046	14.1410	201.28
100	500	6	0.0117	0.0132	0.0230	0.0261	0.9550	0.0016	8.5618	386.25
100	500	7	0.0105	0.0116	0.0199	0.0211	1.5349	0.0052	19.1859	700.12
100	500	8	0.0100	0.0107	0.0196	0.0212	1.1876	0.0100	35.0601	1167.94
100	500	9	0.0084	0.0096	0.0163	0.0189	0.7292	0.0023	7.2050	1854.52
100	500	10	0.0077	0.0107	0.0152	0.0205	1.7005	0.0072	49.1822	2776.96
200	500	2	0.0300	0.0301	0.0672	0.0675	5.6355	0.0679	168.8529	76.53
200	500	3	0.0236	0.0235	0.0440	0.0441	3.2618	0.0141	21.6430	175.64
200	500	4	0.0197	0.0197	0.0387	0.0388	1.8952	0.0042	11.8753	387.51
200	500	5	0.0146	0.0146	0.0295	0.0295	1.6488	0.0123	8.9011	816.60
200	500	6	0.0114	0.0115	0.0224	0.0226	0.8359	0.0016	6.2123	1554.44

Table 4: Two Link Arm - Genfis1 Parameter Experiment

## References

- [1] J. S. R. Jang. Anfis: adaptive-network-based fuzzy inference system. *IEEE Transactions on Systems, Man, and Cybernetics*, 23(3):665–685, May 1993.
- [2] Mathworks - genfis1. url<http://uk.mathworks.com/help/fuzzy/genfis1.html?searchHighlight=genfis1> [Accessed: 16/04/2016].
- [3] Mathworks - genfis2. <http://uk.mathworks.com/help/fuzzy/genfis2.html?searchHighlight=genfis2>, [Accessed: 16/04/2016].