

Archosaurs: Linear Regression Example

jdt

October 2021

Contents

Introduction	1
R	2
SAS	7
Code	7

Introduction

Reptiles of the subclass Archosauria include the now extinct dinosaurs and pterosaurs (flying or gliding dinosaurs) as well as birds and crocodiles. For any subclass of animals, although individual species vary greatly in size, it has been found that there is a relatively consistent relationship between body size and brain size.

In “Relative Brain Size and Behavior of Archosaurian Reptiles” (Annual Review of Ecology and Systematics 1977, by James A. Hopson) the author cites a widely observed power law relationship:

$$Brain\ wgt = k \times (Body\ wgt)^{2/3}$$

Using logarithms, this can be transformed into a linear relationship:

$$\log(Brain\ wgt) = \log(k) + 0.67 \times \log(Body\ wgt)$$

It should be noted we would expect “smart” animals, such as the mammals, to differ from “dumb” animals, such as the reptiles, by having a linear relationship with a larger intercept. In other words, “k” would be larger for mammals than reptiles. Also, it does not matter which logarithmic transformation we use (common logs, natural logs or any others), but we will use the natural log.

Power law models are based on the relationship $y = ax^b$, which can be restated as a linear relationship $\log(y) = \log(a) + b \times \log(x)$ using a logarithmic transformation. Power law models represent scale invariant relationships, that is, relationships thought to hold in the same manner for very large and very small observed values. For example, in biology the relationship between habitat area and number of species fits a power law model quite well (see Case 1 and Exercise 22 from Chapter 8

of The Statistical Sleuth, Second Edition, Ramsey and Schafer, 2002). A Web search on power law models will result in dozens of examples, taken mostly from physics and engineering. This is a typical example of a power law model. Although reptiles vary greatly in size, we would expect about the same proportion of their mass to be devoted to brain size. We expect the same for mammals, except we expect the brains of mammals to be bigger than the reptile of the same overall mass, hence the greater value for “k”.

The Task

Determine whether a power law model fits the data. In other words:

- Does it make sense to take logarithmic transformations of body weight and brain weight in order to perform a linear regression?
- Are the assumptions of the linear regression met?
- Is our final model a good fit to the data?
- Does the slope of 2/3 actually seem to match the data?

Other questions of interest:

- How do we make predictions in a power law model?
- What do large positive and negative residuals mean in this context?

R

Read data from SAS input file

```
# this data came from SASHELP.CARS
brain <- read.csv('archosaur.csv', header = TRUE)
summary(brain)
```


##	Type	Details	Body.Weight	Brain.Weight
##	Length:21	Length:21	Min. : 0.06	Min. : 0.148
##	Class :character	Class :character	1st Qu.: 19.00	1st Qu.: 4.300
##	Mode :character	Mode :character	Median : 173.60	Median : 25.000
##			Mean : 7472.37	Mean : 64.941
##			3rd Qu.: 2236.00	3rd Qu.: 100.000
##			Max. : 70000.00	Max. : 335.000

Transform Data

```
log_body.wt = log(brain$Body.Weight)
log_brain.wt = log(brain$Brain.Weight)
```

Graph of data

```
plot(log_brain.wt~log_body.wt)
abline(lm(log_brain.wt~log_body.wt))
```






Results


```
result<-lm(log_brain.wt~log_body.wt)
summary(result)
```

```
##
## Call:
## lm(formula = log_brain.wt ~ log_body.wt)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.9856 -0.3831 -0.1405  0.4919  1.7389
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  0.21507    0.24518   0.877   0.391
## log_body.wt  0.51621    0.03874  13.324 4.34e-11 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.7008 on 19 degrees of freedom
## Multiple R-squared:  0.9033, Adjusted R-squared:  0.8982
## F-statistic: 177.5 on 1 and 19 DF, p-value: 4.341e-11
```

```
plot(result)
```







SAS

Code

```
options center nodate pagesize=120 ls=80;
libname ldata '/home/jacktubbs/my_shared_file_links/jacktubbs/LaTeX/Class';

/* Simplified LaTeX output that uses plain LaTeX tables */
ods latex path='/home/jacktubbs/my_shared_file_links/jacktubbs/LaTeX/clean'
    file='archosaur.tex' style=journal
    stylesheet="sas.sty"(url="sas");

/*
http://support.sas.com/rnd/base/ods/odsmarkup/latex.html
*/
ods graphics / reset width=4.5in outputfmt=png
    antialias=on;

/*
This data set is from the JMP Case Study Library
*/

title "Archosaurs: Linear Regression Example";
data brain; set ldata.archosaur;
run;

proc contents data=brain short;
run;

data brain; set brain;
log_brain_wt = log(brain_weight);
log_body_wt = log(body_weight);
run;

proc sgplot data=brain;
    histogram brain_weight;
    density brain_weight/ type=kernel;
run;

proc sgplot data=brain;
    histogram log_brain_wt;
    density log_brain_wt/ type=kernel;
run;

proc sgplot data=brain;
    scatter y=log_brain_wt x=log_body_wt;
    reg y=log_brain_wt x=log_body_wt;
run;
```

```

proc reg data=brain plots=diagnostics;
model log_brain_wt = log_body_wt;
run;

proc transreg data=brain;
model BoxCox(brain_weight / convenient lambda=-2 to 2 by 0.05) =
    monotone(body_weight);
output out=new;
run;
title3 'Modified brain weight measurement';

proc sgplot data=new;
histogram tbrain_weight;
density tbrain_weight;
run;

ods latex close;

/* Stream a CSV representation of new_bwgt directly to the user's browser. */
/*
proc export data=new_heart
    outfile=_dataout
    dbms=csv replace;
run;

%let _DATAOUT_MIME_TYPE=text/csv;
%let _DATAOUT_NAME=heart.csv;



```


Archosaurs: Linear Regression Example

The CONTENTS Procedure

<i>Alphabetic List of Variables for WORK.BRAIN</i>
--

Body_Weight Brain_Weight Details Type





Archosaurs: Linear Regression Example

The REG Procedure

Model: MODEL1

Dependent Variable: log_brain_wt

Number of Observations Read	21
Number of Observations Used	21

Analysis of Variance					
Source	DF	Sum of Squares	Mean Square	F Value	Pr > F
Model	1	87.17316	87.17316	177.52	<.0001
Error	19	9.33022	0.49106		
Corrected Total	20	96.50338			

Root MSE	0.70076	R-Square	0.9033
Dependent Mean	2.76846	Adj R-Sq	0.8982
Coeff Var	25.31230		


Parameter Estimates					
Variable	DF	Parameter Estimate	Standard Error	t Value	Pr > t
Intercept	1	0.21507	0.24518	0.88	0.3913
log_body_wt	1	0.51621	0.03874	13.32	<.0001



Archosaurs: Linear Regression Example

The REG Procedure

Model: MODEL1


Dependent Variable: log_brain_wt





Archosaurs: Linear Regression Example

The TRANSREG Procedure



Archosaurs: Linear Regression Example

The TRANSREG Procedure

TRANSREG MORALS Algorithm Iteration History for BoxCox(Brain_Weight)					
Iteration Number	Average Change	Maximum Change	R-Square	Criterion Change	Note
1	0.78669	1.69925	0.28464		
2	0.00000	0.00000	0.94741	0.66277	Converged

Algorithm converged.

