



Two Approaches

Optimization:

2

9

• smooth, convex-concave

- SP-Mirror Prox Requires:
 - projections on
 - projections on

• Convergenze:


$$O\left(\frac{1}{t}\right)$$


$$O\left(\frac{1}{\sqrt{t}}\right)$$

$\Pi(a, b)$

$\Pi(a, b)$







• Non-smooth, convex

- Mirror Descent requires:
 - projections on
 - subgradients of

• Convergenze:

$$\min_{\Gamma \in \Pi(a,b)} f(\Gamma) \equiv \min_{\Gamma \in \Pi(a,b)} \max_{\kappa \in \mathcal{B}_F} \langle \Gamma, \kappa \rangle$$

B

F


Sinkhorn-Knopp Algo.

Edmonds Algo.

We give $O(n \log n)$ algorithm for
our decomposable functions

Optimization: Two Approaches

$$\min_{\Gamma \in \Pi(\mathbf{a}, \mathbf{b})} f(\Gamma) \equiv \min_{\Gamma \in \Pi(\mathbf{a}, \mathbf{b})} \max_{\kappa \in \mathcal{B}_F} \langle \Gamma, \kappa \rangle$$




- Non-smooth, convex
- Mirror Descent requires:

- projections on $\Pi(\mathbf{a}, \mathbf{b})$
- subgradients of f

- Convergence: $O(\frac{1}{\sqrt{t}})$

Sinkhorn-Knopp Algo.

Edmonds Algo.



- Smooth, convex-concave
- SP-Mirror Prox Requires:

- projections on $\Pi(\mathbf{a}, \mathbf{b})$
- projections on \mathcal{B}_F

- Convergence: $O(\frac{1}{t})$

We give $O(n \log n)$ algorithm for our decomposable functions

Structured OT

Application: Domain Adaptation