Combined R3/R4 policy: review-selection v1

Policy version: `r3-r4-review-selection-v1`. Active labels: `hybrid_llm` and `hybrid_llm_fixed`. Scope: banking; evaluation grid $k \in \{0, 1, 3, 5, 7, 9\}$. Both labels share all semantic processing; the allocation threshold is their only difference. The wire schema stays `r3-r4/0.1` because its fields have not changed. Wire-schema version and policy-behavior version are distinct.

Roles and decision boundaries

R3 validates tool semantics, exact scope bindings and effect limits. R4 interprets unresolved checks against the original task and observable evidence. R3 validates the whole response before using any finding, computes review priority and emits the final policy decision. The runtime gate spends review slots and executes only approved calls. The reviewer receives its independently filtered task context, not R4 recommendations or benchmark labels.

Condition	Effect
Invalid proposal/lifecycle, proven scope violation, changed recipient, exceeded exact grant or duplicate effect	R3 denies; R4 cannot override it
Every deterministic required check supported	R3 may auto-approve without R4
Eligible R4 `VIOLATED` finding on an unresolved semantic check	R3 auto-denies this proposal; no reviewer slot is spent
Eligible R4 support establishes both scope and operation relevance	R3 raises relevance to at least 0.75; unresolved checks still require reviewer selection and approval
R4 reports all checks `SATISFIED`	No execution permission or new grant; deterministic unresolved checks stay unresolved
R4 reports `NOT_APPLICABLE`	Does not disable a required check or establish relevance
Missing/partial findings, invalid output, stale identity, timeout, unavailable assessor or insufficient eligible evidence	No semantic influence; retain the deterministic/heuristic fallback
Review budget exhausted	Any call needing review is denied, even if R4 supports it

The negative path uses a **model assessment**, not a mathematically proven violation. False semantic conflicts can cause over-conservative failures. Positive semantic support can route an inappropriate call to review if the model is wrong, but cannot execute it without reviewer approval. These are empirical risks to measure rather than assumed safety guarantees.

Eligibility and response validation

Validate identity/schema, status/error consistency, unresolved check IDs, uniqueness, nonempty bounded reasons, and existing unique evidence citations. Reject the entire response before applying any finding if any validation fails. An error/unavailable response must contain no findings and must have a nonempty reason. An `ok` response must have no error.

Decision-effective findings additionally require:

1. Verified registered tool source and parameter semantics.
2. No malformed explicit task scope.
3. Complete episode evidence within the bounded request; if whole items were omitted, semantic influence is disabled for that request.
4. Citation of original instruction `u0001`, alongside any supporting observation. Observation-only citations cannot influence decisions. Citation presence does not prove factual truth or correct interpretation.
5. A returned status of `SATISFIED` or `VIOLATED` on an unresolved check outside the protected set.

Protected check IDs are `semantics`, `effect_limit`, and `rent_binding`. R4 never changes deterministic check states, grants, ledger entries or budget. Findings unsupported by these conditions are recorded as ignored. Reviewer decisions and execution observations still use trusted host callbacks.

For positive relevance, both `scope` and `operation` must be supported by R3's satisfied checks and/or eligible R4 `SATISFIED` findings. A single positive finding on an otherwise unresolved pair is insufficient. Any eligible semantic conflict takes precedence over positive relevance. Partial valid output is allowed; missing checks remain unresolved.

Allocation equations

Let n_t be the original relevance heuristic, and let R_t indicate supported scope and operation with no eligible semantic conflict. Define effective relevance


$$n_t^\star = \begin{cases} \max(n_t, 0.75), & R_t = 1, \\ n_t, & R_t = 0. \end{cases}$$


Let $v_t \in \{0, 0.5\}$ represent inspectability, $c_t \in \{0, 0.5, 1\}$ metadata consequence, and b_t remaining reviewer budget. The score and thresholds are


$$p_t = n_t^\star v_t[\alpha + (1-\alpha)c_t], \qquad \tau_{\text{fixed}} = \tau_0, \qquad \tau_{\text{dynamic}}(b_t) = \tau_0 + \frac{\delta}{b_t} \quad (b_t > 0).$$

Defaults remain $\alpha = 0.7$, $\tau_0 = 0.15$, and $\delta = 0.1$. After violation checks, a deterministic unresolved call is escalated only when $b_t > 0$, $n_t^\star > 0$, $v_t > 0$ and $p_t \geq \tau(b_t)$, with numerical tolerance 10^{-12}. Budget zero denies without division. These are hand-designed heuristics, not calibrated probabilities.

For a low-risk paraphrased balance request that previously had $n_t = 0$, supported R4 findings yield $n_t^\star = 0.75$, $v_t = 0.5$, $c_t = 0$, and $p_t = 0.2625$. At $b_t = 1$, the default dynamic threshold is 0.25: the proposal reaches independent review rather than being denied for a lexical miss. This is an illustrative regression fixture, not a model-quality result.


Validate proposal and deterministic scope/effect checks
Deterministic violation?
No
All deterministic checks supported?
No
Yes
R4 assesses unresolved checks
AUTO_APPROVE


Whole response valid?
Yes
No
Filter decision-eligible findings; log ignored findings
Eligible semantic conflict?
Yes
Keep original heuristic fallback
No
Use supported scope plus operation to raise review relevance
Apply unchanged fixed or dynamic


allocation threshold
Budget available and priority sufficient?
Yes
No
Yes
ESCALATE; gate spends one reviewer slot
Independent reviewer approves?
No or error
Yes
AUTO_DENY
Execute checked call; record actual effects



Justification: deterministic constraints protect known authorization boundaries; semantic interpretation broadens review eligibility beyond lexical matches; task-grounded semantic conflicts can save reviewer slots; independent review remains necessary for semantic-only authorization. The fixed comparator changes only the scarcity threshold, preserving a controlled allocation comparison.

Audit, evaluation and reproduction

Per-call `policy_audit` records `policy_version`, unchanged deterministic `checks`, raw validated `assessor_result`, and `semantic_influence` with mode/version, evidence completeness, accepted/ignored check IDs, conflict IDs and supported relevance. Allocation includes both `heuristic_necessity` and effective `necessity`, score and threshold. Mode `advisory` preserves stub behavior; mode `review_selection` is selected automatically by live labels. The factory does not permit policy options to silently change a live label into advisory mode.

`config.json` records the behavior version and source/prompt fingerprints. Episode results record behavior version and assessment mode. `semantic_decisions.csv` exports actual per-call policy decisions, semantic eligibility, original/effective relevance, reviewer consultation, approval and actual invocation status. Use it with `review_by_tool.csv`, failures and full audits to discuss whether semantic review selection helps or creates false denials. It does not estimate a causal effect by itself.

The stub demo intentionally remains an advisory/rules ablation. Its findings do not establish live model quality. Existing advisory-only runs cannot be relabeled as this version; generate fresh manifests/output directories, repeat development pilots and freeze before held-out evaluation. Follow the banking guide for all commands and deliverables. No benchmark improvement is assumed.