68000 Addressing Modes

(Specify the location of an operand)

1. Absolute Mode:

Effective address (EA) is in instruction.

 $[B] + [D2] \rightarrow D2$, B is the address of the operand, D2 is data register

2. Immediate Mode

Operand is in instruction

$$#50 + [D2] \rightarrow D2$$
, #50 is the operand, D2 is data register

3. Indirect Mode

Effective address (EA) is in address register

 $[[A2]] + [D2] \rightarrow D2$, A2 is address register and D2 is data register

4. Register Mode

Operand is in data register

 $[D0] + [D1] \rightarrow D1$, D0 and D1 are data register

5. Index Mode

a) Basic index mode

Effective address (EA) is generated by adding a constant value to the content of an address register (the constant has 16 bits).

$$[[A4] - $100] + [D2] \rightarrow D2$$

b) Full index mode

Effective address (EA) is generated by adding a constant value to the contents of two registers (the constant has 8 bits only).

$$EA = 5 + [A3] + [D0], [D1] - [EA] \rightarrow D1$$

6. Autoincrement Mode

Effective address (EA) is the content of a register; after accessing, register is automatically incremented to point to next item

 $[[A1]] + [D2] \rightarrow D2$, $[A1] + 2 \rightarrow A1$ (note: the increment could be 1, 2 or 4 depending on the length of the operand).

7. Autodecrement Mode

The register is decremented first, and the decremented content of the register is the effective address (EA)

[A2] - 2 \rightarrow A2, 0 \rightarrow [[A2]] (note: the decrement could be 1, 2 or 4 depending on the length of the operand).

8. Relative Mode

Effective address (EA) is generated by adding a constant value to the content of the Program Counter (PC)

- Same as index mode except constant added to PC, not An (address register)
- Relative to current instruction in the program
- 68000 has two relative modes
 - a) Basic relative mode: ADD -\$100(PC), D2;

$$[[PC]-$100] + [D2] \rightarrow D2$$

b) Full relative mode: SUB 5(PC, D0), D1

$$[D1] - [[PC] + [D0] + 5] \rightarrow D1$$