

# XML Basics

## lesson #xml01

James L. Parry  
B.C. Institute of Technology

---

## XML BASICS (Refresher)


---

**X M L** stands for eXtensible Markup Language

Used for storing object or data structure state.

Remember COMP1536!

Visualizing XML: elements (dots) may have children (below), may have text values (blue), and may have set of attributes (red)



---

## Agenda

---

1. What is XML?
2. XML Structure
3. Entities
4. Attributes
5. Design Strategies

---

## WHAT IS XML?

---

- Way of digitally representing data structures
- Adds tags to text data so that it can be processed by any application and is human-readable
- Application can understand data's meaning and how to process it
- Can be used to extend HTML, store object state, or even to define new "languages"

---

## XML Documents

---

- Documents are based on a logical tree structure
  - Documents can be recursively broken down into elements
  - Elements can have attributes
- Documents of the same "type" have the same structure
- Physically, a document can be broken up using entities - think separation into files

---

## XML Markup

---

- Represents the logical structure
- Connects/contains the physical entities
- An XML document is made up of markup and character data
- Markup processed by XML parser
- Character data passed on to application
- Markup is found between < and > just like HTML
- Reserved characters: & and ; pair can also be significant

---

## An Example XML Document

---

```
<shoes>
  <item uid="S121">
    <manufacturer>Nike</manufacturer>
    <model>hightop</model>
    <designer>Steve Nash</designer>
    <price>125.00</price>
    <in-stock>176</in-stock>
  </item>
</shoes>
```

---

## XML Design Goals

---

- Simple
- Human readable
- Platform neutral

---

## A More Complex Example

---

<pre>&lt;?xml version="1.0"?&gt; &lt;!DOCTYPE MEMO SYSTEM "memo.dtd"&gt; &lt;memo&gt;   &lt;from&gt;     &lt;name&gt;Paul Prescod&lt;/name&gt;     &lt;email&gt;papresco@prescod.com&lt;/email&gt;   &lt;/from&gt;   &lt;to&gt;     &lt;name&gt;Charles GoldFarb&lt;/name&gt;     &lt;email&gt;charles@sgmlsource.com&lt;/email&gt;   &lt;/to&gt;   &lt;subject&gt;Another Memo Example&lt;/subject&gt;</pre>	<pre>&lt;body&gt; &lt;paragraph&gt; Charles, I wanted to suggest that we &lt;emphasis&gt;not&lt;/emphasis&gt; use the typical memo example in our book. Memos tend to be used anywhere a small, simple document type is needed, but they are just &lt;emphasis&gt;so&lt;/emphasis&gt; boring! &lt;/paragraph&gt; &lt;/body&gt; &lt;/memo&gt;</pre>
---	--

---

## XML STRUCTURE

---

There are three ways to look at the structure of an XML document:

- Tree structure, conceptually
- Text document
- DOM

These all have to do with different ways of thinking about the pieces of an XML document:

- directives (document type & entities)
- elements (with attributes)

---

## Logical Structure

---

- Tree structured hierarchy
- Every document has a single outermost element, called the "root" or "document" element
- Every element can contain from 0 to many nested elements, defined using particular XML tags
- Can be navigated in a predictable way

---

## Physical Structure

---

- Character string
- Stored in 1 or more files
- XML document can be broken down physically into pieces of text or sub strings

---

## Document Contents

---

- XML signature (often forgiven)
- DOCTYPE directive (optional)
  - Entity directives (optional)
- Nested elements (at least one)
  - Attributes for elements (optional)
  - Embedded entity references (optional)

---

## Document Object Model

---

- Tree structure, where each node ...
- Has a text value (or can be empty)
- May have attributes
- May have child nodes

There is a Javascript API for this.

The W3C prescribes language-neutral API for interfaces

---

## ENTITIES

---

- An abbreviation or short form for some text
- Allow a document to be broken up into multiple storage objects or files (external)
- Allow substitution within a file (internal)
- An entity reference substitutes the entity text for the abbreviation

---

## Entity Declaration

---

- Directives define them
  - Abbreviation is entity name
  - Long form is entity content
  - Can build symbolic constants using entity references
- ```
<!ENTITY dtd "document type definition">
<!ENTITY inverted-exclamation "&#161;">
```

---

## parsed Entities

---

- If an entity contains XML that should be parsed by the XML processor, it is called a parsed entity
- Simple example of parsed entity with markup:  
`<!ENTITY dtd "<term> document type definition</term>">`
- This is also an example of an internal entity

---

## External Entities

---

- Content of entity can come from another file...  
`<!ENTITY intro-chapter SYSTEM "http://www.megacorp.com/intro.xml">`
- Keyword "SYSTEM" lets processor know that the next thing in the declaration is a URI
- Content of the entity comes from URI

---

## Entity Reference

---

- A document will use an entity through an entity reference
- & and ; combination is used, around the name of the entity to substitute
- The reference will be replaced by the entity contents

```
<!DOCTYPE MAGAZINE[
<!ENTITY title "Painters Quarterly">
]>
<MAGAZINE>
<TITLE>&title;</TITLE>
<p>Welcome to the first issue of &title;.
&title; is targeted at the amateur
painter.</p>
</MAGAZINE>
```

---

## Unparsed External Entities

---

- Used for data such as images
- Application does not expect the XML processor to parse this data
- NDATA indicates that this is an unparsed entity
- GIF Indicates type of data

```
<!ENTITY picture SYSTEM
"http://www.home.org/mydog.gif"
NDATA GIF>
```

---

## ATTRIBUTES

---

- An attribute is a name followed by an equal sign then an attribute value
- Allows an author to attach extra information to the elements in a document
- An attribute value can be any characters except the ones that start markup
- Used to store information about a tag
- Used for values that are unique to element as a whole and unlikely to change (see example)

---

## Attributes vs Elements

---

- Attributes cannot contain elements or sub-attributes
- Specified once and in any order
- Elements must occur in order specified and may be specified more than once
- Attributes are properties, elements are parts

---

## Structure and Use

---

- Text strings with no explicit structure
- Or simple lists of strings
- Different elements can have attributes with the same name; you should have same semantics
- Attributes are considered immutable ... second or subsequent attribute settings are ignored

---

## Attribute Types

---

- Attribute types enforce lexical and semantic constraints
- Simplest type is the StringType which is made up of character data, CDATA
- Any string of characters
- Tokenized types:
  - Name token or tokens
  - ID and IDREF - used for cross referencing
  - Entity - can refer to external unparsed entities like graphics file

---

## Attribute Example

---

```
<customer cust_id="12345">
  <name salute="Mr" nickname="Bobby">Smith, Robert</name>
  <title>Manager</title>
  <company>My Company Inc.</company>
</customer>
```

---

## XML STRATEGIES

---

- Goals to shoot for:
  - Logical or intuitive
  - Constrainable
  - Easy to process
- Bad things?  
Nothing is right for all uses
- Strategies
  - Element centric
  - Attribute centric
  - Combination

---

## Congratulations!

---

You have completed lesson #xml01: XML Basics

If you would take a minute to [provide some feedback](#), we would appreciate it!

The next activity in sequence is: [xml02](#) Constraining XML

You can use your browser's back button to return to the page you were on before starting this activity, or you can jump directly to the course [homepage](#), [organizer](#), or [reference](#) page.