Statistical Validation for Digital Twins: Global and Subdomain Hypothesis Testing

Chaoan Li, Xianyang Zhang, and Rui Tuo

Department of Industrial and Systems Engineering, Texas A&M University

Before you trust your digital twin — know where it matches reality, and with what confidence

Texas Digital Twin Symposium

Why Digital Twins Need Statistical Validation

Digital twins rely on simulators that must be statistically certified before deployment. A simulator may agree with physical data *on average* while diverging critically in specific operating regimes.

Validation should answer:

- *In which operating regions does the simulator match the physical system?*
- *With what statistical confidence can we certify this agreement?*

Global testing certifies overall simulator fidelity. Subdomain analysis delivers **region-specific reliability guarantees** for digital twin deployment.

Statistical Formulation

Physical observations y_i are compared with simulator predictions $y^s(x)$ — the candidate digital twin component:

$$y_i = f(x_i) + e_i, \qquad i = 1, \ldots, n,$$

where $f(x)$ is the true physical process and $y^s(x)$ is the simulator's prediction.

Global fidelity assessment

$$H_0 : \ f(x) = y^s(x) \quad \forall x \in \Omega.$$

Subdomain fidelity assessment

$$H_{0i} : \ f(x) = y^s(x) \quad \forall x \in \Omega_i.$$

The goal is to **certify in which operating regions the simulator can be trusted as a digital twin component**, and with what probability.

Spectral Detection of Simulator Discrepancy

Key idea: expand the simulator–reality discrepancy $(\hat{f}_n - y^s)\sqrt{\hat{p}_n}$ in an orthogonal Fourier basis and inspect the coefficients.

- Structured deviations appear as **large Fourier coefficients**.
- Spectral decomposition separates global drift from **localized discrepancies**.
- The **maximum standardized coefficient** serves as the test statistic.
- Subregion Fourier bases enable **localized fidelity assessment**.


$$T = \max_{i \geq 1} \left| \frac{\sqrt{n}\, \rho_i\, \hat{s}_n^{(i)}}{\hat{\sigma}_n} \right|$$

$\hat{s}_n^{(i)}$: weighted Fourier coefficient of estimated discrepancy

ρ_i : decay weights controlling high-frequency noise

Method Overview: FMMT

FMMT combines discrepancy estimation with frequency-domain testing to certify simulator fidelity — providing the statistical foundation for reliable digital twin deployment, globally and by operating region.



Core workflow

- Estimate the simulator–reality discrepancy from physical observations and simulator predictions.
- Project that discrepancy onto weighted generalized Fourier bases.
- Assess fidelity via the largest standardized spectral coefficient.

The core test statistic is

$$T = \max_{i \geq 1} \left| \frac{\sqrt{n}\, \rho_i\, \hat{\mathbf{s}}_n^{(i)}}{\hat{\sigma}_n} \right|.$$

The same machinery supports one global test and a family of subdomain tests.

Key Theoretical Result

Under H_0, the weighted generalized Fourier coefficients are asymptotically Gaussian. This yields a closed-form limiting law for the maximum modulus statistic.

$$\lim_{n \to \infty} \mathbb{P}(T \leq t) = \prod_{i=1}^{\infty} (2\Phi(t/\rho_i) - 1).$$

Why it matters for digital twins


- Closed-form p-values — no costly resampling at every subdomain.
- Calibration is interpretable and stable across global and localized tests.
- Asymptotics justify principled fidelity localization, not ad hoc thresholding.

This theory makes FMMT practical for certifying digital twin components across many scientifically meaningful operating regimes.


Simulation Study

Setting: We assess sensitivity to localized subdomain twin–reality discrepancies. Under the null hypothesis (perfect twin fidelity), $H_0 : f_1(x) = f_2(x) = e^x$.


i. Sub1 Low Frequency: $H_1 : f_2(x) = e^x + c\sin(6\pi x)$ on $[0, 1/3)$



ii. Sub1 High Frequency: $H_1 : f_2(x) = e^x + c\cos(12\pi x)$ on $[0, 1/3)$



iii. Multi Subdomain: $H_1 : f_2(x) = e^x + c\sin(6\pi x)$ on $[0, 2/3)$




Key Observations:

- **Type I Error Control:** Accurate calibration under perfect twin fidelity ($c = 0$) across all methods;
- **Precise Localization:** Individual subdomain tests successfully isolate the operating region of reduced fidelity while the global test dilutes the signal;
- **High Sensitivity:** FMMT demonstrates strong power against localized twin–reality discrepancies, remaining highly competitive with Bonferroni-corrected procedures.

Application: Compressible Shear Layer

Main result: reduced twin fidelity is localized to

$$M_c \in [0.75, 1.0].$$



Physical observations are compared with a simulator (surrogate) for compressible shear-layer behavior — a classical digital twin validation benchmark on $[0, 1.5]$.

- the global test detects significant overall twin–reality discrepancy;
- subdomain testing pinpoints the operating region of reduced fidelity;
- the localized result provides actionable guidance for twin refinement.

Contributions & Takeaways

- A unified frequentist framework for **global** and **subdomain** statistical certification of digital twin simulators.
- A Fourier Maximum Modulus Test (FMMT) with a tractable asymptotic null distribution.
- Localized inference identifying **which operating regions** of the simulator can be trusted for digital twin deployment.
- Strong power against regional discrepancies that are diluted by global summaries.

Trustworthy digital twins require a statistical foundation: probabilistic, region-specific simulator certification.

For twin refinement, the local answer is the actionable one.

Future Work & Collaboration

- **Extension to High-Dimensional Inputs:** Developing adaptive basis selection for complex parameter spaces.
- **Real-time Model Refinement:** Integrating FMMT into automated calibration pipelines.

Welcome Collaboration!

We are looking for new applications in simulator validation and digital twins. Email us to discuss!

Connect with Us

Chaoan Li
chaoan@tamu.edu
Dr. Rui Tuo
ruituo@tamu.edu
Dept. of Industrial and Systems Engineering
Texas A&M University
Supported by NSF grants DMS-2312173 and CNS-2328395.