Principles of Database Systems (CS307)

Lecture 7-1: Application Development

Yuxin Ma

Department of Computer Science and Engineering Southern University of Science and Technology


- Most contents are from slides made by Stéphane Faroult and the authors of Database System Concepts (7th Edition).
- Their original slides have been modified to adapt to the schedule of CS307 at SUSTech.

Application Programs and User Interfaces

- Most database users do not use a query language like SQL
- An application program acts as the intermediary between users and the database
 - Applications split into
 - front-end
 - middle layer
 - backend
- Front-end: user interface
 - Forms
 - Graphical user interfaces
 - Many interfaces are Web-based

Application Architecture Evolution

- Three distinct era's of application architecture
 - Mainframe (1960's and 70's)
 - Personal computer era (1980's)
 - Web era (mid 1990's onwards)
 - Web and Smartphone era (2010 onwards)




Web Interface

- Web browsers have become the de-facto standard user interface to databases
 - Enable large numbers of users to access databases from anywhere
 - Avoid the need for downloading/installing specialized code, while providing a good graphical user interface
 - JavaScript, Flash and other scripting languages run in browser, but are downloaded transparently
 - Examples: banks, airline and rental car reservations, university course registration and grading, and so on.

The World Wide Web

- The Web is a distributed information system based on hypertext.
- Most Web documents are hypertext documents formatted via the HyperText Markup Language (HTML)
- HTML documents contain
 - text along with font specifications, and other formatting instructions
 - hypertext links to other documents, which can be associated with regions of the text.
 - forms, enabling users to enter data which can then be sent back to the Web server

Three-Layer Web Architecture



HTML and **HTTP**

- HTML provides formatting, hypertext link, and image display features
 - including tables, stylesheets (to alter default formatting), etc.
- HTML also provides input features
 - Select from a set of options
 - Pop-up menus, radio buttons, check lists
 - Enter values
 - Text boxes
 - Filled in input sent back to the server, to be acted upon by an executable at the server
- HyperText Transfer Protocol (HTTP) used for communication with the Web server

JavaScript

- JavaScript very widely used
 - Forms basis of new generation of Web applications (called Web 2.0 applications)
 offering rich user interfaces
- JavaScript functions can
 - Check input for validity
 - Modify the displayed Web page, by altering the underling document object model (DOM) tree representation of the displayed HTML text
 - Communicate with a Web server to fetch data and modify the current page using fetched data, without needing to reload/refresh the page
 - Forms basis of AJAX technology used widely in Web 2.0 applications
 - E.g. on selecting a country in a drop-down menu, the list of states in that country is automatically populated in a linked drop-down menu

Application Architectures

Controller Internet Web browser View **Data Access**

Model

Database

Layer

Web/Application Server

- Application layers
 - Presentation or user interface
 - model-view-controller (MVC) architecture
 - model: business logic
 - view: presentation of data, depends on display device
 - controller: receives events, executes actions, and returns a view to the user
 - business-logic layer
 - provides high level view of data and actions on data
 - often using an object data model
 - hides details of data storage schema
 - data access layer
 - interfaces between business logic layer and the underlying database
 - provides mapping from object model of business layer to relational model of database

Business Logic Layer

- Provides abstractions of entities
 - E.g., students, instructors, courses, etc
- Enforces business rules for carrying out actions
 - E.g., student can enroll in a class only if she has completed prerequsites, and has paid her tuition fees
- Supports workflows which define how a task involving multiple participants is to be carried out
 - E.g., how to process application by a student applying to a university
 - Sequence of steps to carry out task
 - Error handling
 - E.g. what to do if recommendation letters not received on time

Object-Relational Mapping

- Allows application code to be written on top of object-oriented data model, while storing data in a traditional relational database
 - Alternative: implement object-oriented or object-relational database to store object model
 - Has not been commercially successful
- Schema designer must provide a mapping between object data and relational schema
 - E.g., Java class Student mapped to relation student, with corresponding mapping of attributes
 - An object can map to multiple tuples in multiple relations
- Application opens a session, which connects to the database
- Objects can be created and saved to the database using session.save(object)
 - Mapping used to create appropriate tuples in the database
- Query can be run to retrieve objects satisfying specified predicates

Web Services

- Allow data on Web to be accessed using remote procedure call mechanism
- Two approaches are widely used
 - Representation State Transfer (REST): allows use of standard HTTP request to a URL to execute a request and return data
 - Returned data is encoded either in XML, or in JavaScript Object Notation (JSON)
 - Big Web Services:
 - Uses XML representation for sending request data, as well as for returning results
 - Standard protocol layer built on top of HTTP

Self Study

- Key points:
 - Techniques / libraries / APIs to connect to a database (e.g. PostgreSQL) and run SQL querys in a program
 - ODBC, JDBC?
 - SQLAlchemy? Spring Boot? Hibernate?
 - (Web) Backend Frameworks
 - Spring Boot, Flask, Django
 - NodeJS
 - Frontend Frameworks
 - React, Vue