

## CS323 2025F Quiz #2

There are ten questions in this quiz.

1. Please put down your student ID. \*

2. What is the primary purpose of syntax-directed translation in a compiler? \*

- ☐ To optimize the generated machine code.
- ☒ To associate semantic rules with productions in a context-free grammar.
- ☐ To resolve variable names to their memory addresses.
- ☐ To convert high-level code into assembly language.

3. Which of the following statements best describes an L-attributed definition? \*

- ☒ It allows both synthesized and inherited attributes, with inherited attributes being able to depend on siblings to the left.
- ☐ It allows only synthesized attributes.
- ☐ It allows both synthesized and inherited attributes, with no restrictions on dependencies.
- ☐ It is evaluated in a single pass during parsing.

4. In the context of intermediate code generation, what is a key characteristic of Three-Address Code (TAC)? \*

- ☒ Each instruction can have at most one operator and three operands.
- ☐ It is a high-level representation very close to the source language.
- ☐ It is the final machine code ready for execution.
- ☐ Each instruction performs a complex operation involving multiple array indices.

5.The primary advantage of using a Directed Acyclic Graph (DAG) over an Abstract Syntax Tree (AST) for an expression is that a DAG: \*

- ☐ Is easier to construct during parsing.
- ☐ Explicitly represents the flow of control in the program.
- ☐ Identifies common subexpressions, allowing for more straightforward optimization.
- ☐ Can be directly executed by an interpreter.

6.Which intermediate representation is characterized by representing each instruction as an operation, two source operands, and one destination operand? \*

- ☐ Postfix Notation
- ☐ Abstract Syntax Tree (AST)
- ☐ Quadruples
- ☐ Triples

7.A key difference between triples and quadruples in three-address code is: \*

- ☐ Triples use explicit temporary variable names, while quadruples do not.
- ☐ Quadruples are more compact in memory than triples.
- ☐ Quadruples are easier to rearrange during optimization because they use explicit names for temps.
- ☐ Triples are a higher-level representation than quadruples.

8.When generating three-address code for an array access like  $A[i] = j$ , what is the essential calculation that must be performed? \*

- ☐ Compute the memory address of the element  $A[i]$ .
- ☐ Check that the types of  $i$  and  $j$  are compatible.
- ☐ Ensure that the array  $A$  has been declared.
- ☐ Generate a runtime check to confirm that the index  $i$  is within bounds.

9. An S-attributed definition is best described as: \*

- ☒ An SDD that uses only synthesized attributes.
- ☐ An SDD that uses only inherited attributes.
- ☐ An SDD that can be evaluated in any order.
- ☐ An SDD that is suitable for top-down parsing only.

10. In the representation of three-address code using "indirect triples", the primary benefit over simple triples is: \*

- ☐ They use less memory by eliminating the need for an operation field.
- ☒ They simplify the manipulation of the code by allowing instructions to be easily reordered.
- ☐ They allow for an unlimited number of operands per instruction.
- ☐ They are directly executable by a virtual machine.

11. When generating three-address code for a short-circuit logical AND operation (e.g., `a && b`), the control-flow translation is used primarily to: \*

- ☐ Improve performance by calculating both operands in parallel.
- ☐ Ensure the correct operator precedence is maintained in the code.
- ☒ Prevent the evaluation of the second operand if the first operand is false.
- ☐ Allocate a single temporary variable for the entire expression