



XTMCU02 Datasheet

Microcontroller board for XeThru radar sensors

XeThru Datasheet **by Novelda AS**

B Preliminary - June 09, 2017

Summary

XTMCU02 is a microcontroller board suitable for connection to XeThru radar sensors




Table of Contents

List of Features	2
Order Information	3
Physical Dimensions	4
Connectors	4
16-pin XeThru Interface Connector	4
USB Connector	5
Programming Connector	5
16-pin XeThru Radar Connector	5
Hardware Revisions	6
Identifying HW revision	6
XTMCU02 rev.2	6
XTMCU02 rev.3	6
XTMCU02 rev.4	6
Schematics, Bill of Material and PCB Layout	6
Support and Resources	6
Disclaimer	7

1 List of Features

- Microcontroller board for XeThru UWB radar sensors
- ARM Cortex-M7 MCU
- 8 MB SDRAM
- Connector for antenna and radar board
- Micro USB connector
- 16-pin XeThru interface connector
- Multi color LED



XTMCU02 top view




XTMCU02 bottom view

1.1 Order Information

XTMCU02 is not sold separately. XTMCU02 is included in the X4M03 product. Refer to X4M03 datasheet for Order Information.



2 Physical Dimensions



XTMCU02 Physical dimensions

3 Connectors

3.1 16-pin XeThru Interface Connector

The 16-pin header is compatible with other XeThru sensors such as X2M200 and can be used to power and communicate with XTMCU02. I/O voltage is 3.0V. Refer to the XTMCU02 schematics and the Atmel SAM S70 datasheet for additional details of operation.

Pin	Name	Type
1	VDD_EXT	Power, 3.3 - 5.5V
2	GND	Power
3	MOSI/RX	I/O
4	MISO/TX	I/O
5	SCLK	I/O



Pin	Name	Type
6	nSS	I/O
7	nRESET	Input with pull-up
8	IO7/WAKEUP	I/O
9	IO8/SWCLK	I/O
10	IO9/SWDIO	I/O
11	IO1	I/O
12	IO2	I/O
13	IO3	I/O
14	IO4	I/O
15	IO5	I/O
16	IO6	I/O

3.2 USB Connector

USB micro type B connector supporting USB 2.0 High Speed. This connector can be used to power and communicate with XTMCU02.

3.3 Programming Connector

The 10-pin Programming Connector is compatible with Atmel's development tools for the Atmel SAM S70 microcontroller used in XTMCU02 and is intended for programming and debugging of the microcontroller.

3.4 16-pin XeThru Radar Connector

A 16-pin socket for connecting the 16-pin header from the X4A02 antenna board or similar UWB radar sensors. Signal descriptions below describes signal names when connected to X4A02. Refer to schematics for alternative use of this connector.

Pin descriptions

Pin	Name	Pin	Name
1	VDD3V	2	GND
3	QSPI_SCLK/SPI_SCLK	4	GND
5	QSPI_IO0/SPI_MOSI	6	GND
7	QSPI_IO1/SPI_MISO	8	GND
9	QSPI_IO2	10	GND
11	QSPI_IO3	12	GND
13	QSPI_nSS/SPI_nSS	14	X4_ENABLE



Pin	Name	Pin	Name
15	X4_GPIO1	16	X4_GPIO2

4 Hardware Revisions

4.1 Identifying HW revision



How to identify HW revision of XTMCU02

4.2 XTMCU02 rev.2

Initial revision used for production of XTMCU02.

4.3 XTMCU02 rev.3

MCU change from 1MB to 2MB version.

4.4 XTMCU02 rev.4

MCU clock source changed from crystal to oscillator.

5 Schematics, Bill of Material and PCB Layout

Schematics, bill of material and PCB layout files for XTMCU02 can be downloaded from www.xethru.com.

6 Support and Resources

Development support, resources, links to development partners and resellers can be found on Novelda's web site www.xethru.com.



7 Disclaimer

Novelda™, XeThru™ and others are registered trademarks or trademarks of Novelda AS. Other terms and product names may be trademarks of others.

DISCLAIMER: The information in this document is provided in connection with Novelda products. No license, express or implied, by estoppel or otherwise, to any intellectual property right is granted by this document or in connection with the sale of Novelda products. EXCEPT AS SET FORTH IN THE NOVELDA TERMS AND CONDITIONS OF SALES LOCATED ON THE NOVELDA WEBSITE, NOVELDA ASSUMES NO LIABILITY WHATSOEVER AND DISCLAIMS ANY EXPRESS, IMPLIED OR STATUTORY WARRANTY RELATING TO ITS PRODUCTS INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT SHALL NOVELDA BE LIABLE FOR ANY DIRECT, INDIRECT, CONSEQUENTIAL, PUNITIVE, SPECIAL OR INCIDENTAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS AND PROFITS, BUSINESS INTERRUPTION, OR LOSS OF INFORMATION) ARISING OUT OF THE USE OR INABILITY TO USE THIS DOCUMENT, EVEN IF NOVELDA HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. Novelda makes no representations or warranties with respect to the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and products descriptions at any time without notice. Novelda does not make any commitment to update the information contained herein. Unless specifically provided otherwise, Novelda products are not suitable for, and shall not be used in, automotive applications. Novelda products are not intended, authorized, or warranted for use as components in applications intended to support or sustain life.

SAFETY-CRITICAL, MILITARY, AND AUTOMOTIVE APPLICATIONS DISCLAIMER: Novelda products are not designed for and will not be used in connection with any applications where the failure of such products would reasonably be expected to result in significant personal injury or death ("Safety-Critical Applications") without an Novelda officer's specific written consent. Safety-Critical Applications include, without limitation, life support devices and systems, equipment or systems for the operation of nuclear facilities and weapons systems. Novelda products are not designed nor intended for use in military or aerospace applications or environments unless specifically designated by Novelda as military-grade. Novelda products are not designed nor intended for use in automotive applications unless specifically designated by Novelda as automotive-grade.