

Experiment 5

Implement Functions: Count – Sort – Limit – Skip – Aggregate using MongoDB

```
db.products.insertMany([
  { _id: 1, name: "Laptop",      category: "Electronics", price: 50000 },
  { _id: 2, name: "Smartphone", category: "Electronics", price: 30000 },
  { _id: 3, name: "Chair",      category: "Furniture",   price: 2000  },
  { _id: 4, name: "Table",      category: "Furniture",   price: 4000  },
  { _id: 5, name: "TV",        category: "Electronics", price: 45000 }
]);
```

1) Count() – count total documents

```
db.products.find().count();
```

5

2. Sort – Sort by price descending

```
db.products.find().sort({ price: -1 });
```

```
[
  { _id: 1, name: "Laptop",    price: 50000 },
  { _id: 5, name: "TV",       price: 45000 },
  { _id: 2, name: "Smartphone", price: 30000 },
  { _id: 4, name: "Table",    price: 4000  },
  { _id: 3, name: "Chair",    price: 2000  }
]
```

3. Limit – Show only 3 highest priced products

```
db.products.find().sort({ price: -1 }).limit(3);
```

```
[
  { _id: 1, name: "Laptop",    price: 50000 },
  { _id: 5, name: "TV",       price: 45000 },
  { _id: 2, name: "Smartphone", price: 30000 }
]
```

4. Skip – Skip first 2 documents from sorted result

```
db.products.find().sort({ price: -1 }).skip(2);
```

```
[
  { _id: 2, name: "Smartphone", price: 30000 },
  { _id: 4, name: "Table",      price: 4000  },
  { _id: 3, name: "Chair",     price: 2000  }
]
```

5. Aggregate – Group by category and find total price

```
db.products.aggregate([
  { $group: { _id: "$category", totalPrice: { $sum: "$price" } } }
]);

[
  { _id: "Electronics", totalPrice: 125000 },
  { _id: "Furniture",    totalPrice: 6000   }
]
```