Reinforcement Learning for Investigating, Acting and Escalating in IT Incident Triage and Response: A Systematic Literature Review

Charis Opol

*Department of Computing and Technology, Faculty of Engineering, Design and Technology, Uganda Christian University, [**city**], [**state or region, if used**], Uganda.

Corresponding author(s). E-mail(s): B29654@students.ucu.ac.ug; charisopol@gmail.com;

Abstract

Information technology (IT) support teams must decide how to handle an incident before its cause is known: investigate further, apply a fix, or pass the incident to a person. This review examines how reinforcement learning and related sequential methods are applied to IT incident handling, which of these three decisions their agents make, how operational rules are enforced, and how the agents are evaluated. Following the Preferred Reporting Items for Systematic Reviews and Meta-Analyses (PRISMA) 2020 guideline, searches of Scopus, IEEE Xplore and the ACM Digital Library on 23 October 2026 returned 4,399 records. After 73 duplicates were removed and 4,195 records were filtered out automatically, 131 were screened, 40 reports were assessed in full, and 34 studies (2020–2026) were included and appraised with an eight-item checklist. Four studies represent the hidden incident state with an explicit belief. Seventeen give the agent an information-gathering action and 7 include escalation to a person; only one combines all three decisions, and its escalation is fixed by design rather than learned. Five use a hard filter or shield, and 3 report what happens to a blocked or uncertain decision. Decision quality is measured in 31 studies, escalation behaviour in 5, constraint compliance in 4, and robustness in 15. The evidence is recent (27 studies from 2025 or 2026) and of uneven quality: 12 meet at most two checklist items. No study reports a single policy that learns to investigate, act or escalate for IT service incidents under explicit rules.

Keywords: Reinforcement learning, IT incident management, Incident triage, Escalation, Safe reinforcement learning, Systematic literature review

ORCID: Charis Opol https://orcid.org/0009-0003-7417-7984

Acknowledgements. [Acknowledgements to be supplied by the author, or this section deleted. The names of any funding organisations must be written in full.]

1 Introduction

Organisations depend on information technology (IT) services that are expected to remain available, and incident management is the process that restores those services when they fail. Chen et al. (2020) describe it as the process of detecting a service problem, creating an incident, determining its cause, restoring the service, and capturing knowledge to prevent a recurrence. Triage is the stage at which a reported incident is assessed and directed towards resolution. Chen et al. (2020) define it as engaging the team responsible for investigating the problem, and Remil et al. (2024) use the term more broadly for the prioritisation, assignment and classification of incidents. In both descriptions, triage is a set of decisions made before the cause of the incident is known. The abbreviations used in this review are listed in Table 1.

Table 1 Abbreviations used in this review and their meanings

Abbreviation	Meaning
AIOps	Artificial Intelligence for IT Operations
CAGE	Cyber Autonomy Gym for Experimentation
CMDP	Constrained Markov Decision Process
DQN	Deep Q-Network
EC / IC	Exclusion criterion / Inclusion criterion
ICS	Industrial Control System
IDS	Intrusion detection system
IoT	Internet of Things
IT	Information technology
LLM	Large Language Model
MCC	Matthews Correlation Coefficient
MDP	Markov Decision Process
MTTR	Mean Time to Recovery or Resolution
OT	Operational technology
POMDP	Partially Observable Markov Decision Process
PPO	Proximal Policy Optimisation
PRISMA	Preferred Reporting Items for Systematic Reviews and Meta-Analyses
RCA	Root Cause Analysis
RL	Reinforcement Learning
ROC-AUC	Area under the receiver operating characteristic curve
SO / SRQ	Specific Objective / Systematic Review Question
SOC	Security Operations Centre

These decisions are difficult because the evidence available when they are made is often incomplete or conflicting. In their study of incident management at Microsoft, Chen et al. (2020) found that distinct problems can produce similar symptoms, so that the symptoms alone may not identify the responsible team. Remil et al. (2024) note that data in real IT environments is commonly noisy and incomplete. Yet many triage models produce one prediction per incident report and are evaluated with classification

or ranking metrics (Remil et al. 2024). A model of this kind returns an answer for every report. It has no way to state that more evidence is needed first, and no way to pass the incident to a person.

Reinforcement learning (RL) offers a different framing. In RL, an agent learns a policy, which is a rule for choosing actions, by acting in an environment and receiving rewards that reflect the consequences of its actions (Sutton and Barto 2018). When the agent cannot observe the true state of the environment, the problem can be described as a partially observable Markov decision process (POMDP), in which the agent keeps a belief about the hidden state and may choose an action for the information it yields, weighing the cost of that information against its value (Kaelbling et al. 1998). Under this framing, triage becomes a sequence of decisions: the agent can gather more evidence, recommend an action, or hand the incident to a human expert.

Two further requirements follow when such an agent is meant for IT operations. The first is that its actions must respect operational rules. A reward signal alone does not ensure this, because penalising an undesirable action in the reward does not guarantee that the agent never selects it (Könighofer et al. 2025), and Remil et al. (2024) state that automatic healing actions need to be executed safely. The second is that the agent must know when to involve a person. Learning to defer trains a model to decide when a human should take over (Madras et al. 2018), and recent work treats escalation as a decision with costs in both directions, since a reviewer's attention is limited (Turan 2026).

The literature review for the project of which this review is part (Chapter Two of the project report) found that these strands have developed largely apart. Studies of information gathering let an agent choose between looking further and deciding (Janisch et al. 2019; Kim and Dán 2025), studies of deferral let it choose between deciding and handing over (Madras et al. 2018; Joshi et al. 2023), and a shielded agent proposed for incident response selects responses without choosing whether to investigate or escalate (Alauthman et al. 2026). That review was thematic and not systematic. It drew on a core set of collected publications and on a database search run on 13 October 2026, which returned 10,694 records that were filtered by keyword and not screened. Its conclusions about gaps were therefore conclusions about the literature it had read. This review replaces that search with a narrower, documented one, screens its results against fixed criteria, and synthesises what the included studies report.

The project plans an RL agent for IT incident triage that chooses among requesting a diagnostic check, recommending a fix that the organisation's operational rules permit, and escalating to a human expert, with every proposal checked by an independent rule-based mechanism. The agent is to be trained and evaluated in simulation. Because this review prepares for that study, it could lean towards the planned design. Three measures limit this. The eligibility criteria were written before screening, the decisions that required interpretation are stated in Section 2.5, and the outcome of every report sought is listed in Table S1 of Online Resource 1. These measures do not remove the risk, because the screening and extraction were not independently duplicated (Section 5).

The review addresses five systematic review questions (SRQ1–SRQ5):

- **SRQ1:** How have IT incident handling tasks been formulated as Markov decision process (MDP), POMDP or RL problems, and how is incomplete or conflicting evidence represented in them?
- **SRQ2:** Which decisions do the agents make (gathering information, recommending or taking an action, escalating to a human), and does any study combine all three?
- **SRQ3:** How are operational constraints enforced, for example by a shield, action masking, constrained optimisation, a reward penalty or human approval, and what happens when an action is blocked?
- **SRQ4:** Which environments, datasets, baselines and evaluation metrics are used?
- **SRQ5:** How is robustness to missing, unreliable or ambiguous evidence evaluated, and what results are reported?

The general objective is to systematically identify and synthesise peer-reviewed studies that apply RL or sequential decision-making to IT incident management, with attention to how they represent uncertain evidence, which decisions the agent makes, how constraints are enforced, and how the agents are evaluated. Table 2 gives the five specific objectives (SO1–SO5), the question each answers, the research question of the project that it informs, and the gap that motivated it. The gaps in the table are those stated by the project's thematic review before this search; Section 4 returns to each of them in the light of the included evidence.

2 Methods

This study is a systematic literature review reported according to the Preferred Reporting Items for Systematic Reviews and Meta-Analyses (PRISMA) 2020 guideline (Page et al. 2021) and guided by the review procedure for computing proposed by Kitchenham and Charters (2007). A systematic approach was chosen because it makes the search, selection and extraction of studies transparent and reproducible, and because the earlier search for the project returned too many records to screen. The design follows the five objectives and questions in Table 2. The protocol was not registered. Every count reported below is generated from the screening and extraction records that accompany this review (Section 2.4).

2.1 Information Sources

Three databases were searched: Scopus, IEEE Xplore and the ACM Digital Library. Scopus was the primary source for its broad indexing. IEEE Xplore was chosen for its coverage of network, service management and security venues, and the ACM Digital Library for software engineering and systems venues, where much work on artificial intelligence for IT operations (AIOps) appears. The searches were run on 23 October 2026. The Scopus and ACM Digital Library searches used the all-fields option of each site. The IEEE Xplore search was limited to open-access records.

Other sources were considered and not used. SpringerLink and SIAM, which were searched for the project's earlier review, were dropped: the SpringerLink export of that search contained no abstracts, and SIAM returned three records. Web of Science

Table 2 Specific objectives of the review (SO1–SO5), the systematic review question (SRQ) that each answers, the research question (RQ1–RQ5) of the author's project that each informs, and the gap, as stated by the project's earlier thematic review, that motivated each objective

Specific objective	Review question	Project question informed	Gap that motivated it (from the thematic review)
SO1: Identify which incident tasks have been formulated as sequential decision problems, and how they represent uncertain evidence	SRQ1	RQ1 (representation of ambiguous scenarios)	The environments used in the reviewed studies model cyberattacks and microservice faults, and none lets the ambiguity of IT service incidents be varied (Hammar and Li 2025; Dunsin et al. 2025; Wang et al. 2023).
SO2: Classify the decisions the agents make	SRQ2	RQ2 (investigate, recommend, escalate)	Information gathering and deferral have been studied separately; no reviewed study trained one policy to choose among all three options for IT incident triage (Janisch et al. 2019; Kim and Dán 2025; Madras et al. 2018; Joshi et al. 2023).
SO3: Analyse how constraints are enforced and what is reported about blocked actions	SRQ3	RQ3 (rule-based safety mechanism)	Shields have been demonstrated mainly on control tasks, and the reviewed literature did not report how a rule mechanism behaves when the agent can also investigate or escalate (Alshiekh et al. 2018; Könighofer et al. 2025; Alauthman et al. 2026).
SO4: Catalogue environments, datasets, baselines and metrics	SRQ4	RQ4 (comparison with baselines)	Decision quality, investigation cost, escalation and constraint compliance had each been measured, but not together for one agent (Remil et al. 2024; Levy et al. 2026; Pacella et al. 2026).
SO5: Synthesise how robustness to increasing ambiguity is tested	SRQ5	RQ5 (robustness)	Robustness had been tested for decision accuracy and for the validity of shields, but not for the mix of investigating, recommending and escalating (Kim and Dán 2025; Hammar and Li 2025; Hamel-De le Court et al. 2026).

was not searched. arXiv was not searched directly, so preprints could have entered only through citation searching, which was planned but not carried out (Section 2.6).

2.2 Search Strategy

The search was designed to be narrow. The earlier search had combined a block of terms for the learning approach, a block for uncertainty and oversight, and a block for the incident-management setting. Single words such as "uncertainty" and "triage" match large bodies of unrelated work, including medical triage and traffic incidents. The new string therefore anchors the review on the intersection of two concepts, the RL or sequential-decision method (block A) and the IT incident setting (block B), expressed as exact phrases, and adds a block of decision terms (block C). Synonyms within a block were joined with OR and the blocks were joined with AND. Table 3 lists the keywords and shows where each appears.

Table 4 gives the strings exactly as they were run. The Scopus and ACM Digital Library strings are identical. Both end with a fourth group of quoted years; because the searches ran over all fields, these terms match any record that mentions one of the years anywhere and do not restrict the publication year. The IEEE Xplore string differs in four respects: it uses the Scopus proximity operator `W/5` for the root-cause

Table 3 Keywords used to build the search strings and the block of the string in which each appears (A, method; B, setting; C, decision)

No.	Keyword	Block
1	Reinforcement learning	A (method)
2	Sequential decision-making	A, as MDP, POMDP and bandit terms
3	POMDP	A
4	IT incident management	B (setting)
5	Incident triage	B
6	Incident response	B
7	AIOps	B
8	Root cause analysis	B, limited to computing systems
9	Escalation	C (decision)
10	Human-in-the-loop	C
11	Information gathering	C
12	Safe reinforcement learning	C
13	Shielding	C
14	Operational constraints	C

clause, it spells several terms in full instead of truncating them, it has no year terms, and it was limited to open access. Whether IEEE Xplore interpreted `W/5` as intended was not tested.

The all-fields searches returned many records unrelated to the questions, because a record matched if the terms appeared anywhere, including in reference lists and front matter. Among the ACM records, 630 were whole proceedings volumes. The exports were therefore filtered again with a script, as described in Section 2.4, before any record was screened.

The string was checked against a benchmark set of seven studies already known to be relevant: Alauthman et al. (2026), Hammar and Li (2025), Hammar et al. (2026), Wang et al. (2023), Ding et al. (2023), Ren et al. (2025) and Dunsin et al. (2025). Six of the seven are among the exported records; Ren et al. is not. When block C was re-applied to the titles, abstracts and keywords of the exports, it removed two of the six, the studies of Hammar and Li and of Hammar et al., whose abstracts use none of its terms. Block C was therefore not re-applied in the automated filtering, and its terms were kept as data items in the extraction form (Section 2.7).

2.3 Eligibility Criteria

The inclusion criteria (IC1–IC5) and exclusion criteria (EC1–EC7) in Table 5 were written before screening and are linked to the research questions. Studies from security operations and cybersecurity incident response were kept within scope, because much of the RL work on incident handling comes from that setting. Their setting was recorded during extraction so that it could be separated from IT service incidents in the synthesis.

Table 4 Search strings exactly as run on 23 October 2026 in each database, and the number of records exported from each

Database	String as run
Scopus (all fields) and ACM Digital Library (all fields)	`("reinforcement learning" OR "deep Q-network*" OR "Q-learning" OR "policy gradient" OR "actor-critic" OR "proximal policy optimi*" OR "Markov decision process*" OR "partially observable Markov" OR POMDP OR "contextual bandit*" OR "multi-armed bandit*") AND ("incident management" OR "incident response" OR "incident triage" OR "incident handling" OR "incident resolution" OR "incident mitigation" OR AIOps OR "IT operations" OR "IT service management" OR ITSM OR "site reliability" OR "service desk" OR "help desk" OR "trouble ticket*" OR "ticket routing" OR "ticket assignment" OR "alert triage" OR "alert prioriti*" OR "security operations cent*" OR "automated remediation" OR ("root cause" AND (microservice* OR cloud OR "online service*" OR "IT system*"))) AND (triage OR escalat* OR defer* OR "human-in-the-loop" OR "human in the loop" OR "human oversight" OR investigat* OR diagnos* OR "information gathering" OR "information acquisition" OR remediat* OR mitigat* OR constrain* OR shield* OR "safe reinforcement learning" OR "action mask*" OR "partial* observ*" OR uncertain* OR ambigu*) AND ("2015" OR "2016" OR "2017" OR "2018" OR "2019" OR "2020" OR "2021" OR "2022" OR "2023" OR "2024" OR "2025" OR "2026")`
IEEE Xplore (open access only)	`("reinforcement learning" OR "deep Q-network*" OR "Q-learning" OR "policy gradient" OR "actor-critic" OR "proximal policy optimization" OR "Markov decision process*" OR "partially observable Markov" OR POMDP OR "contextual bandit*" OR "multi-armed bandit*") AND ("incident management" OR "incident response" OR "incident triage" OR "incident handling" OR "incident resolution" OR "incident mitigation" OR AIOps OR "IT operations" OR "IT service management" OR ITSM OR "site reliability" OR "service desk" OR "help desk" OR "trouble ticket*" OR "ticket routing" OR "ticket assignment" OR "alert triage" OR "alert prioritization" OR "security operations center" OR "automated remediation" OR ("root cause" W/5 (microservices OR cloud OR "online services" OR "IT systems"))) AND (triage OR escalation OR defer* OR "human-in-the-loop" OR "human in the loop" OR "human oversight" OR investigation OR diagnosis OR "information gathering" OR "information acquisition" OR remediation OR mitigation OR constraint* OR shield* OR "safe reinforcement learning" OR "action masking" OR "partial observability" OR uncertainty OR ambiguity)`
Records exported	Scopus 3394; ACM Digital Library 1000; IEEE Xplore 5. Total: 4399.

2.4 Record Management, Duplicate Removal and Automated Filtering

Records were exported as a CSV file from Scopus and as BibTeX files from IEEE Xplore and the ACM Digital Library, and combined into one list with a script. Duplicates were identified first by DOI and then by normalised title (lower case, with all

Table 5 Eligibility criteria: the inclusion criteria (IC1–IC5) and exclusion criteria (EC1–EC7) for each aspect of a study, applied in the order shown

Criterion	Inclusion	Exclusion
Method	IC1: A primary study that proposes or evaluates an RL or sequential decision-making method (MDP, POMDP or bandit)	RL named only as one unspecified component of a larger framework, or used only to train a model and not as a decision policy (IC1)
Setting	IC2: Incidents in computing systems: IT services, cloud, microservices, networks, or security incident response in IT and operational technology (OT) networks	EC1: Not a computing incident (for example medical triage, traffic, emergency response, power-grid or physical faults)
Decision	IC3: The agent makes at least one triage-relevant decision: gathering diagnostic information, choosing a remediation or response action, escalating or deferring to a human, or assigning or prioritising the incident	EC2: Resource management only (autoscaling, scheduling, routing, load balancing, caching); EC3: detection or classification only, with no decision after detection; EC4: offensive security
Agent type	Not applicable	EC5: A language-model agent whose policy is not trained with RL and not formulated as an MDP or POMDP
Evidence	IC4: A quantitative evaluation in simulation, on a benchmark or on real data	Framework or design papers with no reported results (IC4)
Publication type	IC5: Peer-reviewed journal or conference paper	EC6: Reviews and surveys, position papers, workshop summaries, theses, book chapters, posters and extended abstracts
Period, language	IC5: Published 2015–2026, in English	Published before 2015 or after 2026, or in another language
Duplication	Not applicable	EC7: A duplicate or an earlier version of an included study; the most complete version is kept
Access	IC5: Full text obtainable	Full text unobtainable (counted as not retrieved)

characters other than letters and digits removed). This step removed 73 duplicate records, leaving 4326. Where a duplicate pair had an abstract in one copy only, the copy with the abstract was kept.

The script then removed 4195 records as ineligible, which PRISMA 2020 reports as records removed by automation tools. It removed 1462 records of document types outside the criteria, among them reviews, books, chapters and the ACM proceedings volumes, and 32 records published outside 2015–2026. It then applied blocks A and B of the string to the title, abstract and keywords of each remaining record, which removed 2270 records with no method term and 431 with no setting term. Records without an abstract were checked by their titles; four were removed in this way, and none of them was in scope. The script, the screening decisions, the full-text decisions and the derivation of each count are kept with the review (Section 2.10).

2.5 Screening and Selection

Screening had two stages. In the first stage, the title and abstract of each of the 131 records that passed the automated filters were screened against the criteria. The criteria were applied in the order shown in Table 5, and the first criterion clearly failed was recorded as the reason for exclusion. Where an abstract did not make clear whether RL was the method under study, the record was kept for full-text

assessment. Two interpretive rules were applied and are stated so that the decisions can be reproduced. First, under IC1, a record was excluded when its abstract named RL only as one unspecified part of a framework that combines several techniques, or used RL only to fine-tune a model such as a language model or a ticket summariser. Second, under IC3, root cause analysis in which the agent decides which part of a system to examine next, or when to stop examining, was counted as a diagnostic decision of the information-gathering kind. Records kept were placed in two priority groups to order retrieval: 25 that address information gathering, triage, escalation, constraints or partial observability, and 22 that use RL only to select response or remediation actions. The groups did not affect eligibility.

In the second stage, the full texts were retrieved manually. Reports that could not be obtained were counted as not retrieved. Each retrieved report was read in full and assessed against the same criteria in the same order. Two further interpretive rules were applied at this stage. A study that described response actions but evaluated its model only with classification or detection metrics was excluded under EC3, because its decision policy was not evaluated. A study that combined RL with planning, as in methods that solve a belief-space model by dynamic programming, was kept under IC1 when the decision problem was formulated as an MDP or POMDP. The decision and its basis for every report sought are listed in Table S1 of Online Resource 1.

The title and abstract decisions and the full-text assessments of the reports on file were made with the AI assistant described in Section 2.11, and two full-text decisions were made manually (Section 3). None of these decisions was independently duplicated, and no measure of agreement was computed.

2.6 Reports Identified Through Other Methods

The protocol planned backward and forward citation searching, one level deep, from the included studies. This step has not been carried out. The review therefore rests on database records only, and studies such as Ren et al. (2025), which the search did not return, are not part of its evidence base. Background citations and included evidence are kept separate: a source cited in the Introduction to describe the problem is not evidence for a research question unless it also passed the eligibility criteria.

2.7 Data Extraction

A structured extraction form was completed for each included study, with fields mapped to the objectives (Table 6). Where a study did not report a field, the field was recorded as not reported, and no value was inferred. Four groups of measures were coded for SRQ4, following the project's evaluation plan: decision quality, investigation or time efficiency, escalation behaviour, and constraint compliance. The response actions a study's agent can take were coded separately from dispositions, such as closing, allowing or prioritising an alert, which end an alert's handling without acting on the system.

Table 6 Data extraction fields, grouped into bibliographic fields, fields for each specific objective (SO) and review question (SRQ), and quality ratings

Category	Fields
Bibliographic	Authors, year, venue, setting
SO1 / SRQ1	Task; formulation (MDP, POMDP, game); method; how uncertainty is represented; environment type
SO2 / SRQ2	Information-gathering actions; response actions; dispositions; escalation, deferral or hand-off
SO3 / SRQ3	Constraint mechanism; what it enforces; what happens to a blocked or uncertain decision
SO4 / SRQ4	Environment or data; baselines; metrics; measure groups covered
SO5 / SRQ5	Conditions under which robustness is tested; results; limitations
Quality	Ratings on the checklist in Table 7

2.8 Quality Assessment

The included studies were appraised with the eight-item checklist in Table 7. It was written for this review from what an RL study of incident handling should report, and it is not a published or validated instrument. Each item was rated as met, partly met or not met, from the full text; an item was rated not met when the information was not found. The ratings were made with the AI assistant described in Section 2.11 and have not been independently checked. No study was excluded on quality grounds. The ratings are used to qualify the synthesis, so that a result from a study with a weak rating is not given the same weight as one from a study with a strong rating.

Table 7 Eight-item reporting and validation checklist used to appraise the included studies. For each item (Q1–Q8) the table gives the question and the condition for a rating of met, with the condition for partly met in parentheses

Item	Question	Rated as met when (partly met when)
Q1	Formulation stated	States, actions and reward are defined (only some of them are)
Q2	Environment described	The simulator, benchmark or dataset is named or described well enough to rebuild (its type is given only)
Q3	Non-learning baseline	A static, rule-based or human policy is evaluated in the same environment (only learning methods are compared)
Q4	Metrics defined	Every reported metric is defined (some are)
Q5	Repeated runs	Results are reported over several runs or seeds with a measure of variance (several runs without variance)
Q6	Test conditions	The agent is tested on scenarios, data or conditions not used in training (on a held-out split of the same scenarios)
Q7	Limitations stated	The study states its own limitations (a caveat is made in passing)
Q8	Reproducible details	Hyperparameters are reported and code or environment is public (one of the two)

2.9 Synthesis Method

The evidence was synthesised narratively and organised by review question. For each question, the extracted items were grouped into themes, and each theme was recorded

with the studies that support it, the evidence they report, and the interpretation drawn; the full mapping is given in Section 3.10 and in the traceability files in Online Resource 2. Counts of studies with each characteristic are reported descriptively. No meta-analysis was performed, because the included studies use different environments, action sets, reward functions and metrics, and many report no measure of variance.

2.10 Records and Audit Files

The review is accompanied by a set of audit files (Online Resource 2; see also the data availability statement): the decision for each of the 131 screened records with its reason, the outcome and basis for each of the 47 reports sought, the extraction form and quality ratings for each included study, a reconciliation of every PRISMA count, and the thematic traceability matrix. The tables and counts in this paper are generated from these files.

2.11 Use of an AI Assistant

An AI assistant, Claude (Anthropic) [**model version and period of use**], was used in conducting this review. It supported the development of the search strings, the eligibility criteria and the data-processing scripts. The title and abstract decisions for all 131 screened records, the full-text assessments of the reports on file other than the two decided manually, the data extraction and the quality ratings were made with the assistant. The database searches, the retrieval of the full texts, the direction and framing of the review, and the full-text decisions for two reports were completed independently of the assistant. None of the decisions made with the assistant was independently duplicated, and no measure of agreement was computed; this limitation is discussed in Section 5. The author is accountable for every decision reported in this review and for the content of this article. [**To confirm: the assistant was also used to reformat the manuscript for this journal, condense the abstract and draft the statements and declarations, and the author reviewed and approved these changes.**]

3 Results

3.1 Study Selection

Fig. 1 shows the flow of records through the review, and Table 8 reconciles every count. The database searches identified 4399 records. Removing 73 duplicates and 4195 records by automated filtering left 131 records for title and abstract screening. Of these, 84 were excluded, for the reasons in Table 9, and 47 reports were sought for retrieval.

Of the 47 reports sought, 7 were not retrieved (Table 10). Five were recorded as closed access at retrieval. For a sixth, Wang et al.'s AlertPro, only the publisher's landing page with the abstract and section snippets was obtained, which is not enough to assess the study. For the seventh, no full text is on file and no reason was recorded; this is an unresolved gap in the retrieval record. The remaining 40 reports were assessed for eligibility, and 6 were excluded (Table 11). Three described response actions but

Table 8 PRISMA reconciliation: the number of records or reports (n) at each stage of the review and how each count is derived

Stage	n	Derivation
Records identified	4399	3394 + 5 + 1000
Duplicates removed	73	DOI, then title
Removed by automation	4195	1462 + 32 + 2270 + 431
Records screened	131	4399 − 73 − 4195
Records excluded	84	Table 9
Reports sought for retrieval	47	131 − 84
Reports not retrieved	7	6 + 1
Reports assessed for eligibility	40	47 − 7
Reports excluded	6	Table 11
Studies included	34	40 − 6
Citation searching	0	Not carried out

Table 9 Primary reasons for excluding records at title and abstract screening, with the criterion code (Table 5) and the number of records excluded for each reason

Code	Reason	Records
EC1	Not a computing incident	22
IC1	RL or sequential decision-making is not the method under study	19
EC6	Review, position paper or workshop summary	12
EC2	Resource management only	11
EC3	Detection or classification only	9
IC4	No quantitative evaluation	3
EC7	Earlier version of an included study	2
EC5	Language-model agent without an RL policy	2
IC3	No triage-relevant decision	2
IC2	Not incident handling in a computing system	1
EC4	Offensive security	1
	Total excluded	84

evaluated their models only as classifiers or detectors (Manoj Kumar et al. 2026; Bompally 2026; Reddy Avula 2026). One, the shielded incident-response agent of Alauthman et al. (2026), which the project's thematic review had treated as the closest precedent, reports an evaluation plan and "indicative findings" shown as arrows, but no measured values. One report was excluded as out of scope on manual judgement, and one because its full text is in French. In all, 34 studies, each described in one report, entered the synthesis: 20 from the first priority group and 14 from the second. Table S1 of Online Resource 1 gives the outcome for every report sought.

3.2 Study Characteristics

Table 12 summarises the 34 included studies, and Table S2 of Online Resource 1 describes each one. The work is recent: 27 of the 34 studies were published in 2025 or 2026, 17 of them in 2026, and the earliest in 2020. Most of the evidence comes from security settings. Only 10 studies concern IT service and cloud operations, and all but one of these address root cause analysis or the remediation of faults in microservice and cloud systems; the exception prioritises incident reports (Peralta et al. 2025). The




Fig. 1 PRISMA 2020 flow diagram for this review, which searched databases only; citation searching was not carried out. The left-hand boxes give the number of records or reports at each stage, from identification through screening to inclusion, and the right-hand boxes give the number removed or excluded at that stage, with the reasons

other 24 studies concern alert triage in security operations centres (SOCs), incident response on enterprise and military networks, industrial and Internet of Things (IoT) systems, or digital forensics during incident response.

The environments are mostly constructed. Of the 34 studies, 13 built their own simulator and 6 used a public benchmark, chiefly the CAGE-2 and CAGE-4 cyber-defence

Table 10 Reports sought for retrieval but not retrieved, with the identifier used in the screening record (ID), the report title and the reason it was not retrieved

ID	Report	Reason
S046	Combating alert fatigue with AlertPro: Context-aware alert prioritization using reinforcement learning for multi-step attack detection	Closed access: only the publisher landing page (abstract and section snippets) was obtained
S058	Digital Sovereignty by Design: Reinforcement Learning–Based Self-Healing for Cyber Resilience	Closed access (recorded at retrieval)
S068	From Rules to Autonomy: Leveraging Reinforcement Learning for Real-Time Cyber Threat Mitigation	Closed access (recorded at retrieval)
S093	Off-policy actor-critic deep reinforcement learning methods for alert prioritization in intrusion detection systems	Closed access (recorded at retrieval)
S108	Reinforcement Learning with AI for Autonomous Incident Response in DevSecOps: Using RL Agents to Detect, Classify, and Mitigate Security Threats in Cloud-Native DevOps Environments	No full text on file and no reason recorded
S109	Reinforcement Learning-Based Alert Prioritisation in Security Operation Centre: A Framework for Enhancing Cybersecurity in the Digital Economy	Closed access (recorded at retrieval)
S113	Risk-Aware SOC Alert Handling in Adaptive Cyber Defense with Reinforcement Learning	Closed access (recorded at retrieval)

Table 11 Reports excluded at full-text assessment, with the identifier used in the screening record (ID), the report and the criterion and reason for its exclusion

ID	Report	Reason
S016	Adaptive NeuroDefense: Graph Neural Network and Reinforcement Learning-based Self-Healing Cybersecurity Architecture (Manoj Kumar et al. 2026)	EC3: evaluated only as a detector (accuracy on NSL-KDD, CICIDS-2017, UNSW-NB15); the DQN mitigation choices are not evaluated
S027	AI-Powered Incident Response Framework for Secure DevOps Environments (Bompally 2026)	EC3: the MDP action set is not specified and the agent is evaluated only with classification metrics (accuracy, AUC)
S065	Explainable Reinforcement Learning for Automated Incident Response in Critical Infrastructure (Alauthman et al. 2026)	IC4: no quantitative evaluation. The paper specifies an evaluation plan and reports "indicative findings" as arrows, with no measured values
S072	Hybrid LSTM-QEQ Framework for Enhanced Cyber Threat Detection and Response in Critical Power Grid Infrastructure	Out of scope (manual full-text judgement)
S104	Reinforced Autonomous Agents with Attack-Defense Exercises in Realistic Environments	IC5: full text is not in English (French)
S130	XAI for Automated Prediction Model for Cyber Incident Response and Security Support in Cloud (Reddy Avula 2026)	EC3: response actions are described, but the model is evaluated only as a classifier of 26 memory dumps (accuracy, AUC)

gyms (Cyber Autonomy Gym for Experimentation) and the RCAEval root-cause benchmark; 6 replayed public datasets, most often intrusion-detection flow records regrouped into decision episodes, and 5 used emulated testbeds. Only 3 studies used operational data from an organisation (Peralta et al. 2025; Wang et al. 2023; Ding

et al. 2023), and one evaluated on a physical testbed as well as a benchmark (Hammar et al. 2026).

Table 12 Characteristics of the 34 included studies: the number of studies by setting, publication year, formulation of the decision problem and evaluation environment

Group	Category	Studies
Setting	IT service and cloud operations	10
	Security operations and alert triage	6
	Network and enterprise incident response	11
	Industrial, cyber-physical and IoT systems	5
	Digital forensics during incident response	2
Year	2020	1
	2022	2
	2023	2
	2024	2
	2025	10
	2026	17
Formulation[a]	Explicit belief (POMDP)	4
	Other partially observable formulation	5
	Constrained MDP	2
	Offline MDP	1
	Game	2
	Hierarchical	3
Environment	Benchmark	6
	Custom simulator	13
	Emulated testbed	5
	Testbed and benchmark	1
	Public dataset	6
	Operational data	3

[a]Formulation categories overlap; a study is counted in each that applies, and studies formulated as a fully observed MDP are not listed.

3.3 Quality of the Included Studies

The quality of the evidence is uneven (Table 13). Of the 34 studies, 9 meet at least six of the eight checklist items, and 12 meet at most two. Hammar et al. (2026) and Şahin and Mert (2026) meet all eight; Nyberg and Johnson (2024) meet seven; Peralta et al. (2025), Okafor (2026), Rojas Rodriguez et al. (2026), Ghanem et al. (2026), Hammar and Li (2025) and Kovtun et al. (2026) meet six. The weakly rated studies typically report a single run without variance, do not test the agent on unseen conditions, and describe their environment or hyperparameters too briefly for the work to be repeated. Table S4 of Online Resource 1 gives every rating.

Three weaknesses run across the set. Only 11 studies report results over several runs with a measure of variance, only 9 test their agents on conditions not seen in training, and only 5 give enough detail, with public code or environment, for the work to be repeated. A non-learning baseline is more common, met by 19. The synthesis below therefore gives most weight to the strongly rated studies and treats results from the weakest as indications only.

Table 13 Quality appraisal of the 34 included studies: for each checklist item (Q1–Q8; Table 7) the number of studies rated met, partly met (Part) or not met (Not)

Item	Question	Met	Part	Not
Q1	Formulation	25	9	0
Q2	Environment	19	14	1
Q3	Non-learning baseline	19	8	7
Q4	Metrics defined	21	10	3
Q5	Repeated runs with variance	11	7	16
Q6	Unseen test conditions	9	10	15
Q7	Limitations	19	7	8
Q8	Reproducible details	5	17	12

3.4 Coverage of the Review Questions

Table 14 counts the studies that contain each element of the review questions, and Fig. 2 shows the same counts against the size of the evidence base. Table S3 of Online Resource 1 records the elements study by study. The counts are descriptive; no effect sizes were pooled, for the reasons given in Section 2.

Table 14 Number of included studies (of 34) that contain each element of the review questions, grouped into decisions, constraints, measures and evaluation

Group	Element	Studies
Decision	Gathers information (explicit action)	17
	Takes or recommends a response or remediation action	22
	Disposes of the alert (close, allow, prioritise)	5
	Escalates, defers or hands off to a person	7
	Information gathering and response action	7
	Information gathering, response action and escalation	1
Constraint	Hard filter or shield	5
	Action masking	6
	Expected-cost or budget constraint	4
	Reward penalty only	11
	None stated	8
	Handling of a blocked action reported	3
Measures	Decision quality	31
	Investigation or time efficiency	19
	Escalation behaviour	5
	Constraint compliance	4
	Three or more of the four groups	5
	All four groups	1
Evaluation	Non-learning (static or rule) baseline	20
	Robustness tested	15




Fig. 2 Horizontal bar chart of the number of included studies, out of 34, that contain each element of the review questions. From top to bottom the bars show the decisions made (gathers information, response action, escalates or defers, all three decisions), constraint handling (hard filter or shield, blocked action handled), the measures reported (decision quality, efficiency, escalation, compliance) and robustness testing. Each bar is labelled with its count

3.5 Synthesis for SRQ1: Formulation and Representation of Uncertain Evidence

The answer to SRQ1 is that incident handling is formulated mostly as a fully observed MDP, and that explicit representation of uncertain evidence is the exception. Four themes support this answer.

3.5.1 Explicit belief over a hidden incident state is used by a minority of studies

Only 4 studies formulate the problem as a POMDP and act on a belief, a probability distribution over the hidden security state. Hammar et al. (2026) estimate the belief with a particle filter and compute policies by belief aggregation and rollout; Hammar and Li (2025) go further and hold a belief over the system model itself, updated by Bayesian learning as the incident unfolds. Kovtun et al. (2026) track a belief over a hidden attack regime in a SOC, and Koupaei and Demirkol (2026) use a Dempster-Shafer belief for small-enterprise incident response. These are among the more strongly rated studies, so the representation the project needs exists and has been evaluated, although mainly on security benchmarks.

3.5.2 Ambiguity is produced mainly by noisy, missing or overlapping evidence in a simulator, and it is usually fixed at one level

Koupaei and Demirkol (2026) set false-positive and false-negative rates of 12% and 18%. Contractor et al. (2025) lower the detection rate from 95% to 50% and add benign users who raise false alerts. Şahin and Mert (2026) design evidence that is stochastic and overlaps across classes, so that gathering evidence can lower confidence in a true threat or raise it for a benign alert, and add a hardened regime in which threats start at low confidence. Wu et al. (2026) vary fault severity and change the link topology during episodes, Peralta et al. (2025) model the vagueness of incident descriptions with fuzzy sets, and multi-agent studies give each agent only local observations (Aenugu 2026; Ravi et al. 2025). Only a few of these studies treat the level of ambiguity as an experimental factor that is varied (Contractor et al. 2025; Şahin and Mert 2026; Wu et al. 2026).

3.5.3 Many studies treat the incident state as a fully observed feature vector

In about half the studies the state is a vector of metrics, alert scores or dataset features with no model of what the agent cannot see (Saeed 2025; Noorul Hassan and Sivaraman 2026; Alturkistani and El-Affendi 2022; Bhosale et al. 2026; Raj et al. 2026; Nimmathi 2026; Yuan 2026; Babar et al. 2026; Hughes et al. 2022; Jaber et al. 2025; Singh 2026; Ghanem et al. 2026; Dunsin et al. 2025; Wang et al. 2024; Ding et al. 2023). In these studies ambiguity is assumed away rather than modelled, and the agent's decision cannot depend on how certain it is.

3.5.4 No shared environment exists for IT service incident triage

The security studies share benchmarks: CAGE-2 is used by three studies (Hammar et al. 2026; Hammar and Li 2025; Nyberg and Johnson 2024) and CAGE-4 or CybORG by two (Castro et al. 2025; Contractor et al. 2025), and RCAEval serves root cause analysis (Rojas Rodriguez et al. 2026). Three studies repurpose intrusion-detection datasets as alert streams or decision episodes (Okafor 2026; Kovtun et al. 2026; Alturkistani and El-Affendi 2022). Apart from the root-cause studies that use RCAEval or open microservice benchmarks, the IT service studies each build their own fault-injection setup or use one organisation's data (Peralta et al. 2025; Wang et al. 2023; Ding et al. 2023; Wu et al. 2026; Yuan 2026). Results from different IT service studies therefore cannot be compared directly.

3.6 Synthesis for SRQ2: The Decisions the Agents Make

The answer to SRQ2 is that gathering information and acting are common decisions, escalation to a person is rare, and no study learns one policy over all three for IT service incidents. Four themes support this answer.

3.6.1 Information gathering is an explicit, costed action in half the studies

A total of 17 studies give the agent an action whose purpose is to obtain evidence. In security settings it takes the form of an analyse or investigate action (Hammar et al. 2026; Hammar and Li 2025; Nyberg and Johnson 2024; Castro et al. 2025; Contractor et al. 2025; Okafor 2026), queries to logs and threat intelligence (Şahin and Mert 2026), a choice of which alerts analysts should investigate within a budget (Tong et al. 2020), a decision to defer and gather context (Kovtun et al. 2026), increased logging (Jaber et al. 2025), or the next step of a forensic examination (Ghanem et al. 2026; Dunsin et al. 2025). In root cause analysis it is the choice of which part of the system to examine next, whether to stop, or which components to exclude (Rojas Rodriguez et al. 2026; Wang et al. 2024; Wu et al. 2026; Ding et al. 2023), and Wang et al. (2023) let the agent choose which dependencies to ask engineers about.

3.6.2 Where investigation is available, it reduces errors or effort

Wu et al. (2026) report 3.2 investigation steps on average against 6.1 for a plain deep Q-network (DQN), with higher accuracy. Kovtun et al. (2026) find that the option to defer cut false escalations from 7.2% to 5.0% and from 9.4% to 6.6% on two datasets. Ghanem et al. (2026) report investigation time cut by up to 68% against analyst-assisted baselines, and Wang et al. (2023) reduce the number of questions put to engineers from $O(N^2)$ to $O(1)$. These results support treating investigation as a decision with a cost, as the project does.

3.6.3 Escalation to a person is rarely a learned action

Only 7 studies include escalation, deferral or hand-off to a person. Bhosale et al. (2026) let a DQN choose to allow, monitor or escalate phishing alerts, where escalation opens a ServiceNow incident, and Alturkistani and El-Affendi (2022) train a DQN to fix an alert or escalate it to the next tier of SOC operators. Şahin and Mert's (2026) agent can escalate to incident response, and a separate layer defers the most uncertain alerts to an analyst; Kovtun et al.'s (2026) agent escalates to deep analysis. In the other three the hand-off is fixed by design rather than learned: Okafor (2026) leaves containment to analysts in the deployed system, Singh (2026) routes an action to a human when a deterministic safety check fails, and Koupaei and Demirkol (2026) include notifying a managed security provider as a playbook. Six of the 7 are in security operations or incident response. The only IT service study among them, Singh's, hands off when a rule check fails; none of the 10 IT service studies learns when to escalate.

3.6.4 No study learns one policy over investigating, remediating and escalating for IT service incidents

Only 1 study combines an information-gathering action, a response action and escalation: Okafor's (2026) offline agents choose to dismiss, investigate or contain SOC alerts, and analyst ownership of containment is a deployment decision, not a learned one. Şahin and Mert (2026) combine evidence gathering with escalation and closure

but have no remediation action, and Kovtun et al. (2026) combine shallow triage, deep analysis and deferral, again without remediation. The three-way decision the project studies is therefore not covered in the evidence base; the nearest work is security alert triage.

3.7 Synthesis for SRQ3: Enforcement of Operational Constraints

The answer to SRQ3 is that constraints are most often encoded as reward penalties, that hard rule enforcement is proposed more often than it is measured, and that what replaces a blocked action is almost never reported. Reward penalties are the most common mechanism. A total of 11 studies express their operational limits only as penalties in the reward: for destructive self-healing actions (Yuan 2026), for restoring hosts (Nyberg and Johnson 2024; Hammar et al. 2026; Hammar and Li 2025), for under-escalation (Bhosale et al. 2026), or for violating an organisation's response policy encoded as a reward profile (Hughes et al. 2022). A further 8 state no constraint at all. A penalty discourages a prohibited action but does not prevent it, which is the distinction the project's design depends on (Könighofer et al. 2025). Four themes describe the studies that go further.

3.7.1 Action masking and expected-cost constraints are the common lightweight alternatives

In 6 studies, actions that are invalid or unsafe in the current state are masked. Contractor et al. (2025) unmask the disruptive restore action only when a persistent threat is present, and the analyse action only after a detection or a message from another agent; root-cause and forensic studies mask expanded nodes or restrict actions to a pool derived from engineers (Wang et al. 2024; Rojas Rodriguez et al. 2026; Ding et al. 2023; Ghanem et al. 2026; Wu et al. 2026). Another 4 bound an expected cost or a budget. Kovtun et al. (2026) constrain both the use of deep analysis and the attack-miss rate, and report that both constraints held in 14 of 15 seeds on one dataset and 13 of 15 on the other; Şahin and Mert (2026) certify error budgets on benign escalation and on threats closed automatically, realising rates of 0.0099 and 0.0101 against budgets of 0.01.

3.7.2 Hard runtime filters are proposed, but only two studies measure them

In 5 studies, proposals are checked against rules at run time. Ravi et al. (2025) check every proposed action against legal, service-level and safety rules and replace a violating action with a safer alternative or a no-op, with a penalty. Singh (2026) restricts the agent to a feasible action region and adds a deterministic execution guard. Koupaei and Demirkol (2026) restrict the allowable action set by cost and time limits, Elicha and Lopez (2026) let expert rules handle known threats before the RL agent sees an alert, and Okafor (2026) adds a severity floor that prevents medium- and high-severity alerts from being dismissed automatically. Only Ravi et al. and Singh report how the rules behaved: Ravi et al.'s (2025) shield intervened 526 to 623 times per scenario,

and removing Singh's (2026) guard left the mean time to resolution almost unchanged (142 s to 144 s) but cut the governance compliance rate from 99.9% to 72.3%.

3.7.3 What happens to a blocked decision is reported in 3 studies

Ravi et al. (2025) substitute an alternative or a no-op, Singh (2026) hands the action to a human, and Şahin and Mert (2026) defer to an analyst any alert that cannot be decided within the error budgets. None of the studies lets the agent propose again after a block, which is the project's rule.

3.7.4 Rule enforcement changes behaviour and has a cost

Singh's (2026) guard bought compliance at almost no cost in resolution time. In Ravi et al.'s (2025) study the cost was larger: the shielded agent took 9 to 11 times more false actions and incurred 74–77% higher cost than an unshielded proximal policy optimisation (PPO) agent, while detecting far more attacks (recall 0.96–0.99 against 0–0.084). This study is weakly rated, and its text reports that the PPO agent proposed unsafe actions although that agent ran without a shield, so its comparison should be read with caution.

3.8 Synthesis for SRQ4: Environments, Baselines and Metrics

The answer to SRQ4 is that the studies measure the quality of the final decision and the time taken, but rarely escalation behaviour or compliance, and that their reporting is often too weak for the results to be compared. Three themes support this answer.

3.8.1 Decision quality and time dominate; escalation and compliance are rarely measured

Decision quality is measured in 31 studies, through accuracy, reward, cost, recall or the Matthews correlation coefficient (MCC), and 19 studies measure time or investigation effort, most often as mean time to recovery (Singh 2026; Koupaei and Demirkol 2026; Nimmathi 2026; Aenugu 2026). Only 5 measure escalation behaviour (Peralta et al. 2025; Şahin and Mert 2026; Nimmathi 2026; Bhosale et al. 2026; Kovtun et al. 2026) and 4 constraint compliance (Singh 2026; Şahin and Mert 2026; Kovtun et al. 2026; Ravi et al. 2025). One study, Kovtun et al. (2026), reports measures in all four groups, for SOC alert escalation. Peralta et al. (2025) report the clearest operational effect on escalation: in a deployment trial, the escalation rate fell from 11.8% to 9.2% and manual priority overrides from 15.2% to 6.2%, although this was a before–after comparison without a control.

3.8.2 A static or rule-based comparison is common but not universal

In all, 20 studies compare against a non-learning policy: static thresholds, fixed scripts, playbooks, heuristics, a periodic recovery policy, or human examiners (Hammar et al. 2026; Koupaei and Demirkol 2026; Bhosale et al. 2026; Wu et al. 2026; Yuan 2026; Aenugu 2026; Ghanem et al. 2026). The others compare only learning methods with each other, compare with values reported by other studies, or have no baseline (Saeed

2025; Noorul Hassan and Sivaraman 2026; Khozam et al. 2025; Elicha and Lopez 2026; Hughes et al. 2022; Jaber et al. 2025; Alturkistani and El-Affendi 2022). The extracted results contain no case in which a static baseline outperformed the learned policy on a study's main measure. How much this reflects the strength of the learned policies and how much the weakness of the baselines cannot be separated from the reports.

3.8.3 Reporting weaknesses limit the comparisons

Several studies show how the choice of metric can mislead. Okafor (2026) found that value-based offline RL and a Decision Transformer degenerated into trivial detectors whose failure the F1 score and the area under the receiver operating characteristic curve (ROC-AUC) concealed and MCC revealed. Ravi et al.'s (2025) PPO baseline scored 0.98 accuracy with near-zero recall. Şahin and Mert (2026) report that an earlier version of their simulator leaked the label into the confidence signal, so that any threshold appeared to achieve perfect recall, and recommend checks against this defect. Several weaker studies contain internal inconsistencies: two different improvement figures for the same result (Koupaei and Demirkol 2026; Varsha et al. 2025), a train–test split that is stated but not used (Bhosale et al. 2026), an action in a worked example that is absent from the action set (Jaber et al. 2025), and training and testing on the same stream (Alturkistani and El-Affendi 2022).

3.9 Synthesis for SRQ5: Robustness to Ambiguity and Change

The answer to SRQ5 is that robustness is tested in under half the studies, mostly for the quality of the final decision, and that no study measures how the mix of investigating, acting and escalating changes as evidence becomes more ambiguous. Three themes support this answer.

3.9.1 Robustness is tested through model error, change, unseen attackers and weaker detection

A total of 15 studies test their agents under conditions that differ from training: a misspecified model of the system (Hammar and Li 2025), a non-stationary system (Hammar et al. 2026), unseen attacker profiles and network structures (Ravi et al. 2025; Nyberg and Johnson 2024; Castro et al. 2025), a lower detection rate (Contractor et al. 2025), dataset shift (Şahin and Mert 2026), terminology drift (Peralta et al. 2025), dynamic topology (Wu et al. 2026), and load near capacity (Aenugu 2026; Kovtun et al. 2026). Performance generally degrades but does not collapse: Peralta et al.'s (2025) accuracy fell from 82.9% to 79.4% under drift, Aenugu's (2026) mean time to recovery rose from 41.2 s to 79.4 s at peak load, and Nyberg and Johnson's (2024) graph agents worked on unseen networks without retraining but scored below agents trained on each network.

3.9.2 Methods that maintain a belief or adapt their model degrade least

Under a misspecified model, Hammar and Li's (2025) method incurred a cost of 35.91 against 91.51 or more for every other method, although it was slightly worse than the best methods when the model was correct. Hammar et al.'s (2026) method adapted its policy to a system change in about 15 s to 19 s, against more than 30 min for PPO, and PPO's results varied about ten times more. Both studies are strongly rated.

3.9.3 As ambiguity rises, deferral to people rises; how the full decision mix shifts is unmeasured

Şahin and Mert (2026) show that when the scoring model degrades under dataset shift, the share of alerts deferred to analysts rises, to 79–99% for the most affected classifiers, so that failure becomes visible instead of silent. Kovtun et al. (2026) show that deferring to gather context reduces false escalations, and Contractor et al. (2025) show that lower detection rates lower returns and that unmasking investigation on a message from another agent recovers part of the loss. No study reports the shares of investigating, acting and escalating at increasing levels of ambiguity.

3.10 Thematic Traceability

Table 15 links each review question to its themes, the studies that support each theme, and the interpretation drawn. It is the basis of the discussion that follows.

Table 15: Thematic traceability matrix: for each review question (SRQ), the themes identified, the studies that support each theme and the interpretation drawn. Study identifiers such as S038 are those of the decision log (Table S1 in Online Resource 1)

SRQ	Theme	Supporting studies	Interpretation
SRQ1	Explicit belief over a hidden incident state is used by a minority of studies	Hammar et al. 2026; Hammar and Li 2025; Koupaei and Demirkol 2026; Kovtun et al. 2026	The representation the project needs exists and has been evaluated, mostly on security benchmarks
	Ambiguity is produced mainly by noisy, missing or overlapping alerts in simulators	Koupaei and Demirkol 2026; Contractor et al. 2025; Şahin and Mert 2026; Wu et al. 2026; Peralta et al. 2025; Aenugu 2026; Ravi et al. 2025	Few studies vary ambiguity as an experimental factor; most fix it at one level
	Many studies treat the incident state as a fully observed feature vector	Saeed 2025; Noorul Hassan and Sivaraman 2026; Alturkistani and El-Affendi 2022; Bhosale et al. 2026; Raj et al. 2026; Nimmathi 2026; Yuan 2026; Babar et al. 2026; Hughes et al. 2022; Jaber et al. 2025; Singh 2026; Ghanem et al. 2026; Dunsin et al. 2025; Wang et al. 2024; Ding et al. 2023	Ambiguity is often assumed away rather than modelled

Table 15: (continued)

SRQ	Theme	Supporting studies	Interpretation
	Evaluation environments are mostly security benchmarks, custom simulators and repurposed intrusion detection system (IDS) datasets	Hammar et al. 2026; Hammar and Li 2025; Castro et al. 2025; Contractor et al. 2025; Nyberg and Johnson 2024; Rojas Rodriguez et al. 2026; Okafor 2026; Kovtun et al. 2026; Şahin and Mert 2026; Peralta et al. 2025; Wang et al. 2023; Ding et al. 2023	No shared environment exists for IT service incident triage
SRQ2	Information gathering is an explicit action in about half the studies	Okafor 2026; Hammar et al. 2026; Rojas Rodriguez et al. 2026; Şahin and Mert 2026; Tong et al. 2020; Castro et al. 2025; Contractor et al. 2025; Ghanem et al. 2026; Jaber et al. 2025; Wang et al. 2024; Hammar and Li 2025; Dunsin et al. 2025; Wu et al. 2026; Kovtun et al. 2026; Wang et al. 2023; Nyberg and Johnson 2024; Ding et al. 2023	Investigation is treated as a decision with a cost, as the project assumes
	Escalation to a human is rarely a learned action	Bhosale et al. 2026; Alturkistani and El-Affendi 2022; Şahin and Mert 2026; Kovtun et al. 2026; Okafor 2026; Singh 2026; Koupaei and Demirkol 2026	Where escalation exists it is mostly in security alert triage, and S038 hands off by rule rather than by learning
	No study learns one policy over investigating, remediating and escalating for IT service incidents	Şahin and Mert 2026; Okafor 2026; Kovtun et al. 2026	The three-way decision of the project is not covered; the nearest work is security alert triage
	When investigation is available it reduces errors or effort	Wu et al. 2026; Kovtun et al. 2026; Ghanem et al. 2026; Wang et al. 2023	Supports giving the agent a costly investigate action
SRQ3	Hard runtime filters and shields are proposed but rarely measured	Ravi et al. 2025; Singh 2026; Koupaei and Demirkol 2026; Elicha and Lopez 2026; Okafor 2026	Only S118 and S038 report how often rules intervened or were complied with
	Action masking and expected-cost constraints are the common lightweight alternatives	Contractor et al. 2025; Rojas Rodriguez et al. 2026; Wang et al. 2024; Ghanem et al. 2026; Wu et al. 2026; Ding et al. 2023; Kovtun et al. 2026; Tong et al. 2020; Varsha et al. 2025; Şahin and Mert 2026	Masking prevents prohibited proposals rather than reacting to them
	What happens to a blocked action is reported in only three studies	Ravi et al. 2025; Singh 2026; Şahin and Mert 2026	The project's rule of one re-proposal then escalation has no direct precedent
	Rule enforcement changes behaviour and has a cost	Singh 2026; Ravi et al. 2025	Compliance has to be measured alongside decision quality and cost

Table 15: (continued)

SRQ	Theme	Supporting studies	Interpretation
SRQ4	Decision quality and time dominate the metrics; escalation and compliance are rarely measured	All 34 (Table S4 in Online Resource 1)	Only one study measures all four groups the project plans, and it concerns SOC alert escalation
	A static or rule-based comparison is common but not universal	Peralta et al. 2025; Hammar et al. 2026; Singh 2026; Babar et al. 2026; Rojas Rodriguez et al. 2026; Koupaei and Demirkol 2026; Şahin and Mert 2026; Tong et al. 2020; Nimmathi 2026; Castro et al. 2025; Ghanem et al. 2026; Varsha et al. 2025; Wang et al. 2024; Aenugu 2026; Bhosale et al. 2026; Dunsin et al. 2025; Wu et al. 2026; Wang et al. 2023; Yuan 2026; Ding et al. 2023	A rule-based baseline is standard and the project should keep one
	Reporting weaknesses limit the comparisons	Okafor 2026; Ravi et al. 2025; Koupaei and Demirkol 2026; Bhosale et al. 2026; Varsha et al. 2025; Jaber et al. 2025; Alturkistani and El-Affendi 2022; Şahin and Mert 2026	Metrics such as MCC, per-class recall and seed variance are needed
SRQ5	Robustness is tested through model error, change, unseen attackers and weaker detection	Hammar and Li 2025; Hammar et al. 2026; Ravi et al. 2025; Nyberg and Johnson 2024; Contractor et al. 2025; Şahin and Mert 2026; Peralta et al. 2025; Wu et al. 2026; Aenugu 2026; Castro et al. 2025; Kovtun et al. 2026	Robustness is tested in about a third of studies, mostly for decision quality
	Methods that maintain a belief or adapt their model degrade least	Hammar and Li 2025; Hammar et al. 2026	Supports explicit belief tracking in the project agent
	As ambiguity rises, deferral to people rises; how the full decision mix shifts is unmeasured	Şahin and Mert 2026; Kovtun et al. 2026; Contractor et al. 2025	No study reports the shares of investigating, acting and escalating across ambiguity levels

4 Discussion

This review set out to find how RL has been applied to IT incident handling, which decisions the agents make, how rules are enforced, and how the agents are evaluated. The 34 included studies show that each part of the planned design has been studied

somewhere, but not together and seldom for IT service incidents. This section interprets the findings for each review question, returns to the gaps stated in Table 2, and sets out what the findings imply for the project.

4.1 Representation of Uncertain Evidence

The thematic review stated that the environments in the literature model cyberattacks and microservice faults and that none lets the ambiguity of IT service incidents be varied. The systematic search confirms this gap and sharpens it. Belief-based formulations exist and perform well under change (Hammar et al. 2026; Hammar and Li 2025), but all 4 studies that use them concern security incidents. The IT service studies are almost all root cause analysis on microservice benchmarks or on one company's data, and they treat the system's metrics as fully observed. Three studies vary the level of ambiguity as an experimental factor (Contractor et al. 2025; Şahin and Mert 2026; Wu et al. 2026); none of them concerns user-reported IT service incidents.

There are two ways to read this. One is that IT service triage does not need a model of hidden state because its evidence is good enough. The studies give no support for this reading, since none tests it. The other is that the field has not yet built an environment in which the question can be asked. Chen et al.'s (2020) observation that distinct problems produce similar symptoms favours the second reading. A simulator in which the overlap between incident causes can be set, as Şahin and Mert (2026) do for alert classes, would let the question be tested directly.

4.2 The Three Decisions

The thematic review found that information gathering and deferral had been studied separately. The included studies agree. Investigation is an explicit action in 17 studies, and where it is measured it reduces either errors or effort (Wu et al. 2026; Kovtun et al. 2026; Ghanem et al. 2026; Wang et al. 2023). Escalation is much rarer, and where it is present it is often fixed by design: a severity floor, a rule-triggered hand-off, or a playbook (Okafor 2026; Singh 2026; Koupaei and Demirkol 2026). Only one study combines all three kinds of decision, and its escalation is not learned (Okafor 2026).

The closest work to the project is therefore in security alert triage, not IT service management. Şahin and Mert's (2026) system gathers evidence, escalates or closes, and defers the uncertain cases to an analyst under certified error budgets. Kovtun et al.'s (2026) agent chooses between shallow triage, deep analysis and deferral under a cost constraint. Both are strongly rated, and both treat escalation as a decision with a cost, as Turan (2026) argues it should be. Neither recommends a remediation. The project's question is whether one policy can learn to make the choice between all three when the third option is a fix with operational consequences. The evidence does not answer that question; it shows the parts that have worked separately.

4.3 Enforcement of Operational Rules

The thematic review found that shields had been demonstrated mainly on control tasks (Alshiekh et al. 2018; Könighofer et al. 2025), and that the one shielded incident-response agent it identified had not reported how its mechanism behaved (Alauthman

et al. 2026). The systematic search confirms that study's status: it reports an evaluation plan and indicative findings, not measurements, and it was excluded on that ground. The 5 included studies with a hard filter show that the idea has reached incident handling, but only two report what the filter did (Ravi et al. 2025; Singh 2026).

Those two results point in different directions. Singh's (2026) guard raised governance compliance from 72.3% to 99.9% at almost no cost in resolution time. Ravi et al.'s (2025) shield intervened hundreds of times per scenario and the shielded agent took many more false actions than an unshielded one. The difference may lie in how often the agent proposes prohibited actions, which depends on how it was trained. If the agent learns with the shield in place, as Alshiekh et al. (2018) propose, it can learn to avoid proposals that will be blocked. Neither study reports the rate of blocked proposals over training, so this explanation cannot be checked from the evidence.

The more important finding for the project is what is missing. Only 3 studies say what happens after a block, and none lets the agent propose again. The project's rule, that a blocked agent may make one further proposal before the incident is escalated, has no direct precedent. Its effect on escalation rates and on the time to resolution will have to be measured, not assumed.

4.4 Environments, Baselines and Metrics

The thematic review stated that decision quality, investigation cost, escalation and constraint compliance had each been measured but not together. The systematic search finds one exception, Kovtun et al. (2026), who measure all four for SOC alert escalation. The rest measure decision quality and time, and few measure escalation or compliance. For an agent whose purpose is to choose between investigating, acting and escalating, decision quality alone is not enough: an agent that escalates every incident makes no wrong fix, and an agent that never escalates may look efficient. Measures of escalation and compliance are needed to see either failure.

The quality appraisal adds a caution about baselines and reporting. A non-learning baseline is common, and the learned policy always beat it in the extracted results, but few studies report variance across runs or test on unseen conditions. Okafor's and Ravi et al.'s results show how a single metric can hide a degenerate policy (Okafor 2026; Ravi et al. 2025), and Şahin and Mert's (2026) account of label leakage in their own simulator shows how a simulator can make a policy look better than it is. These are the failure modes the project's evaluation is most exposed to, because it too will train and test in a simulator it builds.

4.5 Robustness

The thematic review found that robustness had been tested for decision accuracy and for the validity of shields, but not for the mix of investigating, recommending and escalating. The systematic search confirms this. In 15 studies the agents are tested under changed conditions, and the methods that maintain a belief or adapt their model degrade least (Hammar and Li 2025; Hammar et al. 2026). Şahin and Mert (2026) show the most relevant pattern: as the scoring model degrades, more alerts are

deferred to people, so that failure becomes visible. No study reports how the shares of the three decisions change as evidence becomes more ambiguous. That curve is what the project's fifth research question asks for.

4.6 Relevant Excluded Studies

Two groups of excluded reports bear on the interpretation. The first is the shielded incident-response agent of Alauthman et al. (2026), which the thematic review treated as the closest precedent. Its exclusion leaves no included study that combines a shield with incident response in IT operations and reports measurements. The second is three reports that describe response actions but evaluate their models as classifiers (Manoj Kumar et al. 2026; Bompally 2026; Reddy Avula 2026). They show a common pattern in the wider literature: a framework is described as autonomous response, but what is evaluated is detection. A reader who counts such papers as evidence of RL-based response would overestimate how much of that evidence exists.

4.7 Implications for the Project

Fig. 3 places the project against the evidence. Each of its four components has a precedent among the included studies, mostly in security settings, and the combination has none. The findings suggest six things for the project's design and evaluation.

1. The simulator should let the level of ambiguity be set, by controlling how far the symptoms of different causes overlap and how reliable each diagnostic check is, so that robustness can be measured as a function of it (Şahin and Mert 2026; Contractor et al. 2025).
2. The agent should be compared with a learning baseline that keeps a belief, not only with a fully observed one, because belief-based methods were the most robust in the included studies (Hammar and Li 2025; Hammar et al. 2026).
3. Escalation should be a learned action with a cost, and its rate should be reported alongside decision quality, so that an agent which escalates everything cannot appear safe (Kovtun et al. 2026; Turan 2026).
4. The rule mechanism should log every block, the re-proposal that follows, and whether the incident was then escalated, because no included study reports this sequence.
5. Results should be reported over several seeds with variance, with more than one decision-quality metric, and with checks for label leakage in the simulator (Okafor 2026; Şahin and Mert 2026).
6. The static, rule-based baseline should be as strong as a competent support team would use, because a weak baseline makes any learned policy look good.

5 Limitations

The limitations of this review lie in the evidence it found and in the way it was conducted.




Fig. 3 Components of the planned agent (left column) and the included evidence for each (right column). Explicit belief over the hidden incident cause: 4 studies, all in security (Hammar et al. 2026; Hammar and Li 2025; Kovtun et al. 2026; Koupaei and Demirkol 2026). Costed investigate action: 17 studies, with effort reduced in (Wu et al. 2026; Kovtun et al. 2026). Learned escalation: 7 studies, learned in four, all in security (Bhosale et al. 2026; Alturkistani and El-Affendi 2022; Şahin and Mert 2026; Kovtun et al. 2026). Rule mechanism with blocked-action handling: 5 studies with hard filters, of which 3 report how a blocked action is handled and none allows a re-proposal. The hatched box at the bottom states that no study combines all four components for IT service incidents

5.1 Limitations of the Evidence

Most of the evidence comes from simulation. Of the 34 studies, 13 built their own simulator, and only 3 used an organisation's operational data. Results from a simulator show what a policy can learn from the dynamics its authors chose, not how it will behave on real incidents. The evidence also leans towards security. Of the 34 studies, 24 concern security operations, incident response, industrial systems or forensics, and most of the 10 IT service studies concern root cause analysis rather than triage. Findings carried over from security alert triage to IT service incidents assume that the two decision problems are alike, which the studies do not test.

The quality of the evidence is uneven. Of the included studies, 12 meet at most two of the eight checklist items, only 11 report variance over repeated runs, and only 5 give enough detail to repeat the work. Several studies contain internal inconsistencies (Section 3). The checklist itself was written for this review and has not been validated, so the ratings indicate reporting quality and should not be read as a measure of risk of bias. The studies differ too much in task, environment and metric for their results to be pooled, so the synthesis is narrative and the counts are descriptive.

5.2 Limitations of the Review Process

The search may have missed relevant studies. Only three databases were searched, and Web of Science and arXiv were not among them. The IEEE Xplore search was

limited to open-access records and returned 5, so IEEE studies behind a paywall that Scopus does not index are missing. The ACM Digital Library export reached its limit of 1000 records, so records beyond that limit were not seen; most of the exported ACM records were proceedings volumes, which suggests that the all-fields search was too broad for that library. The year terms in the Scopus and ACM strings do not restrict publication year, and the year filter was applied afterwards by the script. Citation searching was planned but not carried out, and at least one known relevant study was therefore not found (Ren et al. 2025).

Automated filtering removed 4195 records by applying the string blocks to titles, abstracts and keywords. A relevant study that uses none of the method terms in these fields would have been removed without being read. Records without an abstract were judged on their titles alone.

Seven reports could not be assessed. Five were closed access, only the landing page of a sixth was obtained, and for the seventh no full text is on file and no reason was recorded. One report was excluded because its full text is in French. The review cannot say whether these eight reports would have changed its findings; at least three of the unretrieved reports concern SOC alert prioritisation, which is close to the review's focus.

Screening and extraction were not duplicated. The title and abstract decisions, the full-text assessments of the reports on file, the extraction and the quality ratings were made with an AI assistant, and two full-text decisions were made manually. The decision log, the extraction file and the quality ratings are provided so that every decision can be checked. Finally, the review was written to prepare for a particular study, and the themes were coded against that study's design. Section 2.5 and Table S1 of Online Resource 1 state the decisions that required interpretation so that a reader can judge whether this framing affected them.

6 Future Research

The gaps identified by this review suggest four directions for research, and two for the review itself.

The first is an environment for IT service incident triage in which the ambiguity of the evidence can be controlled. No such environment was found. It should let a researcher set how far the symptoms of different causes overlap and how reliable each diagnostic check is, and it should be released with its code so that results can be compared across studies, as the CAGE gyms allow for cyber defence.

The second is a single policy that learns to investigate, recommend a fix or escalate, evaluated against both a static policy and learning baselines with and without a belief. The security studies of Şahin and Mert (2026) and Kovtun et al. (2026) show that parts of this design work for alerts; whether they work together when one option changes the system is an open question.

The third is the behaviour of rule enforcement when the agent can also investigate or escalate. Studies should report how often proposals are blocked during training and evaluation, what replaces a blocked proposal, and how blocking changes the rates of investigation and escalation. Only 3 included studies report any part of this.

The fourth is evaluation practice. Studies should report decision quality, investigation cost, escalation behaviour and compliance together; results over several seeds with variance; and performance as a function of ambiguity, including the shares of the three decisions at each level. Checks for label leakage in simulators, of the kind Şahin and Mert (2026) describe, should be routine.

For the review itself, the citation searching that was planned should be carried out, and the IEEE Xplore and ACM Digital Library searches should be repeated, the first without the open-access limit and the second restricted to titles, abstracts and keywords. The seven reports that could not be retrieved should be obtained and assessed.

7 Conclusion

This review searched three databases for studies that apply RL or sequential decision-making to IT incident handling, screened 131 records, and included 34 studies. Its findings answer the five review questions. Most studies formulate incident handling as a fully observed MDP, and only 4 keep an explicit belief over the hidden state. Information gathering is a common action, but escalation to a person is rare and often fixed by design, and only one study combines gathering, acting and escalating. Rule enforcement is usually a reward penalty; hard filters appear in 5 studies, and only 3 say what happens to a blocked decision. Decision quality is measured almost everywhere, while escalation and compliance are measured in few studies, and robustness is tested for the final decision but not for the mix of decisions.

The parts of an agent that investigates, acts or escalates under explicit rules have each been studied, mostly for security incidents, but no included study combines them for IT service incidents. The evidence is recent, largely simulated and uneven in quality. Within those limits, the review supports the project's plan to study such an agent, and it indicates what the evaluation must include: controlled ambiguity, learned escalation with a cost, a record of every blocked proposal, and measures of escalation and compliance reported alongside decision quality.

Supplementary information. The online version contains supplementary material. **Online Resource 1** (ESM_1.pdf): Tables S1–S4, which give the outcome of every report sought for retrieval (S1), the task, formulation, environment and main result of each included study (S2), the coding of the review-question elements for each included study (S3), and the quality rating of each included study on items Q1–Q8 (S4). **Online Resource 2** (ESM_2.xlsx): the audit files of the review, one worksheet each: the decision and reason for each of the 131 screened records, the outcome for each of the 47 reports sought, the data extraction form and the quality ratings of the 34 included studies, the study and thematic traceability matrices, and the reconciliation of every PRISMA count.

Statements and Declarations

Funding. **[Choose one: "No funding was received for conducting this study." or "This work was supported by [funder, written in full] (Grant number [...])."]**

Competing interests. **[To confirm: The author has no relevant financial or non-financial interests to disclose. The review was carried out to inform the author's own undergraduate research project on a reinforcement learning agent for IT incident triage (Section 1).]**

Ethics approval and consent to participate. Not applicable. This review synthesises published studies; it involved no human participants, personal data or animals.

Consent for publication. Not applicable.

Data availability. The audit files that support the findings of this review are available in **[repository name]** (Opol 2026): the decision and reason for every screened record (`exclusion_traceability.csv`), the outcome of every report sought (`fulltext_decisions.csv`), the extraction form (`data_extraction.csv`), the quality ratings (`quality_appraisal.csv`), the study and thematic traceability matrices, the reconciliation of every PRISMA count (`prisma_reconciliation.csv`), and the screening and table-generation scripts. The same files are provided as Online Resource 2. The raw database exports and the full texts of the included studies are not shared, because the database licence terms and the publishers' copyright restrict their redistribution; the exports can be recreated by running the search strings in Table 4.

Materials and code availability. The scripts that combined the exports, applied the automated filters and generated the tables and counts are included in the repository cited under Data availability (Opol 2026). No other materials were produced.

Author contributions. Charis Opol is the sole author. She conceived and designed the review, ran the database searches, retrieved the full texts, conducted the screening, data extraction and quality appraisal with the AI assistance described in Section 2.11, synthesised the evidence, and wrote and revised the manuscript. She read and approved the final manuscript.

Use of artificial intelligence tools. The use of an AI assistant in conducting this review is described in Section 2.11.

Prior dissemination and re-use of material. This review was prepared during the author's undergraduate research project at Uganda Christian University. Parts of the Introduction (the description of incident management and triage, the framing of triage as a sequence of decisions, and the requirements for rule enforcement and escalation) and the gap statements in Table 2 draw on, and in places repeat wording from, Chapters One and Two of the author's project report, *Investigate, Recommend or Escalate: A Rule-Constrained Reinforcement Learning Agent for IT Incident Triage*

under Ambiguous Evidence (Uganda Christian University, 2026), which also summarises some findings of this review. [**To confirm: the report is an unpublished university assessment document and has not been published or submitted to any journal.**]

References

Aenugu GR (2026) Multi-agent proximal policy optimization framework for autonomous reliability engineering in Kubernetes-based cloud-native distributed systems. In: Proceedings of the 7th International Conference on Computational Vision and Bio Inspired Computing (ICCVBIC 2026), pp 500–506, https://doi.org/10.1109/ICCVBIC71195.2026.11688912

Alauthman M, Almomani A, Al-Qerem A, et al (2026) Explainable reinforcement learning for automated incident response in critical infrastructure. In: Proceedings of the 2nd International Conference on Computational Intelligence Approaches and Applications (ICCIAA 2026), pp 1–7, https://doi.org/10.1109/ICCIAA68481.2026.11543556

Alshiekh M, Bloem R, Ehlers R, et al (2018) Safe reinforcement learning via shielding. In: Proceedings of the AAAI Conference on Artificial Intelligence, https://doi.org/10.1609/aaai.v32i1.11797

Alturkistani H, El-Affendi MA (2022) Optimizing cybersecurity incident response decisions using deep reinforcement learning. Int J Electr Comput Eng 12(6):6768–6776. https://doi.org/10.11591/ijece.v12i6.pp6768-6776

Babar A, Halabi T, Zulkernine M (2026) Autonomous and adaptive cyber incident detection and response in industrial cyber-physical systems using hierarchical reinforcement learning. ACM Trans Cyber-Phys Syst 10(1):8. https://doi.org/10.1145/3765622

Bhosale A, Rambhia J, Kharche S, et al (2026) PhishRL: an end-to-end reinforcement learning pipeline for automated email threat triage. In: Proceedings of the 2026 6th International Conference on Intelligent Technologies (CONIT 2026), https://doi.org/10.1109/CONIT69683.2026.11620809

Bompally SD (2026) AI-powered incident response framework for secure DevOps environments. In: Proceedings of the 2026 IEEE International Conference on Emerging Computing and Intelligent Technologies (ICoECIT 2026), https://doi.org/10.1109/ICoECIT68303.2026.11497511

Castro SR, Campbell R, Lau N, et al (2025) Large language models are autonomous cyber defenders. In: Proceedings of the 2025 IEEE Conference on Artificial Intelligence (CAI 2025), pp 1125–1132, https://doi.org/10.1109/CAI64502.2025.00195

Chen Z, et al (2020) Towards intelligent incident management: why we need it and how we make it. In: Proceedings of the 28th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering (ESEC/FSE 2020), pp 1487–1497, https://doi.org/10.1145/3368089.3417055

Contractor F, Li L, Al Mallah R (2025) Learning to communicate in multi-agent reinforcement learning for autonomous cyber defence. In: Proceedings of the International Conference on Machine Learning and Cybernetics (ICMLC 2025), pp 26–31, https://doi.org/10.1109/ICMLC66258.2025.11280109

Ding R, et al (2023) TraceDiag: adaptive, interpretable, and efficient root cause analysis on large-scale microservice systems. In: Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering (ESEC/FSE 2023), pp 1762–1773, https://doi.org/10.1145/3611643.3613864

Dunsin D, Ghanem MC, Ouazzane K, et al (2025) Reinforcement learning for an efficient and effective malware investigation during cyber incident response. High-Confidence Computing 5(3):100299. https://doi.org/10.1016/j.hcc.2025.100299

Elicha J, Lopez J (2026) Dispatching advanced and adaptive intrusion responses for IIoT-based systems. Future Gener Comput Syst 179:108314. https://doi.org/10.1016/j.future.2025.108314

Ghanem MC, Wojtczak D, Benkhelifa E, et al (2026) Leveraging reinforcement learning for an efficient Windows registry analysis during cyber incident response. Sci Rep 16(1):26867. https://doi.org/10.1038/s41598-026-57787-6

Hamel-De le Court E, Badings T, Abate A, et al (2026) Robust shielding for safe reinforcement learning. arXiv preprint arXiv:2606.00270, URL https://arxiv.org/abs/2606.00270

Hammar K, Li T (2025) Online incident response planning under model misspecification through Bayesian learning and belief quantization. In: Proceedings of the 18th ACM Workshop on Artificial Intelligence and Security (AISec 2025), pp 40–51, https://doi.org/10.1145/3733799.3762965

Hammar K, Li Y, Alpcan T, et al (2026) Adaptive network security policies via belief aggregation and rollout. IEEE Trans Inf Forensics Secur 21:6544–6559. https://doi.org/10.1109/TIFS.2026.3709131

Hughes K, McLaughlin K, Sezer S (2022) Policy-based profiles for network intrusion response systems. In: Proceedings of the 2022 IEEE International Conference on Cyber Security and Resilience (CSR 2022), pp 279–286, https://doi.org/10.1109/CSR54599.2022.9850304

Jaber A, Endregard M, Mancini F, et al (2025) Mission-aware cyber incident response generation using reinforcement learning. In: Proceedings of the International Conference on Military Communication and Information Systems (ICMCIS 2025), https://doi.org/10.1109/ICMCIS64378.2025.11047892

Janisch J, Pevný T, Lisý V (2019) Classification with costly features using deep reinforcement learning. In: Proceedings of the AAAI Conference on Artificial Intelligence, pp 3959–3966, https://doi.org/10.1609/aaai.v33i01.33013959

Joshi S, Parbhoo S, Doshi-Velez F (2023) Learning-to-defer for sequential medical decision-making under uncertainty. Transactions on Machine Learning Research URL https://openreview.net/forum?id=0pn3KnbH5F

Kaelbling LP, Littman ML, Cassandra AR (1998) Planning and acting in partially observable stochastic domains. Artif Intell 101(1–2):99–134. https://doi.org/10.1016/S0004-3702(98)00023-X

Khozam S, Blanc G, Tixeuil S, et al (2025) DAMS: double deep Q-network approach for DDoS attack mitigation in SDN. In: ACM International Conference Proceeding Series, pp 1049–1056, https://doi.org/10.1145/3726122.3726282

Kim Y, Dán G (2025) Dynamic alert prioritization for real-time situational awareness: a hidden Markov model framework with active learning. IEEE Trans Dependable Secure Comput 22(6):6913–6928. https://doi.org/10.1109/TDSC.2025.3592127

Kitchenham B, Charters S (2007) Guidelines for performing systematic literature reviews in software engineering. Technical Report EBSE-2007-01, EBSE

Könighofer B, Bloem R, Jansen N, et al (2025) Shields for safe reinforcement learning. Commun ACM 68(11):80–90. https://doi.org/10.1145/3715958

Koupaei ANA, Demirkol I (2026) Designing a scalable and adaptive cyber incident response (DACIR) framework for SMEs. Journal of Intelligent Decision Making and Information Science 3(5S):131–141. https://doi.org/10.59543/jidmis.v3.1073

Kovtun V, Huralnyk A, Husak L, et al (2026) Risk-sensitive decision-making in security operations center alert escalation under resource constraints. In: CEUR Workshop Proceedings, pp 65–83

Levy I, et al (2026) ST-WebAgentBench: a benchmark for evaluating safety and trustworthiness in web agents. In: Proceedings of the International Conference on Learning Representations (ICLR 2026), URL https://arxiv.org/abs/2410.06703

Madras D, Pitassi T, Zemel R (2018) Predict responsibly: improving fairness and accuracy by learning to defer. In: Advances in Neural Information Processing Systems 31 (NeurIPS 2018)

Manoj Kumar R, Srinivasan K, Rohidh S, et al (2026) Adaptive NeuroDefense: graph neural network and reinforcement learning-based self-healing cybersecurity architecture. In: Proceedings of the 4th International Conference on Augmented Intelligence and Sustainable Systems (ICAISS 2026), pp 251–257, https://doi.org/10.1109/ICAISS68683.2026.11525610

Nimmathi SR (2026) Hybrid reinforcement learning and agentic artificial intelligence framework for predictive platform operations and DevOps orchestration. In: Proceedings of the 7th International Conference on Computational Vision and Bio Inspired Computing (ICCVBIC 2026), pp 1197–1203, https://doi.org/10.1109/ICCVBIC71195.2026.11689187

Noorul Hassan S, Sivaraman K (2026) An intelligent proactive cyber threat prediction model leveraging self-supervised deep learning and reinforcement-based control strategies. In: Proceedings of the 2026 International Conference on Trends in Quantum Computing and Emerging Business Technologies (TQCEBT 2026), https://doi.org/10.1109/TQCEBT67648.2026.11681196

Nyberg J, Johnson P (2024) Structural generalization in autonomous cyber incident response with message-passing neural networks and reinforcement learning. In: Proceedings of the 2024 IEEE International Conference on Cyber Security and Resilience (CSR 2024), pp 282–289, https://doi.org/10.1109/CSR61664.2024.10679456

Okafor E (2026) A leakage-free benchmark of offline policy learning for SOC alert triage. Mach Learn Appl 25:100984. https://doi.org/10.1016/j.mlwa.2026.100984

Opol C (2026) Audit files for "reinforcement learning for investigating, acting and escalating in IT incident triage and response: a systematic literature review". Zenodo [dataset], https://doi.org/10.5281/zenodo.XXXXXXX

Pacella M, Papadia G, Giliberti V (2026) Governed agentic process automation: a floor-safety guarantee for compliance-critical LLM routing. Algorithms 19(8):627. https://doi.org/10.3390/a19080627

Page MJ, McKenzie JE, Bossuyt PM, et al (2021) The PRISMA 2020 statement: an updated guideline for reporting systematic reviews. BMJ 372:n71

Peralta A, Olivas JA, Navarro-Illana P, et al (2025) A hybrid mathematical framework for dynamic incident prioritization using fuzzy Q-learning and text analytics. Mathematics 13(12):1941. https://doi.org/10.3390/math13121941

Raj AP, Gantayat SS, Sharma KV (2026) XAI-HDRL: an intelligent framework for cyber threat prediction and automated security response. In: Proceedings of the 7th International Conference on Smart Systems and Inventive Technology (ICSSIT 2026), pp 1115–1123, https://doi.org/10.1109/ICSSIT69151.2026.11656470

Ravi RV, Priyanga KK, Adarsh MD (2025) SAFE-HGX: a hierarchical and safety-aware reinforcement learning framework for intrusion response in industrial control systems. In: Proceedings of the 2025 1st International Conference on Advancement in Futuristic Technologies (ICAFT 2025), https://doi.org/10.1109/ICAFT66710.2025.11453104

Reddy Avula CS (2026) XAI for automated prediction model for cyber incident response and security support in cloud. In: Proceedings of the 2026 2nd International Conference on Big Data and Machine Learning (ICBDML 2026), https://doi.org/10.1109/ICBDML68582.2026.11544635

Remil Y, Bendimerad A, Mathonat R, et al (2024) AIOps solutions for incident management: technical guidelines and a comprehensive literature review. arXiv preprint arXiv:2404.01363, URL https://arxiv.org/abs/2404.01363

Ren S, Jin J, Niu G, et al (2025) ARCS: adaptive reinforcement learning framework for automated cybersecurity incident response strategy optimization. Appl Sci 15(2):951. https://doi.org/10.3390/app15020951

Rojas Rodriguez JS, Lahmadi A, Rusinowitch M (2026) CauseRL: reinforcement learning-based random walks for root cause analysis in microservices. In: Proceedings of the ACM Symposium on Applied Computing (SAC 2026), pp 257–264, https://doi.org/10.1145/3748522.3779836

Saeed MM (2025) An AI-driven cybersecurity framework for IoT: integrating LSTM-based anomaly detection, reinforcement learning, and post-quantum encryption. IEEE Access 13:104027–104036. https://doi.org/10.1109/ACCESS.2025.3576506

Şahin F, Mert NS (2026) Dual-threshold conformal deferral for trustworthy security alert triage. Electronics 15(18):4084. https://doi.org/10.3390/electronics15184084

Singh T (2026) Autonomous AI decision control tower: a deterministic multi-agent decision intelligence framework for enterprise NoOps. In: Proceedings of the 2026 IEEE 1st International Conference on Artificial Intelligence Implementation and Applications (ICAIIA 2026), pp 190–195, https://doi.org/10.1109/ICAIIA70172.2026.11691884

Sutton RS, Barto AG (2018) Reinforcement Learning: An Introduction, 2nd edn. MIT Press, Cambridge, MA

Tong L, Laszka A, Yan C, et al (2020) Finding needles in a moving haystack: prioritizing alerts with adversarial reinforcement learning. In: Proceedings of the 34th AAAI Conference on Artificial Intelligence (AAAI 2020), pp 946–953

Turan E (2026) Oversight has a capacity: calibrating agent guards to a subjective, fatiguing human. arXiv preprint arXiv:2606.08919, URL https://arxiv.org/abs/2606.08919

Varsha MP, Samyuktha S, Manochithra S, et al (2025) LLM-powered deep reinforcement learning for predictive cyber threat mitigation. In: Proceedings of the 5th International Conference on Ubiquitous Computing and Intelligent Information Systems (ICUIS 2025), pp 1020–1025, https://doi.org/10.1109/ICUIS67429.2025.11380737

Wang L, et al (2023) Root cause analysis for microservice systems via hierarchical reinforcement learning from human feedback. In: Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD 2023), pp 5116–5125, https://doi.org/10.1145/3580305.3599934

Wang Y, Zhu Z, Fu Q, et al (2024) MRCA: metric-level root cause analysis for microservices via multi-modal data. In: Proceedings of the 39th ACM/IEEE International Conference on Automated Software Engineering (ASE 2024), pp 1057–1068, https://doi.org/10.1145/3691620.3695485

Wu Z, Fu H, Wang L, et al (2026) Research on cross-layer link fault root cause localization algorithm for microservice architecture integrating deep reinforcement learning. In: Proceedings of the 2026 IEEE 6th International Conference on Electronic Technology, Communication and Information (ICETCI 2026), pp 421–426, https://doi.org/10.1109/ICETCI68937.2026.11610700

Yuan Y (2026) Self-healing and intelligent root cause analysis system for data link faults in cloud-native environments. In: Proceedings of the 2026 6th International Conference on Applied Mathematics, Modelling and Intelligent Computing (CAMMIC 2026), pp 941–946, https://doi.org/10.1145/3817124.3817267