Supplement: Dictionary-Based Slang Normalization for Indonesian Sentiment Classification

Working Draft
Authors and affiliations to be confirmed

These tables accompany the main manuscript and use its frozen held-out predictions. O/N denotes training on original inputs and evaluating normalized inputs; the first symbol always denotes the training condition. Scores for the three IndoBERT seeds use the same held-out reviews and are not independent test samples. No additional model was trained or selected for these tables.

TABLE S1
INDOBERT MATCHED-PIPELINE RESULTS BY SEED

Data	Seed	O/O	N/N	$N/N - O/O$
PRDECT	13	.9848	.9734	$-.0114$
	37	.9823	.9886	$+.0063$
	73	.9861	.9810	$-.0051$
SmSA	13	.8905	.9058	$+.0153$
	37	.8858	.9008	$+.0150$
	73	.8726	.9029	$+.0303$

Differences are paired by seed; the sample SDs of the three effects are .0090 and .0088, respectively. These SDs are distinct from conditional test-sample intervals.

TABLE S2
MATCHED-PIPELINE CLASS F1 AND SUPPORT

Data	Model	Class	n	O/O	N/N
PRDECT	Word	Neg.	412	.9593	.9666
		Pos.	381	.9547	.9626
	Char.	Neg.	412	.9618	.9631
		Pos.	381	.9572	.9585
	BERT	Neg.	412	.9852	.9820
		Pos.	381	.9836	.9801
SmSA	Word	Neg.	204	.8426	.8337
		Neu.	88	.5263	.5674
		Pos.	208	.8363	.8232
	Char.	Neg.	204	.8145	.8238
		Neu.	88	.5507	.5612
		Pos.	208	.7990	.8103
	BERT	Neg.	204	.9372	.9495
		Neu.	88	.7769	.8248
		Pos.	208	.9348	.9352

Support n counts distinct reviews. BERT F1 is the arithmetic mean of seed-specific F1 scores, not a pooled prediction score.

TABLE S3
FIXED-MODEL TRANSITIONS: SEED MEAN AND UNIQUE REVIEWS

Data	Model	Direction	Corrected	Introduced
PRDECT	Word	$O \to N$	10 / 10	9 / 9
		$N \to O$	7 / 7	29 / 29
	Char.	$O \to N$	5 / 5	1 / 1
		$N \to O$	8 / 8	17 / 17
	BERT	$O \to N$	.67 / 1	1.33 / 3
		$N \to O$	1.67 / 5	1.67 / 4
SmSA	Word	$O \to N$	1 / 1	0 / 0
		$N \to O$	1 / 1	3 / 3
	Char.	$O \to N$	2 / 2	0 / 0
		$N \to O$	1 / 1	1 / 1
	BERT	$O \to N$	.33 / 1	.33 / 1
		$N \to O$	1.33 / 4	0 / 0

Entries show mean / unique. Corrected and introduced mean incorrect-to-correct and correct-to-incorrect, respectively. For BERT, the mean is across seeds, and unique is the union of review IDs within the category; a review can appear in both categories across different seeds. $O \to N$ fixes the original-trained model; $N \to O$ fixes the normalized-trained model.

TABLE S4
RETAINED CLASS SUPPORT BY SPLIT

Data	Train	Validation	Test
PRDECT	1922 / – / 1780	412 / – / 381	412 / – / 381
SmSA	3407 / 1136 / 6376	394 / 131 / 735	204 / 88 / 208

Counts are negative / neutral / positive; PRDECT-ID has no neutral class. Splits and label mappings were fixed before evaluation.

TABLE S5
VALIDATION-SELECTED SETTINGS AND FINAL INDOBERT EPOCHS

Data	Cond.	Word C	Char. C	BERT LR	Epochs
PRDECT	O	1	1	2×10^{-5}	2 / 3 / 3
	N	1	1	2×10^{-5}	3 / 2 / 4
SmSA	O	1	1	2×10^{-5}	3 / 5 / 2
	N	10	1	3×10^{-5}	2 / 4 / 5

Epochs are best validation epochs for final seeds 13 / 37 / 73. Learning rates and C were selected on validation; no test-based retuning was performed.

ARTIFACT AVAILABILITY AND REPRODUCTION

The local `review_snapshot_v2` includes manuscript sources, preview PDFs, code, and aggregate results; it excludes review-level inputs or predictions, dictionary mappings, weights, private payloads, and credentials. It is not public and grants no code license. `REPRODUCIBILITY.md` documents commands and tested limits. Exact replay requires private original artifacts; the full workflow was not rerun from the snapshot.

PRDECT-ID's source states CC BY 4.0; the IndoBERT card states MIT. The pinned IndoNLU license file says Apache 2.0 but its README displays an MIT badge; SmSA terms remain unresolved. No explicit Kamus Alay license was identified.