

Voxelwise statistic, two independent groups

CONTENTS

- 1) Create a group-assignment (Excel-file)
- 2) Perform the voxelwise-T-test (independent group)
- 3) Examine Results
 - 3.1) EXPORT RESULTS-TABLE AS EXCELFILE
 - 3.2) DISPLAY RESULT TABLE IN COMMAND WINDOW
 - 3.3) EXPORT RESULTS-TABLE AS TXT-FILE
 - 3.4) SAVE THRESHOLDED IMAGE AS NIFTI-FILE
 - 3.5) EXTRACT PEAK DATA
 - 3.6) CREATE SUMMARY OF CURRENT CONTRAST
 - 3.7) Change to Cluster-based approach
- 4) Check the other contrast
- 5) CREATE BIG-SUMMARY
- 6) Define new Contrast
- 7) Work from Command line
 - 7.1) run voxelwise statistic from command line
 - 7.2) Create full report

Scenario

-**Artificial data** for 14 animals were created, with spherical differences centered in the a) **left Primary somatosensory area mouth layer 4** and b) the **right CaudoPutamen**

Here we have two groups with 6 and 8 animals in each group. The artificially created files are stored as "vimg.nii"-image in the respective animal-folders. Note that the animal-folders are empty, except of the "vimg.nii"-image. This image is in register to the Allen mouse brain atlas (i.e already in standard space).


Prerequisites

-a project with project file was created ...when doing this analysis with your own data, the image that should be analyzed using voxelwise statistic must be in the standard/template space (here : Allen mouse brain space). For instance when analyzing the gray matter image("c1t2.nii"), the image has to be transformed to standard space to make voxelwise statistic feasible.


-Templates: here ,the **mouse_Allen2017HikishimaLR'**-template is already imported in the study's templates-folder

- start ANT-gui and set current working directory to project-folder path

-load project (m-file, here proj.m)



The Figure shows the list of 14 animals (left listbox). Animals of group-1 is selected (just for displaying purpose). Note that for this animals artificial data were created.




The figure shows the simulated image 'vimg.nii' (image is in standard-space) of one animal from the 2nd group with increased intensities centered at a) the left Primary somatosensory area mouth layer 4 and b) the right CaudoPutamen.

1) Create a group-assignment (Excel-file)

We now need a group-assignment file (Excel-file) with definitions of animals and group-assignment.

For this select: **Statistic/create group assignment file** from the **ANTx-MENU**.

This will open the respective parameter file. We keep the default parameter and hit **[RUN]**.



To this end, the Excelfile **"groupassignment.xlsx"** is created, located in the **"group"**-folder in the current study directory (**"F:\data6\voxwise\group"**).

```
.. create group-assignment file ...wait
new group-file [groupassignment.xlsx]: Explorer or open
Done!
fx >>
```

You can select the **'open'-hyperlink** in the command-window to open the Excel-file. The 1st sheet of the excelfile looks as follows:

	A	B	C	D	E	F	G	H	I
1	animal	group	group-column: please specify which animal belongs to which group as string (preferred) or numeric value avoid any spaces!!! example: "control" for "control"-animals; "ABC" for animals from "ABC-group"						
2	animal_grp1_001								
3	animal_grp1_002								
4	animal_grp1_003								
5	animal_grp1_004								
6	animal_grp1_005								
7	animal_grp1_006								
8	animal_grp2_007								
9	animal_grp2_008								
10	animal_grp2_009								
11	animal_grp2_010								
12	animal_grp2_011								
13	animal_grp2_012								
14	animal_grp2_013								
15	animal_grp2_014								
16									

The first column contains the animal-IDs of all animals of the current study. The 2nd column has to be filled with the respective group-assignment. Here the 1st 6 animals belong to the control-group, thus the 'control'-string is inserted for those animals, while the other animals belong to the "VIMG"-group, thus the "VIMG"-string is inserted in the 2nd column (see Fig. below). Note that the string-names are arbitrary. Try to avoid special characters! Save this modifications (here the same filename, "groupassignment.xlsx", is used).

	A	B	C	D	E	F	G	H	I
1	animal	group	group-column: please specify which animal belongs to which group as string (preferred) or numeric value avoid any spaces!!! example: "control" for "control"-animals; "ABC" for animals from "ABC-group"						
2	animal_grp1_001	control							
3	animal_grp1_002	control							
4	animal_grp1_003	control							
5	animal_grp1_004	control							
6	animal_grp1_005	control							
7	animal_grp1_006	control							
8	animal_grp2_007	VIMG							
9	animal_grp2_008	VIMG							
10	animal_grp2_009	VIMG							
11	animal_grp2_010	VIMG							
12	animal_grp2_011	VIMG							
13	animal_grp2_012	VIMG							
14	animal_grp2_013	VIMG							
15	animal_grp2_014	VIMG							
16									


2) Perform the voxelwise-T-test (independent group)

We now want to run the independent voxelwise t-test comparing the two groups for the "vimg.nii"-image.

For this select: **Statistic/SPM-statistic** from the **ANTx -MENU**. This will call the main GUI (from the function [xstat.m](#)):




Next, select the [**indepStat**]-button to open the parameter-GUI for the voxelwise independent t-test (TWO-SAMPLE-TTEST). The default parameter-GUI looks as follows:




We now need to modify (or check) some parameters:

- “**x.excelfile**”: click the left icon and select the group-assignment-file (“groupassignment.xlsx”) located in the group-folder.
- “**x. data_dir**”: click the left icon and select the study’s dat-folder (This folder contain the animals-data and the image that should be statistically tested).
- “**x. inputimage**”: click the left icon and select the image that should be statistically tested: Specifically in the file-selector GUI select “**vimg.nii**”, hit [OK].




- “**x. AVGT**”: click the left icon and select the AVGT-image (“AVGT.nii”) from the study’s templates-folder.
- “**x. ANO**”: click the left icon and select the ANO-image (“ANO.nii”, i.e. the Atlas) from the study’s templates-folder.
- “**x. mask**”: click the left icon and select the AVGTmask-image (“AVGTmask.nii”) from the study’s templates-folder. Note that the animal-folders only contain the ‘vimg.nii’-image. Thus we have to assign the brain-mask (“AVGTmask.nii”) from the templates-folder.
- “**x.output_dir**”: define the output-folder for the voxelwise statistic, here “**voxtest1**”.

The parameter-Gui should now looks as follows:



Note that the image ‘vimg.nii’ will be smoothed (“x.smoothing” is set to [1]) by the triple of the voxel-resolution (“x.smoothing_fwhm” is [0.28 0.28 0.28]). Note also, that “x.showSPMbatch” is set to [1]. This parameter will open the SPM-batch-GUI, when hitting the [RUN]-button, allowing for final post-parameter configurations.

Hit [RUN]-button to run the voxelwise statistic. Because the parameter “x.showSPMbatch” was set to [1], the SPM-batch-GUI will pop-up, allowing for specific post-parameter configurations and final checks (see Fig. below).



Here, everything seems to be ok and no further changes will be made. Hit **[RUN BATCH]**-button (green triangle) to execute this batch. The process will take a couple of minutes.

When done, you can obtain the **xstat-batch**, by typing: **“char(anth)”** in Matlab-cmd window or clicking the **[anth]**-button from the **ANTx-main GUI**:

```
% % =====
% % #g FUNCTION:      [xstat.m]
% % #b info :        xstat: voxelwise statistic [SPM-statistic] for normalized data (nifti volumes)
% % =====
z=[];
z.stattype      = 'twosamplletest'; % % STATISTICAL TEST
z.excelfile     = 'F:\data6\voxwise\group\groupassignment.xlsx'; % % [Excelfile]: this file contains a column with mouseIDs (names) and a column
% % assigning the group
z.sheetnumber   = [1]; % % this sheet contains columns with mouseIDs and group assignment
z.mouseID_col   = [1]; % % column number with the MouseIDs
z.group_col     = [2]; % % column number with group assignment(used when comparing groups, "regress_col"
% % must be empty)
z.data_dir      = 'F:\data6\voxwise\dat'; % % data directory (upper directory) contains dirs with mice data
z.inputimage    = 'vimg.nii'; % % image name (nifti) to run the statistic (datapath has to be defined before
% % using the icon)
z.AVGT          = 'F:\data6\voxwise\templates\AVGT.nii'; % % select the TEMPLATE-file (path of "AVGT.nii")
z.ANO           = 'F:\data6\voxwise\templates\ANO.nii'; % % select the ATLAS-file (path of "ANO.nii")
z.grp_comparison = 'lvs2'; % % groups to compare, use EXCELgroupnames(example: "GroupName1vsGroupName2")
% % or alphabet. order (example: "lvs2"), or
z.mask          = 'F:\data6\voxwise\templates\AVGTmask.nii'; % % <optional> use brainmask [select a mask or type "local" to use the AVGTmask.nii
% % from the templates folder]
z.smoothing     = [1]; % % <optional>smooth data
z.smoothing_fwhm = [0.28 0.28 0.28]; % % smoothing width (FWHM)
z.output_dir    = 'voxtest1'; % % path for output/statistic
z.showSPMbatch  = [1]; % % [0|1] hide/show pipeline in SPM batch window, if [1] you have to run the code
% % by yourself ( hit the green drianle), [0] pipes runs automatically

xstat(1,z); % % RUN
```


To re-run the analysis just execute the code above.

3) Examine Results


If the xstat-GUI is closed, type **‘xstat’** in the cmd-window or select: **Statistic/SPM-statistic** from the **ANTx-MENU**.

Next, hit the **[load CON1]**-button (below the xstat-“View Results” section) to load the 1st contrast from the analysis.


Next, select the path of the voxelwise analysis-folder (**‘voxtest1’**) and the respective **SPM.mat**-file (In the below Fig: Select **SPM.mat** from the right listbox, which than appears in the lower listbox, finally hit **[Done]**).



Basically, for the independent t-statistic two contrasts will be calculated by default ('A>B' and 'A<B'). Executing the **[load CON1]**-button displays the 1st contrast ('VIMG>control').



The SPM-graphics window will show the voxelwise results for the 1st contrast 'VIMG>control' with the parameters, FWE at $p=0.05$, with min. survival spatial cluster (aka clustersize / sl-k) = 1 voxel. As expected, there are two significant 'blobs'. To see the associated results table with anatomical annotations, hit the **[show table]**-button from the xstat-GUI.




Because, the number of peaks per cluster (**#p/CI**) is set to 3 and the cluster distance (**CLdist**) is set to 0.5 mm we see three peak clusters within the large left-hemispheric blob. You can change the respective settings for **"#p/CI"** and **"CLdist"** in the xstat-GUI and **update** the graphic window by hitting the **'VIMG>control'**-contrast from the xstat-listbox.

Again, to **update** any changes in the parameters just select the respective contrast from the xstat contrast listbox. To show the volume again, hit the **[show volume]**-button.

3.1) EXPORT RESULTS-TABLE AS EXCELFILE

To export the results as Excel table, hit the **[export xlsx]**-button. The GUI will prompt you for a path and a proper filename of the Excel file. Note that per default, the output-path is predefined (new folder: 'res_'+name of the analysis-folder), here: "res_voxtest1" is the output-folder, which again contains a subfolder "data" that will contain the output. Also, the filename is predefined, based on the image, contrast-number, contrast-name, method, p-value and clustersize. Thus the filename is: "svimg_C1_VIMG_GT_control_FWE0.05k1.xlsx".



Without changing the path and filename, just hit the **[save]**-button.

```
...export table..wait..
voxSTAT-excelfile [svimg_C1_VIMG_GT_control_FWE0.05k1.xlsx]: Explorer or open
DONE!
fx >>
```

When done click the **[open]**-hyperlink to open the Excel file. The Excel file contains two sheets.

The “voxstat”-sheet contains the results-table:

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
1	set	set	cluster	cluster	cluster	peak	peak	peak	peak	peak	x	y	z	Labels			
2	p	c	p(FWE-corr)	p(FDR-corr)	equivk	p(unc)	p(FWE-corr)	p(FDR-corr)	T	equiv2	p(unc)	mm	mm	mm			
3	1.91226E-05	2	0		2474	6.7698E-301	0	0	108.5761719	65535	4.44089E-16	-3.645000398	0.375518739	-1.450335264	Primary somatosensory area mouth layer 2/3		img: svimg.nii
4							0	0	82.11476898	65535	4.44089E-16	-3.295000434	-0.044481218	-4.570335257	Primary somatosensory area mouth layer 5		vimd-control
5						3.27609E-10	9.98809E-13	58.04750824	65535	4.44089E-16	-3.155000448	0.445518732	-1.170335293	Primary somatosensory area mouth layer 4			NAME: FWE
6			0		176	2.91252E-52	5.15985E-08	4.81779E-11	38.04288864	7.487144601	3.51941E-14	2.374998987	-0.044481218	-2.780335128	Caudoputamen		TR: 0.05
																	k: 1
7																	
8																	
9																	
10																	
11																	
12																	
13																	
14																	
15																	
16																	
17																	
18																	
19																	
20																	
21																	
22																	
23																	
24																	
25																	
26																	
27																	
28																	
29																	
30																	
31																	
32																	
33																	
34																	
35																	
36																	
37																	
38																	
39																	
40																	
41																	
42																	
43																	
44																	
45																	
46																	
47																	
48																	
49																	
50																	
51																	
52																	
53																	
54																	
55																	
56																	
57																	
58																	
59																	
60																	
61																	
62																	
63																	
64																	
65																	
66																	
67																	
68																	
69																	
70																	
71																	
72																	
73																	
74																	
75																	
76																	
77																	
78																	
79																	
80																	
81																	
82																	
83																	
84																	
85																	
86																	
87																	
88																	
89																	
90																	
91																	
92																	
93																	
94																	
95																	
96																	
97																	
98																	
99																	
100																	
101																	
102																	
103																	
104																	
105																	
106																	
107																	
108																	
109																	
110																	
111																	
112																	
113																	
114																	
115																	
116																	
117																	
118																	
119																	
120																	
121																	
122																	
123																	
124																	
125																	
126																	
127																	
128																	
129																	
130																	
131																	
132																	
133																	
134																	
135																	
136																	
137																	
138																	
139																	
140																	
141																	
142																	
143																	
144																	
145																	
146																	
147																	
148																	

The “info”-sheet contains information to backtrack the statistical results:

1	Field	value
2	Image	svimg.nii
3	contrast	VIMG>control
4	MCP	FWE
5	Threshold	p<0.05
6	Clustersize	k=1
7	contrastName	VIMG>control
8	contrastNo	No-1
9	statistic	T
10	contrastDir	[1 -1]
11	dir	F:\data6\voxwise\voxtest1
12	INPUT-DATA***	
13	ANIMAL/Dir	Path
14	animal_grp2_007	F:\data6\voxwise\dat\animal_grp2_007\svimg.nii 1 0
15	animal_grp2_008	F:\data6\voxwise\dat\animal_grp2_008\svimg.nii 1 0
16	animal_grp2_009	F:\data6\voxwise\dat\animal_grp2_009\svimg.nii 1 0
17	animal_grp2_010	F:\data6\voxwise\dat\animal_grp2_010\svimg.nii 1 0
18	animal_grp2_011	F:\data6\voxwise\dat\animal_grp2_011\svimg.nii 1 0
19	animal_grp2_012	F:\data6\voxwise\dat\animal_grp2_012\svimg.nii 1 0
20	animal_grp2_013	F:\data6\voxwise\dat\animal_grp2_013\svimg.nii 1 0
21	animal_grp2_014	F:\data6\voxwise\dat\animal_grp2_014\svimg.nii 1 0
22	animal_grp1_001	F:\data6\voxwise\dat\animal_grp1_001\svimg.nii 0 1
23	animal_grp1_002	F:\data6\voxwise\dat\animal_grp1_002\svimg.nii 0 1
24	animal_grp1_003	F:\data6\voxwise\dat\animal_grp1_003\svimg.nii 0 1
25	animal_grp1_004	F:\data6\voxwise\dat\animal_grp1_004\svimg.nii 0 1
26	animal_grp1_005	F:\data6\voxwise\dat\animal_grp1_005\svimg.nii 0 1
27	animal_grp1_006	F:\data6\voxwise\dat\animal_grp1_006\svimg.nii 0 1
28	ADDITIONAL INFO***	
29		table shows 3 local maxima more than 0.5mm apart
30		Height threshold: T = 11.64, p = 0.000 (0.050)
31		Extent threshold: k = 1 voxels, p = 0.023 (0.006)

3.2) DISPLAY RESULT TABLE IN COMMAND WINDOW

Select **[table-2-CMD]**-button display the results-table in the command window:

```

Command Window
[VIMG>control] Result:
=====
set    set    cluster  cluster  cluster  cluster  peak    peak    peak    peak
p      c      p(FWE-corr) p(FDR-corr) equivk  p(unc)  p(FWE-corr) p(FDR-corr) T      equi
=====
1.9123e-05 2      0      2474  6.7698e-301 0      0      108.576 Ir
|
|      0      176  2.9125e-52 3.2761e-10 9.9881e-13 58.048 Ir
|
|      0      176  2.9125e-52 5.1598e-08 4.8178e-11 38.043 7.4
=====
table shows 3 local maxima more than 0.5mm apart
Height threshold: T = 11.64, p = 0.000 (0.050)
Extent threshold: k = 1 voxels, p = 0.023 (0.006)
Expected voxels per cluster, <k> = 0.181
Expected number of clusters, <c> = 0.01
FWEP: 11.641, FDRp: 5.084, FWEc: 176
Degrees of freedom = [1.0, 12.0]
FWHM = 0.30 0.30 0.30 mm mm mm; 4.28 4.27 4.28 {voxels}
Volume: 506 = 1475422 voxels = 18004.8 resels
Voxel size: 0.07 0.07 0.07 mm mm mm; (resel = 78.19 voxels)
fx >>

```

3.3) EXPORT RESULTS-TABLE AS TXT-FILE

To export the results as text-file, hit the **[export txt]**-button. When path/file is not changed this will save the results-table as "svimg_C1_VIMG_GT_control_FWE0.05k1.txt" in the "res_voxtest1\data"-folder:

```

svimg_C1_VIMG_GT_control_FWE0.05k1.txt
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20

```

set	set	cluster	cluster	cluster	cluster	peak	peak	peak	peak	peak	x	y	z	Labels
p	c	p(FWE-corr)	p(FDR-corr)	equivk	p(unc)	p(FWE-corr)	p(FDR-corr)	T	equivZ	p(unc)	mm	mm	mm	
1.9123e-05	2	0		2474	6.7698e-301	0	0	108.576	Inf	4.4409e-16	-3.65	0.38	-1.45	Primary somatosensory area mouth layer 2/3
						0	0	82.115	Inf	4.4409e-16	-3.30	-0.04	-1.52	Primary somatosensory area mouth layer 5
		0		176	2.9125e-52	3.2761e-10	9.9881e-13	58.048	Inf	4.4409e-16	-3.16	0.45	-1.17	Primary somatosensory area mouth layer 4
						5.1598e-08	4.8178e-11	38.043	7.487	3.5194e-14	2.37	-0.04	-2.78	Caudoputamen

```

table shows 3 local maxima more than 0.5mm apart
Height threshold: T = 11.64, p = 0.000 (0.050)
Extent threshold: k = 1 voxels, p = 0.023 (0.006)
Expected voxels per cluster, <k> = 0.181
Expected number of clusters, <c> = 0.01
FWEP: 11.641, FDRp: 5.084, FWEc: 176
Degrees of freedom = [1.0, 12.0]
FWHM = 0.30 0.30 0.30 mm mm mm; 4.28 4.27 4.28 {voxels}
Volume: 506 = 1475422 voxels = 18004.8 resels
Voxel size: 0.07 0.07 0.07 mm mm mm; (resel = 78.19 voxels)

```

3.4) SAVE THRESHOLDED IMAGE AS NIFTI-FILE

To save the thresholded (surviving) t-map as NIFTI-file hit the **[save volume]**-button. The GUI will prompt you for a path and a proper filename. Note that per default, the output-path is predefined (new folder: 'res_'+analysis-folder), here:

"res_voxtest1" in the subfolder "data". Also, the filename is predefined, based on the image, contrast-number, contrast-name, method, p-value and clustersize. Thus, the filename is: "thresh_svimg_C1_VIMG_GT_control_FWE0.05k1.nii".




When done you can select the hyperlink **"MRicron"** from the command-window to open the saved statistical t-map overlaid onto the template ('AVGT.nii') via MRicron.

```

...saving volume...wait..
voxSTAT-volume [AVGT.nii - thresh_svimg_C1_VIMG_GT_control_FWE0.05k1.nii]: Explorer or MRicron
Done!
fx >>

```



Alternatively, you can hit the **[show MRicron]**-button from the xstat-GUI and select the respective NIFTI ("thresh_svimg_C1_VIMG_GT_control_FWE0.05k1.nii").

3.5) EXTRACT PEAK DATA

To extract the single data (for each animal) of the surviving peak-data of the results-table hit the **[extract data]** button. The GUI will prompt you for a path and a proper filename of the file. Note that per default, the output-path is predefined (new folder: 'res_'+analysis-folder), here: "res_voxtest1" in the subfolder "data". Also, the filename is predefined, based on the image, contrast-number, contrast-name, method, p-value and clustersize. Thus the filename is:

"svimg_C1__VIMG_GT_control__FWE0.05k1_NPC3_ SINGLEDATA.xlsx". Thus, just hit [save].

```
..Extracting data ...wait...DONE!
data extracted [svimg_C1__VIMG_GT_control__FWE0.05k1_NPC3_SINGLEDATA.xlsx]: Explorer or open
fx >>
```

When done, hit the “open”-hyperlink from the cmd-window to open the Excelfile:

A1		animal				
A	B	C	D	E	F	
1	animal	group	Primary somatosensory area mouth layer 2/3	Primary somatosensory area mouth layer 5	Primary somatosensory area mouth layer 4	Caudoputamen
2			[-3.645,0.37552,-1.4503]	[-3.295,-0.044481,-1.5203]	[-3.155,0.44552,-1.1703]	[2.375,-0.044481,-2.7803]
3	animal_grp2_007	VIMG	1.726580307	1.583499897	1.03667339	0.586593763
4	animal_grp2_008	VIMG	1.7326013138	1.523868497	1.047932843	0.680032164
5	animal_grp2_009	VIMG	1.732084074	1.623216213	1.031859421	0.640895512
6	animal_grp2_010	VIMG	1.756582342	1.609011189	0.995671776	0.647707161
7	animal_grp2_011	VIMG	1.661035182	1.618879633	0.984121443	0.572897365
8	animal_grp2_012	VIMG	1.689820455	1.649107412	1.045689146	0.604441618
9	animal_grp2_013	control	1.65941989	1.512732024	1.113033319	0.562852522
10	animal_grp2_014	control	1.645523203	1.578066608	1.0228984	0.600093372
11	animal_grp1_001	control	-0.437822931	-0.412956494	-0.254568327	-0.132901531
12	animal_grp1_002	control	-0.364898759	-0.367373546	-0.250484564	-0.180948705
13	animal_grp1_003	control	-0.433699804	-0.320627867	-0.334920369	-0.104890912
14	animal_grp1_004	control	-0.383939185	-0.434580515	-0.232331362	-0.188000394
15	animal_grp1_005	VIMG	-0.403700956	-0.37832031	-0.239073993	-0.168422552
16	animal_grp1_006	VIMG	-0.40903667	-0.393954919	-0.268529537	-0.13337737
17						
18						

extractdata

The file contains the single-values from each animal (with animal-id and group-assignment) for the 4 observed peaks.


3.6) CREATE SUMMARY OF CURRENT CONTRAST

To obtain a fast summary of the current contrast, select from the **xstat-MENU**: **posthoc/create summary of current contrast**. This will create a Powerpoint-file with the summary for the 1st contrast. Note that the current settings from the xstat-GUI (MCP, thresh, CL-l, “#p/Cl” and “CLdist”) are used.

```
summary saved [sum_sving_con1_VIMG_GT_control_FWE0.05k1.pptx]: Explorer or open
fx >>
```


When done, hit the “open”-hyperlink from the cmd-window to open the PPT-file:

Note that the PPT-file is directly stored in the "res_voxtest1"-folder ('res_'+analysis-folder).




3.7) Change to Cluster-based approach

Now, we are switching from the FEW-method to the cluster-based approach. For this select '**clusterbased, at 0.001**' from the pull-down menu left to MCP-field:




When selected the cluster-based approach will automatically run, and first set the p-value to 0.001, uncorrected and estimates the spatial threshold, i.e. the minimum number of neighboring voxels mandatory for a significant cluster. Next, this spatial threshold is used for the cluster-based approach. Here, a significant cluster-based height threshold at $p=0.001$ needs 164 neighboring voxels to survive.




For the cluster-based approach, the results are quite similar compared to the FWE-approach.

4) Check the other contrast


Now, select the 2nd contrast 'VIMG<control' from the xstat-contrast listbox.




Based on the previous settings, the **cluster-based approach** shows no significant clusters.



Now, select '**FWE at 0.05, clustersize=1**' from the xstat-pulldown MENU and **update** the graphics-window by selecting the 2nd contrast '**VIMG<control**' from the contrast-listbox



We see that for the 2nd contrast, '**VIMG<control**', nothing survives FWE-correction:



5) CREATE BIG-SUMMARY

Sometimes it is useful to obtain a summary for all existing contrasts and all methods (uncorrected, FEW and cluster-based approach). For this, select from the **xstat-MENU**: **posthoc/all methods summary & export tables all contrasts**. This will create three PowerPoint-files in the "res_voxtest1"-folder and also export the resulting tables as Excel-files and will store the respective t-maps as NIFTI-files.


The procedure will create three PPT-files:

'sum_UNCOR_svimg_none0.001k1.pptx' -uncorrected at $p=0.001$

'sum_FWE_svimg_FWE0.05k1.pptx' -using the FWE approach

'sum_CLUST_svimg_CLUST0.001k164.pptx' -using the cluster-based approach

The below figure displays the summary of the FWE approach. This Powerpoint-file contains the table (or first part of the table, depending on the table size) and displays the volume with surviving voxels for the 1st contrast (slides 1-2) and the 2nd contrast (slides 3-4). Note, there are no surviving voxels for the 2nd contrast.




Note that this routine also creates the NIFTI-files and result-tables (Excel-files) for all contrast. The folder **"..\\res_voxtest1\\data"** contains these files:


Name	Änderungsdatum	Typ
svimg_C1_VIMG_GT_control_CLUST0.001k164.nii	23.11.22 11:55	NII
svimg_C1_VIMG_GT_control_CLUST0.001k164.xlsx	23.11.22 11:55	Mi
svimg_C1_VIMG_GT_control_FWE0.05k1.nii	23.11.22 11:55	NII
svimg_C1_VIMG_GT_control_FWE0.05k1.bt	23.11.22 10:45	TX
svimg_C1_VIMG_GT_control_FWE0.05k1.xlsx	23.11.22 11:56	Mi
svimg_C1_VIMG_GT_control_none0.001k1.nii	23.11.22 11:53	NII
svimg_C1_VIMG_GT_control_none0.001k1.xlsx	23.11.22 11:53	Mi
svimg_C2_VIMG_LT_control_CLUST0.001k164.nii	23.11.22 11:55	NII
svimg_C2_VIMG_LT_control_CLUST0.001k164.xlsx	23.11.22 11:55	Mi
svimg_C2_VIMG_LT_control_FWE0.05k1.nii	23.11.22 11:56	NII
svimg_C2_VIMG_LT_control_FWE0.05k1.xlsx	23.11.22 11:56	Mi
svimg_C2_VIMG_LT_control_none0.001k1.nii	23.11.22 11:54	NII
svimg_C2_VIMG_LT_control_none0.001k1.xlsx	23.11.22 11:54	Mi

6) Define new Contrast

To define a new contrast hit **[new contrast]**-button from the **xstat-GUI**. When asked, select the specific **SPM.mat** from the voxelwise analysis-folder. In the SPM contrast-manager, select **[Define new contrast]**:



Here we select an F-contrast (**radio: F-contrast**). Enter **'F-stat'** in the name-field and enter **[1 -1]** in the field 'contrast weights matrix'. Please try to avoid special characters for the contrast-name.




Then, hit **[submit]**-button, and hit **[OK]**. When done, a 3rd contrast (F-contrast) with name **"F-stat"** is created.




Hit **Done**-button. Next, you have to enter some parameters:


1) Masking, click **none**.




2) Method to control the multiple comparison problem: hit **FWE**.




3) p-value: (keep 0.05), just hit the **enter**-key.



4) Extend/spatial threshold: (keep 0), just hit the **enter**-key.



This will produce the output in the graphic window for the F-contrast:



Note also that the contrast list box in the xstat-GUI will be updated (now containing 3 contrasts):



From here you can modify the parameters and **update** the graphic window by selecting a contrast (such as the 3rd contrast) from the contrast-listbox.

7) Work from Command line

7.1) run voxelwise statistic from command line

```
z=[];
z.stattype      = 'twosamplettest';           %STATISTICAL TEST
z.excelfile     = 'F:\data6\voxwise\group\groupassignment.xlsx'; %[Excelfile] containing mouseIDs and group
z.sheetnumber   = [1];                       %sheet with columns mouseIDs and group
z.mouseID_col   = [1];                       %column index with the MouseIDs
z.group_col     = [2];                       %column index with group assignment
z.data_dir      = 'F:\data6\voxwise\dat';     %data directory (upper directory)
z.inputimage    = 'vimg.nii';                %image name (nifti) to run the statistic
z.AVGT          = 'F:\data6\voxwise\templates\AVGT.nii'; % TEMPLATE-file (in templates-folder)
z.ANO           = 'F:\data6\voxwise\templates\ANO.nii'; % ATLAS-file (in templates-folder)
z.grp_comparison = '1vs2';                   %groups to compare (do not modify)
z.mask          = 'F:\data6\voxwise\templates\AVGTmask.nii'; %optional> "brainmask
z.smoothing     = [1];                       %optional>smooth data: [0]no,[1]yes
z.smoothing_fwhm = [0.28 0.28 0.28];         %smoothing kernel (FWHM)
z.output_dir    = 'voxtest2';                %path for output-folder for statistic
z.showSPMbatch  = [0];                       %hide|show pipeline in SPM-batch-manager
xstat(1,z);                                     %RUN
```

execute this code to re-run the voxelwise statistic.

7.2) Create full report

```
xstat('loadspm','F:\data6\voxwise\voxtest2'): % open xstat-GUI and load SPM.mat-file
xstat('fullreport'); % create full report, i.e. three PPTfiles (uncorrected, FWE, cluster-based) + export result tables and statistical maps as NIFTI-files
```

For more information, see scripts [\[scripts\]](#)-button and help of xstat.