

Package ‘BiodiversityR’

December 20, 2018

Type Package

Title Package for Community Ecology and Suitability Analysis

Version 2.10-1

Date 2018-07-14

Author Roeland Kindt

Maintainer Roeland Kindt <R.KINDT@CGIAR.ORG>

Description Graphical User Interface (via the R-Commander) and utility functions (often based on the vegan package) for statistical analysis of biodiversity and ecological communities, including species accumulation curves, diversity indices, Renyi profiles, GLMs for analysis of species abundance and presence-absence, distance matrices, Mantel tests, and cluster, constrained and unconstrained ordination analysis. A book on biodiversity and community ecology analysis is available for free download from the website. In 2012, methods for (ensemble) suitability modelling and mapping were expanded in the package.

License GPL-2

URL <http://www.worldagroforestry.org/output/tree-diversity-analysis>

Depends R (>= 3.2.2), tcltk, vegan (>= 2.5-1)

Imports Rcmdr (>= 2.4-4)

Suggests permute, lattice, MASS, mgcv, cluster, car, RODBC, rpart, effects, multcomp, ellipse, maptree, sp, splancs, spatial, akima, nnet, dismo, raster (>= 2.0-31), rgdal, maxlike, gbm, randomForest, gam (>= 1.15), earth, mda, kernlab, e1071, glmnet, tools, methods, bootstrap, PresenceAbsence, geosphere, maptools, ENMeval, red, rgeos, igraph

NeedsCompilation no

Repository CRAN

Date/Publication 2018-07-14 18:00:02 UTC

R topics documented:

BiodiversityR-package	3
accumresult	4
add.spec.scores	6
balanced.specaccum	7
BCI.env	9
BiodiversityR.changeLog	10

BiodiversityRGUI	10
CAPdiscrim	11
caprescale	14
crosstabanalysis	15
deviancepercentage	16
dist.eval	17
dist.zeroes	19
distdisplayed	20
disttransform	21
diversityresult	22
ensemble.analogue	25
ensemble.batch	29
ensemble.bioclim	40
ensemble.bioclim.graph	44
ensemble.calibrate.models	46
ensemble.dummy.variables	62
ensemble.ecocrop	65
ensemble.novel	68
ensemble.raster	71
ensemble.red	77
ensemble.spatialThin	80
ensemble.zones	82
evaluation.strip.data	85
famea	89
ifri	90
importancevalue	91
loaded.citations	92
makecommunitydataset	93
multiconstrained	94
nested.anova.dbrda	96
NMSrandom	98
nnetrandom	99
ordicoeno	100
ordisymbol	101
PCAsignificance	103
radfitresult	104
rankabundance	106
removeNAcomm	108
renyiresult	110
residualssurface	112
spatialsample	113
transfgradient	115
transfspecies	115
warcom	116
warenv	122

Description

This package provides a GUI (Graphical User Interface, via the R-Commander; [BiodiversityRGUI](#)) and some utility functions (often based on the *vegan* package) for statistical analysis of biodiversity and ecological communities, including species accumulation curves, diversity indices, Renyi profiles, GLMs for analysis of species abundance and presence-absence, distance matrices, Mantel tests, and cluster, constrained and unconstrained ordination analysis. A book on biodiversity and community ecology analysis is available for free download from the website.

Details

We warmly thank all that provided inputs that lead to improvement of the Tree Diversity Analysis manual that describes common methods for biodiversity and community ecology analysis and its accompanying software. We especially appreciate the comments received during training sessions with draft versions of this manual and the accompanying software in Kenya, Uganda and Mali. We are equally grateful to the thoughtful reviews by Dr Simoneta Negrete-Yankelevich (Instituto de Ecologia, Mexico) and Dr Robert Burn (Reading University, UK) of the draft version of this manual, and to Hillary Kipruto for help in editing of this manual. We also want to specifically thank Mikkel Grum, Jane Poole and Paulo van Breugel for helping in testing the packaged version of the software. We also want to give special thanks for all the support that was given by Jan Beniest, Tony Simons and Kris Vanhoutte in realizing the book and software.

We highly appreciate the support of the Programme for Cooperation with International Institutes (SII), Education and Development Division of the Netherlands Ministry of Foreign Affairs, and VVOB (The Flemish Association for Development Cooperation and Technical Assistance, Flanders, Belgium) for funding the development for this manual. We also thank VVOB for seconding Roeland Kindt to the World Agroforestry Centre (ICRAF). The tree diversity analysis manual was inspired by research, development and extension activities that were initiated by ICRAF on tree and landscape diversification. We want to acknowledge the various donor agencies that have funded these activities, especially VVOB, DFID, USAID and EU.

We are grateful for the developers of the R Software for providing a free and powerful statistical package that allowed development of BiodiversityR. We also want to give special thanks to Jari Oksanen for developing the *vegan* package and John Fox for developing the *Rcmdr* package, which are key packages that are used by BiodiversityR.

Author(s)

Maintainer: Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

We suggest to use this citation for this software as well (together with citations of all other packages that were used)

accumresult

*Alternative Species Accumulation Curve Results***Description**

Provides alternative methods of obtaining species accumulation results than provided by functions [specaccum](#) and [plot.specaccum](#) ([vegan](#)).

Usage

```
accumresult(x,y="",factor="",level,scale="",method="exact",permutations=100,
  conditioned=T, gamma="boot", ...)
accumplot(xr,addit=F,labels="",col=1,ci=2,pch=1,type="p",cex=1,xlim=c(1,xmax),
  ylim=c(1,rich),xlab="sites",ylab="species richness",...)
accumcomp(x,y="",factor,scale="",method="exact",permutations=100,
  conditioned=T, gamma="boot",plotit=T,labelit=T,legend=T,rainbow=T,
  xlim=c(1,max),ylim=c(0,rich),type="p",xlab="sites",
  ylab="species richness",...)
```

Arguments

x	Community data frame with sites as rows, species as columns and species abundance as cell values.
y	Environmental data frame.
factor	Variable of the environmental data frame that defines subsets to calculate species accumulation curves for.
level	Level of the variable to create the subset to calculate species accumulation curves.
scale	Continuous variable of the environmental data frame that defines the variable that scales the horizontal axis of the species accumulation curves.
method	Method of calculating the species accumulation curve (as in function specaccum). Method "collector" adds sites in the order they happen to be in the data, "random" adds sites in random order, "exact" finds the expected (mean) species richness, "coleman" finds the expected richness following Coleman et al. 1982, and "rarefaction" finds the mean when accumulating individuals instead of sites.
permutations	Number of permutations to calculate the species accumulation curve (as in function specaccum).
conditioned	Estimation of standard deviation is conditional on the empirical dataset for the exact SAC (as in function specaccum).
gamma	Method for estimating the total extrapolated number of species in the survey area (as in specaccum).
addit	Add species accumulation curve to an existing graph.
xr	Result from specaccum or <code>accumresult</code> .
col	Colour for drawing lines of the species accumulation curve (as in function plot.specaccum).
labels	Labels to plot at left and right of the species accumulation curves.
ci	Multiplier used to get confidence intervals from standard deviation (as in function plot.specaccum).

<code>pch</code>	Symbol used for drawing the species accumulation curve (as in function points).
<code>type</code>	Type of plot (as in function plot).
<code>cex</code>	Character expansion factor (as in function plot).
<code>xlim</code>	Limits for the horizontal axis.
<code>ylim</code>	Limits for the vertical axis.
<code>xlab</code>	Label for the horizontal axis.
<code>ylab</code>	Label for the vertical axis.
<code>plotit</code>	Plot the results.
<code>labelit</code>	Label the species accumulation curves with the levels of the categorical variable.
<code>legend</code>	Add the legend (you need to click in the graph where the legend needs to be plotted).
<code>rainbow</code>	Use rainbow colouring for the different curves.
<code>...</code>	Other items passed to function specaccum or plot.specaccum .

Details

These functions provide some alternative methods of obtaining species accumulation results, although function [specaccum](#) is called by these functions to calculate the actual species accumulation curve.

Functions `accumresult` and `accumcomp` allow to calculate species accumulation curves for subsets of the community and environmental data sets. Function `accumresult` calculates the species accumulation curve for the specified level of a selected environmental variable. Method `accumcomp` calculates the species accumulation curve for all levels of a selected environmental variable separately. Both methods allow to scale the horizontal axis by multiples of the average of a selected continuous variable from the environmental dataset (hint: add the abundance of each site to the environmental data frame to scale accumulation results by mean abundance).

Functions `accumcomp` and `accumplot` provide alternative methods of plotting species accumulation curve results, although function [plot.specaccum](#) is called by these functions. When you choose to add a legend, make sure that you click in the graph on the spot where you want to put the legend.

Value

The functions provide alternative methods of obtaining species accumulation curve results, although results are similar as obtained by functions [specaccum](#) and [plot.specaccum](#).

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune.env)
data(dune)
dune.env$site.totals <- apply(dune,1,sum)
Accum.1 <- accumresult(dune, y=dune.env, scale='site.totals', method='exact', conditioned=TRUE)
Accum.1
accumplot(Accum.1)
accumcomp(dune, y=dune.env, factor='Management', method='exact', legend=FALSE, conditioned=TRUE)
## CLICK IN THE GRAPH TO INDICATE WHERE THE LEGEND NEEDS TO BE PLACED FOR
## OPTION WHERE LEGEND=TRUE (DEFAULT).
```

add.spec.scores	<i>Add Species Scores to Unconstrained Ordination Results</i>
-----------------	---

Description

Calculates scores (coordinates) to plot species for PCoA or NMS results that do not naturally provide species scores. The function can also rescale PCA results to use the choice of rescaling used in **vegan** for the [rda](#) function (after calculating PCA results via PCoA with the euclidean distance first).

Usage

```
add.spec.scores(ordi,comm,method="cor.scores",multi=1,Rscale=F,scaling="1")
```

Arguments

ordi	Ordination result as calculated by cmdscale , isoMDS , sammon , postMDS , metaMDS or NMSrandom .
comm	Community data frame with sites as rows, species as columns and species abundance as cell values.
method	Method for calculating species scores. Method "cor.scores" calculates the scores by the correlation between site scores and species vectors (via function cor), method "wa.scores" calculates the weighted average scores (via function wascores) and method "pcoa.scores" calculates the scores by weighing the correlation between site scores and species vectors by variance explained by the ordination axes.
multi	Multiplier for the species scores.
Rscale	Use the same scaling method used by vegan for rda .
scaling	Scaling method as used by rda .

Value

The function returns a new ordination result with new information on species scores. For PCoA results, the function calculates eigenvalues (not sums-of-squares as provided in results from function [cmdscale](#)), the percentage of explained variance per axis and the sum of all eigenvalues. PCA results (obtained by PCoA obtained by function [cmdscale](#) with the Euclidean distance) can be scaled as in function [rda](#), or be left at the original scale.

Author(s)

Roeland Kindt

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune)
distmatrix <- vegdist(dune, method="euc")
# Principal coordinates analysis with 19 axes to estimate total variance
Ordination.model1 <- cmdscale (distmatrix, k=19, eig=TRUE, add=FALSE)
# Change scores for second axis
Ordination.model1$points[,2] <- -1.0 * Ordination.model1$points[,2]
Ordination.model1 <- add.spec.scores(Ordination.model1, dune,
  method='pcoa.scores', Rscale=TRUE, scaling=1, multi=1)
# Compare Ordination.model1 with PCA
Ordination.model2 <- rda(dune, scale=FALSE)
#
par(mfrow=c(1,2))
ordiplot(Ordination.model1, type="text")
abline(h = 0, lty = 3)
abline(v = 0, lty = 3)
plot(Ordination.model2, type="text", scaling=1)
```

balanced.specaccum	<i>Balanced Species Accumulation Curves</i>
--------------------	---

Description

Provides species accumulation results calculated from balanced (equal subsample sizes) subsampling from each stratum. Sites can be accumulated in a randomized way, or alternatively sites belonging to the same stratum can be kept together. Results are in the same format as [specaccum](#) and can be plotted with [plot.specaccum](#) ([vegan](#)).

Usage

```
balanced.specaccum(comm, permutations=100, strata=strata, grouped=TRUE,
  reps=0, scale=NULL)
```

Arguments

comm	Community data frame with sites as rows, species as columns and species abundance as cell values.
permutations	Number of permutations to calculate the species accumulation curve.
strata	Categorical variable used to specify strata.
grouped	Should sites from the same stratum be kept together (TRUE) or not.
reps	Number of subsamples to be taken from each stratum (see details).
scale	Quantitative variable used to scale the sampling effort (see details).

Details

This function provides an alternative method of obtaining species accumulation results as provided by `specaccum` and `accumresult`.

Balanced sampling is achieved by randomly selecting the same number of sites from each stratum. The number of sites selected from each stratum is determined by `reps`. Sites are selected from strata with sample sizes larger or equal than `reps`. In case that `reps` is smaller than 1 (default: 0), then the number of sites selected from each stratum is equal to the smallest sample size of all strata. Sites from the same stratum can be kept together (`grouped=TRUE`) or the order of sites can be randomized (`grouped=FALSE`).

The results can be scaled by the average accumulation of a quantitative variable (default is number of sites), as in `accumresult` (hint: add the abundance of each site to the environmental data frame to scale accumulation results by mean abundance). When sites are not selected from all strata, then the average is calculated only for the strata that provided sites.

Value

The functions provide alternative methods of obtaining species accumulation curve results, although results are similar as obtained by functions `specaccum` and `accumresult`.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R., Kalinganire, A., Larwanou, M., Belem, M., Dakouo, J.M., Bayala, J. & Kaire, M. (2008) Species accumulation within landuse and tree diameter categories in Burkina Faso, Mali, Niger and Senegal. *Biodiversity and Conservation*. 17: 1883-1905.

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune.env)
data(dune)

# not balancing species accumulation
Accum.orig <- specaccum(dune)
Accum.orig

# randomly sample 3 quadrats from each stratum of Management
Accum.1 <- balanced.specaccum(dune, strata=dune.env$Management, reps=3)
Accum.1

# scale results by number of trees per quadrat
dune.env$site.totals <- apply(dune,1,sum)
Accum.2 <- balanced.specaccum(dune, strata=dune.env$Management, reps=3, scale=dune.env$site.totals)
Accum.2
```


BCI.env

*Barro Colorado Island Quadrat Descriptions***Description**

Topography-derived variables and UTM coordinates and UTM coordinates of a 50 ha sample plot (consisting of 50 1-ha quadrats) from Barro Colorado Island of Panama. Dataset [BCI](#) provides the tree species composition (trees with diameter at breast height equal or larger than 10 cm) of the same plots.

Usage

```
data(BCI.env)
```

Format

A data frame with 50 observations on the following 6 variables.

UTM.EW UTM easting

UTM.NS UTM northing

elevation mean of the elevation values of the four cell corners

convex mean elevation of the target cell minus the mean elevation of the eight surrounding cells

slope mean angular deviation from horizontal of each of the four triangular planes formed by connecting three of its corners

aspectEW the sine of aspect

aspectNS the cosine of aspect

References

Pyke C.R., Condit R., Aguilar S. and Lao S. (2001). Floristic composition across a climatic gradient in a neotropical lowland forest. *Journal of Vegetation Science* 12: 553-566.

Condit R., Pitman N., Leigh E.G., Chave J., Terborgh J., Foster R.B., Nunez P., Aguilar S., Valencia R., Villa G., Muller-Landau H.C., Losos E. and Hubbell, S.P. (2002). Beta-diversity in tropical forest trees. *Science* 295: 666-669.

De Caceres M., P. Legendre, R. Valencia, M. Cao, L.-W. Chang, G. Chuyong, R. Condit, Z. Hao, C.-F. Hsieh, S. Hubbell, D. Kenfack, K. Ma, X. Mi, N. Supardi Noor, A. R. Kassim, H. Ren, S.-H. Su, I-F. Sun, D. Thomas, W. Ye and F. He. (2012). The variation of tree beta diversity across a global network of forest plots. *Global Ecology and Biogeography* 21: 1191-1202

Examples

```
data(BCI.env)
```

BiodiversityR.changeLog

changeLog file for BiodiversityR

Description

ChangeLog file

Usage

BiodiversityR.changeLog()

BiodiversityRGUI

GUI for Biodiversity, Community Ecology and Ensemble Suitability Analysis

Description

This function provides a GUI (Graphical User Interface) for some of the functions of **vegan**, some other packages and some new functions to run biodiversity analysis, including species accumulation curves, diversity indices, Renyi profiles, rank-abundance curves, GLMs for analysis of species abundance and presence-absence, distance matrices, Mantel tests, cluster and ordination analysis (including constrained ordination methods such as RDA, CCA, db-RDA and CAP). In 2012 methods for ensemble suitability The function depends and builds on **Rcmdr**, performing all analyses on the community and environmental datasets that the user selects. A thorough description of the package and the biodiversity and ecological methods that it accomodates (including examples) is provided in the freely available Tree Diversity Analysis manual (Kindt and Coe, 2005) that is accessible via the help menu.

Usage

BiodiversityRGUI(changeLog = FALSE, backward.compatibility.messages = FALSE)

Arguments

changeLog	Show the changeLog file
backward.compatibility.messages	Some notes on backward compatibility

Details

The function launches the R-Commander GUI with an extra menu for common statistical methods for biodiversity and community ecology analysis as described in the Tree Diversity Analysis manual of Roeland Kindt and Richard Coe (available via <http://www.worldagroforestry.org/output/tree-diversity-analysis>) and expanded systematically with new functions that became available from the vegan community ecology package.

Since 2012, functions for ensemble suitability modelling were included in BiodiversityR. In 2016, a GUI was created for ensemble suitability modelling.

The R-Commander is launched by changing the location of the Rcmdr "etc" folder to the "etc" folder of BiodiversityR. As the files of the "etc" folder of BiodiversityR are copied from the Rcmdr, it is possible that newest versions of the R-Commander will not be launched properly. In such situations, it is possible that copying all files from the Rcmdr "etc" folder again and adding the BiodiversityR menu options to the Rcmdr-menus.txt is all that is needed to launch the R-Commander again. However, please alert Roeland Kindt about the issue.

BiodiversityR uses two data sets for biodiversity and community ecology analysis: the community dataset (or community matrix or species matrix) and the environmental dataset (or environmental matrix). The environmental dataset is the same dataset that is used as the "active dataset" of The R-Commander. (Note that you could sometimes use the same dataset as both the community and environmental dataset. For example, you could use the community dataset as environmental dataset as well to add information about specific species to ordination diagrams. As another example, you could use the environmental dataset as community dataset if you first calculated species richness of each site, saved this information in the environmental dataset, and then use species richness as response variable in a regression analysis.) Some options of analysis of ecological distance allow the community matrix to be a distance matrix (the community data set will be interpreted as distance matrix via `as.dist` prior to further analysis).

For ensemble suitability modelling, different data sets should be created and declared such as the calibration stack, the presence data set and the absence data set. The ensemble suitability modelling menu gives some guidelines on getting started with ensemble suitability modelling.

Value

Besides launching the graphical user interface, the function gives some notes on backward compatibility.

Author(s)

Roeland Kindt (with some help from Jari Oksanen)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

CAPdiscrim

Canonical Analysis of Principal Coordinates based on Discriminant Analysis

Description

This function provides a method for CAP that follows the procedure as described by the authors of the ordination method (Anderson & Willis 2003). The CAP method implemented in **vegan** through `capscale` conforms more to distance-based Redundancy Analysis (Legendre & Anderson, 1999) than to the original description for CAP (Anderson & Willis, 2003).

Usage

```
CAPdiscrim(formula, data, dist="bray", axes=4, m=0, mmax=10, add=FALSE, permutations=0)
```

Arguments

formula	Formula with a community data frame (with sites as rows, species as columns and species abundance as cell values) or distance matrix on the left-hand side and a categorical variable on the right-hand side (only the first explanatory variable will be used).
data	Environmental data set.
dist	Method for calculating ecological distance with function vegdist : partial match to "manhattan", "euclidean", "canberra", "bray", "kulczynski", "jaccard", "gower", "morisita", "horn" or "mountford". This argument is ignored in case that the left-hand side of the formula already is a distance matrix.
axes	Number of PCoA axes (cmdscale) to provide in the result.
m	Number of PCoA axes to be investigated by discriminant analysis (lda). If m=0 then the number of axes that provides the best distinction between the groups is calculated (following the method of Anderson and Willis).
mmax	The maximum number of PCoA axes considered when searching (m=0) for the number of axes that provide the best classification success.
add	Add a constant to the non-diagonal dissimilarities such that the modified dissimilarities are Euclidean; see also cmdscale .
permutations	The number of permutations for significance testing.

Details

This function provides a method of Constrained Analysis of Principal Coordinates (CAP) that follows the description of the method by the developers of the method, Anderson and Willis. The method investigates the results of a Principal Coordinates Analysis (function [cmdscale](#)) with linear discriminant analysis ([lda](#)). Anderson and Willis advocate to use the number of principal coordinate axes that result in the best prediction of group identities of the sites.

Results may be different than those obtained in the PRIMER-e package because PRIMER-e does not consider prior probabilities, does not standardize PCOA axes by their eigenvalues and applies an additional spherical standardization to a common within-group variance/covariance matrix.

For permutations > 0, the analysis is repeated by randomising the observations of the environmental data set. The significance is estimated by dividing the number of times the randomisation generated a larger percentage of correct predictions.

Value

The function returns an object with information on CAP based on discriminant analysis. The object contains following elements:

PCoA	the positions of the sites as fitted by PCoA
m	the number of axes analysed by discriminant analysis
tot	the total variance (sum of all eigenvalues of PCoA)
varm	the variance of the m axes that were investigated
group	the original group of the sites
CV	the predicted group for the sites by discriminant analysis
percent	the percentage of correct predictions
percent.level	the percentage of correct predictions for different factor levels

x	the positions of the sites provided by the discriminant analysis
F	the squares of the singular values of the discriminant analysis
manova	the results for MANOVA with the same grouping variable
signi	the significance of the percentage of correct predictions
manova	a summary of the observed randomised prediction percentages

The object can be plotted with `ordiplot`, and species scores can be added by `add.spec.scores`.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Legendre, P. & Anderson, M.J. (1999). Distance-based redundancy analysis: testing multispecies responses in multifactorial ecological experiments. *Ecological Monographs* 69: 1-24.

Anderson, M.J. & Willis, T.J. (2003). Canonical analysis of principal coordinates: a useful method of constrained ordination for ecology. *Ecology* 84: 511-525.

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
library(MASS)
data(dune)
data(dune.env)
Ordination.model1 <- CAPdiscrim(dune~Management, data=dune.env,
  dist="bray", axes=2, m=0, add=FALSE)
Ordination.model1
plot1 <- ordiplot(Ordination.model1, type="none")
ordisymbol(plot1, dune.env, "Management", legend=TRUE)

# plot change in classification success against m
plot(seq(1:14), rep(-1000, 14), xlim=c(1, 14), ylim=c(0, 100), xlab="m",
  ylab="classification success (percent)", type="n")
for (mseq in 1:14) {
  CAPdiscrim.result <- CAPdiscrim(dune~Management, data=dune.env,
    dist="bray", axes=2, m=mseq)
  points(mseq, CAPdiscrim.result$percent)
}

#
```

caprescale

*Rescaling of Capscale Results to Reflect Total Sums of Squares Of Distance Matrix***Description**

This is a simple function that rescales the ordination coordinates obtained from the distance-based redundancy analysis method implemented in **vegan** through [capscale](#). The rescaling of the ordination coordinates results in the distances between fitted site scores in ordination results (scaling=1 obtained via [ordiplot](#) to be equal to the distances between sites on the axes corresponding to positive eigenvalues obtained from principal coordinates analysis ([cmdscale](#)).

Usage

```
caprescale(x, verbose=FALSE)
```

Arguments

x	Ordination result obtained with capscale .
verbose	Give some information on the pairwise distances among sites (TRUE) or not.

Details

The first step of distance-based redundancy analysis involves principal coordinates analysis whereby the distances among sites from a distance matrix are approximated by distances among sites in a multidimensional configuration (ordination). In case that the principal coordinates analysis does not result in negative eigenvalues, then the distances from the distance matrix are the same as the distances among the sites in the ordination. In case that the principal coordinates analysis results in negative eigenvalues, then the distances among the sites on all ordination axes are related to the sum of positive eigenvalues, a sum which is larger than the sum of squared distances of the distance matrix.

The distance-based redundancy analysis method implemented in **vegan** through [capscale](#) uses a specific rescaling method for ordination results. Function [caprescale](#) modifies the results of [capscale](#) so that an ordination with scaling=1 (a distance biplot) obtained via [ordiplot](#) preserves the distances reflected in the principal coordinates analysis implemented as the first step of the analysis. See Legendre and Legendre (1998) about the relationship between fitted site scores and eigenvalues.

Value

The function modifies and returns an object obtained via [capscale](#).

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

- Legendre, P. & Legendre, L. (1998). Numerical Ecology. Amsterdam: Elsevier. 853 pp.
- Legendre, P. & Anderson, M.J. (1999). Distance-based redundancy analysis: testing multispecies responses in multifactorial ecological experiments. Ecological Monographs 69: 1-24.

Examples

```
library(vegan)
library(MASS)
data(dune)
data(dune.env)
Distmatrix.1 <- vegdist(dune,method='bray')
Ordination.model1 <- cmdscale(Distmatrix.1, k=19, eig=TRUE, add=FALSE)
# Sum of all eigenvalues
sum(Ordination.model1$eig)
# [1] 4.395807541512926
sum(Ordination.model1$eig[1:14])
# [1] 4.593946896588808
Distmatrix.2 <- as.matrix(vegdist(Ordination.model1$points[,1:14],method='euc'))
totalsumsquares1 <- sum(Distmatrix.2^2)/(2*20)
# Sum of distances among sites in principal coordinates analysis on axes
# corresponding to positive eigenvalues
totalsumsquares1
# [1] 4.593946896588808
Ordination.model2 <- capscale(dune ~ Management,dune.env,dist='bray', add=FALSE)
# Total sums of positive eigenvalues of the distance-based redundancy analysis
Ordination.model2$CA$tot.chi+Ordination.model2$CCA$tot.chi
# [1] 4.593946896588808
Ordination.model3 <- caprescale(Ordination.model2, verbose=TRUE)
sum1 <- summary(Ordination.model3,axes=17,scaling=1)$constraints
Distmatrix.3 <- as.matrix(vegdist(sum1 ,method='euc'))
totalsumsquares2 <- sum((Distmatrix.3)^2)/(2*20)/19
totalsumsquares2
# [1] 4.593946896588808
```

crosstabanalysis

Presence-absence Analysis by Cross Tabulation

Description

This function makes a cross-tabulation of two variables after transforming the first variable to presence-absence and then returns results of [chisq.test](#).

Usage

```
crosstabanalysis(x,variable,factor)
```

Arguments

x	Data set that contains the variables "variable" and "factor".
variable	Variable to be transformed in presence-absence in the resulting cross-tabulation.
factor	Variable to be used for the cross-tabulation together with the transformed variable.

Value

The function returns the results of [chisq.test](#) on a crosstabulation of two variables, after transforming the first variable to presence-absence first.

Author(s)

Roeland Kindt

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune.env)
crosstabanalysis(dune.env,"Manure","Management")
```

deviancepercentage	<i>Calculate Percentage and Significance of Deviance Explained by a GLM</i>
--------------------	---

Description

This function calculates the percentage of deviance explained by a GLM model and calculates the significance of the model.

Usage

```
deviancepercentage(x,data,test="F",digits=2)
```

Arguments

x	Result of GLM as calculated by glm or glm.nb .
data	Data set to be used for the null model (preferably the same data set used by the 'full' model).
test	Test statistic to be used for the comparison between the null model and the 'full' model as estimated by anova.glm or anova.negbin : partial match of one of "Chisq", "F" or "Cp".
digits	Number of digits in the calculation of the percentage.

Details

The function calculates the percentage of explained deviance and the significance of the 'full' model by contrasting it with the null model.

For the null model, the data is subjected to [na.omit](#). You should check whether the same data are used for the null and 'full' models.

Value

The function calculates the percentage of explained deviance and the significance of the 'full' model by contrasting it with the null model by ANOVA. The results of the ANOVA are also provided.

Author(s)

Roeland Kindt

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune)
data(dune.env)
dune.env$Agrostol <- dune$Agrostol
Count.model1 <- glm(Agrostol ~ Management + A1, family=quasipoisson(link=log),
  data=dune.env, na.action=na.omit)
summary(Count.model1)
deviancepercentage(Count.model1, dune.env, digits=3)
```

dist.eval

Distance Matrix Evaluation

Description

Function `dist.eval` provides one test of a distance matrix, and then continues with `distconnected` (**vegan**). Function `prepare.bioenv` converts selected variables to numeric variables and then excludes all categorical variables in preparation of applying `bioenv` (**vegan**).

Usage

```
dist.eval(x, dist)
prepare.bioenv(env, as.numeric = c())
```

Arguments

<code>x</code>	Community data frame with sites as rows, species as columns and species abundance as cell values.
<code>env</code>	Environmental data frame with sites as rows and variables as columns.
<code>dist</code>	Method for calculating ecological distance with function <code>vegdist</code> : partial match to "manhattan", "euclidean", "canberra", "clark", "bray", "kulczynski", "jaccard", "gower", "morisita", "horn" or "mountford".
<code>as.numeric</code>	Vector with names of variables in the environmental data set to be converted to numeric variables.

Details

Function `dist.eval` provides two tests of a distance matrix:

- (i) The first test checks whether any pair of sites that share some species have a larger distance than any other pair of sites that do not share any species. In case that cases are found, then a warning message is given.
- (ii) The second test is the one implemented by the `distconnected` function (**vegan**). The `distconnected` test is only calculated for distances that calculate a value of 1 if sites share no species (i.e. not manhattan or euclidean), using the threshold of 1 as an indication that the sites do not share any species. Interpretation of analysis of distance matrices that provided these warnings should be cautious.

Function `prepare.bioenv` provides some simple methods of dealing with categorical variables prior to applying `bioenv`.

Value

The function tests whether distance matrices have some desirable properties and provide warnings if this is not the case.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune)
dist.eval(dune,"euclidean")
dist.eval(dune,"bray")

## Not run:
data(dune.env)
dune.env2 <- dune.env[,c('A1', 'Moisture', 'Manure')]
dune.env2$Moisture <- as.numeric(dune.env2$Moisture)
dune.env2$Manure <- as.numeric(dune.env2$Manure)
sol <- bioenv(dune ~ A1 + Moisture + Manure, dune.env2)
sol
summary(sol)
dune.env3 <- prepare.bioenv(dune.env, as.numeric=c('Moisture', 'Manure'))
bioenv(dune, dune.env3)

## End(Not run)
```

dist.zeroes	<i>Distance Matrix Transformation</i>
-------------	---------------------------------------

Description

Sample units without any species result in "NaN" values in the distance matrix for some of the methods of `vegdist` (**vegan**). The function replaces "NA" by "0" if both sample units do not contain any species and "NA" by "1" if only one sample unit does not have any species.

Usage

```
dist.zeroes(comm,dist)
```

Arguments

comm	Community data frame with sites as rows, species as columns and species abundance as cell values.
dist	Distance matrix as calculated with function <code>vegdist</code> .

Details

This functions changes a distance matrix by replacing "NaN" values by "0" if both sample units do not contain any species and by "1" if only one sample unit does not contain any species.

Please note that there is a valid reason (deliberate removal of zero abundance values from calculations) that the original distance matrix contains "NaN", so you may not wish to do this transformation and remove sample units with zero abundances from further analysis.

Value

The function provides a new distance matrix where "NaN" values have been replaced by "0" or "1".

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
matrix <- array(0,dim=c(5,3))
matrix[4,] <- c(1,2,3)
matrix[5,] <- c(1,0,0)
dist1 <- vegdist(matrix,method="kulc")
dist1
dist2 <- dist.zeroes(matrix,dist1)
dist2
```

distdisplayed	<i>Compare Distance Displayed in Ordination Diagram with Distances of Distance Matrix</i>
---------------	---

Description

This function compares the distance among sites as displayed in an ordination diagram (generated by [ordiplot](#)) with the actual distances among sites as available from a distance matrix (as generated by [vegdist](#)).

Usage

```
distdisplayed(x, ordiplot, distx = "bray", plotit = T, addit = F,
             method = "spearman", permutations = 100, abline = F, gam = T, ...)
```

Arguments

x	Community data frame (with sites as rows, species as columns and species abundance as cell values) or distance matrix.
ordiplot	Ordination diagram generated by ordiplot or distance matrix.
distx	Ecological distance used to calculate the distance matrix (theoretically the same distance as displayed in the ordination diagram); passed to vegdist and partial match to "manhattan", "euclidean", "canberra", "bray", "kulczynski", "jaccard", "gower", "morisita", "horn", "mountford", "raup", "binomial" or "chao". This argument is ignored in case that "x" is already a distance matrix.
plotit	Should a plot comparing the distance in ordination diagram (or the distance matrix) with the distance from the distance matrix be generated (or not).
addit	Should the GAM regression result be added to an existing plot (or not).
method	Method for calculating the correlation between the ordination distance and the complete distance; from function mantel passed to function cor : "pearson", "spearman" or "kendall".
permutations	Number of permutations to assess the significance of the Mantel test; passed to mantel .
abline	Should a reference line (y=x) be added to the graph (or not).
gam	Evaluate the correspondence between the original distance and the distance from the ordination diagram with GAMs estimated by gam .
...	Other arguments passed to mantel .

Details

This function compares the Euclidean distances (between sites) displayed in an ordination diagram with the distances of a distance matrix. Alternatively, the distances of one distance matrix are compared against the distances of another distance matrix.

These distances are compared by a Mantel test ([mantel](#)) and (optionally) a GAM regression ([gam](#)). Optionally, a graph is provided comparing the distances and adding GAM results. .

Value

The function returns the results of a Mantel test and (optionally) the results of a GAM analysis.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
library(mgcv)
data(dune)
distmatrix <- vegdist(dune,method="kulc")
ordination.model1 <- cmdscale(distmatrix,k=2)
ordiplot1 <- ordiplot(ordination.model1)
distdisplayed(dune,ordiplot=ordiplot1,distx="kulc",plotit=TRUE,
  method="spearman",permutations=100,gam=TRUE)
```

disttransform	<i>Community Matrix Transformation</i>
---------------	--

Description

Transforms a community matrix. Some transformation methods are described by distances for the original community matrix that result in the same distance matrix as calculated with the euclidean distance from the transformed community matrix. In several cases (methods of "hellinger", "chord", "profiles" and "chi.square"), the method makes use of function [decostand](#). In several other cases ("Braun.Blanquet", "Domin", "Hult", "Hill", "fix" and "coverscale.log"), the method makes use of function [coverscale](#). For method "dispweight" a call is made to function [dispweight](#).

Usage

```
disttransform(x, method="hellinger")
```

Arguments

x	Community data frame with sites as rows, species as columns and species abundance as cell values.
method	Distance measure for the original community matrix that the euclidean distance will calculate for the transformed community matrix: partial match to "hellinger", "chord", "profiles", "chi.square", "log", "square", "pa", "Braun.Blanquet", "Domin", "Hult", "Hill", "fix", "coverscale.log" and "dispweight".

Details

This functions transforms a community matrix.

Some transformation methods ("hellinger", "chord", "profiles" and "chi.square") have the behaviour that the euclidean distance from the transformed matrix will equal a distance of choice for the original matrix. For example, using method "hellinger" and calculating the euclidean distance will result in the same distance matrix as by calculating the Hellinger distance from the original community matrix.

Transformation methods ("Braun.Blanquet", "Domin", "Hult", "Hill", "fix" and "coverscale.log") call function `coverscale`.

Method "dispweight" uses function `dispweight` without specifying a grouping structure.

Value

The function returns a transformed community matrix.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Legendre, P. & Gallagher, E.D. (2001). Ecologically meaningful transformations for ordination of species data. *Oecologia* 129: 271-280.

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune)
Community.1 <- disttransform(dune, method='hellinger')
Distmatrix.1 <- vegdist(Community.1, method='euclidean')
Distmatrix.1
```

diversityresult

Alternative Diversity Results

Description

Provides alternative methods of obtaining results on diversity statistics than provided directly by functions `diversity`, `fisher.alpha`, `specpool` and `specnumber` (all from **vegan**), although these same functions are called. Some other statistics are also calculated such as the reciprocal Berger-Parker diversity index and abundance (not a diversity statistic). The statistics can be calculated for the entire community, for each site separately, the mean of the sites can be calculated or a jackknife estimate can be calculated for the community.

Usage

```
diversityresult(x, y = NULL, factor = NULL, level = NULL,
  index=c("Shannon", "Simpson", "inverseSimpson", "Logalpha", "Berger",
    "richness", "abundance", "Jevenness", "Evenness",
    "jack1", "jack2", "chao", "boot"),
  method=c("pooled", "each site", "mean", "sd", "max", "jackknife"),
  sortit = FALSE, digits = 8)

diversityvariables(x, y, digits=8)

diversitycomp(x, y = NULL,
  factor1 = NULL ,factor2 = NULL,
  index=c("Shannon", "Simpson", "inverseSimpson", "Logalpha", "Berger",
    "richness", "abundance", "Jevenness", "Evenness",
    "jack1", "jack2", "chao", "boot"),
  method=c("pooled", "mean", "sd", "max", "jackknife"),
  sortit=FALSE, digits=8)
```

Arguments

x	Community data frame with sites as rows, species as columns and species abundance as cell values.
y	Environmental data frame.
factor	Variable of the environmental data frame that defines subsets to calculate diversity statistics for.
level	Level of the variable to create the subset to calculate diversity statistics.
index	Type of diversity statistic with "richness" to calculate species richness, "abundance" to calculate abundance, "Shannon" to calculate the Shannon diversity index, "Simpson" to calculate 1-Simpson concentration index, "inverseSimpson" to calculate the reciprocal Simpson diversity index, "Logalpha" to calculate the log series alpha diversity index, "Berger" to calculate the reciprocal Berger-Parker diversity index, "Jevenness" to calculate one Shannon evenness index, "Evenness" to calculate another Shannon evenness index, "jack1" to calculate the first-order jackknife gamma diversity estimator, "jack2" to calculate the second-order jackknife gamma diversity estimator, "chao" to calculate the Chao gamma diversity estimator and "boot" to calculate the bootstrap gamma diversity estimator.
method	Method of calculating the diversity statistics: "pooled" calculates the diversity of the entire community (all sites pooled), "each site" calculates diversity for each site separately, "mean" calculates the average diversity of the sites, "sd" calculates the standard deviation of the diversity of the sites, "max" calculates the maximum diversity of the sites, whereas "jackknife" calculates the jackknifed diversity for the entire data frame.
sortit	Sort the sites by increasing values of the diversity statistic.
digits	Number of digits in the results.
factor1	Variable of the environmental data frame that defines subsets to calculate diversity statistics for.
factor2	Optional second variable of the environmental data frame that defines subsets to calculate diversity statistics for in a crosstabulation with the other variable of the environmental data frame.

Details

These functions provide some alternative methods of obtaining results with diversity statistics, although functions `diversity`, `fisher.alpha`, `specpool`, `estimateR` and `specnumber` (all from **vegan**) are called to calculate the various statistics.

Function `diversityvariables` adds variables to the environmental dataset (richness, Shannon, Simpson, inverseSimpson, Logalpha, Berger, Jevenness, Eevenness).

The reciprocal Berger-Parker diversity index is the reciprocal of the proportional abundance of the most dominant species.

J-evenness is calculated as: $H / \ln(S)$ where H is the Shannon diversity index and S the species richness.

E-evenness is calculated as: $\exp(H) / S$ where H is the Shannon diversity index and S the species richness.

The method of calculating the diversity statistics include following options: "all" calculates the diversity of the entire community (all sites pooled together), "s" calculates the diversity of each site separately, "mean" calculates the average diversity of the sites, whereas "Jackknife" calculates the jackknifed diversity for the entire data frame. Methods "s" and "mean" are not available for function `diversitycomp`. Gamma diversity estimators assume that the method is "all".

Functions `diversityresult` and `diversitycomp` allow to calculate diversity statistics for subsets of the community and environmental data sets. Function `diversityresult` calculates the diversity statistics for the specified level of a selected environmental variable. Function `diversitycomp` calculates the diversity statistics for all levels of a selected environmental variable separately. When a second environmental variable is provided, function `diversitycomp` calculates diversity statistics as a crosstabulation of both variables.

Value

The functions provide alternative methods of obtaining diversity results. For function `diversitycomp`, the number of sites is provided as "n".

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune.env)
data(dune)

diversityresult(dune, y=NULL, index="Shannon", method="each site",
  sortit=TRUE, digits=5)
diversityresult(dune, y=dune.env, factor="Management", level="NM",
  index="Shannon", method="each site",
  sortit=TRUE, digits=5)
```



```

diversityresult(dune, y=NULL, index="Shannon", method="pooled", digits=5)
diversityresult(dune, y=dune.env, factor="Management", level="NM",
  index="Shannon", method="pooled", digits=5)
diversityresult(dune, y=NULL, index="Shannon", method="mean",
  digits=5)
diversityresult(dune, y=NULL, index="Shannon", method="sd",
  digits=5)
diversityresult(dune, y=NULL, index="Shannon", method="jackknife",
  digits=5)
diversityresult(dune, y=dune.env, factor="Management", level="NM",
  index="Shannon", method="jackknife", digits=5)

diversitycomp(dune, y=dune.env, factor1="Moisture", index="Shannon",
  method="pooled", sortit=TRUE)
diversitycomp(dune, y=dune.env, factor1="Moisture", index="Shannon",
  method="mean", sortit=TRUE)
diversitycomp(dune, y=dune.env, factor1="Management", index="Shannon",
  method="jackknife", sortit=TRUE)

diversitycomp(dune, y=dune.env, factor1="Management", factor2="Moisture",
  index="Shannon", method="pooled", digits=6)
diversitycomp(dune, y=dune.env, factor1="Management", factor2="Moisture",
  index="Shannon", method="mean", digits=6)

```

ensemble.analogue	<i>Climate analogues from climatic distance raster layers.</i>
-------------------	--

Description

Function `ensemble.analogue` creates the map with climatic distance and provides the locations of the climate analogues (defined as locations with smallest climatic distance to a reference climate). Function `ensemble.analogue.object` provides the reference values used by the prediction function used by [predict](#).

Usage

```

ensemble.analogue(x = NULL, analogue.object = NULL, analogues = 1,
  RASTER.object.name = analogue.object$name, RASTER.stack.name = x$title,
  RASTER.format = "raster", RASTER.datatype = "INT2S", RASTER.NAflag = -32767,
  KML.out = T, KML.blur = 10, KML.maxpixels = 100000,
  limits = c(1, 5, 20, 50), limit.colours = c('red', 'orange', 'blue', 'grey'),
  CATCH.OFF = FALSE)

ensemble.analogue.object(ref.location, future.stack, current.stack, name = "reference1",
  method = "mahal", an = 10000, probs = c(0.025, 0.975), weights = NULL, z = 2)

```

Arguments

x	RasterStack object (stack) containing all environmental layers (climatic variables) for which climatic distance should be calculated.
---	---

analogue.object	Object listing reference values for the environmental layers and additional parameters (covariance matrix for method = "mahal" or normalization parameters for method = "quantile") that are used by the prediction function that is used internally by predict . This object is created with ensemble.analogue.object .
analogues	Number of analogue locations to be provided
RASTER.object.name	First part of the names of the raster file that will be generated, expected to identify the area and time period for which ranges were calculated
RASTER.stack.name	Last part of the names of the raster file that will be generated, expected to identify the predictor stack used
RASTER.format	Format of the raster files that will be generated. See writeFormats and writeRaster .
RASTER.datatype	Format of the raster files that will be generated. See dataType and writeRaster .
RASTER.NAflag	Value that is used to store missing data. See writeRaster .
KML.out	If TRUE, then kml files will be saved in a subfolder 'kml/zones'.
KML.maxpixels	Maximum number of pixels for the PNG image that will be displayed in Google Earth. See also KML .
KML.blur	Integer that results in increasing the size of the PNG image by $KML.blur^2$, which may help avoid blurring of isolated pixels. See also KML .
limits	Limits indicating the accumulated number of closest analogue sites. These limits will correspond to different colours in the KML map. In the default setting, the closest analogue will be coloured red and the second to fifth closest analogues will be coloured orange.
limit.colours	Colours for the different limits based on number of analogues.
CATCH.OFF	Disable calls to function tryCatch .
ref.location	Location of the reference location for which analogues are searched for and from which climatic distance will be calculated, typically available in 2-column (lon, lat) dataframe; see also extract .
future.stack	RasterStack object (stack) containing the environmental layers (climatic variables) to obtain the conditions of the reference location. For climate change research, this RasterStack object corresponds to the future climatic conditions of the reference location.
current.stack	RasterStack object (stack) containing all environmental layers (climatic variables) for which climatic distance should be calculated. For climate change research, this RasterStack object corresponds to the current climatic conditions and range where climate analogues are searched for.
name	Name of the object, expected to identify the area and time period for which ranges were calculated and where no novel conditions will be detected
method	Method used to calculate climatic distance: method = "mahal" results in using the Mahalanobis distance (mahalanobis); method = "quantile" results in dividing the differences between reference climatic values and climatic values in the 'current' raster by a quantile range obtained from the 'current' raster; method = "sd" results in dividing the differences between reference climatic values and climatic values in the 'current' raster by standard deviations obtained from the 'current' raster; and method = "none" results in not dividing these differences.

an	Number of randomly selected locations points to calculate the covariance matrix (<code>cov</code>) to be used with <code>mahalanobis</code> , therefore only used for method = "mahal". See also <code>randomPoints</code> .
probs	Numeric vector of probabilities [0,1] as used by <code>quantile</code>). Only used for method = "quantile".
weights	Numeric vector of weights by which each variable (difference) should be multiplied by (can be used to give equal weight to 12 monthly rainfall values and 24 minimum and maximum monthly temperature values). Not used for method = "mahal".
z	Parameter used as exponent for differences calculated between reference climatic variables and variables in the 'current' raster and reciprocal exponent for the sum of all differences. Default value of 2 corresponds to the Euclidean distance. Not used for method = "mahal".

Details

Function `ensemble.analogues` maps the climatic distance from reference values determined by `ensemble.analogues.object` and provides the locations of the analogues closest analogues.

The method = "mahal" uses the Mahalanobis distance as environmental (climatic) distance: `mahalanobis`.

Other methods use a normalization method to handle scale differences between environmental (climatic) variables:

$$ClimaticDistance = (\sum_i (weight_i * (|T_i - C_i|/norm_i)^z))^{1/z}$$

where T_i are the target values for environmental (climatic) variable i , C_i are the values in the current environmental layers where analogues are searched for, $weight_i$ are the weights for environmental variable i , and $norm_i$ are the normalization parameters for environmental variable i

Value

Function `ensemble.analogue.object` returns a list with following objects:

name	name for the reference location
ref.location	coordinates of the reference location
stack.name	name for time period for which values are extracted from the <code>future.stack</code>
method	method used for calculating climatic distance
target.values	target environmental values to select analogues for through minimum climatic distance
cov.mahal	covariance matrix
norm.values	parameters by which each difference between target and 'current' value will be divided
weight.values	weights by which each difference between target and 'current' value will be multiplied
z	parameter to be used as exponent for differences between target and 'current' values

Author(s)

Roeland Kindt (World Agroforestry Centre) and Eike Luedeling (World Agroforestry Centre)

References

Bos, Swen PM, et al. "Climate analogs for agricultural impact projection and adaptation-a reliability test." *Frontiers in Environmental Science* 3 (2015): 65. Luedeling, Eike, and Henry Neufeldt. "Carbon sequestration potential of parkland agroforestry in the Sahel." *Climatic Change* 115.3-4 (2012): 443-461.

See Also

[ensemble.novel](#)

Examples

```
## Not run:
# get predictor variables
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
  pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
predictors <- subset(predictors, subset=c("bio1", "bio5", "bio6", "bio7", "bio8",
  "bio12", "bio16", "bio17"))
predictors
predictors@title <- "base"

# instead of searching for current analogue of future climate conditions,
# search for analogue in southern hemisphere
future.stack <- stack(crop(predictors, y=extent(-125, -32, 0, 40)))
future.stack@title <- "north"
current.stack <- stack(crop(predictors, y=extent(-125, -32, -56, 0)))
current.stack@title <- "south"

# reference location in Florida
# in this case future.stack and current.stack are both current
ref.loc <- data.frame(t(c(-80.19, 25.76)))
names(ref.loc) <- c("lon", "lat")

# climate analogue analysis based on the Mahalanobis distance
Florida.object.mahal <- ensemble.analogue.object(ref.location=ref.loc,
  future.stack=future.stack, current.stack=current.stack,
  name="FloridaMahal", method="mahal", an=10000)
Florida.object.mahal

Florida.analogue.mahal <- ensemble.analogue(x=current.stack,
  analogue.object=Florida.object.mahal, analogues=50)
Florida.analogue.mahal

# climate analogue analysis based on the Euclidean distance and dividing each variable by the sd
Florida.object.sd <- ensemble.analogue.object(ref.location=ref.loc,
  future.stack=future.stack, current.stack=current.stack,
  name="FloridaSD", method="sd", z=2)
Florida.object.sd

Florida.analogue.sd <- ensemble.analogue(x=current.stack,
  analogue.object=Florida.object.sd, analogues=50)
Florida.analogue.sd
```

```

# plot analogues on climatic distance maps
par(mfrow=c(1,2))
analogue.file <- paste(getwd(), "//ensembles//analogue//FloridaMahal_south_analogue.grd", sep="")
plot(raster(analogue.file), main="Mahalanobis climatic distance")
points(Florida.analogue.sd[3:50, "lat"] ~ Florida.analogue.sd[3:50, "lon"],
       pch=1, col="red", cex=1)
points(Florida.analogue.mahal[3:50, "lat"] ~ Florida.analogue.mahal[3:50, "lon"],
       pch=3, col="black", cex=1)
points(Florida.analogue.mahal[2, "lat"] ~ Florida.analogue.mahal[2, "lon"],
       pch=22, col="blue", cex=2)
legend(x="topright", legend=c("closest", "Mahalanobis", "SD"), pch=c(22, 3, 1),
       col=c("blue", "black", "red"))

analogue.file <- paste(getwd(), "//ensembles//analogue//FloridaSD_south_analogue.grd", sep="")
plot(raster(analogue.file), main="Climatic distance normalized by standard deviation")
points(Florida.analogue.mahal[3:50, "lat"] ~ Florida.analogue.mahal[3:50, "lon"],
       pch=3, col="black", cex=1)
points(Florida.analogue.sd[3:50, "lat"] ~ Florida.analogue.sd[3:50, "lon"],
       pch=1, col="red", cex=1)
points(Florida.analogue.sd[2, "lat"] ~ Florida.analogue.sd[2, "lon"],
       pch=22, col="blue", cex=2)
legend(x="topright", legend=c("closest", "Mahalanobis", "SD"), pch=c(22, 3, 1),
       col=c("blue", "black", "red"))
par(mfrow=c(1,1))

## End(Not run)

```

ensemble.batch

*Suitability mapping based on ensembles of modelling algorithms:
batch processing*

Description

The main function allows for batch processing of different species and different environmental RasterStacks. The function makes internal calls to [ensemble.calibrate.weights](#), [ensemble.calibrate.models](#) and [ensemble.raster](#).

Usage

```

ensemble.batch(x = NULL, xn = c(x),
               species.presence = NULL, species.absence = NULL,
               presence.min = 20, thin.km = 0.1,
               an = 1000, excludep = FALSE,
               get.block = FALSE,
               SSB.reduce = FALSE, CIRCLES.d = 250000,
               k.splits = 4, k.test = 0,
               n.ensembles = 1,
               VIF.max = 10, VIF.keep = NULL,
               SINK = FALSE, CATCH.OFF = FALSE,
               RASTER.format = "raster", RASTER.datatype = "INT2S", RASTER.NAflag = -32767,
               KML.out = FALSE, KML.maxpixels = 100000, KML.blur = 10,
               models.save = FALSE,

```

```

threshold.method = "spec_sens", threshold.sensitivity = 0.9,
threshold.PresenceAbsence = FALSE,
ENSEMBLE.best = 0, ENSEMBLE.min = 0.7, ENSEMBLE.exponent = 1,
ENSEMBLE.weight.min = 0.05,
input.weights = NULL,
MAXENT = 1, MAXLIKE = 1, GBM = 1, GBMSTEP = 0, RF = 1, GLM = 1, GLMSTEP = 1, GAM = 1,
GAMSTEP = 1, MGCV = 1, MGCVFIX = 0, EARTH = 1, RPART = 1, NNET = 1,
FDA = 1, SVM = 1, SVME = 1, GLMNET = 1,
BIOCLIM.O = 0, BIOCLIM = 1, DOMAIN = 1, MAHAL = 1, MAHAL01 = 1,
PROBIT = FALSE,
Yweights = "BIOMOD",
layer.drops = NULL, factors = NULL, dummy.vars = NULL,
formulae.defaults = TRUE, maxit = 100,
MAXENT.a = NULL, MAXENT.an = 10000,
MAXENT.path = paste(getwd(), "/models/maxent", sep=""),
MAXLIKE.formula = NULL, MAXLIKE.method = "BFGS",
GBM.formula = NULL, GBM.n.trees = 2001,
GBMSTEP.gbm.x = 2:(1 + raster::nlayers(x)),
GBMSTEP.tree.complexity = 5, GBMSTEP.learning.rate = 0.005,
GBMSTEP.bag.fraction = 0.5, GBMSTEP.step.size = 100,
RF.formula = NULL, RF.ntree = 751, RF.mtry = floor(sqrt(raster::nlayers(x))),
GLM.formula = NULL, GLM.family = binomial(link = "logit"),
GLMSTEP.steps = 1000, STEP.formula = NULL, GLMSTEP.scope = NULL, GLMSTEP.k = 2,
GAM.formula = NULL, GAM.family = binomial(link = "logit"),
GAMSTEP.steps = 1000, GAMSTEP.scope = NULL, GAMSTEP.pos = 1,
MGCV.formula = NULL, MGCV.select = FALSE,
MGCVFIX.formula = NULL,
EARTH.formula = NULL,
EARTH.glm = list(family = binomial(link = "logit"), maxit = maxit),
RPART.formula = NULL, RPART.xval = 50,
NNET.formula = NULL, NNET.size = 8, NNET.decay = 0.01,
FDA.formula = NULL,
SVM.formula = NULL, SVME.formula = NULL,
GLMNET.nlambda = 100, GLMNET.class = FALSE,
BIOCLIM.O.fraction = 0.9,
MAHAL.shape = 1)

ensemble.mean(RASTER.species.name = "Species001", RASTER.stack.name = "base",
positive.filters = c("grd", "_ENSEMBLE_"), negative.filters = c("xml"),
RASTER.format = "raster", RASTER.datatype = "INT2S", RASTER.NAflag = -32767,
KML.out = FALSE, KML.maxpixels = 100000, KML.blur = 10,
abs.breaks = 6, pres.breaks = 6, sd.breaks = 9,
p = NULL, a = NULL,
pt = NULL, at = NULL,
threshold = -1,
threshold.method = "spec_sens", threshold.sensitivity = 0.9,
threshold.PresenceAbsence = FALSE)

ensemble.plot(RASTER.species.name = "Species001", RASTER.stack.name = "base",
plot.method=c("suitability", "presence", "count",
"consensus suitability", "consensus presence", "consensus count", "consensus sd"),
dev.new.width = 7, dev.new.height = 7,

```

```

main = paste(RASTER.species.name, " ", plot.method,
             " for ", RASTER.stack.name, sep=""),
positive.filters = c("grd"), negative.filters = c("xml"),
p=NULL, a=NULL,
threshold = -1,
threshold.method = "spec_sens", threshold.sensitivity = 0.9,
threshold.PresenceAbsence = FALSE,
abs.breaks = 6, abs.col = NULL,
pres.breaks = 6, pres.col = NULL,
sd.breaks = 9, sd.col = NULL,
absencePresence.col = NULL,
count.col = NULL,
maptools.boundaries = TRUE, maptools.col = "dimgrey", ...)

```

Arguments

x	RasterStack object (stack) containing all layers to calibrate an ensemble.
xn	RasterStack object (stack) containing all layers that correspond to explanatory variables of an ensemble calibrated earlier with x. Several RasterStack objects can be provided in a format as c(stack1, stack2, stack3); these will be used sequentially. See also predict .
species.presence	presence points used for calibrating the suitability models, available in 3-column (species, x, y) or (species, lon, lat) dataframe
species.absence	background points used for calibrating the suitability models, either available in a 3-column (species, x, y) or (species, lon, lat), or available in a 2-column (x, y) or (lon, lat) dataframe. In case of a 2-column dataframe, the same background locations will be used for all species.
presence.min	minimum number of presence locations for the organism (if smaller, no models are fitted).
thin.km	Threshold for minimum distance (km) between presence point locations for focal species for model calibrations in each run. A new data set is randomly selected via ensemble.spatialThin in each of ensemble run.
an	number of background points for calibration to be selected with randomPoints in case argument a or species.absence is missing
excludep	parameter that indicates (if TRUE) that presence points will be excluded from the background points; see also randomPoints
get.block	if TRUE, instead of creating k-fold cross-validation subsets randomly (kfold), create 4 subsets of presence and background locations with get.block .
SSB.reduce	If TRUE, then new background points that will be used for evaluating the suitability models will be selected (randomPoints) in circular neighbourhoods (created with circles) around presence locations (p and pt). The abbreviation of SSB refers to spatial sorting bias; see also ssb .
CIRCLES.d	Radius in m of circular neighbourhoods (created with circles) around presence locations (p and pt).
k	If larger than 1, the number of groups to split between calibration (k-1) and evaluation (1) data sets (for example, k=5 results in 4/5 of presence and background points to be used for calibrating the models, and 1/5 of presence and background points to be used for evaluating the models). See also kfold .

<code>k.splits</code>	If larger than 1, the number of splits for the ensemble.calibrate.weights step in batch processing. See also kfold .
<code>k.test</code>	If larger than 1, the number of groups to split between calibration (k-1) and evaluation (1) data sets when calibrating the final models (for example, k=5 results in 4/5 of presence and background points to be used for calibrating the models, and 1/5 of presence and background points to be used for evaluating the models). See also kfold .
<code>n.ensembles</code>	If larger than 1, the number of different ensembles generated per species in batch processing.
<code>VIF.max</code>	Maximum Variance Inflation Factor of variables; see ensemble.VIF .
<code>VIF.keep</code>	character vector with names of the variables to be kept; see ensemble.VIF .
<code>SINK</code>	Append the results to a text file in subfolder 'outputs' (if TRUE). The name of file is based on species names. In case a file already exists, then results are appended. See also sink .
<code>CATCH.OFF</code>	Disable calls to function tryCatch .
<code>RASTER.format</code>	Format of the raster files that will be generated. See writeFormats and writeRaster .
<code>RASTER.datatype</code>	Format of the raster files that will be generated. See dataType and writeRaster .
<code>RASTER.NAflag</code>	Value that is used to store missing data. See writeRaster .
<code>KML.out</code>	if FALSE, then no kml layers (layers that can be shown in Google Earth) are produced. If TRUE, then kml files will be saved in a subfolder 'kml'.
<code>KML.maxpixels</code>	Maximum number of pixels for the PNG image that will be displayed in Google Earth. See also KML .
<code>KML.blur</code>	Integer that results in increasing the size of the PNG image by $KML.blur^2$, which may help avoid blurring of isolated pixels. See also KML .
<code>models.save</code>	Save the list with model details to a file (if TRUE). The filename will be <code>species.name</code> with extension <code>.models</code> ; this file will be saved in subfolder of models. When loading this file, model results will be available as <code>ensemble.models</code> .
<code>threshold.method</code>	Method to calculate the threshold between predicted absence and presence; possibilities include <code>spec_sens</code> (highest sum of the true positive rate and the true negative rate), <code>kappa</code> (highest kappa value), <code>no_omission</code> (highest threshold that corresponds to no omission), <code>prevalence</code> (modeled prevalence is closest to observed prevalence) and <code>equal_sens_spec</code> (equal true positive rate and true negative rate). See threshold . Options specific to the BiodiversityR implementation are: <code>threshold.mean</code> (resulting in calculating the mean value of <code>spec_sens</code> , <code>equal_sens_spec</code> and <code>prevalence</code>) and <code>threshold.min</code> (resulting in calculating the minimum value of <code>spec_sens</code> , <code>equal_sens_spec</code> and <code>prevalence</code>).
<code>threshold.sensitivity</code>	Sensitivity value for <code>threshold.method = 'sensitivity'</code> . See threshold .
<code>threshold.PresenceAbsence</code>	If TRUE calculate thresholds with the PresenceAbsence package. See optimal.thresholds .
<code>ENSEMBLE.best</code>	The number of individual suitability models to be used in the consensus suitability map (based on a weighted average). In case this parameter is smaller than 1 or larger than the number of positive input weights of individual models, then all individual suitability models with positive input weights are included in the consensus suitability map. In case a vector is provided, <code>ensemble.strategy</code> is called internally to determine weights for the ensemble model.

ENSEMBLE.min	The minimum input weight (typically corresponding to AUC values) for a model to be included in the ensemble. In case a vector is provided, function <code>ensemble.strategy</code> is called internally to determine weights for the ensemble model.
ENSEMBLE.exponent	Exponent applied to AUC values to convert AUC values into weights (for example, an exponent of 2 converts input weights of 0.7, 0.8 and 0.9 into $0.7^2=0.49$, $0.8^2=0.64$ and $0.9^2=0.81$). See details.
ENSEMBLE.weight.min	The minimum output weight for models included in the ensemble, applying to weights that sum to one. Note that <code>ENSEMBLE.min</code> typically refers to input AUC values.
input.weights	array with numeric values for the different modelling algorithms; if NULL then values provided by parameters such as <code>MAXENT</code> and <code>GBM</code> will be used. As an alternative, the output from <code>ensemble.calibrate.weights</code> can be used.
MAXENT	Input weight for a maximum entropy model (maxent). (Only weights > 0 will be used.)
MAXLIKE	Input weight for a maxlike model (maxlike). (Only weights > 0 will be used.)
GBM	Input weight for a boosted regression trees model (gbm). (Only weights > 0 will be used.)
GBMSTEP	Input weight for a stepwise boosted regression trees model (gbm.step). (Only weights > 0 will be used.)
RF	Input weight for a random forest model (randomForest). (Only weights > 0 will be used.)
GLM	Input weight for a generalized linear model (glm). (Only weights > 0 will be used.)
GLMSTEP	Input weight for a stepwise generalized linear model (stepAIC). (Only weights > 0 will be used.)
GAM	Input weight for a generalized additive model (gam). (Only weights > 0 will be used.)
GAMSTEP	Input weight for a stepwise generalized additive model (step.gam). (Only weights > 0 will be used.)
MGCV	Input weight for a generalized additive model (gam). (Only weights > 0 will be used.)
MGCVFIX	number: if larger than 0, then a generalized additive model with fixed d.f. regression splines (gam) will be fitted among ensemble
EARTH	Input weight for a multivariate adaptive regression spline model (earth). (Only weights > 0 will be used.)
RPART	Input weight for a recursive partitioning and regression tree model (rpart). (Only weights > 0 will be used.)
NNET	Input weight for an artificial neural network model (nnet). (Only weights > 0 will be used.)
FDA	Input weight for a flexible discriminant analysis model (fda). (Only weights > 0 will be used.)
SVM	Input weight for a support vector machine model (ksvm). (Only weights > 0 will be used.)
SVME	Input weight for a support vector machine model (svm). (Only weights > 0 will be used.)

GLMNET	Input weight for a GLM with lasso or elasticnet regularization (glmnet). (Only weights > 0 will be used.)
BIOCLIM.0	Input weight for the original BIOCLIM algorithm (ensemble.bioclim). (Only weights > 0 will be used.)
BIOCLIM	Input weight for the BIOCLIM algorithm (bioclim). (Only weights > 0 will be used.)
DOMAIN	Input weight for the DOMAIN algorithm (domain). (Only weights > 0 will be used.)
MAHAL	Input weight for the Mahalanobis algorithm (mahal). (Only weights > 0 will be used.)
MAHAL01	Input weight for the Mahalanobis algorithm (mahal), using a transformation method afterwards whereby output is within the range between 0 and 1. (Only weights > 0 will be used.)
PROBIT	If TRUE, then subsequently to the fitting of the individual algorithm (e.g. maximum entropy or GAM) a generalized linear model (glm) with probit link family=binomial(link="probit") will be fitted to transform the predictions, using the previous predictions as explanatory variable. This transformation results in all model predictions to be probability estimates.
Yweights	chooses how cases of presence and background (absence) are weighted; "BIOMOD" results in equal weighting of all presence and all background cases, "equal" results in equal weighting of all cases. The user can supply a vector of weights similar to the number of cases in the calibration data set.
layer.drops	vector that indicates which layers should be removed from RasterStack x. See also addLayer .
factors	vector that indicates which variables are factors; see also prepareData
dummy.vars	vector that indicates which variables are dummy variables (influences formulae suggestions)
formulae.defaults	Suggest formulae for most of the models (if TRUE). See also ensemble.formulae .
maxit	Maximum number of iterations for some of the models. See also glm.control , gam.control and nnet .
MAXENT.a	background points used for calibrating the maximum entropy model (maxent), typically available in 2-column (lon, lat) dataframe; see also prepareData and extract .
MAXENT.an	number of background points for calibration to be selected with randomPoints in case argument MAXENT.a is missing. When used with the ensemble.batch function, the same background locations will be used for each of the species runs; this implies that for each species, presence locations are not excluded from the background data for this function.
MAXENT.path	path to the directory where output files of the maximum entropy model are stored; see also maxent
MAXLIKE.formula	formula for the maxlike algorithm; see also maxlike
MAXLIKE.method	method for the maxlike algorithm; see also optim
GBM.formula	formula for the boosted regression trees algorithm; see also gbm
GBM.n.trees	total number of trees to fit for the boosted regression trees model; see also gbm

GBMSTEP.gbm.x	indices of column numbers with explanatory variables for stepwise boosted regression trees; see also gbm.step
GBMSTEP.tree.complexity	complexity of individual trees for stepwise boosted regression trees; see also gbm.step
GBMSTEP.learning.rate	weight applied to individual trees for stepwise boosted regression trees; see also gbm.step
GBMSTEP.bag.fraction	proportion of observations used in selecting variables for stepwise boosted regression trees; see also gbm.step
GBMSTEP.step.size	number of trees to add at each cycle for stepwise boosted regression trees (should be small enough to result in a smaller holdout deviance than the initial number of trees [50]); see also gbm.step
RF.formula	formula for the random forest algorithm; see also randomForest
RF.ntree	number of trees to grow for random forest algorithm; see also randomForest
RF.mtry	number of variables randomly sampled as candidates at each split for random forest algorithm; see also randomForest
GLM.formula	formula for the generalized linear model; see also glm
GLM.family	description of the error distribution and link function for the generalized linear model; see also glm
GLMSTEP.steps	maximum number of steps to be considered for stepwise generalized linear model; see also stepAIC
STEP.formula	formula for the "starting model" to be considered for stepwise generalized linear model; see also stepAIC
GLMSTEP.scope	range of models examined in the stepwise search; see also stepAIC
GLMSTEP.k	multiple of the number of degrees of freedom used for the penalty (only k = 2 gives the genuine AIC); see also stepAIC
GAM.formula	formula for the generalized additive model; see also gam
GAM.family	description of the error distribution and link function for the generalized additive model; see also gam
GAMSTEP.steps	maximum number of steps to be considered in the stepwise generalized additive model; see also step.gam
GAMSTEP.scope	range of models examined in the step-wise search n the stepwise generalized additive model; see also step.gam
GAMSTEP.pos	parameter expected to be set to 1 to allow for fitting of the stepwise generalized additive model
MGCV.formula	formula for the generalized additive model; see also gam
MGCV.select	if TRUE, then the smoothing parameter estimation that is part of fitting can completely remove terms from the model; see also gam
MGCVFIX.formula	formula for the generalized additive model with fixed d.f. regression splines; see also gam (the default formulae sets "s(..., fx=TRUE, ...)"; see also s)
EARTH.formula	formula for the multivariate adaptive regression spline model; see also earth
EARTH.glm	list of arguments to pass on to glm ; see also earth

<code>RPART.formula</code>	formula for the recursive partitioning and regression tree model; see also rpart
<code>RPART.xval</code>	number of cross-validations for the recursive partitioning and regression tree model; see also rpart.control
<code>NNET.formula</code>	formula for the artificial neural network model; see also nnet
<code>NNET.size</code>	number of units in the hidden layer for the artificial neural network model; see also nnet
<code>NNET.decay</code>	parameter of weight decay for the artificial neural network model; see also nnet
<code>FDA.formula</code>	formula for the flexible discriminant analysis model; see also fda
<code>SVM.formula</code>	formula for the support vector machine model; see also ksvm
<code>SVME.formula</code>	formula for the support vector machine model; see also svm
<code>GLMNET.nlambda</code>	The number of lambda values; see also glmnet
<code>GLMNET.class</code>	Use the predicted class to calculate the mean predictions of GLMNET; see also predict.glmnet
<code>BIOCLIM.O.fraction</code>	Fraction of range representing the optimal limits, default value of 0.9 as in the original BIOCLIM software (ensemble.bioclim).
<code>MAHAL.shape</code>	parameter that influences the transformation of output values of mahal .
<code>RASTER.species.name</code>	First part of the names of the raster files, expected to identify the modelled species (or organism).
<code>RASTER.stack.name</code>	Last part of the names of the raster files, expected to identify the predictor stack used.
<code>positive.filters</code>	vector that indicates parts of filenames for files that will be included in the calculation of the mean probability values
<code>negative.filters</code>	vector that indicates parts of filenames for files that will not be included in the calculation of the mean probability values
<code>abs.breaks</code>	Number of breaks in the colouring scheme for absence (only applies to suitability mapping).
<code>pres.breaks</code>	Number of breaks in the colouring scheme for presence (only applies to suitability mapping).
<code>sd.breaks</code>	Number of breaks in the colouring scheme for standard deviation (only applies to sd mapping).
<code>p</code>	presence points used for calibrating the suitability models, typically available in 2-column (x, y) or (lon, lat) dataframe; see also prepareData and extract
<code>a</code>	background points used for calibrating the suitability models, typically available in 2-column (x, y) or (lon, lat) dataframe; see also prepareData and extract
<code>pt</code>	presence points used for evaluating the suitability models, typically available in 2-column (lon, lat) dataframe; see also prepareData
<code>at</code>	background points used for calibrating the suitability models, typically available in 2-column (lon, lat) dataframe; see also prepareData and extract
<code>threshold</code>	Threshold value that will be used to distinguish between presence and absence. If < 0, then a threshold value will be calculated from the provided presence p and absence a locations.

plot.method	Choice of maps to be plotted: suitability plots suitability maps, presence plots presence-absence maps, count plots count maps (count of number of algorithms or number of ensembles predicting presence) and sd plots standard deviation maps.
dev.new.width	Width for new graphics device (dev.new). If < 0, then no new graphics device is opened.
dev.new.height	Height for new graphics device (dev.new). If < 0, then no new graphics device is opened.
main	main title for the plots.
abs.col	specify colours for absence (see examples on how not to plot areas where the species is predicted absent)
pres.col	specify colours for presence
sd.col	specify colours for standard deviation
absencePresence.col	specify colours for absence - presence maps (see examples on how not to plot areas where the species is predicted absent)
count.col	specify colours for number of algorithms or ensembles (see examples on how not to plot areas where the species is predicted absent)
maptools.boundaries	If TRUE, then plot approximate country boundaries wrls_simpl
maptools.col	Colour for approximate country boundaries plotted via wrls_simpl
...	Other items passed to function plot .

Details

This function allows for batch processing of different species and different environmental Raster-Stacks. The function makes internal calls to [ensemble.spatialThin](#), [ensemble.VIF](#), [ensemble.calibrate.weights](#), [ensemble.calibrate.models](#) and [ensemble.raster](#).

Different ensemble runs allow for different random selection of k-fold subsets, background locations or spatial thinning of presence locations.

[ensemble.calibrate.weights](#) results in a cross-validation procedure whereby the data set is split in calibration and testing subsets and the best weights for the ensemble model are determined (including the possibility for weights = 0).

[ensemble.calibrate.models](#) is the step whereby models are calibrated using all the available presence data.

[ensemble.raster](#) is the final step whereby raster layers are produced for the ensemble model.

Function [ensemble.mean](#) results in raster layers that are based on the summary of several ensemble layers: the new ensemble has probability values that are the mean of the probabilities of the different raster layers, the presence-absence threshold is derived for this new ensemble layer, whereas the count reflects the number of ensemble layers where presence was predicted. Note the assumption that input probabilities are scaled between 0 and 1000 (as the output from [ensemble.raster](#)), whereas thresholds are based on actual probabilities (scaled between 0 and 1). After the mean probability has been calculated, the niche overlap ([nicheOverlap](#)) with the different input layers is calculated.

Function [ensemble.plot](#) plots suitability, presence-absence or count maps. In the case of suitability maps, the presence-absence threshold needs to be provided as suitabilities smaller than the threshold will be coloured red to orange, whereas suitabilities larger than the threshold will be coloured light blue to dark blue.

Value

The function finally results in ensemble raster layers for each species, including the fitted values for the ensemble model, the estimated presence-absence and the count of the number of submodels prediction presence and absence.

Author(s)

Roeland Kindt (World Agroforestry Centre), Eike Luedeling (World Agroforestry Centre) and Evert Thomas (Bioversity International)

References

Kindt R. 2018. Ensemble species distribution modelling with transformed suitability values. *Environmental Modelling & Software* 100: 136-145. <https://doi.org/10.1016/j.envsoft.2017.11.009>

Buisson L, Thuiller W, Casajus N, Lek S and Grenouillet G. 2010. Uncertainty in ensemble forecasting of species distribution. *Global Change Biology* 16: 1145-1157

See Also

[ensemble.calibrate.weights](#), [ensemble.calibrate.models](#), [ensemble.raster](#)

Examples

```
## Not run:
# based on examples in the dismo package

# get predictor variables
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
  pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
# subset based on Variance Inflation Factors
predictors <- subset(predictors, subset=c("bio5", "bio6",
  "bio16", "bio17", "biome"))
predictors
predictors@title <- "base"

# presence points
presence_file <- paste(system.file(package="dismo"), '/ex/bradypus.csv', sep='')
pres <- read.table(presence_file, header=TRUE, sep=',')
pres[,1] <- rep("Bradypus", nrow(pres))

# choose background points
background <- randomPoints(predictors, n=1000, extf = 1.00)

# north and south for new predictions (as if new climates)
ext2 <- extent(-90, -32, 0, 23)
predictors2 <- crop(predictors, y=ext2)
predictors2 <- stack(predictors2)
predictors2@title <- "north"

ext3 <- extent(-90, -32, -33, 0)
predictors3 <- crop(predictors, y=ext3)
predictors3 <- stack(predictors3)
```

```

predictors3@title <- "south"

# fit 3 ensembles with batch processing, choosing the best ensemble model based on the
# average weights of 4-fold split of calibration and testing data
# final models use all available presence data and average weights determined by the
# ensemble.calibrate.weights function (called internally)
# batch processing can handle several species by using 3-column species.presence and
# species.absence data sets
# note that these calculations can take a while

ensemble.nofactors <- ensemble.batch(x=predictors,
  xn=c(predictors, predictors2, predictors3),
  species.presence=pres,
  species.absence=background,
  k.splits=4, k.test=0,
  n.ensembles=3,
  SINK=TRUE,
  layer.drops=c("biome"),
  ENSEMBLE.best=0, ENSEMBLE.exponent=c(1, 2, 3),
  ENSEMBLE.min=0.7,
  MAXENT=1, MAXLIKE=1, GBM=1, GBMSTEP=0, RF=1, GLM=1, GLMSTEP=1, GAM=1,
  GAMSTEP=1, MGCV=1, MGCVFIX=1, EARTH=1, RPART=1, NNET=1, FDA=1,
  SVM=1, SVME=1, GLMNET=1,
  BIOCLIM.O=0, BIOCLIM=1, DOMAIN=1, MAHAL=0, MAHAL01=1,
  PROBIT=TRUE,
  Yweights="BIOMOD",
  formulae.defaults=TRUE)

# summaries for the 3 ensembles for the species
# summaries are based on files in folders ensemble/suitability,
# ensemble/presence and ensemble/count
# ensemble.mean is used internally in ensemble.batch

ensemble.mean(RASTER.species.name="Bradypus", RASTER.stack.name="base",
  p=pres, a=background)

# plot mean suitability without specifying colours
plot1 <- ensemble.plot(RASTER.species.name="Bradypus", RASTER.stack.name="base",
  plot.method="consensus suitability",
  p=pres, a=background, abs.breaks=4, pres.breaks=9)
plot1

# only colour the areas where species is predicted to be present
# option is invoked by having no absence breaks
# same colourscheme as \url{http://www.worldagroforestry.org/atlas-central-america}
LAatlascols <- grDevices::colorRampPalette(c("#FFFF80", "#38E009", "#1A93AB", "#0C1078"))
plot2 <- ensemble.plot(RASTER.species.name="Bradypus", RASTER.stack.name="base",
  plot.method="consensus suitability",
  p=pres, a=background, abs.breaks=0, pres.breaks=9, pres.col=LAatlascols(8))
plot2

# only colour the areas where species is predicted to be present
# option is invoked by only setting one colour for absence-presence
plot3 <- ensemble.plot(RASTER.species.name="Bradypus", RASTER.stack.name="base",
  plot.method="consensus presence",
  absencePresence.col=c("#90EE90"))

```

```
# only colour presence area by specifying colours > 0
plot4 <- ensemble.plot(RASTER.species.name="Bradypus", RASTER.stack.name="base",
  plot.method="consensuscount",
  count.col=LAatlascols(3))
```

```
## End(Not run)
```

ensemble.bioclim

Suitability mapping based on the BIOCLIM algorithm

Description

Implementation of the BIOCLIM algorithm more similar to the original BIOCLIM algorithm and software than the implementation through [bioclim](#). Function `ensemble.bioclim` creates the suitability map. Function `ensemble.bioclim.object` provides the reference values used by the prediction function used by [predict](#).

Usage

```
ensemble.bioclim(x = NULL, bioclim.object = NULL,
  RASTER.object.name = bioclim.object$species.name, RASTER.stack.name = x$title,
  RASTER.format = "raster",
  KML.out = TRUE, KML.blur = 10, KML.maxpixels = 100000,
  CATCH.OFF = FALSE)
```

```
ensemble.bioclim.object(x = NULL, p = NULL, fraction = 0.9,
  quantiles = TRUE,
  species.name = "Species001",
  factors = NULL)
```

Arguments

- | | |
|--------------------|---|
| x | RasterStack object (stack) containing all environmental layers for which suitability should be calculated, or alternatively a data.frame containing the bioclimatic variables. |
| bioclim.object | Object listing optimal and absolute minima and maxima for bioclimatic variables, used by the prediction function that is used internally by predict . This object is created with ensemble.bioclim.object . |
| RASTER.object.name | First part of the names of the raster file that will be generated, expected to identify the species or crop for which ranges were calculated |
| RASTER.stack.name | Last part of the names of the raster file that will be generated, expected to identify the predictor stack used |
| RASTER.format | Format of the raster files that will be generated. See writeFormats and writeRaster . |
| KML.out | If TRUE, then kml files will be saved in a subfolder 'kml/zones'. |

KML.blur	Integer that results in increasing the size of the PNG image by KML.blur^2 , which may help avoid blurring of isolated pixels. See also KML .
KML.maxpixels	Maximum number of pixels for the PNG image that will be displayed in Google Earth. See also KML .
CATCH.OFF	Disable calls to function tryCatch .
p	presence points used for calibrating the suitability models, typically available in 2-column (lon, lat) dataframe; see also prepareData and extract .
fraction	Fraction of range representing the optimal limits, default value of 0.9 as in the original BIOCLIM software.
quantiles	If TRUE then optimal limits are calculated as quantiles corresponding to $0.5 - \text{fraction}/2$ and $0.5 + \text{fraction}/2$ percentiles. If FALSE then optimal limits are calculated from the normal distribution with mean - cutoff*sd and mean + cutoff*sd with cutoff calculated as $\text{qnorm}(0.5 + \text{fraction}/2)$.
species.name	Name by which the model results will be saved.
factors	vector that indicates which variables are factors; these variables will be ignored by the BIOCLIM algorithm

Details

Function `ensemble.bioclim` maps suitability for a species based on optimal (percentiles, typically 5 and 95 percent) and absolute (minimum to maximum) limits for bioclimatic variables. If all values at a given location are within the optimal limits, suitability values are mapped as 1 (suitable). If not all values are within the optimal limits, but all values are within the absolute limits, suitability values are mapped as 0.5 (marginal). If not all values are within the absolute limits, suitability values are mapped as 0 (unsuitable).

Function `ensemble.bioclim.object` calculates the optimal and absolute limits. Optimal limits are calculated based on the parameter `fraction`, resulting in optimal limits that correspond to $0.5 - \text{fraction}/2$ and $0.5 + \text{fraction}/2$ (the default value of 0.9 therefore gives a lower limit of 0.05 and an upper limit of 0.95). Two methods are implemented to obtain optimal limits for the lower and upper limits. One method (`quantiles = FALSE`) uses mean, standard deviation and a cutoff parameter calculated with `qnorm` (see also <http://openmodeller.sourceforge.net/algorithms/bioclim.html>). The other method (`quantiles = TRUE`) calculates optimal limits via the `quantile` function. To handle possible asymmetrical distributions better, the second method is used as default.

When `x` is a `RasterStack` and point locations are provided, then optimal and absolute limits correspond to the bioclimatic values observed for the locations. When `x` is `RasterStack` and point locations are not provided, then optimal and absolute limits correspond to the bioclimatic values of the `RasterStack`.

Applying to algorithm without providing point locations will provide results that are similar to the [ensemble.novel](#) function, whereby areas plotted as not suitable will be the same areas that are novel.

Value

Function `ensemble.bioclim.object` returns a list with following objects:

lower.limits	vector with lower limits for each bioclimatic variable
upper.limits	vector with upper limits for each bioclimatic variable
minima	vector with minima for each bioclimatic variable
maxima	vector with maxima for each bioclimatic variable

means	vector with mean values for each bioclimatic variable
medians	vector with median values for each bioclimatic variable
sds	vector with standard deviation values for each bioclimatic variable
cutoff	cutoff value for the normal distribution
fraction	fraction of values within the optimal limits
species.name	name for the species

Author(s)

Roeland Kindt (World Agroforestry Centre) with inputs from Trevor Booth (CSIRO)

References

Nix HA. 1986. A biogeographic analysis of Australian elapid snakes. In: Atlas of Elapid Snakes of Australia. (Ed.) R. Longmore, pp. 4-15. Australian Flora and Fauna Series Number 7. Australian Government Publishing Service: Canberra.

Booth TH, Nix HA, Busby JR and Hutchinson MF. 2014. BIOCLIM: the first species distribution modelling package, its early applications and relevance to most current MAXENT studies. Diversity and Distributions 20: 1-9

See Also

[bioclim](#), [ensemble.bioclim.graph](#) and [ensemble.novel](#)

Examples

```
## Not run:
# get predictor variables
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
  pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
# subset based on Variance Inflation Factors
predictors <- subset(predictors, subset=c("bio5", "bio6",
  "bio16", "bio17", "biome"))
predictors
predictors@title <- "base"

# presence points
presence_file <- paste(system.file(package="dismo"), '/ex/bradypus.csv', sep='')
pres <- read.table(presence_file, header=TRUE, sep=',')[,-1]

background <- dismo::randomPoints(predictors, n=100)
colnames(background)=c('lon', 'lat')

pres.dataset <- data.frame(extract(predictors, y=pres))
names(pres.dataset) <- names(predictors)
pres.dataset$biome <- as.factor(pres.dataset$biome)

Bradypus.bioclim <- ensemble.bioclim.object(predictors, quantiles=T,
  p=pres, factors="biome", species.name="Bradypus")
Bradypus.bioclim
# obtain the same results with a data.frame
```

```

Bradypus.bioclim2 <- ensemble.bioclim.object(pres.dataset, quantiles=T,
  species.name="Bradypus")
Bradypus.bioclim2
# obtain results for entire rasterStack
Bradypus.bioclim3 <- ensemble.bioclim.object(predictors, p=NULL, quantiles=T,
  factors="biome", species.name="America")
Bradypus.bioclim3

ensemble.bioclim(x=predictors, bioclim.object=Bradypus.bioclim, KML.out=T)
ensemble.bioclim(x=predictors, bioclim.object=Bradypus.bioclim3, KML.out=T)

par.old <- graphics::par(no.readonly=T)
graphics::par(mfrow=c(1,2))

rasterfull1 <- paste("ensembles//Bradypus_base_BIOCLIM_orig", sep="")
raster::plot(raster(rasterfull1), breaks=c(-0.1, 0, 0.5, 1),
  col=c("grey", "blue", "green"), main="original method")
rasterfull2 <- paste("ensembles//America_base_BIOCLIM_orig", sep="")
raster::plot(raster(rasterfull2), breaks=c(-0.1, 0, 0.5, 1),
  col=c("grey", "blue", "green"), main="America")

graphics::par(par.old)

# compare with implementation bioclim in dismo
bioclim.dismo <- bioclim(predictors, p=pres)
rasterfull2 <- paste("ensembles//Bradypus_base_BIOCLIM_dismo", sep="")
raster::predict(object=predictors, model=bioclim.dismo, na.rm=TRUE,
  filename=rasterfull2, progress='text', overwrite=TRUE)

par.old <- graphics::par(no.readonly=T)
graphics::par(mfrow=c(1,2))

raster::plot(raster(rasterfull1), breaks=c(-0.1, 0, 0.5, 1),
  col=c("grey", "blue", "green"), main="original method")
raster::plot(raster(rasterfull2), main="dismo method")

graphics::par(par.old)

# use dummy variables to deal with factors
predictors <- stack(predictor.files)
biome.layer <- predictors[["biome"]]
biome.layer
ensemble.dummy.variables(xcat=biome.layer, most.frequent=0, freq.min=1,
  overwrite=TRUE)

predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
  pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
predictors.dummy <- subset(predictors, subset=c("biome_1", "biome_2", "biome_3",
  "biome_4", "biome_5", "biome_7", "biome_8", "biome_9", "biome_10",
  "biome_12", "biome_13", "biome_14"))
predictors.dummy
predictors.dummy@title <- "base_dummy"

Bradypus.dummy <- ensemble.bioclim.object(predictors.dummy, quantiles=T,
  p=pres, species.name="Bradypus")
Bradypus.dummy

```

```

ensemble.bioclim(x=predictors.dummy, bioclim.object=Bradypus.dummy, KML.out=F)

par.old <- graphics::par(no.readonly=T)
graphics::par(mfrow=c(1,2))

rasterfull3 <- paste("ensembles//Bradypus_base_dummy_BIOCLIM_orig", sep="")
raster::plot(raster(rasterfull1), breaks=c(-0.1, 0, 0.5, 1), col=c("grey", "blue", "green"),
  main="numeric predictors")
raster::plot(raster(rasterfull3), breaks=c(-0.1, 0, 0.5, 1), col=c("grey", "blue", "green"),
  main="dummy predictors")

graphics::par(par.old)

## End(Not run)

```

ensemble.bioclim.graph

Graphs of bioclimatic ranges of species and climates

Description

The main graph function makes graphs that show mean, median, minimum, maximum and lower and upper limits for species or climates. The `ensemble.bioclim.graph.data` function creates input data, using [ensemble.bioclim.object](#) internally.

Usage

```

ensemble.bioclim.graph(graph.data = NULL, focal.var = NULL,
  species.climates.subset = NULL, cols = NULL,
  var.multiply = 1.0, ref.lines = TRUE)

ensemble.bioclim.graph.data(
  x=NULL, p=NULL, fraction = 0.9,
  species.climate.name="Species001_base", factors = NULL)

```

Arguments

<code>graph.data</code>	Input data with same variables as created by ensemble.bioclim.graph
<code>focal.var</code>	Bioclimatic variable to be plotted in the graph
<code>species.climates.subset</code>	Character vector with subset of names of species and climates to be plotted in the graph (if not provided, then all species and climates will be plotted).
<code>cols</code>	colours for the different species and climates
<code>var.multiply</code>	multiplier for the values to be plotted; 0.1 should be used if the bioclimatic variable was multiplied by 10 in the raster layers as in WorldClim and AFRICLIM
<code>ref.lines</code>	If TRUE, then horizontal reference lines will be added for the minimum and maximum values of the species or climate plotted on the extreme left in the graph
<code>x</code>	RasterStack object (stack) containing all environmental layers for which statistics should be calculated; see also ensemble.bioclim .

p	presence points used for calibrating the suitability models, typically available in 2-column (lon, lat) dataframe; see also ensemble.bioclim .
fraction	Fraction of range representing the optimal limits, default value of 0.9 as in the original BIOCLIM software; see also ensemble.bioclim .
species.climate.name	Name for the species or climate that will be used as label in the graph.
factors	vector that indicates which variables are factors; these variables will be ignored by the BIOCLIM algorithm; see also ensemble.bioclim .

Details

The function creates a graph that shows mean, median, minimum, maximum and upper and lower limits for a range of species and climates. The graph can be useful in interpreting results of [ensemble.bioclim](#) or [ensemble.novel](#).

In the graphs, means are indicated by an asterisk (pch=8 and medians as larger circles (pch=1)).

Value

function `ensemble.bioclim.graph.data` creates a data frame, function `ensemble.bioclim.graph` allows for plotting.

Author(s)

Roeland Kindt (World Agroforestry Centre)

See Also

[ensemble.bioclim](#)

Examples

```
## Not run:

# get predictor variables
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
  pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
# subset based on Variance Inflation Factors
predictors <- subset(predictors, subset=c("bio5", "bio6",
  "bio16", "bio17", "biome"))
predictors
predictors$title <- "base"

# presence points
presence_file <- paste(system.file(package="dismo"), '/ex/bradypus.csv', sep='')
pres <- read.table(presence_file, header=TRUE, sep=',')[,-1]

# climates for north and south (use same process for future climates)
ext2 <- extent(-90, -32, 0, 23)
predictors2 <- crop(predictors, y=ext2)
predictors2 <- stack(predictors2)
predictors2$title <- "north"
```

```

ext3 <- extent(-90, -32, -33, 0)
predictors3 <- crop(predictors, y=ext3)
predictors3 <- stack(predictors3)
predictors3@title <- "south"

graph.data1 <- ensemble.bioclim.graph.data(predictors, p=pres,
  factors="biome", species.climate.name="Bradypus")
graph.data2 <- ensemble.bioclim.graph.data(predictors, p=NULL,
  factors="biome", species.climate.name="baseline")
graph.data3 <- ensemble.bioclim.graph.data(predictors2, p=NULL,
  factors="biome", species.climate.name="north")
graph.data4 <- ensemble.bioclim.graph.data(predictors3, p=NULL,
  factors="biome", species.climate.name="south")
graph.data.all <- rbind(graph.data1, graph.data2, graph.data3, graph.data4)

par.old <- graphics::par(no.readonly=T)
graphics::par(mfrow=c(2, 2))

ensemble.bioclim.graph(graph.data.all, focal.var="bio5",
  var.multiply=0.1, cols=c("black", rep("blue", 3)))
ensemble.bioclim.graph(graph.data.all, focal.var="bio6",
  var.multiply=0.1, cols=c("black", rep("blue", 3)))
ensemble.bioclim.graph(graph.data.all, focal.var="bio16",
  var.multiply=1.0, cols=c("black", rep("blue", 3)))
ensemble.bioclim.graph(graph.data.all, focal.var="bio17",
  var.multiply=1.0, cols=c("black", rep("blue", 3)))

graphics::par(par.old)

## End(Not run)

```

ensemble.calibrate.models

Suitability mapping based on ensembles of modelling algorithms: calibration of models and weights

Description

The basic function `ensemble.calibrate.models` allows to evaluate different algorithms for (species) suitability modelling, including maximum entropy (MAXENT), boosted regression trees, random forests, generalized linear models (including stepwise selection of explanatory variables), generalized additive models (including stepwise selection of explanatory variables), multivariate adaptive regression splines, regression trees, artificial neural networks, flexible discriminant analysis, support vector machines, the BIOCLIM algorithm, the DOMAIN algorithm and the Mahalanobis algorithm. These sets of functions were developed in parallel with the `biomod2` package, especially for inclusion of the maximum entropy algorithm, but also to allow for a more direct integration with the `BiodiversityR` package, more direct handling of model formulae and greater focus on mapping. Researchers and students of species distribution are strongly encouraged to familiarize themselves with all the options of the `BIOMOD` and `dismo` packages.

Usage

```

ensemble.calibrate.models(x = NULL, p = NULL, a = NULL, an = 1000, excludep = FALSE,
  k = 0, pt = NULL, at = NULL, SSB.reduce = FALSE, CIRCLES.d = 250000,
  TrainData = NULL, TestData = NULL,
  VIF = FALSE, COR = FALSE,
  SINK = FALSE, PLOTS = FALSE, CATCH.OFF = FALSE,
  threshold.method = "spec_sens", threshold.sensitivity = 0.9,
  threshold.PresenceAbsence = FALSE,
  evaluations.keep = FALSE,
  models.list = NULL, models.keep = FALSE,
  models.save = FALSE, species.name = "Species001",
  ENSEMBLE.tune = FALSE,
  ENSEMBLE.best = 0, ENSEMBLE.min = 0.7, ENSEMBLE.exponent = 1,
  ENSEMBLE.weight.min = 0.05,
  input.weights = NULL,
  MAXENT = 1, MAXLIKE = 1, GBM = 1, GBMSTEP = 1, RF = 1, GLM = 1, GLMSTEP = 1,
  GAM = 1, GAMSTEP = 1, MGCV = 1, MGCVFIX = 0, EARTH = 1,
  RPART = 1, NNET = 1, FDA = 1, SVM = 1, SVME = 1, GLMNET = 1,
  BIOCLIM.O = 0, BIOCLIM = 1, DOMAIN = 1, MAHAL = 1, MAHAL01 = 1,
  PROBIT = FALSE,
  Yweights = "BIOMOD",
  layer.drops = NULL, factors = NULL, dummy.vars = NULL,
  formulae.defaults = TRUE, maxit = 100,
  MAXENT.a = NULL, MAXENT.an = 10000,
  MAXENT.path = paste(getwd(), "/models/maxent_", species.name, sep=""),
  MAXLIKE.formula = NULL, MAXLIKE.method = "BFGS",
  GBM.formula = NULL, GBM.n.trees = 2001,
  GBMSTEP.gbm.x = 2:(ncol(TrainData.vars)+1), GBMSTEP.tree.complexity = 5,
  GBMSTEP.learning.rate = 0.005, GBMSTEP.bag.fraction = 0.5,
  GBMSTEP.step.size = 100,
  RF.formula = NULL, RF.ntree = 751,
  RF.mtry = floor(sqrt(ncol(TrainData.vars))),
  GLM.formula = NULL, GLM.family = binomial(link = "logit"),
  GLMSTEP.steps = 1000, STEP.formula = NULL, GLMSTEP.scope = NULL,
  GLMSTEP.k = 2,
  GAM.formula = NULL, GAM.family = binomial(link = "logit"),
  GAMSTEP.steps = 1000, GAMSTEP.scope = NULL, GAMSTEP.pos = 1,
  MGCV.formula = NULL, MGCV.select = FALSE,
  MGCVFIX.formula = NULL,
  EARTH.formula = NULL,
  EARTH.glm = list(family = binomial(link = "logit"), maxit = maxit),
  RPART.formula = NULL, RPART.xval = 50,
  NNET.formula = NULL, NNET.size = 8, NNET.decay = 0.01,
  FDA.formula = NULL,
  SVM.formula = NULL,
  SVME.formula = NULL,
  GLMNET.nlambda = 100, GLMNET.class = FALSE,
  BIOCLIM.O.fraction = 0.9,
  MAHAL.shape = 1)

ensemble.calibrate.weights(x = NULL, p = NULL,
  a = NULL, an = 1000,

```

```

get.block = FALSE,
SSB.reduce = FALSE, CIRCLES.d = 100000,
excludep = FALSE,
k = 4,
VIF = FALSE, COR = FALSE,
SINK = FALSE, PLOTS = FALSE, CATCH.OFF = FALSE,
data.keep = FALSE,
species.name = "Species001",
threshold.method = "spec_sens", threshold.sensitivity = 0.9,
threshold.PresenceAbsence = FALSE,
ENSEMBLE.tune = FALSE,
ENSEMBLE.best = 0, ENSEMBLE.min = 0.7, ENSEMBLE.exponent = 1,
ENSEMBLE.weight.min = 0.05,
input.weights = NULL,
MAXENT = 1, MAXLIKE = 1, GBM = 1, GBMSTEP = 1, RF = 1, GLM = 1, GLMSTEP = 1,
GAM = 1, GAMSTEP = 1, MGCV = 1, MGCVFIX = 0, EARTH = 1,
RPART = 1, NNET = 1, FDA = 1, SVM = 1, SVME = 1, GLMNET = 1,
BIOCLIM.O = 0, BIOCLIM = 1, DOMAIN = 1, MAHAL = 1, MAHAL01 = 1,
PROBIT = FALSE,
Yweights = "BIOMOD",
layer.drops = NULL, factors = NULL, dummy.vars = NULL,
formulae.defaults = TRUE, maxit = 100,
MAXENT.a = NULL, MAXENT.an = 10000,
MAXENT.path = paste(getwd(), "/models/maxent_", species.name, sep=""),
MAXLIKE.formula = NULL, MAXLIKE.method = "BFGS",
GBM.formula = NULL, GBM.n.trees = 2001,
GBMSTEP.gbm.x = 2:(length(var.names)+1), GBMSTEP.tree.complexity = 5,
GBMSTEP.learning.rate = 0.005,
GBMSTEP.bag.fraction = 0.5, GBMSTEP.step.size = 100,
RF.formula = NULL, RF.ntree = 751, RF.mtry = floor(sqrt(length(var.names))),
GLM.formula = NULL, GLM.family = binomial(link = "logit"),
GLMSTEP.steps = 1000, STEP.formula = NULL, GLMSTEP.scope = NULL, GLMSTEP.k = 2,
GAM.formula = NULL, GAM.family = binomial(link = "logit"),
GAMSTEP.steps = 1000, GAMSTEP.scope = NULL, GAMSTEP.pos = 1,
MGCV.formula = NULL, MGCV.select = FALSE,
MGCVFIX.formula = NULL,
EARTH.formula = NULL,
EARTH.glm = list(family = binomial(link = "logit"), maxit = maxit),
RPART.formula = NULL, RPART.xval = 50,
NNET.formula = NULL, NNET.size = 8, NNET.decay = 0.01,
FDA.formula = NULL,
SVM.formula = NULL,
SVME.formula = NULL,
GLMNET.nlambda = 100, GLMNET.class = FALSE,
BIOCLIM.O.fraction = 0.9,
MAHAL.shape = 1)

ensemble.calibrate.models.gbm(x = NULL, p = NULL, a = NULL, an = 1000, excludep = FALSE,
k = 4,
TrainData = NULL,
VIF = FALSE, COR = FALSE,
SINK = FALSE, PLOTS = FALSE,

```



```

species.name = "Species001",
Yweights = "BIOMOD",
layer.drops = NULL, factors = NULL,
GBMSTEP.gbm.x = 2:(ncol(TrainData.orig)),
complexity = c(3:6), learning = c(0.005, 0.002, 0.001),
GBMSTEP.bag.fraction = 0.5, GBMSTEP.step.size = 100)

ensemble.calibrate.models.nnet(x = NULL, p = NULL, a = NULL, an = 1000, excludep = FALSE,
k = 4,
TrainData = NULL,
VIF = FALSE, COR = FALSE,
SINK = FALSE, PLOTS = FALSE,
species.name = "Species001",
Yweights = "BIOMOD",
layer.drops = NULL, factors = NULL,
formulae.defaults = TRUE, maxit = 100,
NNET.formula = NULL,
sizes = c(2, 4, 6, 8), decays = c(0.1, 0.05, 0.01, 0.001) )

ensemble.drop1(x = NULL, p = NULL, a = NULL, an = 1000, excludep = FALSE,
k = 0, pt = NULL, at = NULL, SSB.reduce = FALSE, CIRCLES.d = 100000,
TrainData = NULL, TestData = NULL,
VIF = FALSE, COR = FALSE,
SINK = FALSE,
species.name = "Species001",
difference = FALSE, variables.alone = FALSE,
ENSEMBLE.tune = FALSE,
ENSEMBLE.best = 0, ENSEMBLE.min = 0.7, ENSEMBLE.exponent = 1,
input.weights = NULL,
MAXENT = 1, MAXLIKE = 1, GBM = 1, GBMSTEP = 0, RF = 1, GLM = 1, GLMSTEP = 1,
GAM = 1, GAMSTEP = 1, MGCV = 1, MGCVFIX = 0, EARTH = 1,
RPART = 1, NNET = 1, FDA = 1, SVM = 1, SVME = 1, GLMNET = 1,
BIOCLIM.0 = 0, BIOCLIM = 1, DOMAIN = 1, MAHAL = 1, MAHAL01 = 1,
PROBIT = FALSE,
Yweights = "BIOMOD",
layer.drops = NULL, factors = NULL, dummy.vars = NULL,
maxit = 100,
MAXENT.a = NULL, MAXENT.an = 10000,
MAXENT.path = paste(getwd(), "/models/maxent_", species.name, sep=""),
MAXLIKE.method = "BFGS",
GBM.n.trees = 2001,
GBMSTEP.tree.complexity = 5, GBMSTEP.learning.rate = 0.005,
GBMSTEP.bag.fraction = 0.5, GBMSTEP.step.size = 100,
RF.ntree = 751,
GLM.family = binomial(link = "logit"),
GLMSTEP.steps = 1000, GLMSTEP.scope = NULL, GLMSTEP.k = 2,
GAM.family = binomial(link = "logit"),
GAMSTEP.steps = 1000, GAMSTEP.scope = NULL, GAMSTEP.pos = 1,
MGCV.select = FALSE,
EARTH.glm = list(family = binomial(link = "logit"), maxit = maxit),
RPART.xval = 50,
NNET.size = 8, NNET.decay = 0.01,

```

```

GLMNET.nlambda = 100, GLMNET.class = FALSE,
BIOCLIM.O.fraction = 0.9,
MAHAL.shape = 1)

ensemble.weights(weights = c(0.9, 0.8, 0.7, 0.5),
  best = 0, min.weight = 0,
  exponent = 1, digits = 6)

ensemble.strategy(TrainData = NULL, TestData = NULL,
  verbose = FALSE,
  ENSEMBLE.best = c(4:10), ENSEMBLE.min = c(0.7),
  ENSEMBLE.exponent = c(1, 2, 3) )

ensemble.formulae(x,
  layer.drops = NULL, factors = NULL, dummy.vars = NULL, weights = NULL)

ensemble.threshold(eval, threshold.method = "spec_sens", threshold.sensitivity = 0.9,
  threshold.PresenceAbsence = FALSE, Pres, Abs)

ensemble.VIF(x = NULL, a = NULL, an = 10000,
  VIF.max = 10, keep = NULL,
  layer.drops = NULL, factors = NULL, dummy.vars = NULL)

ensemble.pairs(x = NULL, a = NULL, an = 10000)

```

Arguments

x	RasterStack object (stack) containing all layers that correspond to explanatory variables
p	presence points used for calibrating the suitability models, typically available in 2-column (lon, lat) dataframe; see also prepareData and extract
a	background points used for calibrating the suitability models (except for maxent), typically available in 2-column (lon, lat) dataframe; see also prepareData and extract
an	number of background points for calibration to be selected with randomPoints in case argument a is missing
excludep	parameter that indicates (if TRUE) that presence points will be excluded from the background points; see also randomPoints
k	If larger than 1, the number of groups to split between calibration (k-1) and evaluation (1) data sets (for example, k = 4 results in 3/4 of presence and background points to be used for calibrating the models, and 1/4 of presence and background points to be used for evaluating the models). For <code>ensemble.calibrate.weights</code> , <code>ensemble.calibrate.models.gbm</code> and <code>ensemble.calibrate.models.nnet</code> , this procedure is repeated k times (k-fold cross-validation). See also kfold .
pt	presence points used for evaluating the suitability models, available in 2-column (lon, lat) dataframe; see also prepareData and extract
at	background points used for evaluating the suitability models, available in 2-column (lon, lat) dataframe; see also prepareData and extract
SSB.reduce	If TRUE, then new background points that will be used for evaluating the suitability models will be selected (randomPoints) in circular neighbourhoods (cre-

	ated with circles) around presence locations (p and pt). The abbreviation of SSB refers to spatial sorting bias; see also ssb .
CIRCLES.d	Radius in m of circular neighbourhoods (created with circles) around presence locations (p and pt).
TrainData	dataframe with first column 'pb' describing presence (1) and absence (0) and other columns containing explanatory variables; see also prepareData . In case that this dataframe is provided, then locations p and a are not used. For the maximum entropy model (maxent), a different dataframe is used for calibration; see parameter MAXENT.TrainData.
TestData	dataframe with first column 'pb' describing presence (1) and absence (0) and other columns containing explanatory variables; see also prepareData . In case that this dataframe is provided, then locations pt and at are not used. For <code>ensemble.strategy</code> , this dataframe should be a dataframe that contains predictions for various models - such dataframe can be provided by the <code>ensemble.calibrate.models</code> or ensemble.raster functions.
VIF	Estimate the variance inflation factors based on a linear model calibrated on the training data (if TRUE). Only background locations will be used and the response variable 'pb' will be replaced by a random variable. See also vif .
COR	Provide information on the correlation between the numeric explanatory variables (if TRUE). See also cor .
SINK	Append the results to a text file in subfolder 'outputs' (if TRUE). The name of file is based on argument <code>species.name</code> . In case the file already exists, then results are appended. See also sink .
PLOTS	Disabled option of plotting evaluation results(BiodiversityR version 2.9-1) - see examples how to plot results afterwards and also evaluate .
CATCH.OFF	Disable calls to function tryCatch .
threshold.method	Method to calculate the threshold between predicted absence and presence; possibilities include <code>spec_sens</code> (highest sum of the true positive rate and the true negative rate), <code>kappa</code> (highest kappa value), <code>no_omission</code> (highest threshold that corresponds to no omission), <code>prevalence</code> (modeled prevalence is closest to observed prevalence) and <code>equal_sens_spec</code> (equal true positive rate and true negative rate). See threshold . Options specific to the BiodiversityR implementation are: <code>threshold2005.mean</code> , <code>threshold2005.min</code> , <code>threshold2013.mean</code> and <code>threshold2013.min</code> (resulting in calculating the mean or minimum value of recommended threshold values by studies published in 2005 and 2013; see details below).
threshold.sensitivity	Sensitivity value for <code>threshold.method = 'sensitivity'</code> . See threshold .
threshold.PresenceAbsence	If TRUE calculate thresholds with the PresenceAbsence package. See optimal.thresholds .
evaluations.keep	Keep the results of evaluations (if TRUE). See also evaluate .
models.list	list with 'old' model objects such as MAXENT or RF.
models.keep	store the details for each suitability modelling algorithm (if TRUE). (This may be particularly useful when projecting to different possible future climates.)
models.save	Save the list with model details to a file (if TRUE). The filename will be <code>species.name</code> with extension <code>.models</code> ; this file will be saved in subfolder of models. When loading this file, model results will be available as <code>ensemble.models</code> .

species.name	Name by which the model details will be saved to a file; see also argument <code>models.save</code>
data.keep	Keep the data for each k-fold cross-validation run (if TRUE).
ENSEMBLE.tune	Determine weights for the ensemble model based on AUC values (if TRUE). See details.
ENSEMBLE.best	The number of individual suitability models to be used in the consensus suitability map (based on a weighted average). In case this parameter is smaller than 1 or larger than the number of positive input weights of individual models, then all individual suitability models with positive input weights are included in the consensus suitability map. In case a vector is provided, <code>ensemble.strategy</code> is called internally to determine weights for the ensemble model.
ENSEMBLE.min	The minimum input weight (typically corresponding to AUC values) for a model to be included in the ensemble. In case a vector is provided, function <code>ensemble.strategy</code> is called internally to determine weights for the ensemble model.
ENSEMBLE.exponent	Exponent applied to AUC values to convert AUC values into weights (for example, an exponent of 2 converts input weights of 0.7, 0.8 and 0.9 into $0.7^2=0.49$, $0.8^2=0.64$ and $0.9^2=0.81$). See details.
ENSEMBLE.weight.min	The minimum output weight for models included in the ensemble, applying to weights that sum to one. Note that <code>ENSEMBLE.min</code> typically refers to input AUC values.
input.weights	array with numeric values for the different modelling algorithms; if NULL then values provided by parameters such as <code>MAXENT</code> and <code>GBM</code> will be used. As an alternative, the output from <code>ensemble.calibrate.weights</code> can be used.
MAXENT	number: if larger than 0, then a maximum entropy model (maxent) will be fitted among ensemble
MAXLIKE	number: if larger than 0, then a maxlike model (maxlike) will be fitted among ensemble
GBM	number: if larger than 0, then a boosted regression trees model (gbm) will be fitted among ensemble
GBMSTEP	number: if larger than 0, then a stepwise boosted regression trees model (gbm.step) will be fitted among ensemble
RF	number: if larger than 0, then a random forest model (randomForest) will be fitted among ensemble
GLM	number: if larger than 0, then a generalized linear model (glm) will be fitted among ensemble
GLMSTEP	number: if larger than 0, then a stepwise generalized linear model (stepAIC) will be fitted among ensemble
GAM	number: if larger than 0, then a generalized additive model (gam) will be fitted among ensemble
GAMSTEP	number: if larger than 0, then a stepwise generalized additive model (step.gam) will be fitted among ensemble
MGCV	number: if larger than 0, then a generalized additive model (gam) will be fitted among ensemble
MGCVFIX	number: if larger than 0, then a generalized additive model with fixed d.f. regression splines (gam) will be fitted among ensemble

EARTH	number: if larger than 0, then a multivariate adaptive regression spline model (earth) will be fitted among ensemble
RPART	number: if larger than 0, then a recursive partitioning and regression tree model (rpart) will be fitted among ensemble
NNET	number: if larger than 0, then an artificial neural network model (nnet) will be fitted among ensemble
FDA	number: if larger than 0, then a flexible discriminant analysis model (fda) will be fitted among ensemble
SVM	number: if larger than 0, then a support vector machine model (ksvm) will be fitted among ensemble
SVME	number: if larger than 0, then a support vector machine model (svm) will be fitted among ensemble
GLMNET	number: if larger than 0, then a GLM with lasso or elasticnet regularization (glmnet) will be fitted among ensemble
BIOCLIM.O	number: if larger than 0, then the original BIOCLIM algorithm (ensemble.bioclim) will be fitted among ensemble
BIOCLIM	number: if larger than 0, then the BIOCLIM algorithm (bioclim) will be fitted among ensemble
DOMAIN	number: if larger than 0, then the DOMAIN algorithm (domain) will be fitted among ensemble
MAHAL	number: if larger than 0, then the Mahalanobis algorithm (mahal) will be fitted among ensemble
MAHAL01	number: if larger than 0, then the Mahalanobis algorithm (mahal) will be fitted among ensemble, using a transformation method afterwards whereby output is within the range between 0 and 1 (see details)
PROBIT	If TRUE, then subsequently to the fitting of the individual algorithm (e.g. maximum entropy or GAM) a generalized linear model (glm) with probit link family=binomial(link="p will be fitted to transform the predictions, using the previous predictions as explanatory variable. This transformation results in all model predictions to be probability estimates.
Yweights	chooses how cases of presence and background (absence) are weighted; "BIOMOD" results in equal weighting of all presence and all background cases, "equal" results in equal weighting of all cases. The user can supply a vector of weights similar to the number of cases in the calibration data set.
layer.drops	vector that indicates which layers should be removed from RasterStack x. This argument is especially useful for the <code>ensemble.drop1</code> function. See also addLayer .
factors	vector that indicates which variables are factors; see also prepareData
dummy.vars	vector that indicates which variables are dummy variables (influences formulae suggestions)
formulae.defaults	Suggest formulae for most of the models (if TRUE). See also ensemble.formulae .
maxit	Maximum number of iterations for some of the models. See also glm.control , gam.control and nnet .
MAXENT.a	background points used for calibrating the maximum entropy model (maxent), typically available in 2-column (lon, lat) dataframe; see also prepareData and extract .

MAXENT.an	number of background points for calibration to be selected with randomPoints in case argument MAXENT.a is missing
MAXENT.path	path to the directory where output files of the maximum entropy model are stored; see also maxent
MAXLIKE.formula	formula for the maxlike algorithm; see also maxlike
MAXLIKE.method	method for the maxlike algorithm; see also optim
GBM.formula	formula for the boosted regression trees algorithm; see also gbm
GBM.n.trees	total number of trees to fit for the boosted regression trees model; see also gbm
GBMSTEP.gbm.x	indices of column numbers with explanatory variables for stepwise boosted regression trees; see also gbm.step
GBMSTEP.tree.complexity	complexity of individual trees for stepwise boosted regression trees; see also gbm.step
GBMSTEP.learning.rate	weight applied to individual trees for stepwise boosted regression trees; see also gbm.step
GBMSTEP.bag.fraction	proportion of observations used in selecting variables for stepwise boosted regression trees; see also gbm.step
GBMSTEP.step.size	number of trees to add at each cycle for stepwise boosted regression trees (should be small enough to result in a smaller holdout deviance than the initial number of trees [50]); see also gbm.step
RF.formula	formula for random forest algorithm; see also randomForest
RF.ntree	number of trees to grow for random forest algorithm; see also randomForest
RF.mtry	number of variables randomly sampled as candidates at each split for random forest algorithm; see also randomForest
GLM.formula	formula for the generalized linear model; see also glm
GLM.family	description of the error distribution and link function for the generalized linear model; see also glm
GLMSTEP.steps	maximum number of steps to be considered for stepwise generalized linear model; see also stepAIC
STEP.formula	formula for the "starting model" to be considered for stepwise generalized linear model; see also stepAIC
GLMSTEP.scope	range of models examined in the stepwise search; see also stepAIC
GLMSTEP.k	multiple of the number of degrees of freedom used for the penalty (only k = 2 gives the genuine AIC); see also stepAIC
GAM.formula	formula for the generalized additive model; see also gam
GAM.family	description of the error distribution and link function for the generalized additive model; see also gam
GAMSTEP.steps	maximum number of steps to be considered in the stepwise generalized additive model; see also step.gam
GAMSTEP.scope	range of models examined in the step-wise search n the stepwise generalized additive model; see also step.gam

GAMSTEP.pos	parameter expected to be set to 1 to allow for fitting of the stepwise generalized additive model
MGCV.formula	formula for the generalized additive model; see also gam
MGCV.select	if TRUE, then the smoothing parameter estimation that is part of fitting can completely remove terms from the model; see also gam
MGCVFIX.formula	formula for the generalized additive model with fixed d.f. regression splines; see also gam (the default formulae sets "s(..., fx = TRUE, ...)"; see also s)
EARTH.formula	formula for the multivariate adaptive regression spline model; see also earth
EARTH.glm	list of arguments to pass on to glm ; see also earth
RPART.formula	formula for the recursive partitioning and regression tree model; see also rpart
RPART.xval	number of cross-validations for the recursive partitioning and regression tree model; see also rpart.control
NNET.formula	formula for the artificial neural network model; see also nnet
NNET.size	number of units in the hidden layer for the artificial neural network model; see also nnet
NNET.decay	parameter of weight decay for the artificial neural network model; see also nnet
FDA.formula	formula for the flexible discriminant analysis model; see also fda
SVM.formula	formula for the support vector machine model; see also ksvm
SVME.formula	formula for the support vector machine model; see also svm
GLMNET.nlambda	The number of lambda values; see also glmnet
GLMNET.class	Use the predicted class to calculate the mean predictions of GLMNET; see predict.glmnet
BIOCLIM.O.fraction	Fraction of range representing the optimal limits, default value of 0.9 as in the original BIOCLIM software (ensemble.bioclim).
MAHAL.shape	parameter that influences the transformation of output values of mahal . See details section.
get.block	if TRUE, instead of creating k-fold cross-validation subsets randomly (kfold), create 4 subsets of presence and background locations with get.block .
complexity	vector with values of complexity of individual trees (tree.complexity) for boosted regression trees; see also gbm.step
learning	vector with values of weights applied to individual trees (learning.rate) for boosted regression trees; see also gbm.step
sizes	vector with values of number of units in the hidden layer for the artificial neural network model; see also nnet
decays	vector with values of weight decay for the artificial neural network model; see also nnet
difference	if TRUE, then AUC values of the models with all variables are subtracted from the models where one explanatory variable was excluded. After subtraction, positive values indicate that the model without the explanatory variable has a higher AUC than the model with all variables.
variables.alone	if TRUE, then models are also fitted using each explanatory variable as single explanatory variable

weights	input weights for the ensemble.weights function
best	The number of final weights. In case this parameter is smaller than 1 or larger than the number of positive input weights of individual models, then this parameter is ignored.
min.weight	The minimum input weight to be included in the output.
exponent	Exponent applied to AUC values to convert AUC values into weights (for example, an exponent of 2 converts input weights of 0.7, 0.8 and 0.9 into $0.7^2=0.49$, $0.8^2=0.64$ and $0.9^2=0.81$). See details.
digits	Number of number of decimal places in the output weights; see also round .
verbose	If TRUE, then provide intermediate results for ensemble.strategy)
eval	ModelEvaluation object obtained by evaluate
Pres	Suitabilities (probabilities) at presence locations
Abs	Suitabilities (probabilities) at background locations
VIF.max	Maximum Variance Inflation Factor of the selected subset of variables. In case that at least one of the variables has VIF larger than VIF.max, then the variable with the highest VIF will be removed in the next step.
keep	character vector with names of the variables to be kept.

Details

The basic function `ensemble.calibrate.models` first calibrates individual suitability models based on presence locations `p` and background locations `a`, then evaluates these suitability models based on presence locations `pt` and background locations `at`. While calibrating and testing individual models, results obtained via the [evaluate](#) function can be saved (`evaluations.keep`).

As an alternative to providing presence locations `p`, models can be calibrated with data provided in `TrainData`. In case that both `p` and `TrainData` are provided, then models will be calibrated with `TrainData`.

Calibration of the maximum entropy (MAXENT) algorithm is not based on background locations `a`, but based on background locations `MAXENT.a` instead. However, to compare evaluations with evaluations of other algorithms, during evaluations of the MAXENT algorithm, presence locations `p` and background locations `a` are used (and not background locations `MAXENT.a`).

Output from the GLMNET algorithm is calculated as the mean of the output from [predict.glmnet](#). With option `GLMNET.class = TRUE`, the mean output is the mean prediction of class 1. With option `GLMNET.class = FALSE`, the mean output is the mean of the responses.

As the Mahalanobis function ([mahal](#)) does not always provide values within the range of 0 - 1, the output values are rescaled with option `MAHAL01` by first subtracting the value of `1 - MAHAL.shape` from each prediction, followed by calculating the absolute value, followed by calculating the reciprocal value and finally multiplying this reciprocal value with `MAHAL.shape`. As this rescaling method does not estimate probabilities, inclusion in the calculation of a (weighted) average of ensemble probabilities may be problematic and the PROBIT transformation may help here (the same applies to other distance-based methods).

With parameter `ENSEMBLE.best`, the subset of best models (evaluated by the individual AUC values) can be selected and only those models will be used for calculating the ensemble model (in other words, weights for models not included in the ensemble will be set to zero). It is possible to further increase the contribution to the ensemble model for models with higher AUC values through parameter `ENSEMBLE.exponent`. With `ENSEMBLE.exponent = 2`, AUC values of 0.7, 0.8 and 0.9 are converted into weights of $0.7^2=0.49$, $0.8^2=0.64$ and $0.9^2=0.81$). With `ENSEMBLE.exponent = 4`,

AUC values of 0.7, 0.8 and 0.9 are converted into weights of $0.7^4=0.2401$, $0.8^4=0.4096$ and $0.9^2=0.6561$).

ENSEMBLE.tune will result in an internal procedure whereby the best selection of parameter values for ENSEMBLE.min, ENSEMBLE.best or ENSEMBLE.exponent can be identified. Through a factorial procedure, the ensemble model with best AUC for a specific combination of parameter values is identified. The procedure also provides the weights that correspond to the best ensemble. In case that ENSEMBLE.tune is set to FALSE, then the ensemble is calculated based on the input weights.

Function ensemble.calibrate.weights splits the presence and background locations in a user-defined (k) number of subsets (i.e. k-fold cross-validation), then sequentially calibrates individual suitability models with (k-1) combined subsets and evaluates those with the remaining one subset, whereby each subset is used once for evaluation in the user-defined number (k) of runs. For example, $k = 4$ results in splitting the locations in 4 subsets, then using one of these subsets in turn for evaluations (see also [kfold](#)). Note that for the maximum entropy (MAXENT) algorithm, the same background data will be used in each cross-validation run (this is based on the assumption that a large number (~10000) of background locations are used).

Among the output from function ensemble.calibrate.weights are suggested weights for an ensemble model (output.weights and output.weights.AUC), and information on the respective AUC values of the ensemble model with the suggested weights for each of the (k) subsets. Suggested weights output.weights are calculated as the average of the weights of the different algorithms (submodels) of the k ensembles. Suggested weights output.weights.AUC are calculated as the average of the AUC of the different algorithms of the for the k runs.

Function ensemble.calibrate.models.gbm allows to test various combinations of parameters tree.complexity and learning.rate for the [gbm.step](#) model.

Function ensemble.calibrate.models.nnet allows to test various combinations of parameters size and decay for the [nnet](#) model.

Function ensemble.drop1 allows to test the effects of leaving out each of the explanatory variables, and comparing these results with the "full" model. Note that option of difference = TRUE may result in positive values, indicating that the model without the explanatory variable having larger AUC than the "full" model. A procedure is included to estimate the deviance of a model based on the fitted values, using $-2 * (\sum(x * \log(x)) + \sum((1-x) * \log(1-x)))$ where x is a vector of the fitted values for a respective model. (It was checked that this procedure results in similar deviance estimates for the null and 'full' models for glm, but note that it is not certain whether deviance can be calculated in a similar way for other submodels.)

Function ensemble.formulae provides suggestions for formulae that can be used for ensemble.calibrate.models and [ensemble.raster](#). This function is always used internally by the ensemble.drop1 function.

The ensemble.weights function is used internally by the ensemble.calibrate.models and [ensemble.raster](#) functions, using the input weights for the different suitability modelling algorithms. Ties between input weights result in the same output weights.

The ensemble.strategy function is used internally by the ensemble.calibrate.models function, using the train and test data sets with predictions of the different suitability modelling algorithms and different combinations of parameters ENSEMBLE.best, ENSEMBLE.min and ENSEMBLE.exponent. The final ensemble model is based on the parameters that generate the best AUC.

The ensemble.threshold function is used internally by the ensemble.calibrate.models, ensemble.mean and ensemble.plot functions. threshold2005.mean results in calculating the mean value of threshold methods that resulted in better results (calculated by [optimal.thresholds](#) with methods of ObsPrev, MeanProb, MaxSens+Spec, Sens=Spec and MinROCDist) in a study by Liu et al. (Ecography 28: 385-393. 2005). threshold2005.min results in calculating the mean value of threshold methods that resulted in better results (calculated by [optimal.thresholds](#) with methods of ObsPrev, MeanProb and MaxSens+Spec) in a study by Liu et al. (Ecography 28: 385-393.

2005). `threshold2013.mean` results in calculating the mean value of threshold methods that resulted in better results (calculated by `optimal.thresholds` with methods of `ObsPrev`, `MeanProb`, `MaxSens+Spec`, `Sens=Spec` and `MinROcdist`) in a study by Liu et al. (J. Biogeogr. 40: 778-789. 2013). `threshold2013.min` results in calculating the minimum value of threshold methods that resulted in better results (calculated by `optimal.thresholds` with methods of `ObsPrev`, `MeanProb`, `MaxSens+Spec`, `Sens=Spec` and `MinROcdist`) in a study by Liu et al. (J. Biogeogr. 40: 778-789. 2013).

Function `ensemble.VIF` implements a stepwise procedure whereby the explanatory variable with highest Variance Inflation Factor is removed from the list of variables. The procedure ends when no variable has VIF larger than parameter `VIF.max`.

Function `ensemble.pairs` provides a matrix of scatterplots similar to the example of `pairs` for version 3.4.3 of that package.

Value

Function `ensemble.calibrate.models` (potentially) returns a list with results from evaluations (via `evaluate`) of calibration and test runs of individual suitability models.

Function `ensemble.calibrate.weights` returns a matrix with, for each individual suitability model, the AUC of each run and the average AUC over the runs. Models are sorted by the average AUC. The average AUC for each model can be used as input weights for the `ensemble.raster` function.

Functions `ensemble.calibrate.models.gbm` and `ensemble.calibrate.models.nnet` return a matrix with, for each combination of model parameters, the AUC of each run and the average AUC. Models are sorted by the average AUC.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

- Kindt R. 2018. Ensemble species distribution modelling with transformed suitability values. *Environmental Modelling & Software* 100: 136-145. <https://doi.org/10.1016/j.envsoft.2017.11.009>
- Buisson L, Thuiller W, Casajus N, Lek S and Grenouillet G. 2010. Uncertainty in ensemble forecasting of species distribution. *Global Change Biology* 16: 1145-1157
- Liu C, Berry PM, Dawson TP and Pearson RC. 2005. Selecting thresholds of occurrence in the prediction of species distributions. *Ecography* 28: 385-393
- Liu C, White M and Newell G. 2013. Selecting thresholds for the prediction of species occurrence with presence-only data. *Journal of Biogeography* 40: 778-789

See Also

`ensemble.raster`, `ensemble.batch`

Examples

```
## Not run:
# based on examples in the dismo package

# get predictor variables
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
```

```

    pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
# subset based on Variance Inflation Factors
predictors <- subset(predictors, subset=c("bio5", "bio6",
    "bio16", "bio17", "biome"))
predictors
predictors@title <- "predictors"

# presence points
presence_file <- paste(system.file(package="dismo"), '/ex/bradypus.csv', sep='')
pres <- read.table(presence_file, header=TRUE, sep=',')[,-1]

# the kfold function randomly assigns data to groups;
# groups are used as calibration (1/4) and training (3/4) data
grouppp <- kfold(pres, 4)
pres_train <- pres[grouppp != 1, ]
pres_test <- pres[grouppp == 1, ]

# choose background points
background <- randomPoints(predictors, n=1000, extf=1.00)
colnames(background)=c('lon', 'lat')
groupa <- kfold(background, 4)
backg_train <- background[groupa != 1, ]
backg_test <- background[groupa == 1, ]

# formulae for random forest and generalized linear model
# compare with: ensemble.formulae(predictors, factors=c("biome"))

rffformula <- as.formula(pb ~ bio5+bio6+bio16+bio17)

glmformula <- as.formula(pb ~ bio5 + I(bio5^2) + I(bio5^3) +
    bio6 + I(bio6^2) + I(bio6^3) + bio16 + I(bio16^2) + I(bio16^3) +
    bio17 + I(bio17^2) + I(bio17^3) )

# fit four ensemble models (RF, GLM, BIOCLIM, DOMAIN)
ensemble.nofactors <- ensemble.calibrate.models(x=predictors, p=pres_train, a=backg_train,
    pt=pres_test, at=backg_test,
    species.name="Bradypus",
    ENSEMBLE.tune=TRUE,
    ENSEMBLE.min = 0.65,
    MAXENT=0, MAXLIKE=0, GBM=0, GBMSTEP=0, RF=1, GLM=1, GLMSTEP=0, GAM=0,
    GAMSTEP=0, MGCV=0, MGCVFIX=0, EARTH=0, RPART=0, NNET=0, FDA=0,
    SVM=0, SVME=0, GLMNET=0,
    BIOCLIM.0=0, BIOCLIM=1, DOMAIN=1, MAHAL=0, MAHAL01=0,
    Yweights="BIOMOD",
    evaluations.keep=TRUE, models.keep=TRUE,
    RF.formula=rffformula,
    GLM.formula=glmformula)

# with option models.keep, all model objects are saved in ensemble object
# the same slots can be used to replace model objects with new calibrations
ensemble.nofactors$models$RF
summary(ensemble.nofactors$models$GLM)
ensemble.nofactors$models$BIOCLIM
ensemble.nofactors$models$DOMAIN
ensemble.nofactors$models$formulae

```

```

# evaluations are kept in different slot
attributes(ensemble.nofactors$evaluations)
plot(ensemble.nofactors$evaluations$RF.T, "ROC")

# fit four ensemble models (RF, GLM, BIOCLIM, DOMAIN) using default formulae
# variable 'biome' is not included as explanatory variable
# results are provided in a file in the 'outputs' subfolder of the working
# directory
ensemble.nofactors <- ensemble.calibrate.models(x=predictors,
  p=pres_train, a=backg_train,
  pt=pres_test, at=backg_test,
  layer.drops="biome",
  species.name="Bradypus",
  ENSEMBLE.tune=TRUE,
  ENSEMBLE.min=0.65,
  SINK=TRUE,
  MAXENT=0, MAXLIKE=0, GBM=0, GBMSTEP=0, RF=1, GLM=1, GLMSTEP=0, GAM=0,
  GAMSTEP=0, MGCV=0, MGCVFIX=0, EARTH=0, RPART=0, NNET=0, FDA=0,
  SVM=0, SVME=0, GLMNET=0,
  BIOCLIM.O=0, BIOCLIM=1, DOMAIN=1, MAHAL=0, MAHAL01=0,
  Yweights="BIOMOD",
  evaluations.keep=TRUE,
  formulae.defaults=TRUE)

# after fitting the individual algorithms (submodels),
# transform predictions with a probit link.
ensemble.nofactors <- ensemble.calibrate.models(x=predictors,
  p=pres_train, a=backg_train,
  pt=pres_test, at=backg_test,
  layer.drops="biome",
  species.name="Bradypus",
  SINK=TRUE,
  ENSEMBLE.tune=TRUE,
  ENSEMBLE.min=0.65,
  MAXENT=0, MAXLIKE=0, GBM=0, GBMSTEP=0, RF=1, GLM=1, GLMSTEP=0, GAM=0,
  GAMSTEP=0, MGCV=0, MGCVFIX=0, EARTH=0, RPART=0, NNET=0, FDA=0,
  SVM=0, SVME=0, GLMNET=0,
  BIOCLIM.O=0, BIOCLIM=1, DOMAIN=1, MAHAL=0, MAHAL01=0,
  PROBIT=TRUE,
  Yweights="BIOMOD", factors="biome",
  evaluations.keep=TRUE,
  formulae.defaults=TRUE)

# Instead of providing presence and background locations, provide data.frames.
# Because 'biome' is a factor, RasterStack needs to be provided
# to check for levels in the Training and Testing data set.
TrainData1 <- prepareData(x=predictors, p=pres_train, b=backg_train,
  factors=c("biome"), xy=FALSE)
TestData1 <- prepareData(x=predictors, p=pres_test, b=backg_test,
  factors=c("biome"), xy=FALSE)
ensemble.factors1 <- ensemble.calibrate.models(x=predictors,
  TrainData=TrainData1, TestData=TestData1,
  p=pres_train, a=backg_train,
  pt=pres_test, at=backg_test,
  species.name="Bradypus",
  SINK=TRUE,
  ENSEMBLE.tune=TRUE,

```

```

ENSEMBLE.min=0.65,
MAXENT=0, MAXLIKE=1, GBM=1, GBMSTEP=0, RF=1, GLM=1, GLMSTEP=1, GAM=1,
GAMSTEP=1, MGCV=1, MGCVFIX=0, EARTH=1, RPART=1, NNET=1, FDA=1,
SVM=1, SVME=1, GLMNET=1,
BIOCLIM.O=1, BIOCLIM=1, DOMAIN=1, MAHAL=0, MAHAL01=1,
Yweights="BIOMOD", factors="biome",
evaluations.keep=TRUE)

# compare different methods of calculating ensembles
ensemble.factors2 <- ensemble.calibrate.models(x=predictors,
  TrainData=TrainData1, TestData=TestData1,
  p=pres_train, a=backg_train,
  pt=pres_test, at=backg_test,
  species.name="Bradypus",
  SINK=TRUE,
  ENSEMBLE.tune=TRUE,
  MAXENT=1, MAXLIKE=1, GBM=1, GBMSTEP=0, RF=1, GLM=1, GLMSTEP=1, GAM=1,
  GAMSTEP=1, MGCV=1, MGCVFIX=1, EARTH=1, RPART=1, NNET=1, FDA=1,
  SVM=1, SVME=1, BIOCLIM.O=1, BIOCLIM=1, DOMAIN=1, MAHAL=0, MAHAL01=1,
  ENSEMBLE.best=c(4:10), ENSEMBLE.exponent=c(1, 2, 3),
  Yweights="BIOMOD", factors="biome",
  evaluations.keep=TRUE)

# test performance of different suitability models
# data are split in 4 subsets, each used once for evaluation
ensemble.nofactors2 <- ensemble.calibrate.weights(x=predictors,
  p=pres, a=background, k=4,
  species.name="Bradypus",
  SINK=TRUE, PROBIT=TRUE,
  MAXENT=1, MAXLIKE=1, GBM=1, GBMSTEP=0, RF=1, GLM=1, GLMSTEP=1, GAM=1,
  GAMSTEP=1, MGCV=1, MGCVFIX=1, EARTH=1, RPART=1, NNET=1, FDA=1,
  SVM=1, SVME=1, BIOCLIM.O=1, BIOCLIM=1, DOMAIN=1, MAHAL=0, MAHAL01=1,
  ENSEMBLE.tune=TRUE,
  ENSEMBLE.best=0, ENSEMBLE.exponent=c(1, 2, 3),
  ENSEMBLE.min=0.7,
  Yweights="BIOMOD",
  formulae.defaults=TRUE)
ensemble.nofactors2$AUC.table

# test the result of leaving out one of the variables from the model
# note that positive differences indicate that the model without the variable
# has higher AUC than the full model
ensemble.variables <- ensemble.drop1(x=predictors,
  p=pres, a=background, k=4,
  species.name="Bradypus",
  SINK=TRUE,
  difference=TRUE,
  VIF=TRUE, PROBIT=TRUE,
  MAXENT=0, MAXLIKE=0, GBM=1, GBMSTEP=0, RF=1, GLM=1, GLMSTEP=1, GAM=1,
  GAMSTEP=1, MGCV=1, MGCVFIX=1, EARTH=1, RPART=1, NNET=1, FDA=1,
  SVM=1, SVME=1, GLMNET=1,
  BIOCLIM.O=0, BIOCLIM=0, DOMAIN=1, MAHAL=0, MAHAL01=1,
  ENSEMBLE.tune=TRUE,
  ENSEMBLE.best=0, ENSEMBLE.exponent=c(1, 2, 3),
  ENSEMBLE.min=0.7,
  Yweights="BIOMOD", factors="biome")
ensemble.variables

```

```

# use function ensemble.VIF to select a subset of variables
# factor variables are not handled well by the function
# and therefore factors are removed
# however, one can check for factors with car::vif through
# the ensemble.calibrate.models function
# VIF.analysis$var.drops can be used as input for ensemble.calibrate.models or
# ensemble.calibrate.weights

predictors <- stack(predictor.files)
predictors <- subset(predictors, subset=c("bio1", "bio5", "bio6", "bio8",
    "bio12", "bio16", "bio17", "biome"))

ensemble.pairs(predictors)

VIF.analysis <- ensemble.VIF(predictors, factors="biome")
VIF.analysis
# alternative solution where bio1 and bio12 are kept
VIF.analysis <- ensemble.VIF(predictors, factors="biome",
    keep=c("bio1", "bio12"))
VIF.analysis

## End(Not run)

```

ensemble.dummy.variables

*Suitability mapping based on ensembles of modelling algorithms:
handling of categorical data*

Description

The basic function `ensemble.dummy.variables` creates new raster layers representing dummy variables (coded 0 or 1) for all or the most frequent levels of a categorical variable. Sometimes the creation of dummy variables is needed for proper handling of categorical data for some of the suitability modelling algorithms.

Usage

```

ensemble.dummy.variables(xcat = NULL,
    freq.min = 50, most.frequent = 5,
    new.levels = NULL, overwrite = TRUE, ...)

ensemble.accepted.categories(xcat = NULL, categories = NULL,
    filename = NULL, overwrite = TRUE, ...)

ensemble.simplified.categories(xcat = NULL, p = NULL,
    filename = NULL, overwrite = TRUE, ...)

```

Arguments

<code>xcat</code>	RasterLayer object (raster) containing values for a categorical explanatory variable.
-------------------	---

freq.min	Minimum frequency for a dummy raster layer to be created for the corresponding factor level. See also freq .
most.frequent	Number of dummy raster layers to be created (if larger than 0), corresponding to the same number of most frequent factor levels See also freq .
new.levels	character vector giving factor levels that are not encountered in xcat and for which dummy layers should be created (this could be useful in dealing with novel conditions)
overwrite	overwrite an existing file name with the same name (if TRUE). See also writeRaster .
...	additional arguments for writeRaster or (for ensemble.dummy.variables, writeRaster).
categories	numeric vector providing the accepted levels of a categorical raster layer; expected to correspond to the levels encountered during calibration
filename	name for the output file. See also writeRaster .
p	presence points that will be used for calibrating the suitability models, typically available in 2-column (x, y) or (lon, lat) dataframe; see also prepareData and extract

Details

The basic function `ensemble.dummy.variables` creates dummy variables from a `RasterLayer` object (see [raster](#)) that represents a categorical variable. With `freq.min` and `most.frequent` it is possible to limit the number of dummy variables that will be created. For example, `most.frequent = 5` results in five dummy variables to be created.

Function `ensemble.accepted.categories` modifies the `RasterLayer` object (see [raster](#)) by replacing cell values for categories (levels) that are not accepted with missing values.

Function `ensemble.simplified.categories` modifies the `RasterLayer` object (see [raster](#)) by replacing cell values for categories (levels) where none of the presence points occur with the same level. This new level is coded by the maximum coding level for these 'outside categories'.

Value

The basic function `ensemble.dummy.variables` mainly results in the creation of raster layers that correspond to dummy variables.

Author(s)

Roeland Kindt (World Agroforestry Centre) and Evert Thomas (Bioversity International)

See Also

[ensemble.calibrate.models](#), [ensemble.raster](#)

Examples

```
## Not run:

# get predictor variables
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
  pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
```

```

biome.layer <- predictors[["biome"]]
biome.layer

# create dummy layers for the 5 most frequent factor levels

ensemble.dummy.variables(xcat=biome.layer, most.frequent=5,
  overwrite=TRUE)

# check whether dummy variables were created
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
  pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
predictors
names(predictors)

# once dummy variables were created, avoid using the original categorical data layer
predictors <- subset(predictors, subset=c("bio5", "bio6", "bio16", "bio17",
  "biome_1", "biome_2", "biome_7", "biome_8", "biome_13"))
predictors
predictors@title <- "base"

# presence points
presence_file <- paste(system.file(package="dismo"), '/ex/bradypus.csv', sep='')
pres <- read.table(presence_file, header=TRUE, sep=',')[,-1]

# the kfold function randomly assigns data to groups;
# groups are used as calibration (1/5) and training (4/5) data
grouppp <- kfold(pres, 5)
pres_train <- pres[grouppp != 1, ]
pres_test <- pres[grouppp == 1, ]

# choose background points
background <- randomPoints(predictors, n=1000, extf=1.00)
colnames(background)=c('lon', 'lat')
groupa <- kfold(background, 5)
backg_train <- background[groupa != 1, ]
backg_test <- background[groupa == 1, ]

# note that dummy variables with no variation are not used by DOMAIN
# note that dummy variables are not used by MAHAL and MAHAL01
# (neither are categorical variables)
ensemble.nofactors <- ensemble.calibrate.models(x=predictors, p=pres_train, a=backg_train,
  pt=pres_test, at=backg_test,
  species.name="Bradypus",
  VIF=T,
  MAXENT=1, MAXLIKE=1, GBM=1, GBMSTEP=0, RF=1, GLM=1, GLMSTEP=0, GAM=1,
  GAMSTEP=0, MGCV=1, MGCVFIX=0, EARTH=1, RPART=1, NNET=1, FDA=1,
  SVM=1, SVME=1, BIOCLIM.0=1, BIOCLIM=1, DOMAIN=1, MAHAL=0, MAHAL01=1,
  Yweights="BIOMOD",
  dummy.vars=c("biome_1", "biome_2", "biome_7", "biome_8", "biome_13"),
  PLOTS=FALSE, evaluations.keep=TRUE)

## End(Not run)

```

ensemble.ecocrop	<i>Mapping of novel environmental conditions (areas where some of the environmental conditions are outside the range of environmental conditions of a reference area).</i>
------------------	--

Description

Function `ensemble.novel` creates the map with novel conditions. Function `ensemble.novel.object` provides the reference values used by the prediction function used by [predict](#).

Usage

```
ensemble.ecocrop(x = NULL, ecocrop.object = NULL,
  RASTER.object.name = ecocrop.object$name, RASTER.stack.name = x$title,
  RASTER.format = "raster", RASTER.datatype = "INT2S", RASTER.NAflag = -32767,
  KML.out = TRUE, KML.blur = 10, KML.maxpixels = 100000,
  CATCH.OFF = FALSE)

ensemble.ecocrop.object(temp.thresholds, rain.thresholds, name = "crop01",
  temp.multiply = 10, annual.temps = TRUE, transform = 1)
```

Arguments

x	RasterStack object (stack) containing all environmental layers for which suitability should be calculated.
ecocrop.object	Object listing optimal and absolute minima and maxima for the rainfall and temperature values, used by the prediction function that is used internally by predict . This object is created with ensemble.ecocrop.object .
RASTER.object.name	First part of the names of the raster file that will be generated, expected to identify the species or crop for which ranges were calculated
RASTER.stack.name	Last part of the names of the raster file that will be generated, expected to identify the predictor stack used
RASTER.format	Format of the raster files that will be generated. See writeFormats and writeRaster .
RASTER.datatype	Format of the raster files that will be generated. See dataType and writeRaster .
RASTER.NAflag	Value that is used to store missing data. See writeRaster .
KML.out	If TRUE, then kml files will be saved in a subfolder 'kml/zones'.
KML.maxpixels	Maximum number of pixels for the PNG image that will be displayed in Google Earth. See also KML .
KML.blur	Integer that results in increasing the size of the PNG image by $KML.blur^2$, which may help avoid blurring of isolated pixels. See also KML .
CATCH.OFF	Disable calls to function tryCatch .
temp.thresholds	Optimal and absolute thresholds for temperatures. These will be sorted as: absolute minimum temperature, optimal minimum temperature, optimal maximum temperature and absolute maximum temperature.

rain.thresholds	Optimal and absolute thresholds for annual rainfall. These will be sorted as: absolute minimum rainfall, optimal minimum rainfall, optimal maximum rainfall and absolute maximum rainfall.
name	Name of the object, expect to expected to identify the species or crop
temp.multiply	Multiplier for temperature values. Default of 10 is to be used with raster layers where temperature was multiplied by 10 such as Worldclim or AFRICLIM.
annual.temps	If TRUE then temperature limits are assumed to apply to mean annual temperature (bioclimatic variable bio1). If FALSE then minimum temperature limits are assumed to apply to the temperature of the coldest month (bioclimatic variable bio6) and maximum temperature limits are assumed to apply to the temperature of the hottest month (bioclimatic variable bio5). See also biovars .
transform	Exponent used to transform probability values obtained from interpolating between optimal and absolute limits. Exponent of 2 results in squaring probabilities, for example input probabilities of 0.5 transformed to $0.5^2 = 0.25$.

Details

Function `ensemble.ecocrop` maps suitability for a species or crop based on optimal and absolute temperature and rainfall limits. Where both temperature and rainfall are within the optimal limits, suitability of 1000 is calculated. Where both temperature and rainfall are outside the absolute limits, suitability of 0 is calculated. In situations where temperature or rainfall is in between the optimal and absolute limits, then suitability is interpolated between 0 and 1000, and the lowest suitability from temperature and rainfall is calculated. Setting very wide rainfall limits will simulate the effect of irrigation, i.e. where suitability only depends on temperature limits.

For a large range of crop and plant species, optimal and absolute limits are available from the FAO ecocrop database (<http://ecocrop.fao.org/ecocrop>), hence the name of the function. A different implementation of suitability mapping based on ecocrop limits is available from [ecocrop](#). Ecocrop thresholds for several species are available from: [getCrop](#)

Value

Function `ensemble.ecocrop.object` returns a list with following objects:

name	name for the crop or species
temp.thresholds	optimal and absolute minimum and maximum temperature limits
rain.thresholds	optimal and absolute minimum and maximum annual rainfall limits
annual.temps	logical indicating whether temperature limits apply to annual temperatures
transform	exponent to transform suitability values

Author(s)

Roeland Kindt (World Agroforestry Centre)

See Also

[biovars](#)

Examples

```
## Not run:
#test with Brazil nut (limits from FAO ecocrop)
#temperature: (12) 20-36 (40)
#annual rainfall: (1400) 2400-2800 (3500)

# get predictor variables
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
  pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
# subset based on Variance Inflation Factors
predictors <- subset(predictors, subset=c("bio5", "bio6", "bio12"))
predictors
predictors@title <- "base"

Brazil.ecocrop <- ensemble.ecocrop.object(temp.thresholds=c(20, 36, 12, 40),
  rain.thresholds=c(2400, 2800, 1400, 3500),
  annual.temps=FALSE, name="Bertholletia_excelsa")
Brazil.ecocrop
ensemble.ecocrop(predictors, ecocrop.object=Brazil.ecocrop)

dev.new()
par.old <- graphics::par(no.readonly=T)
graphics::par(mfrow=c(1,2))

rasterfull1 <- paste("ensembles//ecocrop//Bertholletia_excelsa_base.grd", sep="")
rasterfull1 <- raster(rasterfull1)
# raster file saved probabilities as integer values between 0 and 1000
rasterfull1 <- rasterfull1/1000
raster::plot(rasterfull1, main="Ecocrop suitability")

GBIFloc <- gbif(genus="Bertholletia", species="excelsa", geo=TRUE)
GBIFpres <- cbind(GBIFloc$lon, GBIFloc$lat)
GBIFpres <- GBIFpres[complete.cases(GBIFpres), ]
GBIFpres <- GBIFpres[duplicated(GBIFpres) == FALSE, ]
point.suitability <- extract(rasterfull1, y=GBIFpres)
point.suitability[is.na(point.suitability)] <- -1

GBIFpres.optimal <- GBIFpres[point.suitability == 1, ]
GBIFpres.suboptimal <- GBIFpres[point.suitability < 1 & point.suitability > 0, ]
GBIFpres.not <- GBIFpres[point.suitability == 0, ]

raster::plot(rasterfull1, main="GBIF locations",
  sub="blue: optimal, cyan: suboptimal, red: not suitable")
bg.legend <- c("blue", "cyan", "red")

points(GBIFpres.suboptimal, pch=21, cex=1.2, bg=bg.legend[2])
points(GBIFpres.optimal, pch=21, cex=1.2, bg=bg.legend[1])
points(GBIFpres.not, pch=21, cex=1.2, bg=bg.legend[3])

graphics::par(par.old)

## End(Not run)
```

ensemble.novel	<i>Mapping of novel environmental conditions (areas where some of the environmental conditions are outside the range of environmental conditions of a reference area).</i>
----------------	--

Description

Function `ensemble.novel` creates the map with novel conditions. Function `ensemble.novel.object` provides the reference values used by the prediction function used by `predict`.

Usage

```
ensemble.novel(x = NULL, novel.object = NULL,
  RASTER.object.name = novel.object$name, RASTER.stack.name = x$title,
  RASTER.format = "raster", RASTER.datatype = "INT1S", RASTER.NAflag = -127,
  KML.out = FALSE, KML.maxpixels = 100000, KML.blur = 10,
  CATCH.OFF = FALSE)

ensemble.novel.object(x = NULL, name = "reference1", mask.raster = NULL,
  quantiles = FALSE, probs = c(0.05, 0.95), factors = NULL)
```

Arguments

x	RasterStack object (stack) containing all environmental layers for which novel conditions should be calculated. With ensemble.novel.object , x can also be a data.frame.
novel.object	Object listing minima and maxima for the environmental layers, used by the prediction function that is used internally by predict . This object is created with ensemble.novel.object .
RASTER.object.name	First part of the names of the raster file that will be generated, expected to identify the area and time period for which ranges were calculated
RASTER.stack.name	Last part of the names of the raster file that will be generated, expected to identify the predictor stack used
RASTER.format	Format of the raster files that will be generated. See writeFormats and writeRaster .
RASTER.datatype	Format of the raster files that will be generated. See dataType and writeRaster .
RASTER.NAflag	Value that is used to store missing data. See writeRaster .
KML.out	If TRUE, then kml files will be saved in a subfolder 'kml/zones'.
KML.maxpixels	Maximum number of pixels for the PNG image that will be displayed in Google Earth. See also KML .
KML.blur	Integer that results in increasing the size of the PNG image by $KML.blur^2$, which may help avoid blurring of isolated pixels. See also KML .
CATCH.OFF	Disable calls to function tryCatch .

name	Name of the object, expect to expected to identify the area and time period for which ranges were calculated and where no novel conditions will be detected
mask.raster	RasterLayer object (raster) that can be used to select the area for which reference values are obtained (see mask)
quantiles	If TRUE, then replace minima and maxima with quantile values. See also quantile and quantile)
probs	Numeric vector of probabilities [0, 1] as used by quantile and quantile)
factors	vector that indicates which variables are factors; these variables will be ignored for novel conditions

Details

Function `ensemble.novel` maps zones (coded '1') that are novel (outside the minimum-maximum range) relative to the range provided by function `ensemble.novel.object`. Values that are not novel (inside the range of minimum-maximum values) are coded '0'. In theory, the maps show the same areas that have negative Multivariate Environmental Similarity Surface (MESS) values ([mess](#))

Value

Function `ensemble.novel.object` returns a list with following objects:

minima	minima of the reference environmental conditions
maxima	maxima of the reference environmental conditions
name	name for the reference area and time period

Author(s)

Roeland Kindt (World Agroforestry Centre)

See Also

[ensemble.raster](#), [ensemble.bioclim](#) and [ensemble.bioclim.graph](#)

Examples

```
## Not run:
# get predictor variables
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
  pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
predictors <- subset(predictors, subset=c("bio1", "bio5", "bio6", "bio7", "bio8",
  "bio12", "bio16", "bio17"))
predictors
predictors$title <- "base"

# reference area to calculate environmental ranges
ext <- extent(-70, -50, -10, 10)
extent.values2 <- c(-70, -50, -10, 10)
predictors.current <- crop(predictors, y=ext)
predictors.current <- stack(predictors.current)
```

```

novel.test <- ensemble.novel.object(predictors.current, name="noveltest")
novel.test
novel.raster <- ensemble.novel(x=predictors, novel.object=novel.test, KML.out=T)
novel.raster

plot(novel.raster)
# no novel conditions within reference area
rect(extent.values2[1], extent.values2[3], extent.values2[2], extent.values2[4])

# use novel conditions as a simple species suitability mapping method
# presence points
presence_file <- paste(system.file(package="dismo"), '/ex/bradypus.csv', sep='')
pres <- read.table(presence_file, header=TRUE, sep=',')[,-1]
pres.data <- data.frame(extract(predictors, y=pres))

# ranges and maps
Bradypus.ranges1 <- ensemble.novel.object(pres.data, name="Bradypus", quantiles=F)
Bradypus.ranges1
Bradypus.novel1 <- ensemble.novel(x=predictors, novel.object=Bradypus.ranges1, KML.out=T)
Bradypus.novel1

par.old <- graphics::par(no.readonly=T)
graphics::par(mfrow=c(1,2))

# suitable where there are no novel conditions
raster::plot(Bradypus.novel1, breaks=c(-0.1, 0, 1), col=c("green", "grey"),
  main="Suitability mapping using minimum to maximum range")
points(pres[, 2] ~ pres[, 1], pch=1, col="red", cex=0.8)

# use 90 percent intervals similar to BIOCLIM methodology
Bradypus.ranges2 <- ensemble.novel.object(pres.data, name="BradypusQuantiles", quantiles=T)
Bradypus.ranges2
Bradypus.novel2 <- ensemble.novel(x=predictors, novel.object=Bradypus.ranges2, KML.out=T)
Bradypus.novel2
raster::plot(Bradypus.novel2, breaks=c(-0.1, 0, 1), col=c("green", "grey"),
  main="Suitability mapping using quantile range")
points(pres[, 2] ~ pres[, 1], pch=1, col="red", cex=0.8)

graphics::par(par.old)

# deal with novel factor levels through dummy variables
predictors <- stack(predictor.files)
biome.layer <- predictors[["biome"]]
biome.layer
ensemble.dummy.variables(xcat=biome.layer, most.frequent=0, freq.min=1,
  overwrite=TRUE)

predictors.dummy <- stack(predictor.files)
predictors.dummy <- subset(predictors.dummy, subset=c("biome_1", "biome_2", "biome_3",
  "biome_4", "biome_5", "biome_7", "biome_8", "biome_9",
  "biome_10", "biome_12", "biome_13", "biome_14"))
predictors.dummy
predictors.dummy@title <- "base_dummy"

predictors.dummy.current <- crop(predictors.dummy, y=ext)
predictors.dummy.current <- stack(predictors.dummy.current)

```

```

novel.levels <- ensemble.novel.object(predictors.dummy.current, name="novellevels")
novel.levels
novel.levels.raster <- ensemble.novel(x=predictors.dummy, novel.object=novel.levels,
  KML.out=T)
novel.levels.raster

novel.levels.quantiles <- ensemble.novel.object(predictors.dummy.current, quantiles=TRUE,
  name="novellevels_quantiles")
novel.levels.quantiles
novel.levels.quantiles.raster <- ensemble.novel(x=predictors.dummy,
  novel.object=novel.levels.quantiles, KML.out=T)
novel.levels.quantiles.raster

# difference in ranges for variables with low frequencies
background <- dismo::randomPoints(predictors.dummy.current, n=10000, p=NULL, excludep=F)
extract.data <- extract(predictors.dummy.current, y=background)
colSums(extract.data)/sum(extract.data)*100
novel.levels
novel.levels.quantiles

par.old <- graphics::par(no.readonly=T)
graphics::par(mfrow=c(1,2))
raster::plot(novel.levels.raster, breaks=c(-0.1, 0, 1), col=c("grey", "green"),
  main="novel outside minimum to maximum range")
rect(extent.values2[1], extent.values2[3], extent.values2[2], extent.values2[4])
raster::plot(novel.levels.quantiles.raster, breaks=c(-0.1, 0, 1), col=c("grey", "green"),
  main="novel outside quantile range")
rect(extent.values2[1], extent.values2[3], extent.values2[2], extent.values2[4])
graphics::par(par.old)

## End(Not run)

```

ensemble.raster

Suitability mapping based on ensembles of modelling algorithms: consensus mapping

Description

The basic function `ensemble.raster` creates two consensus raster layers, one based on a (weighted) average of different suitability modelling algorithms, and a second one documenting the number of modelling algorithms that predict presence of the focal organisms. Modelling algorithms include maximum entropy (MAXENT), boosted regression trees, random forests, generalized linear models (including stepwise selection of explanatory variables), generalized additive models (including stepwise selection of explanatory variables), multivariate adaptive regression splines, regression trees, artificial neural networks, flexible discriminant analysis, support vector machines, the BIOCLIM algorithm, the DOMAIN algorithm and the Mahalanobis algorithm. These sets of functions were developed in parallel with the `biomod2` package, especially for inclusion of the maximum entropy algorithm, but also to allow for a more direct integration with the `BiodiversityR` package, more direct handling of model formulae and greater focus on mapping. Researchers and students of species distribution are strongly encouraged to familiarize themselves with all the options of the `biomod2` and `dismo` packages.

Usage

```
ensemble.raster(xn = NULL,
  models.list = NULL,
  input.weights = models.list$output.weights,
  thresholds = models.list$thresholds,
  RASTER.species.name = models.list$species.name,
  RASTER.stack.name = xn@title,
  RASTER.format = "raster", RASTER.datatype = "INT2S", RASTER.NAflag = -32767,
  RASTER.models.overwrite = TRUE,
  KML.out = FALSE, KML.maxpixels = 100000, KML.blur = 10,
  evaluate = FALSE, SINK = FALSE,
  p = models.list$p, a = models.list$a,
  pt = models.list$pt, at = models.list$at,
  CATCH.OFF = FALSE)

ensemble.habitat.change(base.map = file.choose(),
  other.maps = utils::choose.files(),
  change.folder = "ensembles/change",
  RASTER.format = "raster", RASTER.datatype = "INT1U", RASTER.NAflag = 255,
  KML.out = FALSE, KML.folder = "kml/change",
  KML.maxpixels = 100000, KML.blur = 10)

ensemble.area(x=NULL, km2=TRUE)
```

Arguments

xn	RasterStack object (stack) containing all layers that correspond to explanatory variables of an ensemble calibrated earlier with ensemble.calibrate.models . See also predict .
models.list	list with 'old' model objects such as MAXENT or RF.
input.weights	array with numeric values for the different modelling algorithms; if NULL then values provided by parameters such as MAXENT and GBM will be used. As an alternative, the output from ensemble.calibrate.weights can be used.
thresholds	array with the threshold values separating predicted presence for each of the algorithms.
RASTER.species.name	First part of the names of the raster files that will be generated, expected to identify the modelled species (or organism).
RASTER.stack.name	Last part of the names of the raster files that will be generated, expected to identify the predictor stack used.
RASTER.format	Format of the raster files that will be generated. See writeFormats and writeRaster .
RASTER.datatype	Format of the raster files that will be generated. See dataType and writeRaster .
RASTER.NAflag	Value that is used to store missing data. See writeRaster .
RASTER.models.overwrite	Overwrite the raster files that correspond to each suitability modelling algorithm (if TRUE). (Overwriting actually implies that raster files are created or overwritten that start with "working_").

KML.out	if FALSE, then no kml layers (layers that can be shown in Google Earth) are produced. If TRUE, then kml files will be saved in a subfolder 'kml'.
KML.maxpixels	Maximum number of pixels for the PNG image that will be displayed in Google Earth. See also KML .
KML.blur	Integer that results in increasing the size of the PNG image by KML.blur^2 , which may help avoid blurring of isolated pixels. See also KML .
evaluate	if TRUE, then evaluate the created raster layers at locations p, a, pt and at (if provided). See also evaluate
SINK	Append the results to a text file in subfolder 'outputs' (if TRUE). The name of file is based on argument RASTER.species.name. In case the file already exists, then results are appended. See also sink .
p	presence points used for calibrating the suitability models, typically available in 2-column (x, y) or (lon, lat) dataframe; see also prepareData and extract
a	background points used for calibrating the suitability models, typically available in 2-column (x, y) or (lon, lat) dataframe; see also prepareData and extract
pt	presence points used for evaluating the suitability models, typically available in 2-column (lon, lat) dataframe; see also prepareData
at	background points used for calibrating the suitability models, typically available in 2-column (lon, lat) dataframe; see also prepareData and extract
CATCH.OFF	Disable calls to function tryCatch .
base.map	filename with baseline map used to produce maps that show changes in suitable habitat
other.maps	files with other maps used to produce maps that show changes in suitable habitat from a defined base.map
change.folder	folder where new maps documenting changes in suitable habitat will be stored. NOTE: please ensure that the base folder (eg: ../ensembles) exists already.
KML.folder	folder where new maps (in Google Earth format) documenting changes in suitable habitat will be stored. NOTE: please ensure that the base folder (eg: ../kml) exists already.
x	RasterLayer object (raster) in a longitude-latitude coordinate system
km2	Provide results in square km rather than square m. See also areaPolygon

Details

The basic function `ensemble.raster` fits individual suitability models for all models with positive input weights. In subfolder "models" of the working directory, suitability maps for the individual suitability modelling algorithms are stored. In subfolder "ensembles", a consensus suitability map based on a weighted average of individual suitability models is stored. In subfolder "ensembles/presence", a presence-absence (1-0) map will be provided. In subfolder "ensembles/count", a consensus suitability map based on the number of individual suitability models that predict presence of the focal organism is stored.

Several of the features of `ensemble.raster` are also available from [ensemble.calibrate.models](#). The main difference between the two functions is that `ensemble.raster` generates raster layers for individual suitability models, whereas the purpose of [ensemble.calibrate.models](#) is specifically to test different suitability modelling algorithms.

Note that values in suitability maps are integer values that were calculated by multiplying probabilities by 1000 (see also [trunc](#)).

As the Mahalanobis function ([mahal](#)) does not always provide values within a range of 0 - 1, the output values are rescaled by first subtracting the value of `1 - MAHAL.shape` from each prediction, followed by calculating the absolute value, followed by calculating the reciprocal value and finally multiplying this reciprocal value with `MAHAL.shape`. As this rescaling method does not estimate probabilities, inclusion in the calculation of a (weighted) average of ensemble probabilities may be problematic (the same applies to other distance-based methods).

The `ensemble.habitat.change` function produces new raster layers that show changes in suitable and not suitable habitat between a base raster and a list of other rasters. The output uses the following coding: 0 = areas that remain unsuitable, 11 = areas that remain suitable, 10 = areas of lost habitat, 1 = areas of new habitat. (Codes are inspired on a binary classification of habitat suitability in base [1- or 0-] and other layer [-1 or -0], eg new habitat is coded 01 = 1).

With `KML.out = TRUE`, kml files are created in a subfolder named "KML". The colouring of the consensus suitability PNG is based on 20 intervals of size 50 between 0 and 1000. The colouring of the presence-absence PNG uses green for presence and red for absence. The colouring of the count suitability PNG uses black for zero (no models predict presence) and blue for the theoretical maximum number of models to predict presence (i.e. the count of all final weights), whereas intermediate numbers (1 to theoretical maximum - 1) are ranged from red to green. The colouring of the habitat change maps are: black (cells that are never suitable [value: 0]), green (cells that are always suitable [value: 11]), red (cells that are lost habitat [value: 10]) and blue (cells that are new habitat [value: 1]).

The `ensemble.area` function calculates the area of different categories with [areaPolygon](#)

Value

The basic function `ensemble.raster` mainly results in the creation of raster layers that correspond to fitted probabilities of presence of individual suitability models (in folder "models") and consensus models (in folder "ensembles"), and the number of suitability models that predict presence (in folder "ensembles"). Prediction of presence is based on a threshold usually defined by maximizing the sum of the true presence and true absence rates (see `threshold.method` and also [ModelEvaluation](#)).

If desired by the user, the `ensemble.raster` function also saves details of fitted suitability models or data that can be plotted with the [evaluation.strip.plot](#) function.

Author(s)

Roeland Kindt (World Agroforestry Centre), Eike Luedeling (World Agroforestry Centre) and Evert Thomas (Bioversity International)

References

Kindt R. 2018. Ensemble species distribution modelling with transformed suitability values. *Environmental Modelling & Software* 100: 136-145. <https://doi.org/10.1016/j.envsoft.2017.11.009> Buisson L, Thuiller W, Casajus N, Lek S and Grenouillet G. 2010. Uncertainty in ensemble forecasting of species distribution. *Global Change Biology* 16: 1145-1157

See Also

[evaluation.strip.plot](#), [ensemble.calibrate.models](#), [ensemble.calibrate.weights](#), [ensemble.batch](#)

Examples

```
## Not run:
# based on examples in the dismo package
```

```

# get predictor variables
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
  pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
# subset based on Variance Inflation Factors
predictors <- subset(predictors, subset=c("bio5", "bio6",
  "bio16", "bio17"))
predictors
predictors$title <- "base"

# presence points
# presence points
presence_file <- paste(system.file(package="dismo"), '/ex/bradypus.csv', sep='')
pres <- read.table(presence_file, header=TRUE, sep=',')[,-1]

# choose background points
background <- randomPoints(predictors, n=1000, extf = 1.00)

# if desired, change working directory where subfolders of "models" and
# "ensembles" will be created
# raster layers will be saved in subfolders of /models and /ensembles:
getwd()

# first calibrate the ensemble
# calibration is done in two steps
# in step 1, a k-fold procedure is used to determine the weights
# in step 2, models are calibrated for all presence and background locations
# factor is not used as it is not certain whether correct levels will be used
# it may therefore be better to use dummy variables

# step 1: determine weights through 4-fold cross-validation
ensemble.calibrate.step1 <- ensemble.calibrate.weights(
  x=predictors, p=pres, a=background, k=4,
  SINK=TRUE, species.name="Bradypus",
  MAXENT=1, MAXLIKE=0, GBM=1, GBMSTEP=0, RF=0, GLM=1, GLMSTEP=0,
  GAM=1, GAMSTEP=0, MGCV=1, MGCVFIX=0,
  EARTH=1, RPART=1, NNET=1, FDA=1, SVM=1, SVME=1, GLMNET=1,
  BIOCLIM.O=0, BIOCLIM=1, DOMAIN=1, MAHAL=0, MAHAL01=1,
  ENSEMBLE.tune=TRUE, PROBIT=TRUE,
  ENSEMBLE.best=0, ENSEMBLE.exponent=c(1, 2, 3),
  ENSEMBLE.min=c(0.65, 0.7),
  Yweights="BIOMOD",
  PLOTS=FALSE, formulae.defaults=TRUE)

# step 1 generated the weights for each algorithm
model.weights <- ensemble.calibrate.step1$output.weights
x.batch <- ensemble.calibrate.step1$x
p.batch <- ensemble.calibrate.step1$p
a.batch <- ensemble.calibrate.step1$a
MAXENT.a.batch <- ensemble.calibrate.step1$MAXENT.a
factors.batch <- ensemble.calibrate.step1$factors
dummy.vars.batch <- ensemble.calibrate.step1$dummy.vars

# step 2: calibrate models with all available presence locations
# weights determined in step 1 calculate ensemble in step 2
ensemble.calibrate.step2 <- ensemble.calibrate.models(

```

```

x=x.batch, p=p.batch, a=a.batch, MAXENT.a=MAXENT.a.batch,
factors=factors.batch, dummy.vars=dummy.vars.batch,
SINK=TRUE, species.name="Bradypus",
models.keep=TRUE,
input.weights=model.weights,
ENSEMBLE.tune=FALSE, PROBIT=TRUE,
Yweights="BIOMOD",
PLOTS=FALSE, formulae.defaults=TRUE)

# step 3: use previously calibrated models to create ensemble raster layers
# re-evaluate the created maps at presence and background locations
# (note that re-evaluation will be different due to truncation of raster layers
# as they were saved as integer values ranged 0 to 1000)
ensemble.raster.results <- ensemble.raster(xn=predictors,
  models.list=ensemble.calibrate.step2$models,
  input.weights=model.weights,
  SINK=TRUE, evaluate=TRUE,
  RASTER.species.name="Bradypus", RASTER.stack.name="base")

# use the base map to check for changes in suitable habitat
# this type of analysis is typically done with different predictor layers
# (for example, predictor layers representing different possible future climates)
# In this example, changes from a previous model (ensemble.raster.results)
# are contrasted with a newly calibrated model (ensemble.raster.results2)
# step 1: 4-fold cross-validation
ensemble.calibrate2.step1 <- ensemble.calibrate.weights(
  x=x.batch, p=p.batch, a=a.batch, MAXENT.a=MAXENT.a.batch,
  factors=factors.batch, dummy.vars=dummy.vars.batch,
  k=4,
  SINK=TRUE, species.name="Bradypus",
  MAXENT=1, MAXLIKE=0, GBM=1, GBMSTEP=0, RF=0, GLM=1, GLMSTEP=0,
  GAM=1, GAMSTEP=0, MGCV=1, MGCVFIX=0,
  EARTH=1, RPART=1, NNET=1, FDA=1, SVM=1, SVME=1, GLMNET=1,
  BIOCLIM.0=0, BIOCLIM=1, DOMAIN=1, MAHAL=0, MAHAL01=1,
  ENSEMBLE.tune=TRUE, PROBIT=TRUE,
  ENSEMBLE.best=0, ENSEMBLE.exponent=c(1, 2, 3),
  ENSEMBLE.min=c(0.65, 0.7),
  Yweights="BIOMOD",
  PLOTS=FALSE, formulae.defaults=TRUE)

model.weights2 <- ensemble.calibrate2.step1$output.weights

ensemble.calibrate2.step2 <- ensemble.calibrate.models(
  x=x.batch, p=p.batch, a=a.batch, MAXENT.a=MAXENT.a.batch,
  factors=factors.batch, dummy.vars=dummy.vars.batch,
  SINK=TRUE, species.name="Bradypus",
  models.keep=TRUE,
  input.weights=model.weights2,
  ENSEMBLE.tune=FALSE, PROBIT=TRUE,
  Yweights="BIOMOD",
  PLOTS=FALSE, formulae.defaults=TRUE)

ensemble.raster.results2 <- ensemble.raster(
  xn=predictors,
  models.list=ensemble.calibrate2.step2$models,
  input.weights=model.weights2,
  SINK=TRUE, evaluate=TRUE,

```

```

RASTER.species.name="Bradypus", RASTER.stack.name="recalibrated")

base.file <- paste(getwd(), "/ensembles/presence/Bradypus_base.grd", sep="")
other.file <- paste(getwd(), "/ensembles/presence/Bradypus_recalibrated.grd", sep="")

changed.habitat <- ensemble.habitat.change(base.map=base.file,
  other.maps=c(other.file),
  change.folder="ensembles/change")

change.file <- paste(getwd(), "/ensembles/change/Bradypus_recalibrated_presence.grd", sep="")

par.old <- graphics::par(no.readonly=T)
dev.new()
par(mfrow=c(2,2))
raster::plot(raster(base.file), breaks=c(-1, 0, 1), col=c("grey", "green"),
  legend.shrink=0.8, main="base presence")
raster::plot(raster(other.file), breaks=c(-1, 0, 1), col=c("grey", "green"),
  legend.shrink=0.8, main="other presence")
raster::plot(raster(change.file), breaks=c(-1, 0, 1, 10, 11),
  col=c("grey", "blue", "red", "green"),
  legend.shrink=0.8, main="habitat change", sub="11 remaining, 10 lost, 1 new")
graphics::par(par.old)

areas <- ensemble.area(raster(change.file))
areas

## End(Not run)

```

ensemble.red	<i>Area of Occupancy (AOO) and Extent of Occurrence (EOO) via the red library.</i>
--------------	---

Description

Function `ensemble.red` is a wrapper function for estimation of AOO and EOO computed for redlisting of species based on IUCN criteria (http://www.iucnredlist.org/static/categories_criteria_3_1). Function `ensemble.chull.create` creates a mask layer based on a convex hull around known presence locations, inspired by `mcp` argument of the `map.sdm` function.

Usage

```

ensemble.red(x)

ensemble.chull.create(x.pres = NULL, p = NULL, buffer.width = 0.2,
  RASTER.format = "raster", RASTER.datatype = "INT1U", RASTER.NAflag = 255,
  overwrite = TRUE, ...)

ensemble.chull.apply(x.spec = NULL, mask.layer=NULL, keep.old=T,
  RASTER.format="raster", RASTER.datatype="INT1U", RASTER.NAflag=255,
  overwrite=TRUE, ...)

```

Arguments

<code>x</code>	RasterLayer object (raster), representing 'count' suitability layers (available from the 'count' and 'consensuscount' subdirectories of the 'ensembles' directory)
<code>x.pres</code>	RasterLayer object (raster), representing 'presence' suitability layers (available from the 'presence' and 'consensuspresence' subdirectories of the 'ensembles' directory)
<code>p</code>	known presence locations, available in 2-column (lon, lat) dataframe; see also prepareData and extract
<code>buffer.width</code>	multiplier to create buffer (via gBuffer) by multiplying the maximum distance among the presence locations (calculated via pointDistance)
<code>RASTER.format</code>	Format of the raster files that will be generated. See writeFormats and writeRaster .
<code>RASTER.datatype</code>	Format of the raster files that will be generated. See dataType and writeRaster .
<code>RASTER.NAflag</code>	Value that is used to store missing data. See writeRaster .
<code>overwrite</code>	Overwrite existing raster files. See writeRaster .
<code>...</code>	Additional arguments for writeRaster .
<code>x.spec</code>	RasterLayer object (raster), representing any suitability layer for the species under investigation)
<code>mask.layer</code>	RasterLayer object (raster), representing the mask based on the convex hull around known presence locations. The function will replace all values in <code>x.spec</code> to zero where corresponding values in the <code>mask.layer</code> are zero.
<code>keep.old</code>	keep a copy of the RasterLayer before the mask is applied.

Details

Function `ensemble.red` calculates AOO ([aoo](#)) and EOO ([aoo](#)) statistics calculated for areas with different consensus levels on species presence (1 model predicting presence, 2 models predicting presence, ...). In case that these statistics are within IUCN criteria for Critically Endangered (CR), Endangered (EN) or Vulnerable (VU), then this information is added in columns documenting the types of AOO and EOO.

Function `ensemble.chull.create` first creates a convex hull around known presence locations. Next, a buffer is created around the convex hull where the width of this buffer is calculated as the maximum distance among presence locations ([pointDistance](#)) multiplied by argument `buffer.width`. Finally, the mask is created by including all polygons of predicted species presence that are partially covered by the convex hull and its buffer.

Value

Function `ensemble.red` returns an array with AOO and EOO Function `ensemble.chull.create` creates a mask layer based on a convex hull around known presence locations.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Cardoso P. 2017. red - an R package to facilitate species red list assessments according to the IUCN criteria. Biodiversity Data Journal 5:e20530. <https://doi.org/10.3897/BDJ.5.e20530>

Kindt R. 2018. Ensemble species distribution modelling with transformed suitability values. Environmental Modelling & Software 100: 136-145. <https://doi.org/10.1016/j.envsoft.2017.11.009>

See Also

[ensemble.batch](#)

Examples

```
## Not run:

## Not run:
# based on examples in the dismo package

# get predictor variables
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
  pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
# subset based on Variance Inflation Factors
predictors <- subset(predictors, subset=c("bio5", "bio6",
  "bio16", "bio17"))
predictors
predictors@title <- "red"

# presence points
presence_file <- paste(system.file(package="dismo"), '/ex/bradypus.csv', sep='')
pres <- read.table(presence_file, header=TRUE, sep=',')

# fit 5 ensemble models (could take some time!)
# (examples for the red package use 100 models)
ensembles <- ensemble.batch(x=predictors,
  xn=c(predictors),
  species.presence=pres,
  thin.km=100,
  k.splits=4, k.test=0,
  n.ensembles=5,
  SINK=TRUE,
  ENSEMBLE.best=10, ENSEMBLE.exponent=c(1, 2, 3),
  ENSEMBLE.min=0.6,
  MAXENT=0, MAXLIKE=1, GBM=1, GBMSTEP=0, RF=1, GLM=1, GLMSTEP=1, GAM=1,
  GAMSTEP=1, MGCV=1, MGCVFIX=1, EARTH=1, RPART=1, NNET=1, FDA=1,
  SVM=1, SVME=1, GLMNET=1,
  BIOCLIM.0=0, BIOCLIM=1, DOMAIN=1, MAHAL=0, MAHAL01=1,
  PROBIT=TRUE,
  Yweights="BIOMOD",
  formulae.defaults=TRUE)

# first application of ensemble.red before applying the convex hull mask
# A00 and E00 are determined for each count level
library(red)
```

```

count.file <- paste(getwd(), "/ensembles/consensuscount/Bradypus variegatus_red.grd", sep="")
count.raster <- raster(count.file)
ensemble.red(count.raster)

# do not predict presence in polygons completely outside convex hull
# of known presence locations
pres.file <- paste(getwd(), "/ensembles/consensuspresence/Bradypus variegatus_red.grd", sep="")
pres.raster <- raster(pres.file)
pres1 <- pres[, -1]
chull.created <- ensemble.chull.create(x.pres=pres.raster, p=pres1)

mask.raster <- chull.created$mask.layer
mask.poly <- chull.created$convex.hull
par.old <- graphics::par(no.readonly=T)
par(mfrow=c(1,2))
plot(pres.raster, breaks=c(-1, 0, 1), col=c("grey", "green"),
     main="before convex hull")
points(pres1, col="blue")

pres.chull <- ensemble.chull.apply(pres.raster, mask=mask.raster, keep.old=T)
# load new
pres.file <- paste(getwd(), "/ensembles/consensuspresence/Bradypus variegatus_red.grd", sep="")
pres.raster <- raster(pres.file)
plot(pres.raster, breaks=c(-1, 0, 1), col=c("grey", "green"),
     main="after convex hull")
plot(mask.poly, add=T, border="blue")

# new application of ensemble.red
dev.new()
plot(count.raster, main="before convex hull")
ensemble.red(count.raster)
# all cells where species is predicted not to be present according to the mask layer
# will be modified to a count of zero
count.chull <- ensemble.chull.apply(count.raster, mask=mask.raster, keep.old=T)
# load new
count.file <- paste(getwd(), "/ensembles/consensuscount/Bradypus variegatus_red.grd", sep="")
count.raster <- raster(count.file)
ensemble.red(count.raster)
dev.new()
plot(count.raster, main="after convex hull")
par.old <- graphics::par(no.readonly=T)

## End(Not run)

```

ensemble.spatialThin	<i>Spatial thinning of presence point locations using the highly accurate geodesic estimates from the geosphere package</i>
----------------------	---

Description

The function creates a randomly selected subset of point locations where the shortest distance (geodesic) is above a predefined minimum. The geodesic is calculated more accurately (via [distGeo](#)) than in the spThin or red packages.

Usage

```
ensemble.spatialThin(x, thin.km=0.1,
  runs=100, verbose=FALSE, return.matrix=FALSE)
```

Arguments

x	Point locations provided in 2-column (lon, lat) format.
thin.km	Threshold for minimum distance (km) in final point location data set.
runs	Number of runs to maximize the retained number of point locations.
verbose	Provide some details on each run.
return.matrix	Include the distance matrix (calculated via distGeo) in the results.

Details

Locations with distances smaller than the threshold distance are randomly removed from the data set until no distance is smaller than the threshold. The function uses a similar algorithm as functions in the `spThin` or `red` packages, but the geodesic is more accurately calculated via [distGeo](#).

With several runs (default of 100 as in the `red` package or some `spThin` examples), the (first) data set with the maximum number of records is retained.

Value

The function returns a spatially thinned point location data set.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Aiello-Lammens ME, Boria RA, Radosavljevic A, Vilela B and Anderson RP. 2015. `spThin`: an R package for spatial thinning of species occurrence records for use in ecological niche models. *Ecography* 38: 541-545

See Also

[ensemble.batch](#)

Examples

```
## Not run:
# get predictor variables, only needed for plotting
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
  pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
# subset based on Variance Inflation Factors
predictors <- subset(predictors, subset=c("bio5", "bio6",
  "bio16", "bio17", "biome"))
predictors
predictors$title <- "base"

# presence points
```

```

presence_file <- paste(system.file(package="dismo"), 'ex/bradypus.csv', sep='')
pres <- read.table(presence_file, header=TRUE, sep=',')[, -1]

# number of locations
nrow(pres)

par.old <- graphics::par(no.readonly=T)
par(mfrow=c(2,2))

pres.thin1 <- ensemble.spatialThin(pres, thin.km=100, runs=10, verbose=T)
plot(predictors[[1]], main="10 runs", ext=extent(SpatialPoints(pres.thin1)))
points(pres.thin1, pch=20, col="red")

pres.thin2 <- ensemble.spatialThin(pres, thin.km=100, runs=10, verbose=T)
plot(predictors[[1]], main="10 runs", ext=extent(SpatialPoints(pres.thin2)))
points(pres.thin2, pch=20, col="red")

pres.thin3 <- ensemble.spatialThin(pres, thin.km=100, runs=100, verbose=T)
plot(predictors[[1]], main="100 runs", ext=extent(SpatialPoints(pres.thin3)))
points(pres.thin3, pch=20, col="red")

pres.thin4 <- ensemble.spatialThin(pres, thin.km=100, runs=100, verbose=T)
plot(predictors[[1]], main="100 runs", ext=extent(SpatialPoints(pres.thin4)))
points(pres.thin4, pch=20, col="red")

graphics::par(par.old)

## End(Not run)

```

ensemble.zones	<i>Mapping of environmental zones based on the Mahalanobis distance from centroids in environmental space.</i>
----------------	--

Description

Function `ensemble.zones` maps the zone of each raster cell within a presence map based on the minimum Mahalanobis distance (via [mahalanobis](#)) to different centroids. Function `ensemble.centroids` defines centroids within a presence map based on Principal Components Analysis (via [rda](#)) and K-means clustering (via [kmeans](#)).

Usage

```

ensemble.zones(presence.raster = NULL, centroid.object = NULL,
  x = NULL, ext = NULL,
  RASTER.species.name = centroid.object$name, RASTER.stack.name = x$title,
  RASTER.format = "raster", RASTER.datatype = "INT1S", RASTER.NAflag = -127,
  KML.out = FALSE, KML.maxpixels = 100000, KML.blur = 10,
  CATCH.OFF = FALSE)

ensemble.centroids(presence.raster = NULL, x = NULL, categories.raster = NULL,
  an = 10000, ext = NULL, name = "Species001",

```

```
pca.var = 0.95, centers = 0, use.silhouette = TRUE,
plotit = FALSE, dev.new.width = 7, dev.new.height = 7)
```

Arguments

presence.raster	RasterLayer object (raster) documenting presence (coded 1) of an organism
centroid.object	Object listing values for centroids and covariance to be used with the mahalanobis distance (used internally by the prediction function called from predict).
x	RasterStack object (stack) containing all environmental layers that correspond to explanatory variables
ext	an Extent object to limit the predictions and selection of background points to a sub-region of presence.raster and x, typically provided as c(lonmin, lonmax, latmin, latmax). See also randomPoints and extent .
RASTER.species.name	First part of the names of the raster file that will be generated, expected to identify the modelled species (or organism)
RASTER.stack.name	Last part of the names of the raster file that will be generated, expected to identify the predictor stack used
RASTER.format	Format of the raster files that will be generated. See writeFormats and writeRaster .
RASTER.datatype	Format of the raster files that will be generated. See dataType and writeRaster .
RASTER.NAflag	Value that is used to store missing data. See writeRaster .
KML.out	If TRUE, then kml files will be saved in a subfolder 'kml/zones'.
KML.maxpixels	Maximum number of pixels for the PNG image that will be displayed in Google Earth. See also KML .
KML.blur	Integer that results in increasing the size of the PNG image by $KML.blur^2$, which may help avoid blurring of isolated pixels. See also KML .
CATCH.OFF	Disable calls to function tryCatch .
categories.raster	RasterLayer object (raster) documenting predefined zones such as vegetation types. In case this object is provided, then centroids will be calculated for each zone.
an	Number of presence points to be used for Principal Components Analysis (via rda); see also prepareData and extract
name	Name for the centroid object, for example identifying the species and area for which centroids are calculated
pca.var	Minimum number of axes based on the fraction of variance explained (default value of 0.95 indicates that at least 95 percent of variance will be explained on the selected number of axes). Axes and coordinates are obtained from Principal Components Analysis (scores).
centers	Number of centers (clusters) to be used for K-means clustering (kmeans). In case a value smaller than 1 is provided, function cascadeKM is called to determine the optimal number of centers via the Calinski-Harabasz criterion.

<code>use.silhouette</code>	If TRUE, then centroid values are only based on presence points that have silhouette values (silhouette) larger than 0.
<code>plotit</code>	If TRUE, then a plot is provided that shows the locations of centroids in geographical and environmental space. Plotting in geographical space is based on determination of the presence location (analogue) with smallest Mahalanobis distance to the centroid in environmental space.
<code>dev.new.width</code>	Width for new graphics device (dev.new). If < 0, then no new graphics device is opened.
<code>dev.new.height</code>	Height for new graphics device (dev.new). If < 0, then no new graphics device is opened.

Details

Function `ensemble.zones` maps the zone of each raster cell of a predefined presence map, whereby the zone is defined as the centroid with the smallest Mahalanobis distance. The function returns a RasterLayer object ([raster](#)) and possibly a KML layer.

Function `ensemble.centroid` provides the centroid locations in environmental space and a covariance matrix ([cov](#)) to be used with [mahalanobis](#). Also provided is information on the analogue presence location that is closest to the centroid in environmental space.

Value

Function `ensemble.centroid` returns a list with following objects:

<code>centroids</code>	Location of centroids in environmental space
<code>centroid.analogs</code>	Location of best analogs to centroids in environmental space
<code>cov.mahal</code>	Covariance matrix

Author(s)

Roeland Kindt (World Agroforestry Centre)

See Also

[ensemble.raster](#)

Examples

```
## Not run:
# get predictor variables
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
                             pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
predictors <- subset(predictors, subset=c("bio1", "bio5", "bio6", "bio7", "bio8",
                                           "bio12", "bio16", "bio17"))
predictors
predictors$title <- "base"

# choose background points
background <- randomPoints(predictors, n=1000, extf=1.00)
```

```

# predicted presence from GLM
ensemble.calibrate.step1 <- ensemble.calibrate.models(
  x=predictors, p=pres, a=background,
  species.name="Bradypus",
  MAXENT=0, MAXLIKE=0, GBM=0, GBMSTEP=0, RF=0, GLM=1, GLMSTEP=0,
  GAM=0, GAMSTEP=0, MGCV=0, MGCVFIX=0,
  EARTH=0, RPART=0, NNET=0, FDA=0, SVM=0, SVME=0, GLMNET=0,
  BIOCLIM.O=0, BIOCLIM=0, DOMAIN=0, MAHAL=0, MAHAL01=0,
  Yweights="BIOMOD",
  models.keep=TRUE)

ensemble.raster.results <- ensemble.raster(xn=predictors,
  models.list=ensemble.calibrate.step1$models,
  RASTER.species.name="Bradypus", RASTER.stack.name="base")

# get presence map as for example created with ensemble.raster in subfolder 'ensemble/presence'
# presence values are values equal to 1
presence.file <- paste("ensembles//presence//Bradypus_base.grd", sep="")
presence.raster <- raster(presence.file)

# let cascadeKM decide on the number of clusters
dev.new()
centroids <- ensemble.centroids(presence.raster=presence.raster,
  x=predictors, an=1000, plotit=T)
ensemble.zones(presence.raster=presence.raster, centroid.object=centroids,
  x=predictors, RASTER.species.name="Bradypus", KML.out=T)

dev.new()
zones.file <- paste("ensembles//zones//Bradypus_base.grd", sep="")
zones.raster <- raster(zones.file)
max.zones <- maxValue(zones.raster)
plot(zones.raster, breaks=c(0, c(1:max.zones)),
  col = grDevices::rainbow(n=max.zones), main="zones")
ensemble.zones(presence.raster=presence.raster, centroid.object=centroids,
  x=predictors, RASTER.species.name="Bradypus", KML.out=T)

# manually choose 6 zones
dev.new()
centroids6 <- ensemble.centroids(presence.raster=presence.raster,
  x=predictors, an=1000, plotit=T, centers=6)
ensemble.zones(presence.raster=presence.raster, centroid.object=centroids6,
  x=predictors, RASTER.species.name="Bradypus6", KML.out=T)

dev.new()
zones.file <- paste("ensembles//zones//Bradypus6_base.grd", sep="")
zones.raster <- raster(zones.file)
max.zones <- maxValue(zones.raster)
plot(zones.raster, breaks=c(0, c(1:max.zones)),
  col = grDevices::rainbow(n=max.zones), main="six zones")

## End(Not run)

```

Description

These functions provide a dataframe which can subsequently be used to evaluate the relationship between environmental variables and the fitted probability of occurrence of individual or ensemble suitability modelling algorithms. The biomod2 package provides an alternative implementation of this approach (`response.plot2`).

Usage

```
evaluation.strip.data(xn = NULL, ext = NULL,
  models.list = NULL,
  input.weights = models.list$output.weights,
  steps=200, CATCH.OFF = FALSE
)

evaluation.strip.plot(data, TrainData=NULL,
  variable.focal = NULL, model.focal = NULL,
  dev.new.width = 7, dev.new.height = 7, ...
)
```

Arguments

<code>xn</code>	RasterStack object (stack) containing all layers that correspond to explanatory variables of an ensemble calibrated earlier with ensemble.calibrate.models . See also predict .
<code>ext</code>	an Extent object to limit the prediction to a sub-region of <code>xn</code> and the selection of background points to a sub-region of <code>x</code> , typically provided as <code>c(lonmin, lonmax, latmin, latmax)</code> ; see also predict , randomPoints and extent
<code>models.list</code>	list with 'old' model objects such as MAXENT or RF.
<code>input.weights</code>	array with numeric values for the different modelling algorithms; if NULL then values provided by parameters such as MAXENT and GBM will be used. As an alternative, the output from <code>ensemble.calibrate.weights</code> can be used.
<code>steps</code>	number of steps within the range of a continuous explanatory variable
<code>CATCH.OFF</code>	Disable calls to function tryCatch .
<code>data</code>	data set with ranges of environmental variables and fitted suitability models, typically returned by <code>evaluation.strip.data</code>
<code>TrainData</code>	Data set representing the calibration data set. If provided, then a boxplot will be added for presence locations via boxplot
<code>variable.focal</code>	focal explanatory variable for plots with evaluation strips
<code>model.focal</code>	focal model for plots with evaluation strips
<code>dev.new.width</code>	Width for new graphics device (dev.new). If < 0, then no new graphics device is opened.
<code>dev.new.height</code>	Height for new graphics device (dev.new). If < 0, then no new graphics device is opened.
<code>...</code>	Other arguments passed to plot

Details

These functions are mainly intended to be used internally by the `ensemble.raster` function.

`evaluation.strip.data` creates a data frame with variables (columns) corresponding to the environmental variables encountered in the `RasterStack` object (`x`) and the suitability modelling approaches that were defined. The variable of `focal.var` is an index of the variable for which values are ranged. The variable of `categorical` is an index for categorical (factor) variables.

A continuous (numeric) variable is ranged between its minimum and maximum values in the number of steps defined by argument `steps`. When a continuous variable is not the focal variable, then the average ([mean](#)) is used.

A categorical (factor) variable is ranged for all the encountered levels ([levels](#)) for this variable. When a categorical variable is not the focal variable, then the most frequent level is used.

Value

function `evaluation.strip.data` creates a data frame, function `codeevaluation.strip.data` allows for plotting.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt R. 2018. Ensemble species distribution modelling with transformed suitability values. *Environmental Modelling & Software* 100: 136-145. <https://doi.org/10.1016/j.envsoft.2017.11.009> Elith J, Ferrier S, Huettmann F & Leathwick J. 2005. The evaluation strip: A new and robust method for plotting predicted responses from species distribution models. *Ecological Modelling* 186: 280-289

See Also

[ensemble.calibrate.models](#) and [ensemble.raster](#)

Examples

```
## Not run:

# get predictor variables
library(dismo)
predictor.files <- list.files(path=paste(system.file(package="dismo"), '/ex', sep=''),
                             pattern='grd', full.names=TRUE)
predictors <- stack(predictor.files)
# subset based on Variance Inflation Factors
predictors <- subset(predictors, subset=c("bio5", "bio6",
    "bio16", "bio17"))
predictors <- stack(predictors)
predictors
predictors@title <- "base"

# presence points
presence_file <- paste(system.file(package="dismo"), '/ex/bradypus.csv', sep='')
pres <- read.table(presence_file, header=TRUE, sep=',')[,-1]

# the kfold function randomly assigns data to groups;
```

```

# groups are used as calibration (1/5) and training (4/5) data
grouppp <- kfold(pres, 5)
pres_train <- pres[grouppp != 1, ]
pres_test <- pres[grouppp == 1, ]

# choose background points
background <- randomPoints(predictors, n=1000, extf=1.00)
colnames(background)=c('lon', 'lat')
groupa <- kfold(background, 5)
backg_train <- background[groupa != 1, ]
backg_test <- background[groupa == 1, ]

# calibrate the models
# MAXLIKE not included as does not allow predictions for data.frames
# ENSEMBLE.min and ENSEMBLE.weight.min set very low to explore all
# algorithms.
# If focus is on actual ensemble, then set ENSEMBLE.min and
# ENSEMBLE.weight.min to more usual values
ensemble.calibrate <- ensemble.calibrate.models(x=predictors,
  p=pres_train, a=backg_train,
  pt=pres_test, at=backg_test,
  ENSEMBLE.min=0.5, ENSEMBLE.weight.min = 0.001,
  MAXENT=1, MAXLIKE=0, GBM=1, GBMSTEP=1, RF=1, GLM=1, GLMSTEP=1, GAM=1,
  GAMSTEP=1, MGCY=1, MGCYFIX=1, EARTH=1, RPART=1, NNET=1, FDA=1,
  SVM=1, SVME=1, GLMNET=1,
  BIOCLIM.O=1, BIOCLIM=1, DOMAIN=1, MAHAL=0, MAHAL01=1,
  Yweights="BIOMOD",
  PLOTS=FALSE, models.keep=TRUE)

# obtain data for plotting the evaluation strip
strip.data <- evaluation.strip.data(xn=predictors, steps=500,
  models.list=ensemble.calibrate$models)

# in case predictions for DOMAIN failed
# however, ENSEMBLE should also be recalculated
DOMAIN.model <- ensemble.calibrate$models$DOMAIN
strip.data$plot.data[, "DOMAIN"] <- dismo::predict(object=DOMAIN.model,
  x=strip.data$plot.data)

# in case predictions for MAHAL01 failed
predict.MAHAL01 <- function(model, newdata, MAHAL.shape) {
  p <- dismo::predict(object=model, x=newdata)
  p <- p - 1 - MAHAL.shape
  p <- abs(p)
  p <- MAHAL.shape / p
  return(as.numeric(p))
}

MAHAL01.model <- ensemble.calibrate$models$MAHAL01
MAHAL.shape1 <- ensemble.calibrate$models$formulae$MAHAL.shape
strip.data$plot.data[, "MAHAL01"] <- predict.MAHAL01(model=MAHAL01.model,
  newdata=strip.data$plot.data, MAHAL.shape=MAHAL.shape1)

# create graphs
evaluation.strip.plot(data=strip.data$plot.data, variable.focal="bio6",
  TrainData=strip.data$TrainData,
  type="o", col="red")

```



```

evaluation.strip.plot(data=strip.data$plot.data, model.focal="ENSEMBLE",
  TrainData=strip.data$TrainData,
  type="o", col="red")

## End(Not run)

```

faramea

Faramea occidentalis abundance in Panama

Description

This dataset describes the abundance (number of trees with diameter at breast height equal or larger than 10 cm) of the tree species *Faramea occidentalis* as observed in a 1-ha quadrat survey from the Barro Colorado Island of Panama. For each quadrat, some environmental characteristics are also provided.

Usage

```
data(faramea)
```

Format

A data frame with 45 observations on the following 8 variables.

UTM.EW a numeric vector

UTM.NS a numeric vector

Precipitation a numeric vector

Elevation a numeric vector

Age a numeric vector

Age.cat a factor with levels c1 c2 c3

Geology a factor with levels pT Tb Tbo Tc Tcm Tgo Tl

Faramea.occidentalis a numeric vector

Details

Although the original survey documented tree species composition of all 1-ha subplots of larger (over 1 ha) sample plot, only the first (and sometimes the last) quadrats of the larger plots were included. This selection was made to avoid that larger sample plots dominated the analysis. This selection of sites is therefore different from the selection of the 50 1-ha quadrats of the largest sample plot of the same survey ([BCI](#) and [BCI.env](#))

This dataset is the main dataset used for the examples provided in chapters 6 and 7 of the Tree Diversity Analysis manual (Kindt & Coe, 2005).

Source

<http://www.sciencemag.org/cgi/content/full/295/5555/666/DC1>

References

Pyke CR, Condit R, Aguilar S and Lao S. (2001). Floristic composition across a climatic gradient in a neotropical lowland forest. *Journal of Vegetation Science* 12: 553-566.

Condit, R, Pitman, N, Leigh, E.G., Chave, J., Terborgh, J., Foster, R.B., Nunez, P., Aguilar, S., Valencia, R., Villa, G., Muller-Landau, H.C., Losos, E. & Hubbell, S.P. (2002). Beta-diversity in tropical forest trees. *Science* 295: 666-669.

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
data(faramea)
```

ifri

Example data from the International Forestry Resources and Institutions (IFRI) research network

Description

This data set contains information on the number of stems (individuals) and basal areas for 34 vegetation plots inventoried in February 1997 in Lothlorien forest, 37 vegetation plots inventoried in February 1996 in May Creek Forest and 36 vegetation plots inventoried in May 1995 in Yellowwood State Forest. All three sites are in Indiana, USA. Data were gathered through IFRI inventory protocols to record any tree, palm and woody climber with diameter at breast height greater than or equal to 10 cm in 10-m radius circular plots; only tree species data were kept in the example data sets (IFRI research instruments and IFRI manual section P: Forest Plot Form, section D1: Tree, Palm and Woody Climber Information).

Usage

```
data(ifri)
```

Format

A data frame with 486 observations on the following 5 variables.

forest a factor with 3 levels: "LOT" (Lothlorien forest), "MCF" (May Creek Forest) and "YSF" (Yellowwood State Forest)

plotID a factor with 107 levels providing an identification code for a 314.16 square metres (10 m radius) vegetation plot

species a factor with 50 levels providing an 8 character code for a tree species

count a numeric vector providing the number of stems (individuals) for each species in each vegetation plot

basal a numeric vector providing the basal area (calculated from the diameter at breast height) in square cm for each species in each vegetation plot

Source

IFRI (2014) Data from the International Forestry Resources and Institutions (IFRI) research network. <http://www.ifriresearch.net>

Examples

```
data(ifri)
```

importancevalue	<i>Importance Value</i>
-----------------	-------------------------

Description

Calculates the importance values of tree species based on frequency (calculated from number of plots), density (calculated from number of individuals) and dominance (calculated from basal area). See details.

Usage

```
importancevalue(x, site="plotID", species="species",
  count="count", basal="basal",
  factor="forest", level="")

importancevalue.comp(x, site="plotID", species="species",
  count="count", basal="basal",
  factor="forest")
```

Arguments

x	data frame with information on plot identities, species identities, number of individuals and basal areas
site	factor variable providing the identities of survey plots
species	factor variable providing the identities of tree species
count	number of individuals for each tree species in each survey plot
basal	basal area for each tree species in each survey plot
factor	factor variable used to define subsets (typically different forest reserves)
level	level of the factor variable used to create a subset from the original data

Details

The importance value is calculated as the sum from (i) the relative frequency; (ii) the relative density; and (iii) the relative dominance. The importance value ranges between 0 and 300.

Frequency is calculated as the number of plots where a species is observed divided by the total number of survey plots. Relative frequency is calculated by dividing the frequency by the sum of the frequencies of all species, multiplied by 100 (to obtain a percentage).

Density is calculated as the total number of individuals of a species. Relative density is calculated by dividing the density by the sum of the densities of all species, multiplied by 100 (to obtain a percentage).

Dominance is calculated as the total basal area of a species. Relative dominance is calculated by dividing the dominance by the sum of the dominance of all species, multiplied by 100 (to obtain a percentage).

Functions `importancevalue.comp` applies function `importancevalue` to all available levels of a factor variable.

Value

Provides information on the importance value for all tree species

Author(s)

Roeland Kindt (World Agroforestry Centre), Peter Newton (University of Michigan)

References

Curtis, J.T. & McIntosh, R. P. (1951) An Upland Forest Continuum in the Prairie-Forest Border Region of Wisconsin. *Ecology* 32: 476-496.

Kent, M. (2011) *Vegetation Description and Data Analysis: A Practical Approach*. Second edition. 428 pages.

See Also

[ifri](#)

Examples

```
data(ifri)
importancevalue(ifri, site='plotID', species='species', count='count',
  basal='basal', factor='forest', level='YSF')
importancevalue.comp(ifri, site='plotID', species='species', count='count',
  basal='basal', factor='forest')

# When all survey plots are the same size, importance value
# is not affected. Counts and basal areas now calculated per square metre
ifri$count <- ifri$count/314.16
ifri$basal <- ifri$basal/314.16

importancevalue(ifri, site='plotID', species='species', count='count',
  basal='basal', factor='forest', level='YSF')
importancevalue.comp(ifri, site='plotID', species='species', count='count',
  basal='basal', factor='forest')
```

loaded.citations

Give Citation Information for all Loaded Packages

Description

This function provides citation information for all loaded packages.

Usage

```
loaded.citations()
```

Details

The function checks for the loaded packages via `.packages`. Citation information is provided for the base package and for all the non-standard packages via `citation`.

Value

The function provides a list of all loaded packages and the relevant citation information.

Author(s)

Roeland Kindt (World Agroforestry Centre)

makecommunitydataset	<i>Make a Community Dataset from a Stacked Dataset</i>
----------------------	--

Description

Makes a community data set from a stacked dataset (with separate variables for the site identities, the species identities and the abundance).

Usage

```
makecommunitydataset(x, row, column, value, factor="", level="", drop=F)
stackcommunitydataset(comm, remove.zeroes=FALSE, order.sites=FALSE, order.species=FALSE)
```

Arguments

<code>x</code>	Data frame.
<code>row</code>	Name of the categorical variable for the rows of the crosstabulation (typically indicating sites)
<code>column</code>	Name of the categorical variable for the columns of the crosstabulation (typically indicating species)
<code>value</code>	Name of numerical variable for the cells of the crosstabulation (typically indicating abundance). The cells provide the sum of all values in the data frame.
<code>factor</code>	Name of the variable to calculate a subset of the data frame.
<code>level</code>	Value of the subset of the factor variable to calculate a subset of the data frame.
<code>drop</code>	Drop rows without species (species with total abundance of zero are always dropped)
<code>comm</code>	Community data set
<code>remove.zeroes</code>	Should rows with zero abundance be removed?
<code>order.sites</code>	Should sites be ordered alphabetically?
<code>order.species</code>	Should species be ordered alphabetically?

Details

`makecommunitydataset` calculates a cross-tabulation from a data frame, summing up all the values of the numerical variable identified as variable for the cell values. If `factor=""`, then no subset is calculated from the data frame in the first step.

`stackcommunitydataset` reverses the actions of `makecommunitydataset` and recreates the data in stacked format.

Value

The function provides a community dataset from another data frame.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
## Not run:
dune.file <- normalizePath(paste(system.file(package="BiodiversityR"),
  'etc/dunestacked.csv', sep=''))
dune.stacked <- read.csv(dune.file)

# dune.stacked has different variables for sites, species and abundance
head(dune.stacked)
dune.comm2 <- makecommunitydataset(dune.stacked, row='sites', column='species',
  value='abundance')

# recreate the original stack
dune.stacked2 <- stackcommunitydataset(dune.comm2, remove.zeros=T)

## End(Not run)
```

multiconstrained

Pairwise Comparisons for All Levels of a Categorical Variable by RDA, CCA or Capscale

Description

This function implements pairwise comparisons for categorical variable through `capscale`, `cca`, `dbrda` or `rda` followed by `anova.cca`. The function simply repeats constrained ordination analysis by selecting subsets of data that correspond to two factor levels.

Usage

```
multiconstrained(method="capscale", formula, data, distance = "bray"
, comm = NULL, add = FALSE, multicomp="", contrast=0, ...)
```

Arguments

method	Method for constrained ordination analysis; one of "rda", "cca", "dbrda" or "capscale".
formula	Model formula as in capscale , cca or rda . The LHS can be a community data matrix or a distance matrix for capscale .
data	Data frame containing the variables on the right hand side of the model formula as in capscale , cca or rda .
distance	Dissimilarity (or distance) index in vegdist used if the LHS of the formula is a data frame instead of dissimilarity matrix; used only with function vegdist and partial match to "manhattan", "euclidean", "canberra", "bray", "kulczynski", "jaccard", "gower", "morisita", "horn" or "mountford". This argument is only used for capscale in case that the LHS of the formula is a community matrix.
comm	Community data frame which will be used for finding species scores when the LHS of the formula was a dissimilarity matrix as only allowed for capscale . This is not used if the LHS is a data frame.
add	Logical indicating if an additive constant should be computed, and added to the non-diagonal dissimilarities such that all eigenvalues are non-negative in underlying Principal Co-ordinates Analysis; only applicable in capscale .
multicomp	Categorical variable used to construct the contrasts from. In case that this variable is missing, then the first explanatory variable of the formula will be used.
contrast	Return the ordination results for the particular contrast indicated by this number (e.g. with 5 levels, one can choose in between contrast 1-10). In case=0, then the first row of the anova.cca results for all contrasts is provided.
...	Other parameters passed to anova.cca .

Details

This function provides a simple expansion of [capscale](#), [cca](#) and [rda](#) by conducting the analysis for subsets of the community and environmental datasets that only contain two levels of a categorical variable.

When the choice is made to return results from all contrasts (contrast=0), then the first row of the [anova.cca](#) tables for each contrast are provided. It is therefore possible to compare differences in results by modifying the "by" argument of this function (i.e. obtain the total of explained variance, the variance explained on the first axis or the variance explained by the variable alone).

When the choice is made to return results from a particular contrast (contrast>0), then the ordination result is returned and two new datasets ("newcommunity" and "newenvdata") are created that only contain data for the two selected contrasts.

Value

The function returns an ANOVA table that contains the first rows of the ANOVA tables obtained for all possible combinations of levels of the first variable. Alternatively, it returns an ordination result for the selected contrast and creates two new datasets ("newcommunity" and "newenvdata")

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Legendre, P. & Anderson, M.J. (1999). Distance-based redundancy analysis: testing multispecies responses in multifactorial ecological experiments. *Ecological Monographs* 69: 1-24.

Anderson, M.J. & Willis, T.J. (2003). Canonical analysis of principal coordinates: a useful method of constrained ordination for ecology. *Ecology* 84: 511-525.

Examples

```
## Not run:
library(vegan)
library(MASS)
data(dune)
data(dune.env)
multiconstrained(method="capscale", dune~Management, data=dune.env,
  distance="bray", add=TRUE)
multiconstrained(method="capscale", dune~Management, data=dune.env,
  distance="bray", add=TRUE, contrast=3)

## End(Not run)
```

nested.anova.dbrda

*Nested Analysis of Variance via Distance-based Redundancy Analysis
or Non-parametric Multivariate Analysis of Variance*

Description

The functions provide nested analysis of variance for a two-level hierarchical model. The functions are implemented by estimating the correct F-ratio for the main and nested factors (assuming the nested factor is random) and using the recommended permutation procedures to test the significance of these F-ratios. F-ratios are estimated from variance estimates that are provided by distance-based redundancy analysis ([capscale](#)) or non-parametric multivariate analysis of variance ([adonis](#)).

Usage

```
nested.anova.dbrda(formula, data, method="euc", add=FALSE,
  permutations=100, warnings=FALSE)
nested.npmanova(formula, data, method="euc", permutations=100, warnings=FALSE)
```

Arguments

formula	Formula with a community data frame (with sites as rows, species as columns and species abundance as cell values) or (for nested.anova.dbrda only) distance matrix on the left-hand side and two categorical variables on the right-hand side (with the second variable assumed to be nested within the first).
data	Environmental data set.

method	Method for calculating ecological distance with function vegdist : partial match to "manhattan", "euclidean", "canberra", "bray", "kulczynski", "jaccard", "gower", "morisita", "horn" or "mountford". This argument is ignored in case that the left-hand side of the formula already is a distance matrix.
add	Should a constant be added to the off-diagonal elements of the distance-matrix (TRUE) or not.
permutations	The number of permutations for significance testing.
warnings	Should warnings be suppressed (TRUE) or not.

Details

The functions provide two alternative procedures for multivariate analysis of variance on the basis of any distance measure. Function `nested.anova.dbrda` proceeds via [capscale](#), whereas `nested.npmanova` proceeds via [adonis](#). Both methods are complementary to each other as `nested.npmanova` always provides correct F-ratios and estimations of significance, whereas `nested.anova.dbrda` does not provide correct F-ratios and estimations of significance when negative eigenvalues are encountered or constants are added to the distance matrix, but always provides an ordination diagram.

The F-ratio for the main factor is estimated as the mean square of the main factor divided by the mean square of the nested factor. The significance of the F-ratio of the main factor is tested by permuting entire blocks belonging to levels of the nested factor. The significance of the F-ratio of the nested factor is tested by permuting sample units within strata defined by levels of the main factor.

Value

The functions provide an ANOVA table.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

- Legendre, P. & Anderson, M. J. (1999). Distance-based redundancy analysis: testing multispecies responses in multifactorial ecological experiments. *Ecological Monographs* 69, 1-24.
- Anderson, M.J. (2001). A new method for non-parametric multivariate analysis of variance. *Austral Ecology*, 26: 32-46.
- McCordle, B.H. and M.J. Anderson. (2001). Fitting multivariate models to community data: A comment on distance-based redundancy analysis. *Ecology*, 82: 290-297.

Examples

```
## Not run:
library(vegan)
data(warcom)
data(warenv)
# use larger number of permutations for real studies
nested.npmanova(warcom~rift.valley+popshort, data=warenv, method="jac",
  permutations=5)
nested.anova.dbrda(warcom~rift.valley+popshort, data=warenv, method="jac",
  permutations=5)

## End(Not run)
```

NMSrandom

Calculate the NMS Result with the Smallest Stress from Various Random Starts

Description

This function provides a simplified version of the method of calculating NMS results implemented by the function `metaMDS` (**vegan**).

Usage

```
NMSrandom(x, perm=100, k=2, stressresult=F, method="isoMDS")
```

Arguments

<code>x</code>	Distance matrix.
<code>perm</code>	Number of permutations to select the configuration with the lowest stress.
<code>k</code>	Number of dimensions for the non metric scaling result; passed to <code>isoMDS</code> or <code>sammon</code> .
<code>stressresult</code>	Provide the calculated stress for each permutation.
<code>method</code>	Method for calculating the NMS: <code>isoMDS</code> or <code>sammon</code> .

Details

This function is an easier method of calculating the best NMS configuration after various random starts than implemented in the `metaMDS` function (**vegan**). The function uses a distance matrix (as calculated for example by function `vegdist` from a community data set) and calculates random starting positions by function `initMDS` (**vegan**) analogous to `metaMDS`.

Value

The function returns the NMS ordination result with the lowest stress (calculated by `isoMDS` or `sammon`), or the stress of each NMS ordination.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
library(MASS)
data(dune)
distmatrix <- vegdist(dune)
Ordination.model1 <- NMSrandom(distmatrix,perm=100,k=2)
Ordination.model1 <- add.spec.scores(Ordination.model1,dune,
  method='wa.scores')
Ordination.model1
```

nnetrandom	<i>Calculate the NNET Result with the Smallest Value from Various Random Starts</i>
------------	---

Description

This function provides the best solution from various calls to the [nnet](#) feed-forward artificial neural networks function (**nnet**).

Usage

```
nnetrandom(formula,data,tries=10,leave.one.out=F,...)
```

Arguments

formula	Formula as passed to nnet .
data	Data as passed to nnet .
tries	Number of calls to nnet to obtain the best solution.
leave.one.out	Calculate leave-one-out predictions.
...	Other arguments passed to nnet .

Details

This function makes various calls to [nnet](#). If desired by the user, leave-one-out statistics are provided that report the prediction if one particular sample unit was not used for iterating the networks.

Value

The function returns the same components as [nnet](#), but adds the following components:

range	Summary of the observed "values".
tries	Number of different attempts to iterate an ANN.
CV	Predicted class when not using the respective sample unit for iterating ANN.
successful	Test whether leave-one-out statistics provided the same class as the original class.

Author(s)

Roeland Kindt (World Agroforestry Centre)

Examples

```
## Not run:
data(faramea)
faramea <- na.omit(faramea)
faramea$presence <- as.numeric(faramea$Faramea.occidentalis > 0)
attach(faramea)
library(nnet)
result <- nnetrandom(presence ~ Elevation, data=faramea, size=2,
  skip=FALSE, entropy=TRUE, trace=FALSE, maxit=1000, tries=100,
  leave.one.out=FALSE)
summary(result)
result$fitted.values
result$value
result2 <- nnetrandom(presence ~ Elevation, data=faramea, size=2,
  skip=FALSE, entropy=TRUE, trace=FALSE, maxit=1000, tries=50,
  leave.one.out=TRUE)
result2$range
result2$CV
result2$successful

## End(Not run)
```

ordicoeno

Coenoclines for an Ordination Axis

Description

A graph is produced that summarizes (through GAM as implemented by [gam](#)) how the abundance of all species of the community data set change along an ordination axis (based on the position of sites along the axis and the information from the community data set).

Usage

```
ordicoeno(x, ordiplot, axis = 1, legend = FALSE, cex = 0.8, ncol = 4, ...)
```

Arguments

<code>x</code>	Community data frame with sites as rows, species as columns and species abundance as cell values.
<code>ordiplot</code>	Ordination plot created by ordiplot .
<code>axis</code>	Axis of the ordination graph (1: horizontal, 2: vertical).
<code>legend</code>	if TRUE, then add a legend to the plot.
<code>cex</code>	the amount by which plotting text and symbols should be magnified relative to the default; see also par
<code>ncol</code>	the number of columns in which to set the legend items; see also legend
<code>...</code>	Other arguments passed to functions plot and points .

Details

This functions investigates the relationship between the species vectors and the position of sites on an ordination axis. A GAM ([gam](#)) investigates the relationship by using the species abundances of each species as response variable, and the site position as the explanatory variable. The graph shows how the abundance of each species changes over the gradient of the ordination axis.

Value

The function plots coenoclines and provides the expected degrees of freedom (complexity of the relationship) estimated for each species by GAM.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
library(mgcv)
data(dune)
Ordination.model1 <- rda(dune)
plot1 <- ordiplot(Ordination.model1, choices=c(1,2), scaling=1)
ordicoeno(dune, ordiplot=plot1, legend=TRUE)
```

ordisymbol

Add Other Graphical Items to Ordination Diagrams

Description

Functions to add some other graphical itmes to ordination diagrams than provided within **vegan** by [ordihull](#), [ordispider](#), [ordiarrows](#), [ordisegments](#), [ordigrid](#), [ordiellipse](#), [ordicluste](#)r and [lines.span](#)tree.

Usage

```
ordisymbol(ordiplot, y, factor, col = 1, colors = TRUE, pchs = TRUE,
  rainbow = TRUE, heat.colors = FALSE, terrain.colors = FALSE,
  topo.colors = FALSE, cm.colors = FALSE,
  legend = TRUE, legend.x = "topleft", legend.ncol = 1, ...)
ordibubble(ordiplot,var,...)
ordicluste
```

r2(ordiplot, cluster, mingroups = 1, maxgroups = nrow(ordiplot\$sites), ...)
ordinearest(ordiplot, dist,...)
ordivector(ordiplot, spec, lty=2,...)
Arguments

ordiplot	An ordination graph created by ordiplot (vegan).
y	Environmental data frame.
factor	Variable of the environmental data frame that defines subsets to be given different symbols.
var	Continous variable of the environmental dataset or species from the community dataset.

<code>col</code>	Colour (as points).
<code>colors</code>	Apply different colours to different factor levels
<code>pchs</code>	Apply different symbols (plotting characters) to different factor levels (as in points))
<code>rainbow</code>	Use rainbow colours
<code>heat.colors</code>	Use heat colours
<code>terrain.colors</code>	Use terrain colours
<code>topo.colors</code>	Use topo colours
<code>cm.colors</code>	Use cm colours
<code>legend</code>	Add the legend.
<code>legend.x</code>	Location of the legend; see also legend .
<code>legend.ncol</code>	the number of columns in which to set the legend items; see also legend
<code>cluster</code>	Cluster object.
<code>mingroups</code>	Minimum of clusters to be plotted.
<code>maxgroups</code>	Maximum of clusters to be plotted..
<code>dist</code>	Distance matrix.
<code>spec</code>	Species name from the community dataset.
<code>lty</code>	Line type as specified for par .
<code>...</code>	Other arguments passed to functions points , symbols , ordihull or arrows .

Details

Function `ordisymbol` plots different levels of the specified variable in different symbols and different colours. In case more than one colour palettes are selected, the last palette selected will be used.

Function `ordibubble` draws bubble diagrams indicating the value of the specified continuous variable. Circles indicate positive values, squares indicate negative values.

Function `ordiclust2` provides an alternative method of overlaying information from hierarchical clustering on an ordination diagram than provided by function `ordicluster`. The method draws convex hulls around sites that are grouped into the same cluster. You can select the minimum and maximum number of clusters that are plotted (i.e. the range of clustering steps to be shown).

Function `ordinearest` draws a vector from each site to the site that is nearest to it as determined from a distance matrix. When you combine the method with `lines.spantree` using the same distance measure, then you can evaluate in part how the minimum spanning tree was constructed.

Function `ordivector` draws a vector for the specified species on the ordination diagramme and draws perpendicular lines from each site to a line that connects the origin and the head of species vector. This method helps in the biplot interpretation of a species vector as described by Jongman, ter Braak and van Tongeren (1995).

Value

These functions add graphical items to an existing ordination diagram.

Author(s)

Roeland Kindt (World Agroforestry Centre) and Jari Oksanen (`ordinearest`)

References

Jongman, R.H.G, ter Braak, C.J.F & van Tongeren, O.F.R. (1987). Data Analysis in Community and Landscape Ecology. Pudog, Wageningen.

Kindt, R. & Coe, R. (2005). Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune)
data(dune.env)
Ordination.model1 <- rda(dune)
plot1 <- ordiplot(Ordination.model1, choices=c(1,2), scaling=2)
ordisymbol(plot1, dune.env, "Management", legend=TRUE,
  legend.x="topleft", legend.ncol=1)
plot2 <- ordiplot(Ordination.model1, choices=c(1,2), scaling=1)
distmatrix <- vegdist(dune, method='bray')
cluster <- hclust(distmatrix, method='single')
ordicluster2(plot2, cluster)
ordinearest(plot2, distmatrix, col=2)
ordivector(plot2, "Agrostol", lty=2)
```

PCAsignificance

PCA Significance

Description

Calculates the number of significant axes from a Principal Components Analysis based on the broken-stick criterion, or adds an equilibrium circle to an ordination diagram.

Usage

```
PCAsignificance(pca, axes=8)
ordiequilibriumcircle(pca, ordiplot, ...)
```

Arguments

pca	Principal Components Analysis result as calculated by rda (vegan).
axes	Number of axes to calculate results for.
ordiplot	Ordination plot created by ordiplot (vegan)
...	Other arguments passed to function arrows .

Details

These functions provide two methods of providing some information on significance for a Principal Components Analysis (PCA).

Function PCAsignificance uses the broken-stick distribution to evaluate how many PCA axes are significant. This criterion is one of the most reliable to check how many axes are significant.

PCA axes with larger percentages of (accumulated) variance than the broken-stick variances are significant (Legendre and Legendre, 1998).

Function `ordiequilibriumcircle` draws an equilibrium circle to a PCA ordination diagram. Only species vectors with heads outside of the equilibrium circle significantly contribute to the ordination diagram (Legendre and Legendre, 1998). Vectors are drawn for these species. The function considers the scaling methods used by `rda` for `scaling=1`. The method should only be used for `scaling=1` and PCA calculated by function `rda`.

Value

Function `PCAsignificance` returns a matrix with the variances that are explained by the PCA axes and by the broken-stick criterion.

Function `ordiequilibriumcircle` plots an equilibrium circle and returns a list with the radius and the scaling constant used by `rda`.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Legendre, P. & Legendre, L. (1998). Numerical Ecology. 2nd English Edition. Elsevier.

Kindt, R. & Coe, R. (2005). Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune)
Ordination.model1 <- rda(dune)
PCAsignificance(Ordination.model1)
plot1 <- ordiplot(Ordination.model1, choices=c(1,2), scaling=1)
ordiequilibriumcircle(Ordination.model1,plot1)
```

radfitresult

Alternative Rank Abundance Fitting Results

Description

Provides alternative methods of obtaining rank abundance curves than provided by functions `radfit`, `fisherfit` and `prestonfit` (**vegan**), although these same functions are called.

Usage

```
radfitresult(x,y="",factor="",level,plotit=T)
```


Arguments

x	Community data frame with sites as rows, species as columns and species abundance as cell values.
y	Environmental data frame.
factor	Variable of the environmental data frame that defines subsets to calculate fitted rank-abundance curves for.
level	Level of the variable to create the subset to calculate fitted rank-abundance curves.
plotit	Plot the results obtained by <code>plot.radfit</code> .

Details

These functions provide some alternative methods of obtaining fitted rank-abundance curves, although functions `radfit`, `fisherfit` and `prestonfit` (**vegan**) are called to calculate the actual results.

Value

The function returns the results from three methods of fitting rank-abundance curves:

radfit	results of <code>radfit</code> .
fisherfit	results of <code>fisherfit</code> .
prestonfit	results of <code>prestonfit</code> .

Optionally, a plot is provided of the `radfit` results by `plot.radfit`.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(BCI)
BCIall <- t(as.matrix(colSums(BCI)))
radfitresult(BCIall)
```

rankabundance

*Rank Abundance Curves***Description**

Provides methods of calculating rank-abundance curves.

Usage

```
rankabundance(x, y="", factor="", level, digits=1, t=qt(0.975, df=n-1))

rankabunplot(xr, addit=F, labels="", scale="abundance", scaledx=F, type="o",
             xlim=c(min(xpos), max(xpos)),
             ylim=c(0, max(x[,scale])),
             specnames=c(1:5), srt=0, ...)

rankabuncomp(x, y="", factor, scale="abundance",
             scaledx=F, type="o", rainbow=T,
             legend=T, xlim=c(1, max1), ylim=c(0, max2), ...)
```

Arguments

x	Community data frame with sites as rows, species as columns and species abundance as cell values.
y	Environmental data frame.
factor	Variable of the environmental data frame that defines subsets to calculate rank abundance curves for.
level	Level of the variable to create the subset to calculate rank abundance curves.
digits	Number of digits in the results.
t	t-value to calculate confidence interval limits for the species proportion for cluster sampling (following Hayek and Buzas 1997).
xr	Result from rankabundance.
addit	Add rank abundance curve to an existing graph.
labels	Labels to plot at left of the rank abundance curves.
scale	Method of scaling the vertical axis. Method "abundance" uses abundance, "proportion" uses proportional abundance (species abundance / total abundance), "logabun" calculates the logarithm of abundance using base 10 and "accumfreq" accumulates the proportional abundance.
scaledx	Scale the horizontal axis to 100 percent of total number of species.
type	Type of plot (as in function plot)
xlim	Limits for the horizontal axis.
ylim	Limits for the vertical axis.
specnames	Vector positions of species names to add to the rank-abundance curve.
srt	The string rotation in degrees of the species names (as in par).
rainbow	Use rainbow colouring for the different curves.
legend	Add the legend (you need to click in the graph where the legend needs to be plotted).
...	Other arguments to be passed to functions plot or points .

Details

These functions provide methods of calculating and plotting rank-abundance curves.

The vertical axis can be scaled by various methods. Method "abundance" uses abundance, "proportion" uses proportional abundance (species abundance / total abundance), "logabun" calculates the logarithm of abundance using base 10 and "accumfreq" accumulates the proportional abundance.

The horizontal axis can be scaled by the total number of species, or by 100 percent of all species by option "scaledx".

The method of calculating the confidence interval for species proportion is described in Hayek and Buzas (1997).

Functions rankabundance and rankabuncomp allow to calculate rank abundance curves for subsets of the community and environmental data sets. Function rankabundance calculates the rank abundance curve for the specified level of a selected environmental variable. Method rankabuncomp calculates the rank abundance curve for all levels of a selected environmental variable separately.

Value

The functions provide information on rankabundance curves. Function rankabundance provides information on abundance, proportional abundance, logarithmic abundance and accumulated proportional abundance. The function also provides confidence interval limits for the proportion of each species (pflower, pupper) and the proportion of species ranks (in percentage).

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Hayek, L.-A. C. & Buzas, M.A. (1997). Surveying Natural Populations. Columbia University Press.

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune.env)
data(dune)
RankAbun.1 <- rankabundance(dune)
RankAbun.1
rankabunplot(RankAbun.1, scale='abundance', addit=FALSE, specnames=c(1,2,3))
rankabunplot(RankAbun.1, scale='logabun', addit=FALSE, specnames=c(1:30),
  srt=45, ylim=c(1,100))
rankabuncomp(dune, y=dune.env, factor='Management',
  scale='proportion', legend=FALSE)
## CLICK IN THE GRAPH TO INDICATE WHERE THE LEGEND NEEDS TO BE PLACED
## IF YOU OPT FOR LEGEND=TRUE.
```

removeNAcomm

*Synchronize Community and Environmental Datasets***Description**

These functions may assist to ensure that the sites of the community dataset are the same sites as those from the environmental dataset, something that is assumed to be the case for the **BiodiversityR** and **vegan** packages.

Usage

```
same.sites(x, y)
check.datasets(x, y)
check.ordiscores(x, ord, check.species = TRUE)
removeNAcomm(x, y, variable)
removeNAenv(x, variable)
removezerospecies(x)
subsetcomm(x, y, factor, level, returncomm = TRUE)
```

Arguments

<code>x</code>	Data frame assumed to be the community dataset with variables corresponding to species.
<code>y</code>	Data frame assumed to be the environmental dataset with variables corresponding to descriptors of sites.
<code>ord</code>	Ordination result.
<code>check.species</code>	Should the species scores be checked (TRUE) or not.
<code>variable</code>	Name of the variable from the environmental dataset with NA values that indicate those sites that should be removed.
<code>factor</code>	Variable of the environmental data frame that defines subsets for the data frame.
<code>level</code>	Level of the variable to create the subsets for the data frame.
<code>returncomm</code>	For the selected sites, return the community dataset (TRUE) or the environmental dataset.

Details

Function `same.sites` provides a new data frame that has the same row names as the row names of the environmental data set and the same (species) variables as the original community data set. Sites from the original community data set that have no corresponding sites in the environmental data set are not included in the new community data set. (Hint: this function can be especially useful when some sites do not contain any species and where a community dataset was generated by the [makecommunitydataset](#) function.)

Function `check.datasets` checks whether the community and environmental data sets have the same number of rows, and (if this was the case) whether the rownames of both data sets are the same. The function also returns the dimensions of both data sets.

Function `check.ordiscores` checks whether the community data set and the ordination result have the same number of rows (sites) and columns (species, optional for `check.species==TRUE`), and

(if this was the case) whether the row and column names of both data sets are the same. Site and species scores for the ordination result are obtained via function `scores` (**vegan**).

Functions `removeNAcomm` and `removeNAenv` provide a new data frame that does not contain NA for the specified variable. The specified variable is part of the environmental data set. These functions are particularly useful when using community and environmental datasets, as new community and environmental datasets can be calculated that contain information from the same sample plots (sites). An additional result of `removeNAenv` is that factor levels of any categorical variable that do not occur any longer in the new data set are removed from the levels of the categorical variable.

Function `replaceNAcomm` substitutes cells containing NA with 0 in the community data set.

Function `removezerospecies` removes species from a community dataset that have total abundance that is smaller or equal to zero.

Function `subsetcomm` makes a subset of sites that contain a specified level of a categorical variable from the environmental data set. The same functionality of selecting subsets of the community or environmental data sets are implemented in various functions of **BiodiversityR** (for example `diversityresult`, `renyireresult` and `accumresult`) and have the advantage that it is not necessary to create a new data set. If a community dataset is returned, species that did not contain any individuals were removed from the data set. If an environmental dataset is returned, factor levels that did not occur were removed from the data set.

Value

The functions return a data frame or results of tests on the correspondence between community and environmental data sets.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune.env)
data(dune)
dune.env2 <- dune.env
dune.env2[1:4,"Moisture"] <- NA
dune2 <- removeNAcomm(dune,dune.env2,"Moisture")
dune.env2 <- removeNAenv(dune.env2,"Moisture")
dune3 <- same.sites(dune,dune.env2)
check.datasets(dune,dune.env2)
check.datasets(dune2,dune.env2)
check.datasets(dune3,dune.env2)
dune4 <- subsetcomm(dune,dune.env,"Management","NM",returncomm=TRUE)
dune.env4 <- subsetcomm(dune,dune.env,"Management","NM",returncomm=FALSE)
dune5 <- same.sites(dune,dune.env4)
check.datasets(dune4,dune5)
```

renyiresult*Alternative Renyi Diversity Results*

Description

Provides some alternative methods of obtaining results on Renyi diversity profile values than provided by [renyi](#) (**vegan**).

Usage

```
renyiresult(x, y=NULL, factor, level, method = "all",
  scales = c(0, 0.25, 0.5, 1, 2, 4, 8, Inf), evenness = FALSE, ...)

renyiplot(xr, addit=FALSE, pch = 1,
  xlab = "alpha", ylab = "H-alpha", ylim = NULL,
  labelit = TRUE, legend = TRUE, legend.x="topleft", legend.ncol = 8,
  col = 1, cex = 1, rainbow = TRUE, evenness = FALSE, ...)

renyiaccumresult(x, y=NULL, factor, level,
  scales=c(0, 0.25, 0.5, 1, 2, 4, 8, Inf), permutations = 100,...)

renyicomp(x, y, factor, sites=Inf,
  scales = c(0, 0.25, 0.5, 1, 2, 4, 8, Inf), permutations = 100, plotit = FALSE, ...)
```

Arguments

<code>x</code>	Community data frame with sites as rows, species as columns and species abundance as cell values.
<code>y</code>	Environmental data frame.
<code>factor</code>	Variable of the environmental data frame that defines subsets to calculate diversity profiles for.
<code>level</code>	Level of the variable to create the subset to calculate diversity profiles.
<code>method</code>	Method of calculating the diversity profiles: "all" calculates the diversity of the entire community (all sites pooled together), "s" calculates the diversity of each site separately.
<code>scales</code>	Scale parameter values as in function renyi (vegan).
<code>evenness</code>	Calculate or plot the evenness profile.
<code>xr</code>	Result from renyi or <code>renyiresult</code> .
<code>addit</code>	Add diversity profile to an existing graph.
<code>pch</code>	Symbol used for drawing the diversity profiles (as in function points).
<code>xlab</code>	Label for the horizontal axis.
<code>ylab</code>	Label for the vertical axis.
<code>ylim</code>	Limits of the vertical axis.
<code>labelit</code>	Provide site labels (site names) at beginning and end of the diversity profiles.
<code>legend</code>	Add the legend (you need to click in the graph where the legend needs to be plotted).

legend.x	Location of the legend; see also legend .
legend.ncol	number of columns for the legend (as in function legend).
col	Colour for the diversity profile (as in function points).
cex	Character expansion factor (as in function points).
rainbow	Use rainbow colours for the diversity profiles.
sites	Number of accumulated sites to provide profile values.
permutations	Number of permutations for the Monte-Carlo simulations for accumulated renyi diversity profiles (estimated by renyiaccum).
plotit	Plot the results (you need to click in the graph where the legend should be plotted).
...	Other arguments to be passed to functions renyi or plot .

Details

These functions provide some alternative methods of obtaining results with diversity profiles, although function [renyi](#) is always used to calculate the diversity profiles.

The method of calculating the diversity profiles: "all" calculates the diversity profile of the entire community (all sites pooled together), whereas "s" calculates the diversity profile of each site separately. The evenness profile is calculated by subtracting the profile value at scale 0 from all the profile values.

Functions [renyiresult](#), [renyiaccumresult](#) and [renyicomp](#) allow to calculate diversity profiles for subsets of the community and environmental data sets. functions [renyiresult](#) and [renyiaccumresult](#) calculate the diversity profiles for the specified level of a selected environmental variable. Method [renyicomp](#) calculates the diversity profile for all levels of a selected environmental variable separately.

Functions [renyicomp](#) and [renyiaccumresult](#) calculate accumulation curves for the Renyi diversity profile by randomised pooling of sites and calculating diversity profiles for the pooled sites as implemented in [renyiaccum](#). The method is similar to the random method of species accumulation ([specaccum](#)). If the number of "sites" is not changed from the default, it is replaced by the sample size of the level with the fewest number of sites.

Value

The functions provide alternative methods of obtaining Renyi diversity profiles.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt R., Degrande A., Turyomurugyendo L., Mbosso C., Van Damme P., Simons A.J. (2001). Comparing species richness and evenness contributions to on-farm tree diversity for data sets with varying sample sizes from Kenya, Uganda, Cameroon and Nigeria with randomised diversity profiles. Paper presented at IUFRO conference on forest biometry, modeling and information science, 26-29 June, University of Greenwich, UK

Kindt R. (2002). Methodology for tree species diversification planning for African agroecosystems. Thesis submitted in fulfilment of the requirement of the degree of doctor (PhD) in applied biological sciences. Faculty of agricultural and applied biological sciences, Ghent University, Ghent (Belgium), 332+xi pp.

Kindt R., Van Damme P. & Simons A.J. (2006). Tree diversity in western Kenya: using diversity profiles to characterise richness and evenness. *Biodiversity and Conservation* 15: 1253-1270.

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
data(dune.env)
data(dune)
Renyi.1 <- renyiresult(dune, y=dune.env, factor='Management', level='NM',
  method='s')
Renyi.1
renyiplot(Renyi.1, evenness=FALSE, addit=FALSE, pch=1,col='1', cex=1,
  legend=FALSE)
## CLICK IN THE GRAPH TO INDICATE WHERE THE LEGEND NEEDS TO BE PLACED
## IN CASE THAT YOU OPT FOR LEGEND=TRUE
```

residualssurface

Show and Interpolate Two Dimensional Distribution of Residuals

Description

This function interpolates the spatial structure of residuals of a GLM through [gam](#) or [surf.ls](#) and optionally provides a graph.

Usage

```
residualssurface(model, data, x, y, gam = F, npol = 2, plotit = T, filled = F, bubble = F)
```

Arguments

model	Result of GLM as calculated by glm or glm.nb .
data	Data set that contains the spatial coordinates of the sample units used for the original model (specified as "x" and "y").
x	Horizontal position of the sample units.
y	Vertical position of the sample units.
gam	Interpolate the spatial structure by gam (if "TRUE") or by surf.ls (if "FALSE").
npol	Degree of polynomial surface as passed to surf.ls .
plotit	Plot the interpolated surface (through interp and the residuals) .
filled	Fill the contours by filled.contour .
bubble	Provide a bubble graph of the residuals: circles indicate positive residuals, whereas squares indicate negative residuals.

Details

The function reports the results of a GAM or least-squares trend surface analysis of the spatial distribution of residuals of a model (through [residuals](#)).

Optionally, a graph is produced that can contain the trend surface, filled contours and bubble graphs in addition to the spatial location of the sample units.

Value

The function reports the results of a GAM or least-squares trend surface analysis of the spatial distribution of residuals. Optionally, a graph is provided.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(vegan)
library(mgcv)
library(akima)
data(faramea)
Count.model1 <- lm(Faramea occidentalis ~ Precipitation,
  data=faramea, na.action=na.exclude)
surface.1 <- residualssurface(Count.model1, na.omit(faramea),
  'UTM.EW', 'UTM.NS', gam=TRUE, plotit=TRUE, bubble=TRUE)
```

spatialsample

Spatial Sampling within a Polygon

Description

Spatial sampling within a polygon provides several methods of selecting rectangular sample plots within a polygon. Using a GIS package may be preferred for actual survey design.

Usage

```
spatialsample(x,method="random",n=5,xwidth=0.5,ywidth=0.5,xleft=0,
  ylower=0,xdist=0,ydist=0,plotit=T,plothull=F)
```

Arguments

x	2-column matrix with the coordinates of the vertices of the polygon. The first column contains the horizontal (x) position, the second column contains the vertical (y) position.
method	Method of sampling, any of "random", "grid" or "random grid".
n	Number of sample plots to be selected, or number of horizontal and vertical grid positions.
xwidth	Horizontal width of the sample plots.
ywidth	Vertical width of the sample plots.
xleft	Horizontal starting position of the grid.
ylower	Vertical starting position of the grid.

xdist	Horizontal distance between grid locations.
ydist	Vertical distance between grid locations.
plotit	Plot the sample plots on the current graph.
plothull	Plot a convex hull around the sample plots.

Details

Spatial sampling within a polygon provides several methods of selecting the position of sample plots.

Method "random" selects random positions of the sample plots using simple random sampling.

Method "grid" selects sample plots from a grid defined by "xleft", "ylower", "xdist" and "ydist". In case xdist=0 or ydist=0, then the number of grid positions are defined by "n". In case "xleft" or "ylower" are below the minimum position of any vertex of the polygon, then a random starting position is selected for the grid.

Method "random grid" selects sample plots at random from the sampling grid using the same methods of defining the grid as for method "grid".

Value

The function returns a list of centres of rectangular sample plots.

Author(s)

Roeland Kindt (World Agroforestry Centre)

References

Kindt, R. & Coe, R. (2005) Tree diversity analysis: A manual and software for common statistical methods for ecological and biodiversity studies.

<http://www.worldagroforestry.org/output/tree-diversity-analysis>

Examples

```
library(splancs)
area <- array(c(10,10,15,35,40,35,5,35,35,30,30,10), dim=c(6,2))
landuse1 <- array(c(10,10,15,15,30,35,35,30), dim=c(4,2))
landuse2 <- array(c(10,10,15,15,35,30,10,30,30,35,30,15), dim=c(6,2))
landuse3 <- array(c(10,10,30,35,40,35,5,10,15,30,30,10), dim=c(6,2))
plot(area[,1], area[,2], type="n", xlab="horizontal position",
      ylab="vertical position", lwd=2, bty="l")
polygon(landuse1)
polygon(landuse2)
polygon(landuse3)
spatialsample(area, method="random", n=20, xwidth=1, ywidth=1, plotit=TRUE,
              plothull=FALSE)
spatialsample(area, method="grid", xwidth=1, ywidth=1, plotit=TRUE, xleft=12,
              ylower=7, xdist=4, ydist=4)
spatialsample(area, method="random grid", n=20, xwidth=1, ywidth=1,
              plotit=TRUE, xleft=12, ylower=7, xdist=4, ydist=4)
```

transfgradient

*Gradient for Hypothetical Example of Turnover of Species Composition***Description**

This dataset documents the site sequence of 19 sites on a gradient determined from unimodal species distributions. The dataset is accompanied by [transfspecies](#) that documents the species composition of the sites. This is a hypothetical example that allows to investigate how well ecological distance measures or ordination methods recover the expected best sequence of sites.

Usage

```
data(transfgradient)
```

Format

A data frame with 19 observations on the following variable.

`gradient` a numeric vector

Source

Legendre, P. & Gallagher, E.D. (2001) Ecologically meaningful transformations for ordination of species data. *Oecologia* 129: 271-280.

References

Figure 3a.

Examples

```
data(transfspecies)
data(transfgradient)
plot(transfspecies[,1]~transfgradient[,1],xlab="gradient",
      ylab="species abundance",type="n",ylim=c(0.5,8.5))
for (i in 1:9) {points(transfgradient[,1],transfspecies[,i],type="o",pch=i)}
```

transfspecies

*Hypothetical Example of Turnover of Species Composition***Description**

This dataset documents the species composition of 19 sites that follow a specific sequence of sites as determined from unimodal species distributions. The dataset is accompanied by [transfgradient](#) that documents the gradient in species turnover. This is a hypothetical example that allows to investigate how well ecological distance measures or ordination methods recover the expected best sequence of sites.

Usage

```
data(transfspecies)
```

Format

A data frame with 19 observations on the following 9 variables.

species1 a numeric vector
 species2 a numeric vector
 species3 a numeric vector
 species4 a numeric vector
 species5 a numeric vector
 species6 a numeric vector
 species7 a numeric vector
 species8 a numeric vector
 species9 a numeric vector

Details

The example in the Tree Diversity Analysis manual only looks at the ecological distance from the first site. Hence, only the first 10 sites that share some species with this site should be selected.

This dataset enables investigations of how well ecological distance measures and ordination diagrams reconstruct the gradient (sequence of sites). The gradient expresses how the sites would be arranged based on their species composition.

Source

Legendre, P. & Gallagher, E.D. (2001) Ecologically meaningful transformations for ordination of species data. *Oecologia* 129: 271-280.

References

Figure 3a.

Examples

```
data(transfspecies)
data(transfgradient)
plot(transfspecies[,1]~transfgradient[,1],xlab="gradient",
      ylab="species abundance",type="n",ylim=c(0.5,8.5))
for (i in 1:9) {points(transfgradient[,1],transfspecies[,i],type="o",pch=i)}
```

warcom

Warburgia ugandensis AFLP Scores

Description

This data set contains scores for 185 loci for 100 individuals of the *Warburgia ugandensis* tree species (a medicinal tree species native to Eastern Africa). Since the data set is a subset of a larger data set that originated from a study of several *Warburgia* species, some of the loci did not produce bands for *W. ugandensis* (i.e. some loci only contain zeroes). This data set is accompanied by *warenv* that describes population and regional structure of the 100 individuals.

Usage

```
data(warcom)
```

Format

A data frame with 100 observations on the following 185 variables.

locus001 a numeric vector
locus002 a numeric vector
locus003 a numeric vector
locus004 a numeric vector
locus005 a numeric vector
locus006 a numeric vector
locus007 a numeric vector
locus008 a numeric vector
locus009 a numeric vector
locus010 a numeric vector
locus011 a numeric vector
locus012 a numeric vector
locus013 a numeric vector
locus014 a numeric vector
locus015 a numeric vector
locus016 a numeric vector
locus017 a numeric vector
locus018 a numeric vector
locus019 a numeric vector
locus020 a numeric vector
locus021 a numeric vector
locus022 a numeric vector
locus023 a numeric vector
locus024 a numeric vector
locus025 a numeric vector
locus026 a numeric vector
locus027 a numeric vector
locus028 a numeric vector
locus029 a numeric vector
locus030 a numeric vector
locus031 a numeric vector
locus032 a numeric vector
locus033 a numeric vector
locus034 a numeric vector
locus035 a numeric vector

locus036 a numeric vector
locus037 a numeric vector
locus038 a numeric vector
locus039 a numeric vector
locus040 a numeric vector
locus041 a numeric vector
locus042 a numeric vector
locus043 a numeric vector
locus044 a numeric vector
locus045 a numeric vector
locus046 a numeric vector
locus047 a numeric vector
locus048 a numeric vector
locus049 a numeric vector
locus050 a numeric vector
locus051 a numeric vector
locus052 a numeric vector
locus053 a numeric vector
locus054 a numeric vector
locus055 a numeric vector
locus056 a numeric vector
locus057 a numeric vector
locus058 a numeric vector
locus059 a numeric vector
locus060 a numeric vector
locus061 a numeric vector
locus062 a numeric vector
locus063 a numeric vector
locus064 a numeric vector
locus065 a numeric vector
locus066 a numeric vector
locus067 a numeric vector
locus068 a numeric vector
locus069 a numeric vector
locus070 a numeric vector
locus071 a numeric vector
locus072 a numeric vector
locus073 a numeric vector
locus074 a numeric vector
locus075 a numeric vector

locus076 a numeric vector
locus077 a numeric vector
locus078 a numeric vector
locus079 a numeric vector
locus080 a numeric vector
locus081 a numeric vector
locus082 a numeric vector
locus083 a numeric vector
locus084 a numeric vector
locus085 a numeric vector
locus086 a numeric vector
locus087 a numeric vector
locus088 a numeric vector
locus089 a numeric vector
locus090 a numeric vector
locus091 a numeric vector
locus092 a numeric vector
locus093 a numeric vector
locus094 a numeric vector
locus095 a numeric vector
locus096 a numeric vector
locus097 a numeric vector
locus098 a numeric vector
locus099 a numeric vector
locus100 a numeric vector
locus101 a numeric vector
locus102 a numeric vector
locus103 a numeric vector
locus104 a numeric vector
locus105 a numeric vector
locus106 a numeric vector
locus107 a numeric vector
locus108 a numeric vector
locus109 a numeric vector
locus110 a numeric vector
locus111 a numeric vector
locus112 a numeric vector
locus113 a numeric vector
locus114 a numeric vector
locus115 a numeric vector

locus116 a numeric vector
locus117 a numeric vector
locus118 a numeric vector
locus119 a numeric vector
locus120 a numeric vector
locus121 a numeric vector
locus122 a numeric vector
locus123 a numeric vector
locus124 a numeric vector
locus125 a numeric vector
locus126 a numeric vector
locus127 a numeric vector
locus128 a numeric vector
locus129 a numeric vector
locus130 a numeric vector
locus131 a numeric vector
locus132 a numeric vector
locus133 a numeric vector
locus134 a numeric vector
locus135 a numeric vector
locus136 a numeric vector
locus137 a numeric vector
locus138 a numeric vector
locus139 a numeric vector
locus140 a numeric vector
locus141 a numeric vector
locus142 a numeric vector
locus143 a numeric vector
locus144 a numeric vector
locus145 a numeric vector
locus146 a numeric vector
locus147 a numeric vector
locus148 a numeric vector
locus149 a numeric vector
locus150 a numeric vector
locus151 a numeric vector
locus152 a numeric vector
locus153 a numeric vector
locus154 a numeric vector
locus155 a numeric vector

locus156 a numeric vector
locus157 a numeric vector
locus158 a numeric vector
locus159 a numeric vector
locus160 a numeric vector
locus161 a numeric vector
locus162 a numeric vector
locus163 a numeric vector
locus164 a numeric vector
locus165 a numeric vector
locus166 a numeric vector
locus167 a numeric vector
locus168 a numeric vector
locus169 a numeric vector
locus170 a numeric vector
locus171 a numeric vector
locus172 a numeric vector
locus173 a numeric vector
locus174 a numeric vector
locus175 a numeric vector
locus176 a numeric vector
locus177 a numeric vector
locus178 a numeric vector
locus179 a numeric vector
locus180 a numeric vector
locus181 a numeric vector
locus182 a numeric vector
locus183 a numeric vector
locus184 a numeric vector
locus185 a numeric vector

Source

Muchugi, A.N. (2007) Population genetics and taxonomy of important medicinal tree species of the genus *Warburgia*. PhD Thesis. Kenyatta University, Kenya.

Examples

```
data(warcom)
```

`warenv`*Warburgia ugandensis* Population Structure

Description

This data set contains population and regional locations for 100 individuals of the *Warburgia ugandensis* tree species (a medicinal tree species native to Eastern Africa). This data set is associated with `warcom` that contains scores for 185 AFLP loci.

Usage

```
data(warenv)
```

Format

A data frame with 100 observations on the following 4 variables.

`population` a factor with levels Kibale Kitale Laikipia Lushoto Mara

`popshort` a factor with levels KKIT KLAI KMAR TLUS UKIB

`country` a factor with levels Kenya Tanzania Uganda

`rift.valley` a factor with levels east west

Source

Muchugi, A.N. (2007) Population genetics and taxonomy of important medicinal tree species of the genus *Warburgia*. PhD Thesis. Kenyatta University, Kenya.

Examples

```
data(warenv)
```

Index

*Topic **datasets**

BCI.env, [9](#)
faramea, [89](#)
ifri, [90](#)
transfgradient, [115](#)
transfspecies, [115](#)
warcom, [116](#)
warenv, [122](#)

*Topic **multivariate**

accumresult, [4](#)
add.spec.scores, [6](#)
balanced.specaccum, [7](#)
BiodiversityRGUI, [10](#)
CAPdiscrim, [11](#)
caprescale, [14](#)
crosstabanalysis, [15](#)
deviancepercentage, [16](#)
dist.eval, [17](#)
dist.zeroes, [19](#)
distdisplayed, [20](#)
disttransform, [21](#)
diversityresult, [22](#)
importancevalue, [91](#)
loaded.citations, [92](#)
makecommunitydataset, [93](#)
multiconstrained, [94](#)
nested.anova.dbrda, [96](#)
NMSrandom, [98](#)
nnetrandom, [99](#)
ordicoeno, [100](#)
ordisymbol, [101](#)
PCAsignificance, [103](#)
radfitresult, [104](#)
rankabundance, [106](#)
removeNAcomm, [108](#)
renyiresult, [110](#)
residualssurface, [112](#)
spatialsample, [113](#)

*Topic **package**

BiodiversityR-package, [3](#)
.packages, [93](#)

accumcomp (accumresult), [4](#)
accumplot (accumresult), [4](#)

accumresult, [4](#), [8](#), [109](#)
add.spec.scores, [6](#), [13](#)
addLayer, [34](#), [53](#)
adonis, [96](#), [97](#)
anova.cca, [94](#), [95](#)
anova.glm, [16](#)
anova.negbin, [16](#)
aoo, [78](#)
areaPolygon, [73](#), [74](#)
arrows, [102](#), [103](#)
as.dist, [11](#)

balanced.specaccum, [7](#)
BCI, [9](#), [89](#)
BCI.env, [9](#), [89](#)
bioclim, [34](#), [40](#), [42](#), [53](#)
BiodiversityR (BiodiversityR-package), [3](#)
BiodiversityR-package, [3](#)
BiodiversityR.changeLog, [10](#)
BiodiversityRGUI, [3](#), [10](#)
bioenv, [17](#), [18](#)
biovars, [66](#)
boxplot, [86](#)

CAPdiscrim, [11](#)
caprescale, [14](#)
capscale, [11](#), [14](#), [94–97](#)
cascadeKM, [83](#)
cca, [94](#), [95](#)
check.datasets (removeNAcomm), [108](#)
check.ordiscores (removeNAcomm), [108](#)
chisq.test, [15](#)
circles, [31](#), [51](#)
citation, [93](#)
cmdscale, [6](#), [12](#), [14](#)
cor, [6](#), [20](#), [51](#)
cov, [27](#), [84](#)
coverscale, [21](#), [22](#)
crosstabanalysis, [15](#)

dataType, [26](#), [32](#), [65](#), [68](#), [72](#), [78](#), [83](#)
dbrda, [94](#)
decostand, [21](#)
dev.new, [37](#), [84](#), [86](#)

- deviancepercentage, 16
- dispweight, 21, 22
- dist.eval, 17
- dist zeroes, 19
- distconnected, 17, 18
- distdisplayed, 20
- distGeo, 80, 81
- disttransform, 21
- diversity, 22, 24
- diversitycomp (diversityresult), 22
- diversityresult, 22, 109
- diversityvariables (diversityresult), 22
- domain, 34, 53

- earth, 33, 35, 53, 55
- ecocrop, 66
- ensemble.accepted.categories
(ensemble.dummy.variables), 62
- ensemble.analogue, 25
- ensemble.analogue.object, 26
- ensemble.area (ensemble.raster), 71
- ensemble.batch, 29, 58, 74, 79, 81
- ensemble.bioclim, 34, 36, 40, 44, 45, 53, 55, 69
- ensemble.bioclim.graph, 42, 44, 44, 69
- ensemble.bioclim.object, 40, 44
- ensemble.calibrate.models, 29, 37, 38, 46, 63, 72–74, 86, 87
- ensemble.calibrate.weights, 29, 32, 37, 38, 74
- ensemble.calibrate.weights
(ensemble.calibrate.models), 46
- ensemble.centroids (ensemble.zones), 82
- ensemble.chull.apply (ensemble.red), 77
- ensemble.chull.create (ensemble.red), 77
- ensemble.drop1
(ensemble.calibrate.models), 46
- ensemble.dummy.variables, 62
- ensemble.ecocrop, 65
- ensemble.ecocrop.object, 65
- ensemble.formulae, 34, 53
- ensemble.formulae
(ensemble.calibrate.models), 46
- ensemble.habitat.change
(ensemble.raster), 71
- ensemble.mean (ensemble.batch), 29
- ensemble.novel, 28, 41, 42, 45, 68
- ensemble.novel.object, 68
- ensemble.pairs
(ensemble.calibrate.models), 46
- ensemble.plot (ensemble.batch), 29
- ensemble.raster, 29, 37, 38, 51, 57, 58, 63, 69, 71, 84, 87
- ensemble.red, 77
- ensemble.simplified.categories
(ensemble.dummy.variables), 62
- ensemble.spatialThin, 31, 37, 80
- ensemble.strategy
(ensemble.calibrate.models), 46
- ensemble.threshold
(ensemble.calibrate.models), 46
- ensemble.VIF, 32, 37
- ensemble.VIF
(ensemble.calibrate.models), 46
- ensemble.weights
(ensemble.calibrate.models), 46
- ensemble.zones, 82
- estimateR, 24
- evaluate, 51, 56, 58, 73
- evaluation.strip.data, 85
- evaluation.strip.plot, 74
- evaluation.strip.plot
(evaluation.strip.data), 85
- extent, 83, 86
- extract, 26, 34, 36, 41, 50, 53, 63, 73, 78, 83

- faramea, 89
- fda, 33, 36, 53, 55
- filled.contour, 112
- fisher.alpha, 22, 24
- fisherfit, 104, 105
- freq, 63

- gam, 20, 33, 35, 52, 54, 55, 100, 112
- gam.control, 34, 53
- gbm, 33, 34, 52, 54
- gbm.step, 33, 35, 52, 54, 55, 57
- gBuffer, 78
- get.block, 31, 55
- getCrop, 66
- glm, 16, 33–35, 52–55, 112
- glm.control, 34, 53
- glm.nb, 16, 112
- glmnet, 34, 36, 53, 55

- ifri, 90, 92
- importancevalue, 91
- initMDS, 98
- interp, 112
- isoMDS, 6, 98

- kfold, 31, 32, 50, 55, 57
- kmeans, 82, 83
- KML, 26, 32, 41, 65, 68, 73, 83
- ksvm, 33, 36, 53, 55

- lda, 12

- legend, [100](#), [102](#), [111](#)
- levels, [87](#)
- lines.spantree, [101](#), [102](#)
- loaded.citations, [92](#)
- mahal, [34](#), [36](#), [53](#), [55](#), [56](#), [74](#)
- mahalanobis, [26](#), [27](#), [82–84](#)
- makecommunitydataset, [93](#), [108](#)
- mantel, [20](#)
- map.sdm, [77](#)
- mask, [69](#)
- maxent, [33](#), [34](#), [50–54](#)
- maxlike, [33](#), [34](#), [52](#), [54](#)
- mean, [87](#)
- mess, [69](#)
- metaMDS, [6](#), [98](#)
- ModelEvaluation, [74](#)
- multiconstrained, [94](#)
- na.omit, [16](#)
- nested.anova.dbrda, [96](#)
- nested.npmanova (nested.anova.dbrda), [96](#)
- nicheOverlap, [37](#)
- NMSrandom, [6](#), [98](#)
- nnet, [33](#), [34](#), [36](#), [53](#), [55](#), [57](#), [99](#)
- nnetrandom, [99](#)
- optim, [34](#), [54](#)
- optimal.thresholds, [32](#), [51](#), [57](#), [58](#)
- ordiarrows, [101](#)
- ordibubble (ordisymbol), [101](#)
- ordiclust, [101](#), [102](#)
- ordiclust2 (ordisymbol), [101](#)
- ordicoeno, [100](#)
- ordielipse, [101](#)
- ordiequilibriumcircle
(PCAsignificance), [103](#)
- ordigrd, [101](#)
- ordihull, [101](#), [102](#)
- ordinearest (ordisymbol), [101](#)
- ordiplot, [13](#), [14](#), [20](#), [100](#), [101](#), [103](#)
- ordisegments, [101](#)
- ordispider, [101](#)
- ordisymbol, [101](#)
- ordivector (ordisymbol), [101](#)
- pairs, [58](#)
- par, [100](#), [102](#), [106](#)
- PCAsignificance, [103](#)
- plot, [5](#), [37](#), [86](#), [100](#), [106](#), [111](#)
- plot.radfit, [105](#)
- plot.specaccum, [4](#), [5](#), [7](#)
- pointDistance, [78](#)
- points, [5](#), [100](#), [102](#), [106](#), [110](#), [111](#)
- postMDS, [6](#)
- predict, [25](#), [26](#), [31](#), [40](#), [65](#), [68](#), [72](#), [83](#), [86](#)
- predict.glmnet, [36](#), [55](#), [56](#)
- prepare.bioenv (dist.eval), [17](#)
- prepareData, [34](#), [36](#), [41](#), [50](#), [51](#), [53](#), [63](#), [73](#),
[78](#), [83](#)
- prestonfit, [104](#), [105](#)
- qnrm, [41](#)
- quantile, [27](#), [41](#), [69](#)
- radfit, [104](#), [105](#)
- radfitresult, [104](#)
- randomForest, [33](#), [35](#), [52](#), [54](#)
- randomPoints, [27](#), [31](#), [34](#), [50](#), [54](#), [83](#), [86](#)
- rankabuncomp (rankabundance), [106](#)
- rankabundance, [106](#)
- rankabunplot (rankabundance), [106](#)
- raster, [62](#), [63](#), [69](#), [73](#), [78](#), [83](#), [84](#)
- rda, [6](#), [82](#), [83](#), [94](#), [95](#), [103](#), [104](#)
- removeNAcomm, [108](#)
- removeNAenv (removeNAcomm), [108](#)
- removezerospecies (removeNAcomm), [108](#)
- renyi, [110](#), [111](#)
- renyiaccum, [111](#)
- renyiaccumresult (renyiresult), [110](#)
- renyicomp (renyiresult), [110](#)
- renyiplot (renyiresult), [110](#)
- renyiresult, [109](#), [110](#)
- replaceNAcomm (removeNAcomm), [108](#)
- residuals, [112](#)
- residualssurface, [112](#)
- round, [56](#)
- rpart, [33](#), [36](#), [53](#), [55](#)
- rpart.control, [36](#), [55](#)
- s, [35](#), [55](#)
- same.sites (removeNAcomm), [108](#)
- sammon, [6](#), [98](#)
- scores, [83](#), [109](#)
- silhouette, [84](#)
- sink, [32](#), [51](#), [73](#)
- spatialsample, [113](#)
- specaccum, [4](#), [5](#), [7](#), [8](#), [111](#)
- specnumber, [22](#), [24](#)
- specpool, [22](#), [24](#)
- ssb, [31](#), [51](#)
- stack, [25](#), [26](#), [31](#), [40](#), [44](#), [50](#), [65](#), [68](#), [72](#), [83](#), [86](#)
- stackcommunitydataset
(makecommunitydataset), [93](#)
- step.gam, [33](#), [35](#), [52](#), [54](#)
- stepAIC, [33](#), [35](#), [52](#), [54](#)

subsetcomm (removeNAcomm), 108
surf.ls, 112
svm, 33, 36, 53, 55
symbols, 102

threshold, 32, 51
transfgradient, 115, 115
transfspecies, 115, 115
trunc, 73
tryCatch, 26, 32, 41, 51, 65, 68, 73, 83, 86

vegdist, 12, 17, 19, 20, 95, 97, 98
vif, 51

warcom, 116
warenv, 122
wascores, 6
writeFormats, 26, 32, 40, 65, 68, 72, 78, 83
writeRaster, 26, 32, 40, 63, 65, 68, 72, 78, 83
wrld_simpl, 37