

# Machine-Level Programming III: Procedures

15-213/18-213/15-513: Introduction to Computer Systems  
7<sup>th</sup> Lecture, September 19, 2017

**Today's Instructor:**  
Phil Gibbons

# Today

## ■ Procedures

- Mechanisms
- Stack Structure
- Calling Conventions
  - Passing control
  - Passing data
  - Managing local data
- Illustration of Recursion

# Mechanisms in Procedures

## ■ Passing control

- To beginning of procedure code
- Back to return point

## ■ Passing data

- Procedure arguments
- Return value

## ■ Memory management

- Allocate during procedure execution
- Deallocate upon return

## ■ Mechanisms all implemented with machine instructions

## ■ x86-64 implementation of a procedure uses only those mechanisms required

```
P (...) {  
    •  
    •  
    y = Q(x);  
    print(y)  
    •  
}
```

```
int Q(int i)  
{  
    int t = 3*i;  
    int v[10];  
    •  
    •  
    return v[t];  
}
```

# Mechanisms in Procedures

## ■ Passing control

- To beginning of procedure code
- Back to return point

## ■ Passing data

- Procedure arguments
- Return value


## ■ Memory management

- Allocate during procedure execution
- Deallocate upon return

## ■ Mechanisms all implemented with machine instructions

## ■ x86-64 implementation of a procedure uses only those mechanisms required

```
P (...) {  
    .  
    .  
    y = Q(x);  
    print(y)  
    .  
}
```



```
int Q(int i)  
{  
    int t = 3*i;  
    int v[10];  
    .  
    .  
    return v[t];  
}
```

# Mechanisms in Procedures

## ■ Passing control

- To beginning of procedure code
- Back to return point

## ■ Passing data

- Procedure arguments
- Return value

## ■ Memory management

- Allocate during procedure execution
- Deallocate upon return

## ■ Mechanisms all implemented with machine instructions

## ■ x86-64 implementation of a procedure uses only those mechanisms required

```
P (...) {  
    •  
    •  
    y = Q(x);  
    print(y)  
    •  
}
```

```
int Q(int i)  
{  
    int t = 3*i;  
    int v[10];  
    •  
    •  
    return v[t];  
}
```

# Mechanisms in Procedures

## ■ Passing control

- To beginning of procedure code
- Back to return point

## ■ Passing data

- Procedure arguments
- Return value

## ■ Memory management

- Allocate during procedure execution
- Deallocate upon return

## ■ Mechanisms all implemented with machine instructions

## ■ x86-64 implementation of a procedure uses only those mechanisms required

```
P (...) {  
    •  
    •  
    y = Q(x);  
    print(y)  
    •  
}
```

```
int Q(int i)  
{  
    int t = 3*i;  
    int v[10];  
    •  
    •  
    return v[t];  
}
```

# Mechanisms in Procedures

```
P (...) {
```

Machine instructions implement the mechanisms, but the choices are determined by designers. These choices make up the **Application Binary Interface (ABI)**.

- Deallocate upon return
- **Mechanisms all implemented with machine instructions**
- **x86-64 implementation of a procedure uses only those mechanisms required**

```
int v[10];  
.  
.  
return v[t];  
}
```

# Today

## ■ Procedures


- Mechanisms
- **Stack Structure**
- Calling Conventions
  - Passing control
  - Passing data
  - Managing local data
- Illustration of Recursion



# x86-64 Stack


## ■ Region of memory managed with stack discipline

- Memory viewed as array of bytes.
- Different regions have different purposes.
- (Like ABI, a policy decision)




# x86-64 Stack

- Region of memory managed with stack discipline



# x86-64 Stack


- Region of memory managed with stack discipline
- Grows toward lower addresses
- Register `%rsp` contains lowest stack address
  - address of “top” element



# x86-64 Stack: Push

## ■ `pushq Src`


- Fetch operand at *Src*
- Decrement `%rsp` by 8
- Write operand at address given by `%rsp`



# x86-64 Stack: Push

## ■ `pushq Src`


- Fetch operand at *Src*
- Decrement `%rsp` by 8
- Write operand at address given by `%rsp`



# x86-64 Stack: Pop

## ■ `popq Dest`

- Read value at address given by `%rsp`
- Increment `%rsp` by 8
- Store value at `Dest` (usually a register)



# x86-64 Stack: Pop

## ■ `popq Dest`


- Read value at address given by `%rsp`
- Increment `%rsp` by 8
- Store value at `Dest` (usually a register)

val

Stack Pointer: `%rsp`

+8

Stack “Bottom”



Increasing  
Addresses

Stack  
Grows  
Down

Stack “Top”

# x86-64 Stack: Pop

## ■ `popq Dest`

- Read value at address given by `%rsp`
- Increment `%rsp` by 8
- Store value at `Dest` (usually a register)

Stack Pointer: `%rsp` →

Stack “Bottom”



Increasing  
Addresses

Stack  
Grows  
Down

Stack “Top”

(The memory doesn't change,  
only the value of `%rsp`)



# Today

## ■ Procedures

- Mechanisms
- Stack Structure
- Calling Conventions
  - Passing control
  - Passing data
  - Managing local data
- Illustration of Recursion

# Code Examples

```
void multstore(long x, long y, long *dest)
{
    long t = mult2(x, y);
    *dest = t;
}
```

```
00000000000400540 <multstore>:
400540: push    %rbx                # Save %rbx
400541: mov     %rdx,%rbx           # Save dest
400544: callq   400550 <mult2>      # mult2(x,y)
400549: mov     %rax, (%rbx)         # Save at dest
40054c: pop     %rbx                # Restore %rbx
40054d: retq                      # Return
```

```
long mult2(long a, long b)
{
    long s = a * b;
    return s;
}
```

```
00000000000400550 <mult2>:
400550: mov     %rdi,%rax           # a
400553: imul    %rsi,%rax           # a * b
400557: retq                      # Return
```

# Procedure Control Flow

- Use stack to support procedure call and return
- **Procedure call:** `call label`
  - Push return address on stack
  - Jump to *label*
- **Return address:**
  - Address of the next instruction right after call
  - Example from disassembly
- **Procedure return:** `ret`
  - Pop address from stack
  - Jump to address

# Control Flow Example #1

```
00000000000400540 <multstore>:  
.  
.  
400544: callq 400550 <mult2>  
400549: mov  %rax, (%rbx)  
.  
.
```

```
00000000000400550 <mult2>:  
400550: mov  %rdi,%rax  
.  
.  
400557: retq
```

0x130

0x128

0x120

%rsp

%rip

0x120

0x400544

# Control Flow Example #2

```
00000000000400540 <multstore>:
```

•

•

```
400544: callq 400550 <mult2>
```

```
400549: mov    %rax, (%rbx) ←
```

•

•

```
00000000000400550 <mult2>:
```

```
400550: mov    %rdi,%rax ←
```

•

•

```
400557: retq
```

0x130

0x128

0x120

0x118

0x400549

%rsp

0x118

%rip

0x400550

# Control Flow Example #3

```
00000000000400540 <multstore>:
```

•

•

```
400544: callq 400550 <mult2>
```

```
400549: mov    %rax, (%rbx) ←
```

•

•

```
00000000000400550 <mult2>:
```

```
400550: mov    %rdi,%rax
```

•

•

```
400557: retq ←
```

0x130

0x128

0x120

0x118

0x400549

%rsp

0x118

%rip

0x400557

# Control Flow Example #4

```
00000000000400540 <multstore>:  
.  
.  
400544: callq 400550 <mult2>  
400549: mov  %rax, (%rbx)  
.  
.
```

```
00000000000400550 <mult2>:  
400550: mov  %rdi,%rax  
.  
.  
400557: retq
```

0x130

0x128

0x120

%rsp

0x120

%rip

0x400549

# Today

## ■ Procedures


- Mechanisms
- Stack Structure
- Calling Conventions
  - Passing control
  - **Passing data**
  - Managing local data
- Illustrations of Recursion & Pointers




# Procedure Data Flow

## Registers


### ■ First 6 arguments



### ■ Return value



## Stack



### ■ Only allocate stack space when needed

# Data Flow Examples

```
void multstore
(long x, long y, long *dest)
{
    long t = mult2(x, y);
    *dest = t;
}
```

```
0000000000400540 <multstore>:
    # x in %rdi, y in %rsi, dest in %rdx
    ...
400541: mov     %rdx,%rbx           # Save dest
400544: callq   400550 <mult2>      # mult2(x,y)
    # t in %rax
400549: mov     %rax, (%rbx)        # Save at dest
    ...
```

```
long mult2
(long a, long b)
{
    long s = a * b;
    return s;
}
```

```
0000000000400550 <mult2>:
    # a in %rdi, b in %rsi
400550: mov     %rdi,%rax           # a
400553: imul    %rsi,%rax           # a * b
    # s in %rax
400557: retq                                # Return
```

# Today

## ■ Procedures

- Mechanisms
- Stack Structure
- Calling Conventions
  - Passing control
  - Passing data
  - **Managing local data**
- Illustration of Recursion

# Stack-Based Languages

## ■ Languages that support recursion

- e.g., C, Pascal, Java
- Code must be “*Reentrant*”
  - Multiple simultaneous instantiations of single procedure
- Need some place to store state of each instantiation
  - Arguments
  - Local variables
  - Return pointer

## ■ Stack discipline

- State for given procedure needed for limited time
  - From when called to when return
- Callee returns before caller does

## ■ Stack allocated in *Frames*

- state for single procedure instantiation

# Call Chain Example


```
yoo (...)  
{  
  .  
  .  
  who ();  
  .  
  .  
}
```

```
who (...)  
{  
  . . .  
  amI ();  
  . . .  
  amI ();  
  . . .  
}
```

```
amI (...)  
{  
  .  
  .  
  amI ();  
  .  
  .  
}
```

**Procedure `amI ()` is recursive**

## Example Call Chain




# Stack Frames

## ■ Contents

- Return information
- Local storage (if needed)
- Temporary space (if needed)

Frame Pointer: `%rbp`  
(Optional)

Stack Pointer: `%rsp`




## ■ Management

- Space allocated when enter procedure
  - “Set-up” code
  - Includes push by **call** instruction
- Deallocated when return
  - “Finish” code
  - Includes pop by **ret** instruction


Stack “Top”

# Example






```
yoo (...)  
{  
  .  
  .  
  who ();  
  .  
  .  
}
```

```
yoo  
  ↓  
who  
  ↓  ↘  
amI  amI  
  ↓  
amI  
  ↓  
amI
```






# Example











# Example






# Example






# Example






# Example






# Example






# Example



# Example






# Example





# Example




# x86-64/Linux Stack Frame

## ■ Current Stack Frame (“Top” to Bottom)

- “Argument build:”  
Parameters for function about to call
- Local variables  
If can’t keep in registers
- Saved register context
- Old frame pointer (optional)

## ■ Caller Stack Frame

- Return address
  - Pushed by **call** instruction
- Arguments for this call



# Example: `incr`

```
long incr(long *p, long val) {  
    long x = *p;  
    long y = x + val;  
    *p = y;  
    return x;  
}
```


```
incr:  
    movq    (%rdi), %rax  
    addq    %rax, %rsi  
    movq    %rsi, (%rdi)  
    ret
```

| Register | Use(s)                        |
|----------|-------------------------------|
| %rdi     | Argument <code>p</code>       |
| %rsi     | Argument <code>val, y</code>  |
| %rax     | <code>x</code> , Return value |

# Example: Calling `incr` #1


```
long call_incr() {  
    long v1 = 15213;  
    long v2 = incr(&v1, 3000);  
    return v1+v2;  
}
```

## Initial Stack Structure



```
call_incr:  
    subq    $16, %rsp  
    movq    $15213, 8(%rsp)  
    movl    $3000, %esi  
    leaq    8(%rsp), %rdi  
    call    incr  
    addq    8(%rsp), %rax  
    addq    $16, %rsp  
    ret
```

## Resulting Stack Structure




# Example: Calling `incr` #2

```
long call_incr() {
    long v1 = 15213;
    long v2 = incr(&v1, 3000);
    return v1+v2;
}
```

```
call_incr:
    subq    $16, %rsp
    movq    $15213, 8(%rsp)
    movl    $3000, %esi
    leaq    8(%rsp), %rdi
    call    incr
    addq    8(%rsp), %rax
    addq    $16, %rsp
    ret
```

## Stack Structure




| Register          | Use(s)               |
|-------------------|----------------------|
| <code>%rdi</code> | <code>&amp;v1</code> |
| <code>%rsi</code> | 3000                 |

# Example: Calling `incr` #2

```
long call_incr() {
    long v1 = 15213;
    long v2 = incr(&v1, 3000);
    return v1+v2;
}
```

## Stack Structure



Aside 1: `movl $3000, %esi`

- Remember, `movl` -> `%eax` zeros out high order 32 bits.
- Why use `movl` instead of `movq`? 1 byte shorter.


```
movl    $3000, %esi
leaq    8(%rsp), %rdi
call    incr
addq    8(%rsp), %rax
addq    $16, %rsp
ret
```

|                   |                      |
|-------------------|----------------------|
| <code>%rdi</code> | <code>&amp;v1</code> |
| <code>%rsi</code> | 3000                 |

# Example: Calling `incr` #2

```
long call_incr() {
    long v1 = 15213;
    long v2 = incr(&v1, 3000);
    return v1+v2;
}
```

## Stack Structure



Aside 2: `leaq 8(%rsp), %rdi`

- Computes `%rsp+8`
- Actually, used for what it is meant!

```
leaq    8(%rsp), %rdi
call    incr
addq    8(%rsp), %rax
addq    $16, %rsp
ret
```


| Case(s) |      |
|---------|------|
| ...     | v1   |
| %rsi    | 3000 |

# Example: Calling `incr` #2

```
long call_incr() {
    long v1 = 15213;
    long v2 = incr(&v1, 3000);
    return v1+v2;
}
```

```
call_incr:
    subq    $16, %rsp
    movq    $15213, 8(%rsp)
    movl    $3000, %esi
    leaq    8(%rsp), %rdi
    call    incr
    addq    8(%rsp), %rax
    addq    $16, %rsp
    ret
```

## Stack Structure



| Register          | Use(s)               |
|-------------------|----------------------|
| <code>%rdi</code> | <code>&amp;v1</code> |
| <code>%rsi</code> | 3000                 |




# Example: Calling `incr` #3

```
long call_incr() {
    long v1 = 15213;
    long v2 = incr(&v1, 3000);
    return v1+v2;
}
```

```
call_incr:
    subq    $16, %rsp
    movq    $15213, 8(%rsp)
    movl    $3000, %esi
    leaq    8(%rsp), %rdi
    call    incr
    addq    8(%rsp), %rax
    addq    $16, %rsp
    ret
```

## Stack Structure




| Register | Use(s) |
|----------|--------|
| %rdi     | &v1    |
| %rsi     | 3000   |

# Example: Calling `incr` #4

## Stack Structure

```
long call_incr() {
    long v1 = 15213;
    long v2 = incr(&v1, 3000);
    return v1+v2;
}
```




```
call_incr:
    subq    $16, %rsp
    movq    $15213, 8(%rsp)
    movl    $3000, %esi
    leaq    8(%rsp), %rdi
    call    incr
    addq    8(%rsp), %rax
    addq    $16, %rsp
    ret
```

| Register | Use(s)       |
|----------|--------------|
| %rax     | Return value |

# Example: Calling `incr` #5a

## Stack Structure


```
long call_incr() {
    long v1 = 15213;
    long v2 = incr(&v1, 3000);
    return v1+v2;
}
```



```
call_incr:
    subq    $16, %rsp
    movq    $15213, 8(%rsp)
    movl    $3000, %esi
    leaq    8(%rsp), %rdi
    call    incr
    addq    8(%rsp), %rax
    addq    $16, %rsp
    ret
```

| Register          | Use(s)       |
|-------------------|--------------|
| <code>%rax</code> | Return value |

## Updated Stack Structure




# Example: Calling `incr` #5b

```
long call_incr() {
    long v1 = 15213;
    long v2 = incr(&v1, 3000);
    return v1+v2;
}
```


```
call_incr:
    subq    $16, %rsp
    movq    $15213, 8(%rsp)
    movl    $3000, %esi
    leaq    8(%rsp), %rdi
    call    incr
    addq    8(%rsp), %rax
    addq    $16, %rsp
    ret
```

## Updated Stack Structure



| Register          | Use(s)       |
|-------------------|--------------|
| <code>%rax</code> | Return value |

## Final Stack Structure



# Register Saving Conventions

## ■ When procedure `yoo` calls `who`:

- `yoo` is the *caller*
- `who` is the *callee*

## ■ Can register be used for temporary storage?

```
yoo:
    . . .
    movq $15213, %rdx
    call who
    addq %rdx, %rax
    . . .
    ret
```

```
who:
    . . .
    subq $18213, %rdx
    . . .
    ret
```

- Contents of register `%rdx` overwritten by `who`
- This could be trouble → something should be done!
  - Need some coordination

# Register Saving Conventions

- When procedure *yoo* calls *who*:
  - *yoo* is the *caller*
  - *who* is the *callee*
- Can register be used for temporary storage?
- Conventions
  - *“Caller Saved”*
    - Caller saves temporary values in its frame before the call
  - *“Callee Saved”*
    - Callee saves temporary values in its frame before using
    - Callee restores them before returning to caller

# x86-64 Linux Register Usage #1

## ■ **%rax**

- Return value
- Also caller-saved
- Can be modified by procedure

## ■ **%rdi, ..., %r9**

- Arguments
- Also caller-saved
- Can be modified by procedure


## ■ **%r10, %r11**

- Caller-saved
- Can be modified by procedure

Return value

Arguments

Caller-saved  
temporaries



# x86-64 Linux Register Usage #2

## ■ **%rbx, %r12, %r13, %r14**


- Callee-saved
- Callee must save & restore

## ■ **%rbp**

- Callee-saved
- Callee must save & restore
- May be used as frame pointer
- Can mix & match

## ■ **%rsp**

- Special form of callee save
- Restored to original value upon exit from procedure





# Quiz Time!

**Check out:**


<https://canvas.cmu.edu/courses/1221>

# Small Exercise

```
long add5(long b0, long b1, long b2, long b3, long b4) {
    return b0+b1+b2+b3+b4;
}

long add10(long a0, long a1, long a2, long a3, long a4, long a5,
           long a6, long a7, long a8, long a9) {
    return add5(a0, a1, a2, a3, a4)+
           add5(a5, a6, a7, a8, a9);
}
```

- Where are a0,..., a9 passed?  
rdi, rsi, rdx, rcx, r8, r9, stack
- Where are b0,..., b4 passed?  
rdi, rsi, rdx, rcx, r8
- Which registers do we need to save?  
Ill-posed question. Need assembly.  
rbx, rbp, r9 (during first call to add5)




# Small Exercise

```
long add5(long b0, long b1, long b2, long b3, long b4) {
    return b0+b1+b2+b3+b4;
}

long add10(long a0, long a1, long a2, long a3, long a4, long a5,
           long a6, long a7, long a8, long a9) {
    return add5(a0, a1, a2, a3, a4)+
           add5(a5, a6, a7, a8, a9);
}
```

```
add10:
    pushq    %rbp
    pushq    %rbx
    movq     %r9, %rbp
    call     add5
    movq     %rax, %rbx
    movq     48(%rsp), %r8
    movq     40(%rsp), %rcx
    movq     32(%rsp), %rdx
    movq     24(%rsp), %rsi
    movq     %rbp, %rdi
    call     add5
    addq     %rbx, %rax
    popq     %rbx
    popq     %rbp
    ret
```


```
add5:
    addq     %rsi, %rdi
    addq     %rdi, %rdx
    addq     %rdx, %rcx
    leaq     (%rcx,%r8), %rax
    ret
```



# Callee-Saved Example #1

```
long call_incr2(long x) {  
    long v1 = 15213;  
    long v2 = incr(&v1, 3000);  
    return x+v2;  
}
```

Initial Stack Structure




- X comes in register **%rdi**.
- We need **%rdi** for the call to incr.
- Where should be put x, so we can use it after the call to incr?

# Callee-Saved Example #2


```
long call_incr2(long x) {  
    long v1 = 15213;  
    long v2 = incr(&v1, 3000);  
    return x+v2;  
}
```

```
call_incr2:  
    pushq    %rbx  
    subq     $16, %rsp  
    movq     %rdi, %rbx  
    movq     $15213, 8(%rsp)  
    movl     $3000, %esi  
    leaq     8(%rsp), %rdi  
    call     incr  
    addq     %rbx, %rax  
    addq     $16, %rsp  
    popq     %rbx  
    ret
```

## Initial Stack Structure



## Resulting Stack Structure




# Callee-Saved Example #3


```
long call_incr2(long x) {
    long v1 = 15213;
    long v2 = incr(&v1, 3000);
    return x+v2;
}
```

```
call_incr2:
    pushq    %rbx
    subq     $16, %rsp
    movq     %rdi, %rbx
    movq     $15213, 8(%rsp)
    movl     $3000, %esi
    leaq     8(%rsp), %rdi
    call     incr
    addq     %rbx, %rax
    addq     $16, %rsp
    popq     %rbx
    ret
```

## Initial Stack Structure



## Resulting Stack Structure




# Callee-Saved Example #4

```
long call_incr2(long x) {  
    long v1 = 15213;  
    long v2 = incr(&v1, 3000);  
    return x+v2;  
}
```

```
call_incr2:  
    pushq    %rbx  
    subq     $16, %rsp  
    movq     %rdi, %rbx  
    movq     $15213, 8(%rsp)  
    movl     $3000, %esi  
    leaq     8(%rsp), %rdi  
    call     incr  
    addq     %rbx, %rax  
    addq     $16, %rsp  
    popq     %rbx  
    ret
```

Stack Structure




- X saved in **%rbx**.
- A callee saved register.

# Callee-Saved Example #5

```
long call_incr2(long x) {
    long v1 = 15213;
    long v2 = incr(&v1, 3000);
    return x+v2;
}
```

```
call_incr2:
    pushq    %rbx
    subq     $16, %rsp
    movq     %rdi, %rbx
    movq     $15213, 8(%rsp)
    movl     $3000, %esi
    leaq     8(%rsp), %rdi
    call     incr
    addq     %rbx, %rax
    addq     $16, %rsp
    popq     %rbx
    ret
```

Stack Structure



- X saved in **%rbx**.
- A callee saved register.




# Callee-Saved Example #6

```
long call_incr2(long x) {
    long v1 = 15213;
    long v2 = incr(&v1, 3000);
    return x+v2;
}
```

```
call_incr2:
    pushq    %rbx
    subq     $16, %rsp
    movq     %rdi, %rbx
    movq     $15213, 8(%rsp)
    movl     $3000, %esi
    leaq     8(%rsp), %rdi
    call     incr
    addq     %rbx, %rax
    addq     $16, %rsp
    popq     %rbx
    ret
```

Stack Structure




- X is safe in **%rbx**
- Return result in **%rax**

# Callee-Saved Example #7

```
long call_incr2(long x) {  
    long v1 = 15213;  
    long v2 = incr(&v1, 3000);  
    return x+v2;  
}
```

```
call_incr2:  
    pushq    %rbx  
    subq     $16, %rsp  
    movq     %rdi, %rbx  
    movq     $15213, 8(%rsp)  
    movl     $3000, %esi  
    leaq     8(%rsp), %rdi  
    call     incr  
    addq     %rbx, %rax  
    addq     $16, %rsp  
    popq     %rbx  
    ret
```

Stack Structure




- Return result in **%rax**

# Callee-Saved Example #8


```
long call_incr2(long x) {
    long v1 = 15213;
    long v2 = incr(&v1, 3000);
    return x+v2;
}
```

```
call_incr2:
    pushq    %rbx
    subq     $16, %rsp
    movq     %rdi, %rbx
    movq     $15213, 8(%rsp)
    movl     $3000, %esi
    leaq     8(%rsp), %rdi
    call     incr
    addq     %rbx, %rax
    addq     $16, %rsp
    popq     %rbx
    ret
```

## Initial Stack Structure



## final Stack Structure



# Today

## ■ Procedures

- Mechanisms
- Stack Structure
- Calling Conventions
  - Passing control
  - Passing data
  - Managing local data
- **Illustration of Recursion**

# Recursive Function

```
/* Recursive popcount */
long pcount_r(unsigned long x) {
    if (x == 0)
        return 0;
    else
        return (x & 1)
            + pcount_r(x >> 1);
}
```

```
pcount_r:
    movl    $0, %eax
    testq   %rdi, %rdi
    je      .L6
    pushq   %rbx
    movq    %rdi, %rbx
    andl    $1, %ebx
    shrq    %rdi
    call    pcount_r
    addq    %rbx, %rax
    popq    %rbx
.L6:
    rep; ret
```

# Recursive Function Terminal Case

```
/* Recursive popcount */
long pcount_r(unsigned long x) {
    if (x == 0)
        return 0;
    else
        return (x & 1)
            + pcount_r(x >> 1);
}
```

```
pcount_r:
    movl    $0, %eax
    testq   %rdi, %rdi
    je      .L6
    pushq   %rbx
    movq    %rdi, %rbx
    andl    $1, %ebx
    shrq    %rdi
    call    pcount_r
    addq    %rbx, %rax
    popq    %rbx
.L6:
    rep; ret
```


| Register | Use(s)       | Type         |
|----------|--------------|--------------|
| %rdi     | x            | Argument     |
| %rax     | Return value | Return value |

# Recursive Function Register Save

```
/* Recursive popcount */
long pcount_r(unsigned long x) {
    if (x == 0)
        return 0;
    else
        return (x & 1)
            + pcount_r(x >> 1);
}
```

```
pcount_r:
    movl    $0, %eax
    testq   %rdi, %rdi
    je      .L6
    pushq   %rbx
    movq    %rdi, %rbx
    andl    $1, %ebx
    shrq    %rdi
    call    pcount_r
    addq    %rbx, %rax
    popq    %rbx
.L6:
    rep; ret
```

| Register | Use(s) | Type     |
|----------|--------|----------|
| %rdi     | x      | Argument |



# Recursive Function Call Setup

```
/* Recursive popcount */
long pcount_r(unsigned long x) {
    if (x == 0)
        return 0;
    else
        return (x & 1)
            + pcount_r(x >> 1);
}
```

```
pcount_r:
    movl    $0, %eax
    testq   %rdi, %rdi
    je      .L6
    pushq   %rbx
    movq    %rdi, %rbx
    andl    $1, %ebx
    shrq    %rdi
    call    pcount_r
    addq    %rbx, %rax
    popq    %rbx
.L6:
    rep; ret
```

| Register | Use(s) | Type          |
|----------|--------|---------------|
| %rdi     | x >> 1 | Rec. argument |
| %rbx     | x & 1  | Callee-saved  |



# Recursive Function Call

```
/* Recursive popcount */
long pcount_r(unsigned long x) {
    if (x == 0)
        return 0;
    else
        return (x & 1)
            + pcount_r(x >> 1);
}
```

```
pcount_r:
    movl    $0, %eax
    testq   %rdi, %rdi
    je      .L6
    pushq   %rbx
    movq    %rdi, %rbx
    andl    $1, %ebx
    shrq    %rdi
    call    pcount_r
    addq    %rbx, %rax
    popq    %rbx
.L6:
    rep; ret
```

| Register | Use(s)                         | Type         |
|----------|--------------------------------|--------------|
| %rbx     | x & 1                          | Callee-saved |
| %rax     | Recursive call<br>return value |              |

# Recursive Function Result

```
/* Recursive popcount */
long pcount_r(unsigned long x) {
    if (x == 0)
        return 0;
    else
        return (x & 1)
            + pcount_r(x >> 1);
}
```

```
pcount_r:
    movl    $0, %eax
    testq   %rdi, %rdi
    je      .L6
    pushq   %rbx
    movq    %rdi, %rbx
    andl    $1, %ebx
    shrq    %rdi
    call    pcount_r
    addq    %rbx, %rax
    popq    %rbx
.L6:
    rep; ret
```


| Register | Use(s)       | Type         |
|----------|--------------|--------------|
| %rbx     | x & 1        | Callee-saved |
| %rax     | Return value |              |

# Recursive Function Completion

```
/* Recursive popcount */
long pcount_r(unsigned long x) {
    if (x == 0)
        return 0;
    else
        return (x & 1)
            + pcount_r(x >> 1);
}
```

```
pcount_r:
    movl    $0, %eax
    testq   %rdi, %rdi
    je      .L6
    pushq   %rbx
    movq    %rdi, %rbx
    andl    $1, %ebx
    shrq    %rdi
    call    pcount_r
    addq    %rbx, %rax
    popq    %rbx
.L6:
    rep; ret
```

| Register | Use(s)       | Type         |
|----------|--------------|--------------|
| %rax     | Return value | Return value |



# Observations About Recursion

## ■ Handled Without Special Consideration

- Stack frames mean that each function call has private storage
  - Saved registers & local variables
  - Saved return pointer
- Register saving conventions prevent one function call from corrupting another's data
  - Unless the C code explicitly does so (e.g., buffer overflow in Lecture 9)
- Stack discipline follows call / return pattern
  - If P calls Q, then Q returns before P
  - Last-In, First-Out

## ■ Also works for mutual recursion

- P calls Q; Q calls P

# x86-64 Procedure Summary

## ■ Important Points

- Stack is the right data structure for procedure call/return
  - If P calls Q, then Q returns before P

## ■ Recursion (& mutual recursion) handled by normal calling conventions

- Can safely store values in local stack frame and in callee-saved registers
- Put function arguments at top of stack
- Result return in **%rax**

## ■ Pointers are addresses of values

- On stack or global

