Risk-Aware Payment Delegation: From Intent to Executable Decisions

Anonymous ACL submission

Abstract

Delegated purchasing must respect existing authorization when interpretations or contractual outcomes remain uncertain. We formulate purchase or refusal without further user interaction by separating joint authorization from worst-case utility. We introduce SET, our executable decision workflow, which selects a purchase admissible across retained states with the highest positive worst-case value, or refuses when none qualifies. On synthetic contractual-boundary tasks across model families, it improves exact decisions and useful completion while reducing unsafe acceptances and false refusals relative to direct decisions under the same policy. Yet a correct current choice does not certify the permissions encoded by the generated conditions. We analyze how ranking conceals false admissions and test this distinction by freezing specifications and varying candidate availability. Across 800 requests and three model configurations, removing at most eight high-ranked offers exposes unauthorized purchases on 48 requests spanning 15 contract templates and all four families. Every witness retains alternatives authorized and positively valued under both generated conditions and references; eight begin with exact decisions. These findings connect intent fidelity to executable decisions and motivate checking the admitted domain alongside the selected purchase: losing a preferred offer does not expand the user's authorization.

1 Introduction

Language agents use external tools to carry out multi-step tasks (Yao et al., 2023; Schick et al., 2023). Benchmarks cover shopping, travel, and service workflows (Yao et al., 2022; Xie et al., 2024; Yao et al., 2025), as well as broader web tasks (Zhou et al., 2024; Deng et al., 2023). ST-WebAgentBench counts completion as successful only when applicable policies are satisfied (Levy et al., 2026). In delegated purchasing, the commitment and its possible consequences must stay within the user's authorization. Cancellation, return, or replacement costs can exceed that authorization even when the initial price is within budget.

Requests can have several readings, and future events determine financial consequences. We study purchase or refusal without another user turn, using only existing authorization. Choosing a convenient reading can permit an unauthorized purchase; refusing every uncertain request can discard useful options. Yet one purchase may satisfy every retained possibility. The task is to find a common authorized purchase with positive worst-case value.

Clarification and uncertainty-aware planning use additional information to improve decisions (Ren et al., 2023; Dong et al., 2026; Suri et al., 2026). We apply the fixed-set max–min principle of Risk-Averse Calibration (RAC) (Kiyani et al., 2025), with purchasing permissions that cannot be traded against utility. Turning intent into executable decisions requires preserving which conditions apply under each reading or event. For example, a loss limit restricts permission; it is not compensation that reduces the loss. That distinction affects both admissibility and value.

We introduce SET to evaluate authorization across retained states and rank admissible purchases by worst-case utility through a fixed procedure. We assess how reliably this workflow turns natural-language delegation into purchasing decisions across model families.

A preferred offer becoming unavailable does not expand the user's authorization. Yet a safe purchase can reflect either a rule that excludes unauthorized offers or a ranking that keeps them from winning. In one controlled replay, a specification initially makes an exact decision, but selects an unauthorized offer after four high-ranked offers are removed, while 59 alternatives remain permitted and positively valued under both its conditions and the reference. The request, permissions, utilities, and surviving offers are unchanged. We therefore

distinguish a correct current decision from a sound admitted domain. Frozen-specification tests examine whether candidate unavailability exposes permissions the original selection left untested, connecting the fidelity of generated authorization to executable decisions.

The paper makes three contributions:

- **Risk-aware decisions under unresolved uncertainty:** a formulation of purchase or refusal that requires a common authorized action and separates its permission from its worst-case value.
- **Authorization beyond the selected action:** an analysis distinguishing current decision correctness from domain soundness, including how errors in generated conditions can remain hidden by ranking.
- **Decision reliability and authorization fidelity:** multi-model boundary and intent tests, together with a prospective frozen-specification study that exposes hidden permissions across contract structures while viable authorized alternatives remain.

Code, benchmark materials, retained responses, evaluation records, and reproduction tools are available in our anonymous artifact package (Appendix B.5).[1]

2 Related Work

Decisions under uncertainty. KnowNo and AmbiK address ambiguous planning instructions (Ren et al., 2023; Ivanova et al., 2025); IntentSim evaluates clarification across language tasks (Zhang and Choi, 2025). AmbigQA and AmbiEnt examine multiple readings in question answering and natural language inference (Min et al., 2020; Liu et al., 2023). Value of Information (VoI) balances clarification gains against user effort (Dong et al., 2026). Structured Argument Uncertainty guided Elicitation Agent (SAGE-Agent) represents uncertainty over tool parameters to select clarification questions (Suri et al., 2026). We study purchase or refusal without another user turn. RAC supplies a max–min rule over prediction sets; related methods study calibrated risk guarantees (Kiyani et al., 2025; Angelopoulos et al., 2024; Zhu et al., 2026). We apply the fixed-set principle to purchasing permissions and a common action across states, with refusal as the outside option. Our analysis does not add a calibration guarantee.

Policy reasoning and decision conditions. Complex-policy studies identify workflow-governing rules as a major reasoning difficulty (Liu et al., 2026). AgentIF examines conditional constraints and rules governing which constraints apply and take priority (Qi et al., 2025). These findings motivate attention to relationships among conditions. Executable reasoning separates interpretation from computation (Gao et al., 2023; Pan et al., 2023; Olausson et al., 2023); semantic parsing captures compositional requests and constrains their representation (Gupta et al., 2018; Shin et al., 2021). Genie maps assistant commands to ThingTalk programs (Campagna et al., 2019), while financial contract languages define interpretation and valuation rules (Peyton Jones et al., 2000). Formalization studies examine translation errors (Liu, 2025; Pei et al., 2025; Quansah et al., 2026). We study their consequences for authorization and worst-case value under retained readings and events.

Agent safeguards and policy compliance. ToolEmu and ToolSword evaluate risks in tool use (Ruan et al., 2024; Ye et al., 2024); AgentDojo and AgentHarm study prompt injection and harmful tasks (Debenedetti et al., 2024; Andriushchenko et al., 2025). GuardAgent, DeAction, AgentSpec, and VeriGuard generate or enforce behavioral constraints (Xiang et al., 2025; Ning et al., 2026; Wang et al., 2026; Miculicich et al., 2026). AgentAuditor assesses evaluator reliability, using strict and lenient standards for ambiguous risk judgments (Luo et al., 2025). Our experiments use explicit purchasing permissions and assess both unauthorized acceptance and missed authorized purchases.

Errors hidden by outcomes. OpenAgentSafety distinguishes safe behavior from unsuccessful unsafe attempts and failures before exposure to risk (Vijayvargiya et al., 2026). Near-Miss, published at the Generation, Evaluation and Metrics (GEM) workshop, detects missing information checks before state-changing actions even when the final outcome is correct (Rabinovich et al., 2026). These studies complement challenge sets, behavioral tests, and contrast sets (McCoy et al., 2019; Ribeiro et al., 2020; Gardner et al., 2020). We examine false

[1] https://anonymous.4open.science/r/risk-aware-payment-delegation-D4FC/

permissions already encoded in a purchase specification but hidden by its selected action. Frozen-specification tests vary availability while viable authorized alternatives remain. They connect the fidelity of executable conditions to the admitted domain, whose soundness cannot be inferred from current decision correctness.

3 Risk-Aware Delegation under Uncertainty

We define which purchases a delegation permits before deciding which is most valuable. The same commitment must remain acceptable across the possibilities retained from the request and its contractual context.

3.1 Authorization and Value across States

Let P be the natural-language request, c its context, and $x = (P, c)$. Let $\mathcal{Z}$ be the space of complete purchases, $C \subseteq \mathcal{Z}$ a finite catalogue, and $z \in C$ a candidate purchase. The nonempty state set $\Theta(x)$ contains retained interpretations, future events, or their combinations. Interpretations determine requirements; events determine purchase consequences. The same purchase is evaluated in every state without further user interaction or state probabilities.

For $\theta \in \Theta(x)$, let $H_\theta(x, z)$ encode hard requirements, $\ell_\theta(x, z)$ financial consequences, $\mathcal{A}_\theta(x)$ the authorized risk region, and $u_\theta(x, z)$ utility on a common cardinal scale. Define

$$F_\theta(x) = \{z : H_\theta(x, z) = 1,\ \ell_\theta(x, z) \in \mathcal{A}_\theta(x)\}, \tag{1}$$

$$F(x) = \bigcap_{\theta \in \Theta(x)} F_\theta(x), \tag{2}$$

$$\psi_x(z) = \inf_{\theta \in \Theta(x)} u_\theta(x, z). \tag{3}$$

Authorization requires one purchase to satisfy every retained state: $\exists z\, \forall \theta$. Separate purchases that work under separate readings do not meet this requirement. With refusal worth zero, the decision solves

$$\max_{z \in C \cap F(x)} \psi_x(z). \tag{4}$$

The agent selects a maximizer only if this maximum is positive. It refuses when the domain is empty or the maximum is nonpositive. Utility ranks authorized purchases; it cannot justify violating a hard requirement or increasing a financial permission. This instantiates RAC's fixed-set max–min principle (Kiyani et al., 2025) with explicit authorization and an outside option.

A common purchase need not resolve meaning. In our ticket tasks, Zhang and Li need tickets within 3,000 monetary units (MU), and "his ticket" must allow a fee-free refund. Two 2,400-MU orders refunding only one traveller each are separately feasible but provide no common purchase. Adding a 2,800-MU order refunding both permits action, with stipulated utility $(3000 - 2800)/1000 = 1/5$. The ambiguity remains. Buying the common order relies on the existing budget and value conditions, not additional authorization (Appendix A.4).

These equations define the target semantics used for offline references. Experimental inputs state events, permissions, and utility conventions, but do not supply their executable reference expressions. Errors in deriving the conditions, including omitted readings and incorrect clause binding, remain part of the end-to-end evaluation.

3.2 Purchase, Refusal, and Incomplete Evaluation

The preparation procedure f maps x and attribute schema Σ (names and types) to executable conditions Q. A valid Q has $K \geq 1$ clauses, indexed by $j = 1, \ldots, K$, each specifying a hard predicate $\widehat{H}_j$, financial-permission predicate $\widehat{R}_j$, and utility $\widehat{u}_j$. Hats denote quantities computed from Q for fixed x. Predicate conjunction defines $\widehat{F}_C$, the admitted catalogue domain; minimum utility gives $\widehat{\psi}$. Algorithm 1 performs selection.

The procedure exactly solves the compiled version of Equation (4) on a complete, resolved finite catalogue. Every candidate's admissibility, and every admitted candidate's state utilities, must be known. A feasible offer cannot be certified optimal while a competitor has unknown value. Correctness relative to the request additionally requires the decision conditions to preserve its target semantics.

REFUSE establishes that the evaluated conditions admit no positive-value solution. FAIL means the required compilation or evaluation did not complete. Both prevent purchase, but only the former is a decision about the evaluated domain. The procedure computes all maximizers; the response may name a nonempty subset of tied optima with their correct value, from which one complete purchase is chosen. Exhaustive evaluation costs $O(MKT)$ for

Algorithm 1 Risk-aware purchase selection

Input: request/context x, attribute schema Σ, catalogue C
Output: ACCEPT, REFUSE, or FAIL, with diagnostics

1 $Q \leftarrow f(x, \Sigma)$ *derive conditions; no C*
2 Validate the generated conditions and their types.
3 If invalid, return FAIL(compilation).
4 Evaluate every generated state on every $z \in C$; retain the condition/value matrix.
5 If execution is invalid, return FAIL(execution).
6 For each $z \in C$, set $\widehat{f}(z) = \bigwedge_j (\widehat{H}_j(z) \wedge \widehat{R}_j(z))$.
7 If catalogue coverage or any $\widehat{f}(z)$ is unresolved, or a candidate with $\widehat{f}(z) = 1$ has an unknown state utility, return FAIL(uncertified).
8 $\widehat{F}_C \leftarrow \{z \in C : \widehat{f}(z) = 1\}$.
9 If $\widehat{F}_C = \varnothing$, return REFUSE(infeasible).
10 For $z \in \widehat{F}_C$, set $\widehat{\psi}(z) = \min_j \widehat{u}_j(z)$.
11 $v \leftarrow \max_{z \in \widehat{F}_C} \widehat{\psi}(z)$.
12 If $v \leq 0$, return REFUSE(nonpositive value).
13 Return ACCEPT($\{z \in \widehat{F}_C : \widehat{\psi}(z) = v\}, v$).

Fixed evaluator: lines 2–13. Reference answers are used only in offline evaluation.

M candidates, K generated states, and expression cost T. Appendix A.2 gives the execution rules and guarantee conditions.

4 Why Safe Choices Can Hide Authorization Errors

A safe purchase does not show whether a rule excludes unauthorized offers or merely ranks them lower. Executable delegation requires permissions that hold independently of ranking. We distinguish that requirement from correctness of the selected action.

4.1 Selected Actions and Admitted Domains

Write $F_C = C \cap F(x)$ for the reference-authorized domain. A selected purchase $z^\star$ is safe when $z^\star \in F_C$. Soundness of the generated authorization domain is stronger:

$$\widehat{F}_C \subseteq F_C. \tag{5}$$

The difference $\widehat{F}_C \setminus F_C$ contains unauthorized offers the rule admits, including those never selected. An exact acceptance selects a reference maximizer and reports its value correctly. Even this stronger outcome check does not establish that the difference is empty. It checks the chosen purchase, leaving permissions for unselected offers untested.

The reverse difference, $F_C \setminus \widehat{F}_C$, contains authorized offers the rule excludes, potentially removing the best purchase or causing false refusal. An empty domain is sound but can miss an authorized task. Refusal is correct only when no reference-authorized purchase has positive guaranteed value. We therefore evaluate useful completion alongside authorization soundness.

4.2 Omitted States Affect Permission and Value

Fix x and write $\Theta = \Theta(x)$. For a nonempty $S \subseteq \Theta$, let F_S and ψ_S denote the intersection in Equation (2) and the worst-case utility in Equation (3), restricted to states in S. Retaining only $\Theta' \subseteq \Theta$, with $\Theta' \neq \varnothing$ and all remaining state functions unchanged, gives

$$F_\Theta \subseteq F_{\Theta'}, \qquad \psi_{\Theta'}(z) \geq \psi_\Theta(z). \tag{6}$$

Removing conjuncts cannot shrink the admissible set, and removing terms cannot lower the worst-case value. A single omission can thus weaken authorization and inflate the value used for selection. Both inequalities can be equalities: a redundant state changes neither quantity. The relevant issue is whether its conditions affect the aggregate, not the number of labels emitted. Equivalent merged conditions preserve the decision semantics.

In the hotel tasks, "his room" binds one guest to the arrival-dependent cancellation deadline, fee checked against the cap, and utility penalty. Omitting that reading can remove both a permission check and a source of low value. Incorrect binding is a separate error; Equation (6) assumes deletion with all remaining functions fixed. Appendix D gives the task semantics.

State omission is one source of incorrect permission. Clause aggregation and financial-consequence calculations can also be wrong even when all relevant event terms are present. The availability analysis below applies to the resulting domain, regardless of the error source.

4.3 Availability and Ranking Can Mask Permission Errors

For a fixed request and fully evaluated specification, restricting C to $C' \subseteq C$ leaves surviving offers' permissions and utilities unchanged: $\widehat{F}_{C'} = \widehat{F}_C \cap C'$ and $F_{C'} = F_C \cap C'$. Thus a sound domain remains sound under deletion. Availability can expose an existing false permission, not create one.

Suppose the only admitted offers are reference-authorized a, c and unauthorized b, with $\psi_x(c) > 0$ and

$$\widehat{\psi}(a) > \widehat{\psi}(b) > \widehat{\psi}(c) > 0. \tag{7}$$

The selector chooses a. Removing it exposes b, although c remains permitted and positively valued under both the specification and reference. The failure does not require losing all viable authorized choices. An incorrectly admitted offer with nonpositive estimated value, however, cannot win under deletion alone. Domain errors and unsafe purchases therefore need separate measurements.

Section 5.4 tests these conditions on model-generated specifications, changing availability alone while retaining viable authorized alternatives. It asks whether the executable conditions preserve the user's permission beyond the currently selected purchase.

5 Experimental Study

Boundary and intent tests assess decision reliability under a shared policy (Sections 5.2–5.3); frozen-specification replays test authorization beyond the selected purchase, following the analysis in Section 4 (Section 5.4). Table 1 maps these questions to their evidence.

5.1 Tasks, Comparisons, and Scoring

Contractual boundaries. We construct 200 tasks from 20 templates in four families: coupon cancellation, insured cancellation, threshold-dependent returns, and service replacement. Contracts combine overlapping groups, compensation layers, shipping charges, and item/order caps. Each purchase has six components; all subsets of up to four affected components give 57 events, including the empty event. Catalogues contain 128–1,024 candidates. One MU equals 100 integer subunits.

Each template contributes five feasible/infeasible pairs. A feasible task has exactly one authorized positive-value candidate. Increasing its fee by the feasible margin plus one subunit puts its worst loss exactly one subunit above the limit; other attributes and offer order remain fixed. The pairs isolate responsiveness to authorization boundaries (Ribeiro et al., 2020; Gardner et al., 2020). Separate cash-ledger and expression implementations agree on 6,712,320 candidate–event checks, supplemented by 25,600 random-attribute checks and three hand-calculated witnesses. Inputs and references were frozen before primary calls (Appendix B).

Decision workflows. DIRECT receives the request, schema, catalogue, and the joint-feasibility, worst-value, and refusal rules of Section 3. It returns a decision and utility without external execution. SET separates preparation of the state-dependent conditions from fixed catalogue evaluation. The preparation stage receives the request and schema but excludes the catalogue. Conditions use exact arithmetic and retain clause scope, compensation order, and value binding. Evaluation semantics and observed compilations are in Appendix A. The shared decision policy fixes the target behavior for both methods; the comparison measures how reliably each complete workflow realizes that behavior. Appendix E reports the textual-checklist baseline and sensitivity analyses.

Outcomes. An *exact decision* agrees with the reference and, for acceptance, returns authorized maximizers with correct utility. *Safe completion* is exact acceptance on a feasible task. *Unsafe acceptance* selects a reference-infeasible offer; *false refusal* rejects an available authorized positive-value purchase. *Other* includes value errors and failed or unresolved execution, never credited as correct refusal. All outcomes remain in cohort denominators. Workflow comparisons are paired within configurations, with one semantic attempt and bounded transport retries (Appendix B). Inputs and evaluation records accompany the artifact (Appendix B.5).

5.2 Useful Completion at Authorization Boundaries

All eleven primary configurations improve exactness and safe completion while reducing unsafe acceptances and false refusals (Figure 1). For DeepSeek low/high, exact decisions rise from 248/400 (62.0%) to 369/400 (92.25%). The gain is 30.25 percentage points, with a 95% template-cluster bootstrap interval of $[22.75, 37.25]$, retaining both settings within each template. Exact purchases rise from 100 to 186 across 200 feasible outcomes; unsafe acceptances fall from 79 to 9 and false refusals from 53 to 1. On these tasks, stronger safety accompanies more useful purchases and fewer missed opportunities.

Gains cover all four contract families and 18 of 20 templates at each DeepSeek setting. They vary across models: GLM high improves from 64/200 to 188/200, Sol medium from 137/200 to 196/200, and Opus medium from 142/200 to 194/200. Qwen Max low rises from 59 to 87 exact outcomes but retains 46 unsafe acceptances. Appendix C gives complete partitions and template results. These pairs test authorization boundaries; their unique feasible offers limit conclusions about ranking.

Research question	Controlled evidence	Purpose and protocol
Can the agent complete safely?	200 tasks, 20 contract templates, 100 feasibility pairs; 11 configurations	Authorization boundaries App. B–C
Can it act across unresolved readings?	Three intent families; 147 paired task–configuration units	Common actions and value App. D
What can a safe choice conceal?	800 new requests, 20 templates, three configurations; frozen-specification availability tests	Permissions and viable alternatives App. F
How do settings affect the workflow?	Effort and language panels; prompt and output-budget controls	Configuration sensitivity App. E

Table 1: **Questions, evidence, and scope.** Primary compilation excludes catalogues; intent tests supply them. Availability replays freeze generated permissions and utilities. Studies share tasks and are not pooled as independent samples.




Figure 1: **Risk-aware decisions across models and contract structures.** Plain bars denote Direct; hatched bars denote SET. (a) Exact-decision rates by configuration (DS: DeepSeek). (b) All eleven configurations: unsafe acceptance over 2,200 outcomes and safe completion over 1,100 feasible outcomes per method. (c) DeepSeek low/high across four contract families, each pooling 100 outcomes per method from five templates. Axes start at zero; configurations share tasks.

5.3 Purchasing under Signaled Intent Ambiguity

Figure 2 reports 294 outcomes from 147 matched task–configuration pairs covering ticket-holder reference, conditional hotel cancellation, and individual versus batch exchange-cost limits. Both methods receive the catalogue, ambiguity cues, and decision policy; SET's primary compilation instead withholds catalogues. Table 12 gives denominators.

SET improves exactness in all four configurations as risk limits, penalties, and the positive-value boundary vary. Qwen records six unsafe acceptances with SET and five with Direct, so better exactness does not ensure fewer unsafe actions in every panel. Separate checks illustrate common purchases, empty intersections, worst-case ranking, and the zero-value boundary (Appendix D.3); they do not establish a comparative accuracy advantage.




Figure 2: **Decisions with unresolved user intent.** Exact-decision rates over 294 outcomes from 147 matched task–configuration pairs, using each configuration's denominator. Compilation is catalogue-visible and ambiguity is explicitly signaled. Appendix D gives counts and errors.




Figure 3: **Availability exposes permission errors despite viable alternatives.** Percentage of planned trials with a safe-to-unsafe transition within k removals, following the original generated ranking. Each witness retains a jointly authorized alternative with positive value under both valuations. The primary budget is $k = 8$. Curves measure cumulative directed exposure, not random-stockout probability. Appendix F.2 gives coverage and controls.

5.4 Authorization beyond the Selected Purchase

Frozen-specification test. We freeze 800 new requests from 20 templates in four contract families, each with 128 offers. DeepSeek Flash, GLM, and Qwen Max, all at low effort, receive requests, contracts, and schemas without catalogues. Catalogues are fixed before generation and stratified by whether their highest-reference-value offer is authorized (Appendix F.1).

The primary stress test removes prefixes of the original generated ranking, without using reference labels to choose removals. Exposure requires an initially safe purchase to become unauthorized within eight removals, while an alternative remains permitted and positively valued under both generated conditions and references. Permissions, utilities, surviving attributes, and the selector stay fixed; replays make no model calls.

Hidden permissions and behavioral exposure. Across the planned cohort, 2.96% produce safe purchases that conceal false admissions; the primary budget exposes 2.00%. Figure 3 shows cumulative exposure by removal budget and its structural coverage. The exposed specifications span 48 distinct requests, 15 templates, all four families, and all three configurations. Their minimum witnesses retain 40–67 viable authorized alternatives. Every exposed maximizer is unauthorized, so these transitions do not depend on mixed-authorization ties. Native-expression replay and independent contract calculations verify the witnesses.

Exposure from exact decisions. 8 exposed specifications initially select a reference maximizer and report its value correctly, spanning four templates and two configurations. In one GLM coupon-cancellation case, removing four offers exposes an unauthorized purchase while 59 viable authorized alternatives remain. Its risk expression includes all 57 event terms but omits a group charge within one term. The generated worst loss is 263,194 subunits, whereas the reference loss is 268,094 against a limit of 267,994. The original exact choice had left this false permission untested (Appendix F.3).

From intent to executable decisions. These transitions expose permissions already present in the frozen specification. Candidate removal changes which admitted offer wins, not whether an unchanged offer is authorized. The surviving alternatives also remain permitted and positively valued by the specification itself. Thus the failure requires neither a new model response nor the loss of all viable authorized choices. It reflects the distinction in Section 3: complete execution can consistently apply generated conditions without establishing their fidelity to the request. Appendix F.2 reports all templates, random removals, reverse transitions, and non-triggering cases.




Figure 4: **Method performance across reasoning settings and task languages.** (a) Sol, Terra, and Luna: 18 settings, 60 tasks per method. Off denotes none; L/M/H/XH denote low/medium/high/xhigh. (b) DeepSeek: 60 tasks per language and method. Plain bars denote Chinese (ZH), hatched bars English (EN). Tables 14 and 15 give counts.

5.5 Sensitivity Analyses

On the 60-task panel, SET improves exactness in 17 of 18 Sol/Terra/Luna settings (Figure 4a); Luna off falls from 25/60 to 13/60. Sol reaches 60/60 at medium, high, and max; Terra reaches 59/60 at xhigh and max. Requested effort does not measure equal provider computation.

Chinese/English wording preserves quantities, events, and authorization. Across six DeepSeek setting–language cells, Direct achieves 33–36/60 exact decisions and SET 55–59/60 (Figure 4b). Appendix E gives complete results and prompt and output-budget controls.

6 Conclusion

SET separates authorization across retained states from worst-case value to make executable purchase-or-refusal decisions. On controlled tasks, it improves useful completion while reducing unsafe acceptances and false refusals. Frozen-specification tests reveal a limit of current-outcome evaluation: a safe or exact purchase can conceal false permissions that candidate unavailability exposes, even while viable authorized alternatives remain. Cross-template replays and original-expression checks trace these transitions to errors already present in the generated conditions. Faithful payment delegation requires checking the admitted domain alongside the selected purchase. Losing a preferred offer does not expand the user's authorization.

Limitations

The evaluated contracts are synthetic, with complete catalogues, known attributes, correct item grounding, and finite state sets. Risk limits and utility are supplied as inputs. The main benchmark isolates authorization boundaries. Its unique feasible candidate provides limited evidence about ranking among several admissible purchases. The availability study instead retains multiple viable purchases and tests a constructed, reference-stratified distribution. Its directed-removal rates describe pressure on frozen specifications, not random stockouts or deployment frequencies. Intent tests signal unresolved readings explicitly. The evaluation does not cover open-ended interpretation discovery, hidden merchant terms, unknown inventory, fraud, or settlement.

Decision conditions can omit a relevant requirement or bind it to the wrong state, even when the resulting specification executes successfully. Reference implementations check consistency with stipulated semantics and share a development workflow. Configuration, language, and diagnostic panels overlap and do not provide independent task samples. Catalogue visibility and provider compute differ across some controls. The appendix specifies the reported cohorts and evaluation protocols. Workflow gains concern the complete decision process; availability replays test frozen generated conditions. Earlier selected-output and exploratory studies remain separately archived and

are not pooled with these results.

Ethical Considerations

All purchases are synthetic, with no monetary transfers or customer records. Financial consequences follow stipulated benchmark contracts. Saved artifacts distinguish original responses, reference-assisted interventions, and subsequent analysis. In deployment, erroneous acceptance could cause financial loss, while erroneous refusal could prevent access to a needed service. A deployed system would need explicit authorization and failure handling. Correct execution alone cannot establish that a compiled specification faithfully represents the user's request.

References

Maksym Andriushchenko, Alexandra Souly, Mateusz Dziemian, Derek Duenas, Maxwell Lin, Justin Wang, Dan Hendrycks, Andy Zou, Zico Kolter, Matt Fredrikson, Yarin Gal, and Xander Davies. 2025. AgentHarm: A benchmark for measuring harmfulness of LLM agents. In *The Thirteenth International Conference on Learning Representations*, pages 79185–79220.

Anastasios N. Angelopoulos, Stephen Bates, Adam Fisch, Lihua Lei, and Tal Schuster. 2024. Conformal risk control. In *International Conference on Learning Representations*, volume 2024, pages 55198–55218.

Giovanni Campagna, Silei Xu, Mehrad Moradshahi, Richard Socher, and Monica S. Lam. 2019. Genie: A generator of natural language semantic parsers for virtual assistant commands. In *Proceedings of the 40th ACM SIGPLAN Conference on Programming Language Design and Implementation*, pages 394–410. Association for Computing Machinery.

Edoardo Debenedetti, Jie Zhang, Mislav Balunovic, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. 2024. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. In *Advances in Neural Information Processing Systems*, volume 37, pages 82895–82920.

Xiang Deng, Yu Gu, Boyuan Zheng, Shijie Chen, Samuel Stevens, Boshi Wang, Huan Sun, and Yu Su. 2023. Mind2Web: Towards a generalist agent for the web. In *Advances in Neural Information Processing Systems*, volume 36, pages 28091–28114.

Yijiang River Dong, Tiancheng Hu, Zheng Hui, Caiqi Zhang, Ivan Vulić, Andreea Bobu, and Nigel Collier. 2026. Value of information: A framework for human–agent communication. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 42879–42896, San Diego, California, United States. Association for Computational Linguistics.

Rotem Dror, Gili Baumer, Segev Shlomov, and Roi Reichart. 2018. The hitchhiker's guide to testing statistical significance in natural language processing. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1383–1392, Melbourne, Australia. Association for Computational Linguistics.

Luyu Gao, Aman Madaan, Shuyan Zhou, Uri Alon, Pengfei Liu, Yiming Yang, Jamie Callan, and Graham Neubig. 2023. PAL: Program-aided language models. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 10764–10799. PMLR.

Matt Gardner, Yoav Artzi, Victoria Basmova, Jonathan Berant, Ben Bogin, Sihao Chen, Pradeep Dasigi, Dheeru Dua, Yanai Elazar, Ananth Gottumukkala, Nitish Gupta, Hanna Hajishirzi, Gabriel Ilharco, Daniel Khashabi, Kevin Lin, Jiangming Liu, Nelson F. Liu, Phoebe Mulcaire, Qiang Ning, and 7 others. 2020. Evaluating models' local decision boundaries via contrast sets. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 1307–1323, Online. Association for Computational Linguistics.

Sonal Gupta, Rushin Shah, Mrinal Mohit, Anuj Kumar, and Michael Lewis. 2018. Semantic parsing for task oriented dialog using hierarchical representations. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 2787–2792. Association for Computational Linguistics.

Anastasiia Ivanova, Eva Bakaeva, Zoya Volovikova, Alexey K. Kovalev, and Aleksandr I. Panov. 2025. AmbiK: Dataset of ambiguous tasks in kitchen environment. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 33216–33241, Vienna, Austria. Association for Computational Linguistics.

Shayan Kiyani, George J. Pappas, Aaron Roth, and Hamed Hassani. 2025. Decision theoretic foundations for conformal prediction: Optimal uncertainty quantification for risk-averse agents. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 30943–30965. PMLR.

Ido Levy, Ben Wiesel, Sami Marreed, Alon Oved, Avi Yaeli, Nir Mashkif, and Segev Shlomov. 2026. ST-WebAgentBench: A benchmark for evaluating safety and trustworthiness in web agents. In *International Conference on Learning Representations*, pages 122213–122255.

Alisa Liu, Zhaofeng Wu, Julian Michael, Alane Suhr, Peter West, Alexander Koller, Swabha Swayamdipta, Noah A. Smith, and Yejin Choi. 2023. We're afraid

language models aren't modeling ambiguity. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 790–807. Association for Computational Linguistics.

Jiateng Liu, Zhenhailong Wang, Xiaojiang Huang, Yingjie Li, Xiang Li, Chenlei Guo, Xing Fan, Ruhi Sarikaya, and Heng Ji. 2026. Analyzing and internalizing complex policy documents for LLM agents. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 16814–16851, San Diego, California, United States. Association for Computational Linguistics.

Junnan Liu. 2025. Few-shot natural language to first-order logic translation via code generation. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 10939–10960, Albuquerque, New Mexico. Association for Computational Linguistics.

Hanjun Luo, Shenyu Dai, Chiming Ni, Xinfeng Li, Guibin Zhang, Kun Wang, Tongliang Liu, and Hanan Salam. 2025. AgentAuditor: Human-level safety and security evaluation for LLM agents. In *Advances in Neural Information Processing Systems*, volume 38, pages 43241–43298. Curran Associates, Inc.

R. Thomas McCoy, Ellie Pavlick, and Tal Linzen. 2019. Right for the wrong reasons: Diagnosing syntactic heuristics in natural language inference. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3428–3448. Association for Computational Linguistics.

Lesly Miculicich, Mihir Parmar, Hamid Palangi, Krishnamurthy Dj Dvijotham, Mirko Montanari, Tomas Pfister, and Long T. Le. 2026. VeriGuard: Enhancing LLM agent safety via verified code generation. In *ACL 2026*.

Sewon Min, Julian Michael, Hannaneh Hajishirzi, and Luke Zettlemoyer. 2020. AmbigQA: Answering ambiguous open-domain questions. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 5783–5797. Association for Computational Linguistics.

Yuting Ning, Jaylen Jones, Zhehao Zhang, Chentao Ye, Weitong Ruan, Junyi Li, Rahul Gupta, and Huan Sun. 2026. When actions go off-task: Detecting and correcting misaligned actions in computer-use agents. In *Proceedings of the 43rd International Conference on Machine Learning*, volume 306 of *Proceedings of Machine Learning Research*, pages 93346–93375. PMLR.

Theo X. Olausson, Alex Gu, Benjamin Lipkin, Cedegao E. Zhang, Armando Solar-Lezama, Joshua B. Tenenbaum, and Roger Levy. 2023. LINC: A neurosymbolic approach for logical reasoning by combining language models with first-order logic provers. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 5153–5176, Singapore. Association for Computational Linguistics.

Liangming Pan, Alon Albalak, Xinyi Wang, and William Yang Wang. 2023. Logic-LM: Empowering large language models with symbolic solvers for faithful logical reasoning. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 3806–3824, Singapore. Association for Computational Linguistics.

Yu Pei, Yongping Du, and Xingnan Jin. 2025. FoVer: First-order logic verification for natural language reasoning. *Transactions of the Association for Computational Linguistics*, 13:1340–1359.

Simon Peyton Jones, Jean-Marc Eber, and Julian Seward. 2000. Composing contracts: An adventure in financial engineering. In *Proceedings of the ACM SIGPLAN International Conference on Functional Programming*, pages 280–292. ACM.

Yunjia Qi, Hao Peng, Xiaozhi Wang, Amy Xin, Youfeng Liu, Bin Xu, Lei Hou, and Juanzi Li. 2025. AgentIF: Benchmarking instruction following of large language models in agentic scenarios. In *Advances in Neural Information Processing Systems*, volume 38. Curran Associates, Inc. Datasets and Benchmarks Track.

Paapa Kwesi Quansah, Pablo Rivas Perea, and Ernest Bonnah. 2026. VERIFY: A novel multi-domain dataset grounding LTL in contextual natural language via provable intermediate logic. In *International Conference on Learning Representations*, volume 2026, pages 86416–86453.

Ella Rabinovich, David Boaz, Naama Zwerdling, and Ateret Anaby-Tavor. 2026. Near-Miss: Latent policy failure detection in agentic workflows. In *Proceedings of the Fifth Workshop on Generation, Evaluation and Metrics (GEM)*, pages 296–308, San Diego, California, USA. Association for Computational Linguistics.

Allen Z. Ren, Anushri Dixit, Alexandra Bodrova, Sumeet Singh, Stephen Tu, Noah Brown, Peng Xu, Leila Takayama, Fei Xia, Jake Varley, Zhenjia Xu, Dorsa Sadigh, Andy Zeng, and Anirudha Majumdar. 2023. Robots that ask for help: Uncertainty alignment for large language model planners. In *Proceedings of The 7th Conference on Robot Learning*, volume 229 of *Proceedings of Machine Learning Research*, pages 661–682. PMLR.

Marco Tulio Ribeiro, Tongshuang Wu, Carlos Guestrin, and Sameer Singh. 2020. Beyond accuracy: Behavioral testing of NLP models with CheckList. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4902–4912, Online. Association for Computational Linguistics.

Yangjun Ruan, Honghua Dong, Andrew Wang, Silviu Pitis, Yongchao Zhou, Jimmy Ba, Yann Dubois, Chris J. Maddison, and Tatsunori Hashimoto. 2024. Identifying the risks of LM agents with an LM-emulated sandbox. In *The Twelfth International Conference on Learning Representations*, pages 27031–27098.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023. Toolformer: Language models can teach themselves to use tools. In *Advances in Neural Information Processing Systems*, volume 36, pages 68539–68551.

Richard Shin, Christopher H. Lin, Sam Thomson, Charles Chen, Subhro Roy, Emmanouil Antonios Platanios, Adam Pauls, Dan Klein, Jason Eisner, and Benjamin Van Durme. 2021. Constrained language models yield few-shot semantic parsers. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 7699–7715. Association for Computational Linguistics.

Manan Suri, Puneet Mathur, Nedim Lipka, Franck Dernoncourt, Ryan A. Rossi, and Dinesh Manocha. 2026. Structured uncertainty guided clarification for LLM agents. In *Findings of the Association for Computational Linguistics: ACL 2026*, pages 40811–40838, San Diego, California, United States. Association for Computational Linguistics.

Sanidhya Vijayvargiya, Aditya Bharat Soni, Xuhui Zhou, Zora Zhiruo Wang, Nouha Dziri, Graham Neubig, and Maarten Sap. 2026. OpenAgentSafety: A comprehensive framework for evaluating real-world AI agent safety. In *International Conference on Learning Representations*, pages 99089–99114.

Haoyu Wang, Christopher M. Poskitt, and Jun Sun. 2026. AgentSpec: Customizable runtime enforcement for safe and reliable LLM agents. In *Proceedings of the 48th IEEE/ACM International Conference on Software Engineering*, pages 2938–2950.

Zhen Xiang, Linzhi Zheng, Yanjie Li, Junyuan Hong, Qinbin Li, Han Xie, Jiawei Zhang, Zidi Xiong, Chulin Xie, Carl Yang, Dawn Song, and Bo Li. 2025. GuardAgent: Safeguard LLM agents via knowledge-enabled reasoning. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 68316–68342. PMLR.

Jian Xie, Kai Zhang, Jiangjie Chen, Tinghui Zhu, Renze Lou, Yuandong Tian, Yanghua Xiao, and Yu Su. 2024. TravelPlanner: A benchmark for real-world planning with language agents. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 54590–54613. PMLR.

Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. 2022. WebShop: Towards scalable real-world web interaction with grounded language agents. In *Advances in Neural Information Processing Systems*, volume 35, pages 20744–20757. Curran Associates, Inc.

Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. 2025. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. In *The Thirteenth International Conference on Learning Representations*, pages 9965–10017.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. ReAct: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*.

Junjie Ye, Sixian Li, Guanyu Li, Caishuang Huang, Songyang Gao, Yilong Wu, Qi Zhang, Tao Gui, and Xuanjing Huang. 2024. ToolSword: Unveiling safety issues of large language models in tool learning across three stages. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2181–2211. Association for Computational Linguistics.

Michael J.Q. Zhang and Eunsol Choi. 2025. Clarify when necessary: Resolving ambiguity through interaction with LMs. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 5541–5558, Albuquerque, New Mexico. Association for Computational Linguistics.

Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. 2024. WebArena: A realistic web environment for building autonomous agents. In *The Twelfth International Conference on Learning Representations*, pages 15585–15606.

Zihan Zhu, Shayan Kiyani, George J. Pappas, and Hamed Hassani. 2026. Conformal risk-averse decision making with action conditional guarantee. In *Proceedings of the 43rd International Conference on Machine Learning*, volume 306 of *Proceedings of Machine Learning Research*, pages 167248–167276. PMLR.

Appendix guide. A: decision semantics and implementation; B: tasks and protocol; C: complete primary results; D: retained-intent decisions; E: textual guidance and sensitivity; F: availability study and verification.

A Decision Semantics and Implementation Details

A.1 Decision semantics and assumptions

The formulation in Section 3 fixes a nonempty retained state set and utilities on a common cardinal scale, bounded over the finite experimental domain. It requires no unique reading, state probabilities, linearity, or convexity. Correct execution implies correctness for the request only when generated conditions preserve its decision-relevant semantics. We use RAC's fixed-set principle (Kiyani et al., 2025), without implementing conformal coverage or action-conditional calibration.

A.2 Generated conditions and evaluation

The SET implementation uses a small expression language to encode the conditions used by Algorithm 1. A specification Q contains state-indexed clauses $(\widehat{H}_j, \widehat{R}_j, \widehat{u}_j)$. Each state record contains a label and expressions `hard`, `risk`, and `utility`. Boolean expressions support conjunction, disjunction, negation, comparisons, and conditionals. Arithmetic supports exact literals, basic operations, minimum, maximum, and absolute value. Boolean and numeric values have distinct types. Expression variables refer to attributes in the schema. A missing attribute needed for a feasibility check leaves that check uncertified. The primary benchmark provides complete attributes.

For the K generated clauses, indexed by $j = 1, \ldots, K$, evaluation gives

$$\widehat{f}(z) = \bigwedge_{j=1}^{K} (\widehat{H}_j(z) \wedge \widehat{R}_j(z)), \tag{8}$$

$$\widehat{\psi}(z) = \min_{1 \le j \le K} \widehat{u}_j(z). \tag{9}$$

Algorithm 1 requires complete enumeration of C, a decided $\widehat{f}(z)$ for every candidate, and known state utilities whenever $\widehat{f}(z) = 1$. A known false conjunct determines an aggregate predicate even if another conjunct is unknown. Invalid expressions or unresolved required checks produce failure before selection. The evaluator forms $\widehat{F}_C = \{z \in C : \widehat{f}(z) = 1\}$ and its maximizing set $Z^\star$. The scorer accepts a nonempty subset of tied positive-value maximizers with the correct guaranteed value; one complete purchase is chosen from that subset. Equivalent merged clauses may encode the same decision functions.

Exactness on the declared domain. After these checks, membership in $\widehat{F}_C$ is decided for every $z \in C$, and all values over that domain are known. Finite enumeration therefore returns the complete set of maximizers when the maximum is positive. Otherwise, an empty domain or a nonpositive maximum proves that the compiled problem has no positive-value option. No unresolved candidate is silently excluded from the optimization.

Incomplete or uncertified execution counts as Other in the outcome protocol (Appendix B.3).

Concrete syntax, serialization, decoding, and runtime bounds are documented with the implementation in the artifact. The evaluation semantics and certification conditions above apply to the generated specification.

Contract: Up to four of six services may cancel. Insurance pays half the gross loss above an order deductible, capped by coverage. The administrative fee is uncovered.

Generated conditions (equivalent notation, MU): let G_4 sum the four largest component losses; d, c, a, p denote deductible, coverage, admin, and price. The worst net loss is $\widehat{L}$.

$$\widehat{L} = G_4 - \min\{c, \max(0, G_4 - d)/2\} + a,$$
$$\widehat{H} = [p \le 12{,}000], \quad \widehat{R} = [\widehat{L} \le 2{,}000],$$
$$\widehat{u} = 20{,}000 - p - \widehat{L}.$$

Selected offer: price / gross worst loss	8,568.35 / 880
Deductible / payout cap / admin	149 / 73 / 1,192
Worst net loss / guaranteed value	1,999 / 9,432.65

Table 2: **Observed primary compilation.** DeepSeek high generates the clause without seeing the catalogue. Complete-domain execution selects the authorized offer among 256 candidates. The shortened expressions agree with the retained output and all 57-event reference calculations (Appendix A.3).

A.3 Observed primary contract compilation

Table 2 uses a retained DeepSeek high output for template b2, second stratum, generated without the catalogue. Its clause sums the four largest losses as the total minus the smallest and second-smallest, expressing the latter through pairwise maxima. We abbreviate this as G_4 and rename variables. The table converts original integer subunits to MU by dividing by 100.

For this deductible–coinsurance contract with

Request: "Buy tickets for Zhang and Li, total at most 3,000 monetary units (MU); his ticket must allow a fee-free refund." The referent remains unspecified.

Generated clauses (notation shortened): p is the total price; r_Z and r_L indicate fee-free refundability for Zhang and Li, respectively.

State	$\widehat{H}$	$(\widehat{R}, \widehat{u})$
Zhang	$p \leq 3000 \ \wedge \ r_Z$	$(\text{True}, (3000 - p)/1000)$
Li	$p \leq 3000 \ \wedge \ r_L$	$(\text{True}, (3000 - p)/1000)$

Order	Price (MU)	Refunds	Jointly allowed	Value
B	2,400	Zhang	No	—
C	2,400	Li	No	—
D	2,800	Both	Yes	$1/5$

Table 3: **Observed request-to-decision trace.** Astra max generates both clauses: the executor selects D, but refuses a catalogue containing only B and C. Utility is stipulated. Translation and notation preserve the recorded semantics (Appendix A.4).

nonnegative component losses, net loss is nondecreasing in gross loss, so its worst nonempty event uses the four largest losses. The empty event has zero loss. One generated clause represents all 57 events with the same aggregate semantics. Offline verification compares the retained expressions with the displayed notation and the reference ledger across 256 candidates and 14,592 candidate–event calculations. The current complete-domain evaluator reproduces the recorded purchase and value. The source package includes the original expressions, candidate attributes, and verification. This check uses the retained output without a new model call.

A.4 Recorded ambiguity trace

Table 3 uses archived Astra max SET outputs for F02a/F02b (clean context, first sample). Both inputs include the catalogue and stipulated utility $(3000 - p)/1000$. The generated clauses preserve both refund readings: the executor refuses F02a and accepts D in F02b with value $1/5$. Display translation and variable renaming preserve the expressions. Original responses and execution records remain in the artifact. This is a method illustration, not evidence of comparative accuracy.

B Benchmark Construction and Experimental Protocol

B.1 Contract structures and paired boundaries

The primary dataset contains 20 templates (Table 4), with five feasible/infeasible pairs per template. Each purchase has six components; the retained events are the 57 affected subsets of size at most four, including the empty event. Empty events have zero assessment. A nonempty event incurs one administrative fee, outside insurance or compensation offsets. Public contracts state that no additional hidden clauses apply.

The master construction seed is 39071007, with predetermined template and stratum offsets. The unique authorized positive-value candidate has loss margin m: the authorized cap minus its worst loss, in subunits (Table 5). Increasing only its administrative fee by $m + 1$ makes the paired task infeasible, with maximum loss of 200,001 subunits against a 200,000-subunit limit. The resulting violation is always one subunit, although the fee increment depends on the feasible margin. Other candidates already exceed the limit by 1–20,000 subunits. Opaque candidate identifiers contain no answer labels, and positions are sampled before attributes are generated. Amounts are reported in MU without changing the stored values.

The design fixes unique feasibility, balanced acceptance/refusal, and complete catalogues. The task balance is not an estimate of real purchasing frequencies.

B.2 Reference calculations and freezing

A cash-flow ledger evaluates bitmask events with integer or rational arithmetic, and a separate expression implementation uses the rule engine. Before model evaluation, we compare candidate feasibility, worst loss, guaranteed utility, and final decisions. They agree on all 6,712,320 candidate–event checks. Twenty fresh attribute assignments per template are also checked on all 64 subsets, yielding $20 \times 20 \times 64 = 25{,}600$ checks, plus three hand-calculated threshold witnesses. Both implementations arose within one development workflow and may share a misunderstanding of a clause despite agreeing numerically.

Tasks, references, prompts, and evaluator code are frozen before model evaluation. Public inputs exclude construction seeds, reference matrices, labels, and designated safe identifiers. Candidate visibility follows Table 6.

B.3 Common instructions and outcome protocol

Table 1 is the protocol index. This section defines primary inputs, policy, and scoring; Section B.4 specifies model settings. Appendix D records the

ID	Family	Distinct contractual structure
a1	Coupon cancellation	Overlapping three-person groups; a clawback applies to partial but not full group cancellation.
a2	Coupon cancellation	Different settlement charges for one versus both members of a two-person group.
a3	Coupon cancellation	A cap on group clawbacks plus a conditional order-level clawback.
a4	Coupon cancellation	A rebate offsets group charges only after multiple groups are broken.
a5	Coupon cancellation	Only the largest group clawback is charged, with a specified combination surcharge.
b1	Insured cancellation	Item deductibles and item payout limits, followed by an aggregate payout cap.
b2	Insured cancellation	An order-level deductible followed by proportional coinsurance.
b3	Insured cancellation	The number of cancellations changes the aggregate insurance limit.
b4	Insured cancellation	Primary insurance followed by secondary insurance on remaining loss.
b5	Insured cancellation	Payout is triggered by a strict threshold, then calculated from the first unit of loss.
c1	Threshold returns	Two product groups have separate retained-value discount clawbacks.
c2	Threshold returns	Fixed shipping parcels; return freight is the largest item fee within each affected parcel.
c3	Threshold returns	Retained purchase value determines a tiered retained discount.
c4	Threshold returns	Separate retained-value and retained-weight thresholds govern two subsidies.
c5	Threshold returns	Restocking fees are capped; sufficiently large returns waive return freight.
d1	Service replacement	Item-level compensation limits apply before an order-level cap.
d2	Service replacement	Activating replacement service incurs a fixed fee per affected group.
d3	Service replacement	The number of failures determines the aggregate compensation cap.
d4	Service replacement	Cash compensation combines with explicitly authorized, discounted service credits.
d5	Service replacement	Overlapping group dispatch fees and threshold-triggered additional compensation.

Table 4: All 20 primary structures. Numerical instances vary within each template; the four families contain 50 cases each. These contracts define synthetic assessment rules and are not claims about actual merchants' terms.

Stratum	Candidates	Margin (subunits)	Cases
1	128	1	40
2	256	100	40
3	512	10,000	40
4	1,024	100	40
5	1,024	1	40

Table 5: Each stratum includes one pair for every template. Catalogue size, margin, and seed change together; these strata do not isolate their individual causal effects.

catalogue-visible intent variant, Appendix E the sensitivity controls, and Appendix F.1 the frozen-specification interventions. These cohorts retain their own inputs and denominators.

All primary routes receive the same substantive policy, summarized below in English. The frozen model-facing prompts retain their original language and are unchanged by this summary.

> Retain applicable interpretations. Respect current authorization in every retained state. Evaluate hard requirements and the complete risk permission, then maximize the minimum state-dependent utility. Buy only for positive guaranteed value; otherwise refuse. Do not ask the user or change permissions.

Direct returns a decision, allowed identifiers, and guaranteed utility. SET returns the state-wise expressions of Appendix A.2. Exactness requires agreement with the reference decision and, for acceptance, a nonempty subset of authorized maximizers and correct value. Disjoint failures are unsafe acceptance, false refusal, and Other (remaining value or invalid-execution failures). SET executions must satisfy the complete-domain checks in Algorithm 1. Failed or unresolved execution counts as Other, including a no-action output whose reference decision is refusal.

Property	Direct	SET
Natural-language records	Yes	Yes
Attribute schema	Yes	Yes
Catalogue in model input	Yes	No
Deterministic row evaluation	No	Yes
Exact arithmetic in executor	—	Yes
Observable allowed domain	No	Yes
Model calls per primary trial	1	1

Table 6: Primary method controls. Different catalogue visibility is a declared architectural choice. "One call" refers to a logical trial; transport retries are separately retained.

A primary comparison trial allows one semantic attempt. Transport failures may be retried within the recorded limit; formatting, semantic, and output-budget failures end the trial. We save every received response before scoring and count all failures in completed cohorts. Calls not issued remain missing. We reuse an earlier result only when the messages, schema, requested model, ef-

fort setting, deadline, output budget, and both task and reference data are unchanged. Sources are selected without using the outcome.

B.4 Model configurations

Table 7 specifies the primary, intent, and prospective availability settings. The effort panel uses off, low, medium, high, xhigh, and max for each of Sol, Terra, and Luna; language tests use DeepSeek low/high/max and Astra max. Their requested identities follow the same table. Complete per-study settings, including archived explorations, remain in the artifact. Paired Direct/SET comparisons share requested generation settings. Primary command-line interface (CLI) calls use fresh contexts with tools and delegation disabled; application programming interface (API) outputs pass the common validator. Requested effort and output caps do not establish equivalent compute across providers.

B.5 Unified reproduction entry point

The anonymous artifact provides implementation code, benchmark inputs and references, prompts, generation settings, retained outputs, and reporting materials at `https://anonymous.4open.science/r/risk-aware-payment-delegation-D4FC/`. Its documentation gives the environment setup and commands for rebuilding the reported results and running the corresponding checks. Table 8 distinguishes report reconstruction, retained-output verification, and reference recomputation. These offline checks make no model calls and leave experimental records unchanged; new inference runs are documented separately.

C Complete Results and Statistical Analysis

C.1 Primary outcomes and matched comparisons

Table 9 gives the counts underlying Figure 1, with 200 tasks per method in each of eleven configurations. Error categories and feasible-task completion use the same cohorts. Table 7 specifies the generation settings.

C.2 Structural coverage

Table 10 reports the primary DeepSeek comparison for all 20 ten-task templates. Each setting improves over Direct on 18 templates, ties on one, and declines on one. The four families have 50 cases each. Low-effort service replacement improves from 20 to 42 exact decisions, and high-effort threshold returns from 30 to 49. Table 9 reports Astra's 180-to-196 aggregate.

C.3 Paired statistical analysis

Paired bootstrap resampling keeps the two methods' outcomes together (Dror et al., 2018). We additionally group cases by contract template. For each configuration and metric, we compute a mean paired difference d_k over the cases of template k. In the pooled DeepSeek comparison, both configurations remain in the same template cluster. We resample 20 template indices with replacement and average their d_k, repeating this procedure 20,000 times with seed 20261008. The interval uses the 2.5th/97.5th percentiles. This grouping retains all outcomes within each template, including feasibility pairs; precision is limited by the 20 clusters. Table 11 reports descriptive percentage-point intervals without multiplicity-adjusted hypothesis claims. The 400 pooled outcomes per method come from 200 tasks under two configurations, not 400 independent problems.

D Controlled Decisions under Retained Intent Ambiguity

D.1 Task semantics and controlled inputs

The frozen parameter-boundary campaign contains three families with unresolved user interpretations. We include all three and exclude five families whose requirements are conditional but unambiguous. Selection is based on task semantics. This retrospective study is separate from the primary benchmark of contractual events.

Ticket-holder reference. Two male travellers need tickets, and "his" ticket must be refundable with a fee below the authorized limit. Utility penalizes that same traveller's delay and refund fee. Both referents remain possible. Each reading binds the hard requirement, risk bound, and value function to the corresponding traveller.

Hotel reference and conditional binding. Two guests need correctly registered rooms. "His room" must permit cancellation at 18:00 if he arrives at or after 18:00, or 24 hours before his expected arrival otherwise. The cancellation fee and utility weights refer to the same guest, so the unresolved antecedent affects conditional requirements and value.

Configuration	Requested model	Output cap	Deadline
Primary 200-task comparison			
DeepSeek low / high	`deepseek-flash`	262,144	1,800
Qwen Flash low	`qwen3.8-flash`	131,072	1,800
Qwen Max low	`qwen3.8-max`	131,072	1,800
GLM Flash low	`glm-5.3-flash`	131,072	1,800
GLM high	`glm-5.3`	131,072	1,800
5.6 Luna medium	`gpt-5.6-luna`	128,000	1,800
5.6 Terra medium	`gpt-5.6-terra`	128,000	1,800
5.6 Sol medium	`gpt-5.6-sol`	128,000	1,800
Astra max	`gpt-6-astra`	128,000	1,800
Opus 5.5 medium	`claude-opus-5-5`	128,000	1,800
Retained-intent comparison (Figure 2)			
DeepSeek low / max	`deepseek-flash`	32,768	300
GLM low	`glm-5.3`	32,768	300
Qwen Max low	`qwen3.8-max-0902`	32,768	300
Prospective availability (Figure 3)		Output cap	
DeepSeek low	`deepseek-flash`	32,768	
GLM low	`glm-5.3`	32,768	
Qwen Max low	`qwen3.8-max`	32,768	

Table 7: Requested model configurations. Output caps are in tokens; primary and intent deadlines are in seconds. Each primary configuration uses 200 tasks per method. Intent counts appear in Table 12; the availability protocol is in Appendix F.1. Names refer to requested configurations, not independently attested backend versions.

Result	Supporting materials	Verification level
Primary outcomes	Benchmark instances, per-trial observations, and separately indexed aggregate updates	Rebuild tables from their designated inputs; reference checking is separate.
Retained requests and decisions	Original requests, responses, configurations, and stored evaluations	Check response integrity and agreement with stored scores; rescore retained prompt-control decisions.
Intent and observed trace	Paired tasks, original generated conditions, and the evidence map	Rebuild intent counts and verify the displayed traces against retained outputs.
Prospective availability	Fixed requests, frozen specifications, catalogue matrices, and witness certificates	Recompute Figure 3 and complete template counts; verify original-expression witnesses.
Decision contract and plots	Evaluator, reference ledger, reporting inputs, and figure-generation tools	Check Algorithm 1 and regenerate figures and tables; reference recomputation is a separate check.

Table 8: **Result-to-artifact map.** Supporting materials distinguish report reconstruction, response rescoring, and reference recomputation. Aggregate updates remain separate from archived per-trial observations; new inference is documented separately.

Model	n	Exact ↑	Unsafe ↓	Refusal ↓	Other ↓	Accept / feasible ↑
DeepSeek low	200	$117 \to \mathbf{184}$	$48 \to \mathbf{3}$	$24 \to \mathbf{1}$	$11 \to \mathbf{12}$	$45/100 \to \mathbf{94/100}$
DeepSeek high	200	$131 \to \mathbf{185}$	$31 \to \mathbf{6}$	$29 \to \mathbf{0}$	$9 \to \mathbf{9}$	$55/100 \to \mathbf{92/100}$
Qwen Flash low	200	$66 \to \mathbf{194}$	$52 \to \mathbf{1}$	$26 \to \mathbf{0}$	$56 \to \mathbf{5}$	$20/100 \to \mathbf{99/100}$
Qwen Max low	200	$59 \to \mathbf{87}$	$49 \to \mathbf{46}$	$57 \to \mathbf{41}$	$35 \to \mathbf{26}$	$0/100 \to \mathbf{26/100}$
GLM Flash low	200	$29 \to \mathbf{136}$	$95 \to \mathbf{31}$	$10 \to \mathbf{5}$	$66 \to \mathbf{28}$	$17/100 \to \mathbf{68/100}$
GLM high	200	$64 \to \mathbf{188}$	$20 \to \mathbf{5}$	$4 \to \mathbf{0}$	$112 \to \mathbf{7}$	$34/100 \to \mathbf{94/100}$
5.6 Luna medium	200	$41 \to \mathbf{91}$	$129 \to \mathbf{75}$	$28 \to \mathbf{6}$	$2 \to \mathbf{28}$	$13/100 \to \mathbf{39/100}$
5.6 Terra medium	200	$81 \to \mathbf{158}$	$78 \to \mathbf{24}$	$40 \to \mathbf{3}$	$1 \to \mathbf{15}$	$24/100 \to \mathbf{75/100}$
5.6 Sol medium	200	$137 \to \mathbf{196}$	$21 \to \mathbf{2}$	$42 \to \mathbf{2}$	$0 \to \mathbf{0}$	$49/100 \to \mathbf{97/100}$
Astra max	200	$180 \to \mathbf{196}$	$6 \to \mathbf{2}$	$6 \to \mathbf{2}$	$8 \to \mathbf{0}$	$87/100 \to \mathbf{97/100}$
Opus 5.5 medium	200	$142 \to \mathbf{194}$	$8 \to \mathbf{1}$	$14 \to \mathbf{1}$	$36 \to \mathbf{4}$	$76/100 \to \mathbf{98/100}$

Table 9: **Primary comparison: Direct→SET.** Here n counts tasks per method. Exact requires decision and value correctness. Unsafe acceptance, false refusal (Refusal), and Other partition errors; Accept is exact completion among feasible cases.

Template	DS low	DS high
a1	$6 \to 10$	$8 \to 9$
a2	$8 \to 10$	$6 \to 10$
a3	$6 \to 10$	$7 \to 10$
a4	$5 \to 10$	$7 \to 10$
a5	$8 \to 8$	$7 \to 10$
b1	$7 \to 10$	$9 \to 10$
b2	$8 \to 10$	$7 \to 9$
b3	$7 \to 9$	$9 \to 10$
b4	$6 \to 10$	$7 \to 7$
b5	$7 \to 9$	$5 \to 9$
c1	$6 \to 9$	$5 \to 10$
c2	$4 \to 9$	$7 \to 10$
c3	$4 \to 9$	$7 \to 9$
c4	$7 \to 10$	$6 \to 10$
c5	$8 \to 9$	$5 \to 10$
d1	$3 \to 9$	$4 \to 9$
d2	$3 \to 8$	$7 \to 8$
d3	$9 \to 6$	$8 \to 7$
d4	$5 \to 10$	$6 \to 10$
d5	$0 \to 9$	$4 \to 8$

Table 10: Primary DeepSeek (DS) template coverage: Direct→SET exact decisions, each out of ten. All 20 templates are included; family boundaries follow Table 4.

Control	Metric	Difference	95% interval
Direct	Exact	+30.25	[+22.75, +37.25]
Direct	Unsafe	-17.50	[-24.75, -10.25]

Table 11: Paired template-bootstrap differences, SET minus the listed control, on the pooled DeepSeek primary results. Larger exactness and smaller unsafe rate are desirable. Intervals are descriptive, without multiplicity-adjusted hypothesis claims.

Distributive versus collective scope. Gifts must satisfy recipients' preferences and wrapping requirements. "Buy one for each; the exchange top-up is at most r" may bound each recipient or the batch. Stipulated utility uses the corresponding maximum individual or total top-up. With nonnegative charges, the batch bound may dominate the individual bounds. The representation must still preserve the bound and score for each reading.

All requests explicitly signal unresolved reference or scope. Methods receive identical user text, complete catalogue attributes, synthetic utility formulas, and the common decision policy. Compilation in this historical panel is catalogue-visible; the primary SET protocol excludes the catalogue. Models receive no reference expressions, answers, or subsequent user clarification. The study evaluates decisions under the signaled ambiguity and does not test automatic discovery of unrestricted interpretations.

D.2 Parameter design and findings

Three families, seven settings, and two frozen seeds give 42 API variants. Within each parameter group the candidates and identifiers stay fixed. The authorized risk limit takes values of 0, 500, and 1,000 subunits, and the risk penalty takes values of 1, 3, and 10. A value offset places the best common candidate at exactly zero or one. Each seed has 18 acceptance and three zero-value refusal variants. The refusal cases have a nonempty feasible intersection and test the value boundary. The second seed changes the instance within the same templates.

Table 12 supplies all four paired configurations in Figure 2: 42 variants per method for DeepSeek low/max and GLM low, and 21 for Qwen Max low. Reference-arithmetic checks and response replay reproduce these recorded evaluations.

D.3 Semantic boundary checks

Separate capability checks instantiate common feasible purchases, empty intersections, worst-case ranking, and the zero-value refusal boundary. The empty-intersection case complements the parameter panel, whose refusal cases instead have zero best value. These checks exercise the prescribed behaviors without establishing a comparative advantage; their repeated-generation records remain in the artifact. Appendix A.4 gives a recorded common-purchase/empty-intersection trace.

The small capability checks and earlier input interventions remain separate from the formal intent panel.

E Additional Controls and Sensitivity

E.1 Textual Guidance

The *prompt engineering baseline*, Prompt, adds five checks to Direct: identify requirements, check conditions, verify financial arithmetic, compare eligible purchases, and review the answer. Direct already specifies joint feasibility, worst-case value, and refusal. This comparison tests the effect of additional written guidance under the same policy.

We make 200 new calls per configuration for DeepSeek low/high and Sol/Luna/Terra medium. Task, catalogue, answer schema, model setting, output cap, and deadline match the retained Direct runs. The prompts add no examples or reference answers. The checklist follows the recorded instruction constraints for each configuration. Com-

Configuration	n	Exact ↑	Unsafe ↓	False refusal ↓	Other ↓
DeepSeek low	42	40→42	1→0	0→0	1→0
DeepSeek max	42	40→42	0→0	0→0	2→0
GLM low	42	32→36	2→0	0→0	8→6
Qwen Max low	21	1→13	5→6	7→0	8→2

Table 12: Complete results underlying Figure 2. Each arrow is Direct→SET; n is the number of matched tasks per method. Exact, unsafe acceptance, false refusal, and Other form a disjoint partition of each method's n outcomes. Other includes remaining value and execution failures. The four rows contain 294 evaluations in total and are separate from the primary 200-task benchmark.

plete prompts and generation settings are provided with the evaluation records. Comparisons across run dates do not control service-version drift.

The checklist changes exactness by -6.5 to $+1.0$ percentage points, with an improvement only for Terra. This result applies to the tested checklist and does not establish the effect of other prompt engineering strategies.

E.2 Requested Reasoning Settings

The 60-task panel combines ten historical feasibility pairs and one pair from each primary template. Figure 4 and Table 14 cover 18 complete Sol/Terra/Luna settings. SET improves in 17, with Luna off decreasing from 25/60 to 13/60. Each reported configuration has 60 tasks per method.

E.3 Task Language

We report paired Direct and SET evaluations on the same 60 task identifiers in Chinese and English. A reviewed 183-phrase translation map preserves quantities, types, events, and authorization, with system instructions held fixed. Table 15 reports the complete Direct/SET outcomes for these paired 60-task runs. The results concern these controlled Chinese/English renderings, not language invariance in general.

E.4 Output-Budget Control

On 46 historically budget-sensitive Direct tasks, 92 new calls compare the original cap with 262,144 tokens under the same 1,800-second deadline. Exact decisions rise from 10/46 to 26/46, with unsafe acceptance and false refusal still observed. The original outcomes remain in their cohorts. Results on this selected subset do not estimate general failure rates.

F Availability Study and Verification

F.1 Design and frozen interventions

Tasks and frozen specifications. We fix 800 distinct request–contract inputs before generation: 40 numerical instances of each of the 20 templates in Table 4, across four contract families. Each has 128 candidates. DeepSeek Flash (`deepseek-flash`), GLM (`glm-5.3`), and Qwen Max (`qwen3.8-max`) use low effort and a 32,768-token output budget. Preparation receives the request, contract, and schema, excluding candidates and reference information.

We evaluate permissions and required utilities over the complete catalogue. Determinate evaluation does not imply agreement with reference semantics. Percentages use all planned trials. Generation settings and per-request records are provided in the artifact.

Catalogue construction and reference checks. The construction allocates 32 offers each to authorized positive-value purchases, unauthorized boundary cases, contract-branch controls, and ordinary sampled attributes. Construction categories differ from authorization labels: the latter two blocks may add authorized purchases. Boundary distances include one monetary subunit and approximately 1%, 5%, and 20% of the risk limit. Attributes remain contract-consistent.

Each template has 20 S and 20 T requests. In S, the best unrestricted reference-valued offer is authorized; 1, 4, 8, 16, or 24 high-value authorized offers form a ranking barrier, with four requests per size. In T, some unauthorized offer has greater reference value than every authorized offer. These strata and all candidates are fixed before generation. The study therefore probes a controlled pressure distribution. Independent cash-ledger and expression references agree on all 5,836,800 candidate–event checks; input uniqueness, branch coverage, and random-removal plans are also checked before

Configuration	n	Direct	Prompt	SET	Prompt U/R/O	Δ (pp)
DS low	200	58.5	53.5	92.0	48/27/18	-5.0
DS high	200	65.5	59.0	92.5	43/27/12	-6.5
Sol medium	200	68.5	67.5	98.0	23/41/1	-1.0
Luna medium	200	20.5	19.0	45.5	129/30/3	-1.5
Terra medium	200	40.5	41.5	79.0	74/41/2	$+1.0$

Table 13: **Textual guidance and fixed decision processing.** Direct, Prompt, and SET are exact-decision percentages on the same 200 tasks per configuration. SET uses the primary results in Table 9. Prompt U/R/O gives unsafe acceptance, false refusal, and other errors; Δ is Prompt minus Direct in percentage points (pp). All outcomes remain in their denominators.

		Direct		SET	
Model	Setting	Exact/n	U/R/O	Exact/n	U/R/O
Sol	off	0/60	60/0/0	49/60	8/1/2
	low	30/60	9/20/1	58/60	2/0/0
	medium	41/60	3/16/0	60/60	0/0/0
	high	43/60	0/17/0	60/60	0/0/0
	xhigh	46/60	0/14/0	59/60	0/0/1
	max	45/60	0/15/0	60/60	0/0/0
Terra	off	0/60	59/0/1	27/60	8/3/22
	low	24/60	17/19/0	53/60	6/0/1
	medium	26/60	15/19/0	52/60	6/0/2
	high	33/60	7/20/0	52/60	5/0/3
	xhigh	37/60	8/14/1	59/60	1/0/0
	max	33/60	3/15/9	59/60	0/0/1
Luna	off	25/60	6/28/1	13/60	24/12/11
	low	6/60	44/10/0	19/60	28/6/7
	medium	13/60	40/7/0	32/60	20/2/6
	high	24/60	28/8/0	47/60	10/0/3
	xhigh	35/60	11/13/1	53/60	3/0/4
	max	41/60	4/12/3	58/60	2/0/0

Table 14: All complete GPT-5.6 reasoning settings: exact/n and unsafe/false-refusal/other (U/R/O), with $n = 60$ in every cell. The 18 configurations cover six settings each for Sol, Terra, and Luna. Settings denote requested effort, not equal or measured compute.

calls.

Frozen interventions and endpoint. The original catalogue, 128 random-removal conditions (32 each for $k \in \{1, 4, 8, 16\}$), 16 generated-rank prefixes, and one unauthorized-only catalogue define 146 conditions per specification. Random plans are fixed in advance and shared across models. Ranked removals order originally admitted offers by generated utility, retaining original candidate order for ties; the removal rule uses no reference labels. Surviving attributes, permissions, utilities, and the selector remain unchanged. The unauthorized-only condition retains all reference-unauthorized offers and is an extreme control.

The primary endpoint requires an originally safe acceptance, an unauthorized selection for some prefix of at most eight removals, and at least one surviving offer permitted and positively valued under both generated conditions and the reference. Each specification counts once per budget. Refusals do not count as safe purchases. Algorithm 1 returns all positive-value maximizers; any unauthorized maximizer makes a selection unsafe. Mixed-authorization ties and fixed-first selection are checked separately. Cumulative exposure is distinct from the outcome at exactly k removals, which may return to safety after an unauthorized winner is itself removed.

F.2 Complete results and controls

Coverage, controls, and verification. The primary endpoint covers 48 distinct requests, 15 templates, four families, and three configurations. All its witnesses occur in the predeclared S stratum; the family counts are 14 coupon, five insurance, ten return, and nineteen replacement cases. Coverage is uneven: DeepSeek's cases remain concentrated in service replacement. The endpoint holds with wholly unauthorized maximizing sets

Configuration	Language	Direct Exact/n	Direct U/R/O	SET Exact/n	SET U/R/O
DS low	ZH	36/60	9/14/1	59/60	0/0/1
	EN	34/60	6/15/5	57/60	0/0/3
DS high	ZH	34/60	10/14/2	55/60	0/0/5
	EN	33/60	8/16/3	58/60	0/0/2
DS max	ZH	35/60	11/13/1	57/60	2/0/1
	EN	34/60	12/11/3	58/60	0/0/2
Astra max	ZH	55/60	0/4/1	60/60	0/0/0
	EN	49/60	0/9/2	60/60	0/0/0

Table 15: Language outcomes and failure partitions: ZH is Chinese and EN is English. U/R/O denotes unsafe/false-refusal/other. Each setting–language cell has $n = 60$ per method. Figure 4b shows the DeepSeek subset.

Configuration	Method	n per cap	Exact	Budget	Unsafe	Refusal	Other
DS high	Direct	21	$4 \to 12$	$11 \to 0$	$0 \to 3$	$6 \to 6$	$0 \to 0$
DS low	Direct	25	$6 \to 14$	$11 \to 1$	$0 \to 1$	$7 \to 7$	$1 \to 2$

Table 16: Original→expanded output cap for Direct; the outcome columns partition each row's n tasks. Budget counts output-token exhaustion; Other denotes remaining value errors. Selection of historically budget-sensitive tasks limits prevalence estimates.

Model	Hidden (%)	Exposed (%)	Requests	Templates
DeepSeek	1.50	1.50	12	3
GLM	6.88	4.13	33	12
Qwen	0.50	0.38	3	3
All	2.96	2.00	48	15

Table 17: Availability outcomes over the planned cohort. Hidden counts safe purchases concealing false admissions; Exposed requires a transition within eight removals with a viable authorized alternative. Requests and Templates count exposure coverage.

in every case, so no primary witness relies on a mixed-authorization tie. The minimum witnesses retain 40–67 viable authorized alternatives. Eight exposed outputs began with exact decisions, covering four templates and two model configurations.

Every observed transition and attainable minimum-deletion witness is independently selected from the candidate matrix and replayed through the original expressions. Native permissions and values must equal the corresponding subset of the original matrix. Certificates retain the violating reference loss, selected maximizing set, surviving alternatives, and source hashes. These checks validate the controlled mechanism; they do not estimate deployment frequency.

Across all 71 initially safe specifications with false admissions, the unauthorized-only control exposes a positive-valued unauthorized offer. Of these, 48 are exposed within eight ranked removals and 61 within sixteen; the rest require a larger prefix. Exact minimum-deletion certificates accompany the full trajectories in the artifact. Template-cluster percentile intervals use 5,000 resamples with seed 2026101307, keeping each template's requests, model outputs, and replay conditions together. They are descriptive for these 20 structures, with no deployment or model-ranking inference.

F.3 Original-expression verification

The GLM a3 specification initially selects a reference maximizer with the correct value of 1,457,778 subunits. It contains one state record whose risk expression includes all 57 event terms. For event $\{0, 1, 3, 5\}$, two partial-cancellation group charges must be added before the group cap: the correct capped charge is 19,500, but the expression includes only the second charge, yielding 9,900. Event coverage alone therefore does not ensure correct contractual aggregation.

After four originally higher-ranked offers become unavailable, the admitted unauthorized offer wins with generated value 1,359,878, ahead of the best surviving authorized value 1,257,378. Its true worst loss is 268,094 against a 267,994 limit; the specification's maximum is 263,194. The difference in this event's omitted charge is 9,600, whereas the difference between the two worst losses is 4,900; the maxima arise from different event calculations. All 59 surviving authorized alternatives have positive value under both valua-

Template	Hidden (%)	Exposed (%)	Requests
a1	4.17	1.67	2
a2	0.00	0.00	0
a3	5.00	2.50	3
a4	1.67	1.67	2
a5	9.17	5.83	7
b1	1.67	1.67	2
b2	0.00	0.00	0
b3	0.00	0.00	0
b4	0.83	0.83	1
b5	3.33	1.67	2
c1	1.67	0.83	1
c2	5.00	4.17	5
c3	0.00	0.00	0
c4	0.83	0.83	1
c5	6.67	2.50	3
d1	3.33	3.33	4
d2	2.50	2.50	3
d3	5.83	5.00	6
d4	0.83	0.00	0
d5	6.67	5.00	6

Table 18: All 20 templates, including zero-event structures. Percentages use each template's planned cohort across models. Shared requests and numerical variants are not independent logical structures.

Budget k	1	4	8	16
Directed safe to unsafe	0.71	1.42	2.00	2.54
Directed unsafe to safe	0.29	0.79	1.21	1.54
Random safe to unsafe	0.001	0.034	0.035	0.103
Random unsafe to safe	0.003	0.009	0.014	0.044

Table 19: Availability controls as percentages of all planned trials. Directed rows count whether a transition occurs at any prefix within the budget; random rows average observed transition fractions over 32 draws per trial. Safe-to-unsafe requires a viable authorized alternative. Forward and reverse cumulative events need not occur at the same prefix.

tions. The request, conditions, remaining attributes, and selector are unchanged. Original expressions, event ledgers, and the complete candidate-level certificate are provided in the artifact.

Archived exploratory scope. The artifact separately archives earlier catalogue probes, selected-output component interventions, supplied-reading tests, and exploratory input, price, and component changes. They use different cohorts and are not pooled with this study. Selected reversals were accompanied by non-triggering checks and improving transitions; they do not establish that more accurate valuation generally increases unsafe purchasing. Complete protocols and positive and negative outcomes remain in the archival reports.