




Machine Learning

Neural Networks: Learning

Cost function

Neural Network (Classification)



$$\{(x^{(1)}, y^{(1)}), (x^{(2)}, y^{(2)}), \dots, (x^{(m)}, y^{(m)})\}$$

$L =$ total no. of layers in network

$s_l =$ no. of units (not counting bias unit) in layer l

Binary classification

$y = 0$ or 1

1 output unit

Multi-class classification (K classes)

$y \in \mathbb{R}^K$ E.g. $\begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$, $\begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$, $\begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$, $\begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}$
pedestrian car motorcycle truck

K output units

Cost function


Logistic regression:

$$J(\theta) = -\frac{1}{m} \left[\sum_{i=1}^m y^{(i)} \log h_{\theta}(x^{(i)}) + (1 - y^{(i)}) \log(1 - h_{\theta}(x^{(i)})) \right] + \frac{\lambda}{2m} \sum_{j=1}^n \theta_j^2$$

Neural network:

$$h_{\Theta}(x) \in \mathbb{R}^K \quad (h_{\Theta}(x))_i = i^{th} \text{ output}$$

$$J(\Theta) = -\frac{1}{m} \left[\sum_{i=1}^m \sum_{k=1}^K y_k^{(i)} \log(h_{\Theta}(x^{(i)}))_k + (1 - y_k^{(i)}) \log(1 - (h_{\Theta}(x^{(i)}))_k) \right] \\ + \frac{\lambda}{2m} \sum_{l=1}^{L-1} \sum_{i=1}^{s_l} \sum_{j=1}^{s_{l+1}} (\Theta_{ji}^{(l)})^2$$



Machine Learning

Neural Networks: Learning

Backpropagation algorithm

Gradient computation

$$J(\Theta) = -\frac{1}{m} \left[\sum_{i=1}^m \sum_{k=1}^K y_k^{(i)} \log h_{\theta}(x^{(i)})_k + (1 - y_k^{(i)}) \log(1 - h_{\theta}(x^{(i)})_k) \right] \\ + \frac{\lambda}{2m} \sum_{l=1}^{L-1} \sum_{i=1}^{s_l} \sum_{j=1}^{s_{l+1}} (\Theta_j^{(l)})^2$$

$$\min_{\Theta} J(\Theta)$$

Need code to compute:

- $J(\Theta)$
- $\frac{\partial}{\partial \Theta_{ij}^{(l)}} J(\Theta)$

Gradient computation

Given one training example (x, y) :

Forward propagation:

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$


$$a^{(2)} = g(z^{(2)}) \quad (\text{add } a_0^{(2)})$$

$$z^{(3)} = \Theta^{(2)} a^{(2)}$$

$$a^{(3)} = g(z^{(3)}) \quad (\text{add } a_0^{(3)})$$

$$z^{(4)} = \Theta^{(3)} a^{(3)}$$

$$a^{(4)} = h_{\Theta}(x) = g(z^{(4)})$$



Gradient computation: Backpropagation algorithm


Intuition: $\delta_j^{(l)}$ = “error” of node j in layer l .

For each output unit (layer $L = 4$)

$$\delta_j^{(4)} = a_j^{(4)} - y_j$$

$$\delta^{(3)} = (\Theta^{(3)})^T \delta^{(4)} \cdot * g'(z^{(3)})$$

$$\delta^{(2)} = (\Theta^{(2)})^T \delta^{(3)} \cdot * g'(z^{(2)})$$



Backpropagation algorithm

Training set $\{(x^{(1)}, y^{(1)}), \dots, (x^{(m)}, y^{(m)})\}$

Set $\Delta_{ij}^{(l)} = 0$ (for all l, i, j).

For $i = 1$ to m

Set $a^{(1)} = x^{(i)}$

Perform forward propagation to compute $a^{(l)}$ for $l = 2, 3, \dots, L$

Using $y^{(i)}$, compute $\delta^{(L)} = a^{(L)} - y^{(i)}$

Compute $\delta^{(L-1)}, \delta^{(L-2)}, \dots, \delta^{(2)}$

$$\Delta_{ij}^{(l)} := \Delta_{ij}^{(l)} + a_j^{(l)} \delta_i^{(l+1)}$$

$$D_{ij}^{(l)} := \frac{1}{m} \Delta_{ij}^{(l)} + \lambda \Theta_{ij}^{(l)} \text{ if } j \neq 0$$

$$D_{ij}^{(l)} := \frac{1}{m} \Delta_{ij}^{(l)} \quad \text{if } j = 0$$

$$\frac{\partial}{\partial \Theta_{ij}^{(l)}} J(\Theta) = D_{ij}^{(l)}$$




Machine Learning


Neural Networks: Learning

Backpropagation intuition

Forward Propagation



Forward Propagation



What is backpropagation doing?

$$J(\Theta) = -\frac{1}{m} \left[\sum_{i=1}^m y^{(i)} \log(h_{\Theta}(x^{(i)})) + (1 - y^{(i)}) \log(1 - (h_{\Theta}(x^{(i)}))) \right] \\ + \frac{\lambda}{2m} \sum_{l=1}^{L-1} \sum_{i=1}^{s_l} \sum_{j=1}^{s_{l+1}} (\Theta_{ji}^{(l)})^2$$


Focusing on a single example $x^{(i)}$, $y^{(i)}$, the case of 1 output unit, and ignoring regularization ($\lambda = 0$),

$$\text{cost}(i) = y^{(i)} \log h_{\Theta}(x^{(i)}) + (1 - y^{(i)}) \log h_{\Theta}(x^{(i)})$$

(Think of $\text{cost}(i) \approx (h_{\Theta}(x^{(i)}) - y^{(i)})^2$)


I.e. how well is the network doing on example i ?

Forward Propagation



$\delta_j^{(l)}$ = “error” of cost for $a_j^{(l)}$ (unit j in layer l).

Formally, $\delta_j^{(l)} = \frac{\partial}{\partial z_j^{(l)}} \text{cost}(i)$ (for $j \geq 0$), where
 $\text{cost}(i) = y^{(i)} \log h_{\Theta}(x^{(i)}) + (1 - y^{(i)}) \log h_{\Theta}(x^{(i)})$



Machine Learning

Neural Networks: Learning

Implementation note:
Unrolling parameters

Advanced optimization

```
function [jVal, gradient] = costFunction(theta)
```

```
...
```

```
optTheta = fminunc(@costFunction, initialTheta, options)
```

Neural Network (L=4):

$\Theta^{(1)}, \Theta^{(2)}, \Theta^{(3)}$ - matrices (**Theta1, Theta2, Theta3**)

$D^{(1)}, D^{(2)}, D^{(3)}$ - matrices (**D1, D2, D3**)


“Unroll” into vectors

Example

$$s_1 = 10, s_2 = 10, s_3 = 1$$

$$\Theta^{(1)} \in \mathbb{R}^{10 \times 11}, \Theta^{(2)} \in \mathbb{R}^{10 \times 11}, \Theta^{(3)} \in \mathbb{R}^{1 \times 11}$$

$$D^{(1)} \in \mathbb{R}^{10 \times 11}, D^{(2)} \in \mathbb{R}^{10 \times 11}, D^{(3)} \in \mathbb{R}^{1 \times 11}$$



```
thetaVec = [ Theta1(:); Theta2(:); Theta3(:)];  
DVec = [D1(:); D2(:); D3(:)];
```

```
Theta1 = reshape(thetaVec(1:110),10,11);  
Theta2 = reshape(thetaVec(111:220),10,11);  
Theta3 = reshape(thetaVec(221:231),1,11);
```


Learning Algorithm

Have initial parameters $\Theta^{(1)}, \Theta^{(2)}, \Theta^{(3)}$.

Unroll to get `initialTheta` to pass to


```
fminunc(@costFunction, initialTheta, options)
```

```
function [jval, gradientVec] = costFunction(thetaVec)
```

From `thetaVec`, get $\Theta^{(1)}, \Theta^{(2)}, \Theta^{(3)}$.

Use forward prop/back prop to compute $D^{(1)}, D^{(2)}, D^{(3)}$ and $J(\Theta)$.

Unroll $D^{(1)}, D^{(2)}, D^{(3)}$ to get `gradientVec`.




Machine Learning

Neural Networks: Learning

Gradient checking

Numerical estimation of gradients



Implement: $\text{gradApprox} = \frac{J(\text{theta} + \text{EPSILON}) - J(\text{theta} - \text{EPSILON})}{2 * \text{EPSILON}}$

Parameter vector θ

$\theta \in \mathbb{R}^n$ (E.g. θ is “unrolled” version of $\Theta^{(1)}, \Theta^{(2)}, \Theta^{(3)}$)

$$\theta = \theta_1, \theta_2, \theta_3, \dots, \theta_n$$

$$\frac{\partial}{\partial \theta_1} J(\theta) \approx \frac{J(\theta_1 + \epsilon, \theta_2, \theta_3, \dots, \theta_n) - J(\theta_1 - \epsilon, \theta_2, \theta_3, \dots, \theta_n)}{2\epsilon}$$

$$\frac{\partial}{\partial \theta_2} J(\theta) \approx \frac{J(\theta_1, \theta_2 + \epsilon, \theta_3, \dots, \theta_n) - J(\theta_1, \theta_2 - \epsilon, \theta_3, \dots, \theta_n)}{2\epsilon}$$

\vdots

$$\frac{\partial}{\partial \theta_n} J(\theta) \approx \frac{J(\theta_1, \theta_2, \theta_3, \dots, \theta_n + \epsilon) - J(\theta_1, \theta_2, \theta_3, \dots, \theta_n - \epsilon)}{2\epsilon}$$

```
for i = 1:n,  
    thetaPlus = theta;  
    thetaPlus(i) = thetaPlus(i) + EPSILON;  
    thetaMinus = theta;  
    thetaMinus(i) = thetaMinus(i) - EPSILON;  
    gradApprox(i) = (J(thetaPlus) - J(thetaMinus))  
                    / (2*EPSILON);  
end;
```


Check that $\text{gradApprox} \approx \text{DVec}$

Implementation Note:

- Implement backprop to compute **DVec** (unrolled $D^{(1)}, D^{(2)}, D^{(3)}$).
- Implement numerical gradient check to compute **gradApprox**.
- Make sure they give similar values.
- Turn off gradient checking. Using backprop code for learning.

Important:

- Be sure to disable your gradient checking code before training your classifier. If you run numerical gradient computation on every iteration of gradient descent (or in the inner loop of **costFunction(...)**) your code will be very slow.



Machine Learning

Neural Networks: Learning

Random initialization

Initial value of Θ


For gradient descent and advanced optimization method, need initial value for Θ .

```
optTheta = fminunc(@costFunction,  
                  initialTheta, options)
```

Consider gradient descent

Set `initialTheta = zeros(n,1)` ?

Zero initialization



$$\Theta_{ij}^{(l)} = 0 \text{ for all } i, j, l.$$

After each update, parameters corresponding to inputs going into each of two hidden units are identical.


Random initialization: Symmetry breaking

Initialize each $\Theta_{ij}^{(l)}$ to a random value in $[-\epsilon, \epsilon]$
(i.e. $-\epsilon \leq \Theta_{ij}^{(l)} \leq \epsilon$)

E.g.

```
Theta1 = rand(10,11)*(2*INIT_EPSILON)  
        - INIT_EPSILON;
```

```
Theta2 = rand(1,11)*(2*INIT_EPSILON)  
        - INIT_EPSILON;
```






Machine Learning

Neural Networks: Learning

Putting it together

Training a neural network

Pick a network architecture (connectivity pattern between neurons)



No. of input units: Dimension of features $x^{(i)}$

No. output units: Number of classes

Reasonable default: 1 hidden layer, or if >1 hidden layer, have same no. of hidden units in every layer (usually the more the better)


Training a neural network

1. Randomly initialize weights
2. Implement forward propagation to get $h_{\Theta}(x^{(i)})$ for any $x^{(i)}$
3. Implement code to compute cost function $J(\Theta)$
4. Implement backprop to compute partial derivatives $\frac{\partial}{\partial \Theta_{jk}^{(l)}} J(\Theta)$

for i = 1:m

Perform forward propagation and backpropagation using example $(x^{(i)}, y^{(i)})$

(Get activations $a^{(l)}$ and delta terms $\delta^{(l)}$ for $l = 2, \dots, L$).





Training a neural network

5. Use gradient checking to compare $\frac{\partial}{\partial \Theta_{jk}^{(l)}} J(\Theta)$ computed using backpropagation vs. using numerical estimate of gradient of $J(\Theta)$.

Then disable gradient checking code.

6. Use gradient descent or advanced optimization method with backpropagation to try to minimize $J(\Theta)$ as a function of parameters Θ





Machine Learning

Neural Networks: Learning

Backpropagation
example: Autonomous
driving (optional)

