8频合路器技术规格书

KXT-FF-22 · 誊自清工厂 Word 原稿

下表按原稿誊清。整列与前一列完全相同的合并格已去掉。页末点名的笔误已改正，其余数字没有改写。

端口 1

项目	原稿指标
端口	1
频率范围(MHz)	1717.5-1777.5
插入损耗(dB)	≤2.0
驻波比	≤1.3
带内波动（dB)	≤1.8
带外抑制（dB)	80@1812.5-1872.5 80@1927.5-1980 80@1887.5-1915 80@2010-2025 80@2117.5-2167.5 80@2317.5-2380 80@2496-2690 80@3400-3600
平均功率容量(W)	≥20W
工作温度(℃)	-30～+60
工作湿度（%）	5～95
接口形式	N-F/SMA-F
外观	黑色油漆
外形尺寸	300*200*39

端口 2

项目	原稿指标
端口	2
频率范围(MHz)	1812.5-1872.5
插入损耗(dB)	≤2.0
带内波动（dB)	≤1.8
带外抑制（dB)	80@1717.5-1777.5 80@1927.5-1980 80@1887.5-1915 80@2010-2025 80@2117.5-2167.5 80@2317.5-2380 80@2496-2690 80@3400-3600
平均功率容量(W)	≥20W †
工作温度(℃)	-30～+60 †
工作湿度（%）	5～95 †
接口形式	N-F/SMA-F †
外观	黑色油漆 †
外形尺寸	300*200*39 †

端口 3

项目	原稿指标
端口	3
频率范围(MHz)	1927.5-1980
插入损耗(dB)	≤2.0
带内波动（dB)	≤1.8
带外抑制（dB)	80@1717.5-1777.5 80@1812.5-1872.5 80@1887.5-1915 80@2010-2025 80@2117.5-2167.5 80@2317.5-2380 80@2496-2690 80@3400-3600
平均功率容量(W)	≥20W †
工作温度(℃)	-30～+60 †
工作湿度（%）	5～95 †
接口形式	N-F/SMA-F †
外观	黑色油漆 †
外形尺寸	300*200*39 †

端口 4

项目	原稿指标

端口	4
频率范围(MHz)	1887.5-1915/2010-2025
插入损耗(dB)	≤2.0
带内波动（dB)	≤1.8
带外抑制（dB)	80@1717.5-1777.5 80@1812.5-1872.5 80@1927.5-1980 80@2117.5-2167.5 80@2317.5-2380 80@2496-2690 80@3400-3600
平均功率容量(W)	≥20W †
工作温度(℃)	-30～+60 †
工作湿度（%)	5～95 †
接口形式	N-F/SMA-F †
外观	黑色油漆 †
外形尺寸	300*200*39 †

端口 5

项目	原稿指标
端口	5
频率范围(MHz)	2117.5-2167.5
插入损耗(dB)	≤2.0
带内波动（dB)	≤1.8
带外抑制（dB)	80@1717.5-1777.5 80@1812.5-1872.5 80@1887.5-1915 80@2010-2025 80@1927.5-1980 80@2317.5-2380 80@2496-2690 80@3400-3600
平均功率容量(W)	≥20W †
工作温度(℃)	-30～+60 †
工作湿度（%)	5～95 †
接口形式	N-F/SMA-F †
外观	黑色油漆 †
外形尺寸	300*200*39 †

端口 6

项目	原稿指标
端口	6
频率范围(MHz)	2317.5-2380
插入损耗(dB)	≤2.0
带内波动（dB)	≤1.8
带外抑制（dB)	80@1717.5-1777.5 80@1812.5-1872.5 80@1887.5-1915 80@2010-2025 80@1927.5-1980 80@1887.5-1915 80@2496-2690 80@3400-3600
平均功率容量(W)	≥20W †
工作温度(℃)	-30～+60 †
工作湿度（%)	5～95 †
接口形式	N-F/SMA-F †
外观	黑色油漆 †
外形尺寸	300*200*39 †

端口 7

项目	原稿指标
端口	7
频率范围(MHz)	2496-2690
插入损耗(dB)	≤2.0
带内波动（dB)	≤1.8
带外抑制（dB)	80@1717.5-1777.5 80@1812.5-1872.5 80@1887.5-1915 80@2010-2025 80@1927.5-1980 80@1887.5-1915 80@2317.5-2380 80@3400-3600
平均功率容量(W)	≥20W †

工作温度(℃)	-30～+60 †
工作湿度（%）	5～95 †
接口形式	N-F/SMA-F †
外观	黑色油漆 †
外形尺寸	300*200*39 †

端口 8

项目	原稿指标
端口	8
频率范围(MHz)	3400-3600
插入损耗(dB)	≤1.0
带内波动（dB）	≤0.8
带外抑制（dB）	80@1717.5-1777.5 80@1812.5-1872.5 80@1887.5-1915 80@2010-2025 80@1927.5-1980 80@1887.5-1915 80@2317.5-2380 80@2496-2690
平均功率容量(W)	≥20W †
工作温度(℃)	-30～+60 †
工作湿度（%）	5～95 †
接口形式	N-F/SMA-F †
外观	黑色油漆 †
外形尺寸	300*200*39 †

说明

- 来源文件：9频合路器技术规格书 -.doc
- 工厂文件名为「9频合路器技术规格书」，表内只有 8 个端口（第 4 端口含两个通带 1887.5-1915 / 2010-2025），公开标题按 8 频合路器发布。
- 特性阻抗：原稿写了 50 Ω 的，以原稿为准；原稿没写的，N 与 SMA 口按 50 Ω。
- 室内型铝合金腔体。测试条件 25 °C、50 Ω、矢量网络分析仪。出货附该件测试报告。
- 原稿没有互调指标。若订单选择低互调档，按 PIM3 ≤ −150 dBc @ 2×43 dBm 测试并写入报告。
- 多端口表：插损、抑制、隔离只印该端口原稿里有的格子。标 † 的是合并单元格，字只出现在部分端口，已抄到空白端口，数字未改。
- 相同内容还出现在：9频合路器技术规格书 -(1).doc

English

Factory specification

KXT-FF-22 • 8-band Cavity Combiner, 1717.5–3600 MHz

Transcribed from the factory Word file. A column is omitted only when it duplicates the previous column in every row. Typos named in the notes are corrected. Every other number is unchanged.

Port 1

Item	As written
端口	1
频率范围(MHz) / Frequency	1717.5-1777.5
插入损耗(dB) / Insertion loss	≤2.0
驻波比 / VSWR	≤1.3
带内波动（dB） / Ripple	≤1.8
带外抑制（dB） / Rejection	80@1812.5-1872.5 80@1927.5-1980 80@1887.5-1915 80@2010-2025 80@2117.5-2167.5 80@2317.5-2380 80@2496-2690 80@3400-3600
平均功率容量(W) / Average power	≥20W
工作温度(℃) / Operating temperature	-30～+60
工作湿度（%） / Humidity	5～95
接口形式 / Connector	N-F/SMA-F
外观 / Finish	黑色油漆
外形尺寸 / Outline	300*200*39

Port 2

Item	As written
端口	2
频率范围(MHz) / Frequency	1812.5-1872.5
插入损耗(dB) / Insertion loss	≤2.0
带内波动（dB） / Ripple	≤1.8
带外抑制（dB） / Rejection	80@1717.5-1777.5 80@1927.5-1980 80@1887.5-1915 80@2010-2025 80@2117.5-2167.5 80@2317.5-2380 80@2496-2690 80@3400-3600
平均功率容量(W) / Average power	≥20W †
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	N-F/SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	300*200*39 †

Port 3

Item	As written
端口	3
频率范围(MHz) / Frequency	1927.5-1980
插入损耗(dB) / Insertion loss	≤2.0
带内波动（dB） / Ripple	≤1.8
带外抑制（dB） / Rejection	80@1717.5-1777.5 80@1812.5-1872.5 80@1887.5-1915 80@2010-2025 80@2117.5-2167.5 80@2317.5-2380 80@2496-2690 80@3400-3600
平均功率容量(W) / Average power	≥20W †
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	N-F/SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	300*200*39 †

Port 4

Item	As written
端口	4
频率范围(MHz) / Frequency	1887.5-1915/2010-2025
插入损耗(dB) / Insertion loss	≤2.0
带内波动（dB） / Ripple	≤1.8
带外抑制（dB） / Rejection	80@1717.5-1777.5 80@1812.5-1872.5 80@1927.5-1980 80@2117.5-2167.5 80@2317.5-2380 80@2496-2690 80@3400-3600
平均功率容量(W) / Average power	≥20W †
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	N-F/SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	300*200*39 †

Port 5

Item	As written
端口	5
频率范围(MHz) / Frequency	2117.5-2167.5
插入损耗(dB) / Insertion loss	≤2.0
带内波动（dB） / Ripple	≤1.8
带外抑制（dB） / Rejection	80@1717.5-1777.5 80@1812.5-1872.5 80@1887.5-1915 80@2010-2025 80@1927.5-1980 80@2317.5-2380 80@2496-2690 80@3400-3600
平均功率容量(W) / Average power	≥20W †
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	N-F/SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	300*200*39 †

Port 6

Item	As written
端口	6
频率范围(MHz) / Frequency	2317.5-2380
插入损耗(dB) / Insertion loss	≤2.0
带内波动（dB） / Ripple	≤1.8
带外抑制（dB） / Rejection	80@1717.5-1777.5 80@1812.5-1872.5 80@1887.5-1915 80@2010-2025 80@1927.5-1980 80@1887.5-1915 80@2496-2690 80@3400-3600
平均功率容量(W) / Average power	≥20W †
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	N-F/SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	300*200*39 †

Port 7

Item	As written
端口	7
频率范围(MHz) / Frequency	2496-2690
插入损耗(dB) / Insertion loss	≤2.0
带内波动（dB） / Ripple	≤1.8

带外抑制（dB） / Rejection	80@1717.5-1777.5 80@1812.5-1872.5 80@1887.5-1915 80@2010-2025 80@1927.5-1980 80@1887.5-1915 80@2317.5-2380 80@3400-3600
平均功率容量(W) / Average power	≥20W †
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	N-F/SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	300*200*39 †

Port 8

Item	As written
端口	8
频率范围(MHz) / Frequency	3400-3600
插入损耗(dB) / Insertion loss	≤1.0
带内波动（dB） / Ripple	≤0.8
带外抑制（dB） / Rejection	80@1717.5-1777.5 80@1812.5-1872.5 80@1887.5-1915 80@2010-2025 80@1927.5-1980 80@1887.5-1915 80@2317.5-2380 80@2496-2690
平均功率容量(W) / Average power	≥20W †
工作温度(℃) / Operating temperature	-30～+60 †
工作湿度（%） / Humidity	5～95 †
接口形式 / Connector	N-F/SMA-F †
外观 / Finish	黑色油漆 †
外形尺寸 / Outline	300*200*39 †

Notes

- Source file: 9频合路器技术规格书 -.doc
- The factory file was named 9频合路器技术规格书, but the table has 8 ports (port 4 carries two passbands 1887.5-1915 / 2010-2025), so the published title is 8-band.
- Impedance: where the source states 50 Ω, that stands. Where it is silent, N and SMA ports are 50 Ω.
- Indoor aluminum cavity. Tested at 25 °C in a 50 Ω system on a vector network analyzer. A test report ships with the unit.
- The source sheet has no PIM limit. If the order selects the low-PIM option, test PIM3 to ≤ −150 dBc @ 2×43 dBm and put it on the report.
- Multi-port sheet: insertion loss, rejection and isolation are printed only where that port’ s source cell has text. A cell marked † repeats a merged source cell onto a blank port. The number is unchanged.
- The same table also appears in: 9频合路器技术规格书 -(1).doc