2400-2500滤波器技术规格书 - -

KXT-FF-05 · 誊自清工厂 Word 原稿

下表按原稿誊清。整列与前一列完全相同的合并格已去掉。页末点名的笔误已改正，其余数字没有改写。

项目	原稿指标
—	2400-2500
频率范围(MHz)	2400-2500
带宽(MHz)	100
插入损耗(dB)	≤1.5
驻波比	≤1.3
带内波动（dB)	≤1.3
带外抑制（dB)	40@≥2390 40@≥2510 60@≥2380 60@≥2520
平均功率容量(W)	40
工作温度(℃)	-40～+85
工作湿度（%)	5～95
接口形式	SMA-F
外观	黑色油漆

说明

· 来源文件：2400-2500滤波器技术规格书 - - .doc
· 特性阻抗：原稿写了 50 Ω 的，以原稿为准；原稿没写的，N 与 SMA 口按 50 Ω。
· 室内型铝合金腔体。测试条件 25 ℃、50 Ω、矢量网络分析仪。出货附该件测试报告。
· 原稿没有互调指标。若订单选择低互调档，按 PIM3 ≤ −150 dBc @ 2×43 dBm 测试并写入报告。

English

Factory specification

KXT-FF-05 · 2400-2500滤波器技术规格书 - -

Transcribed from the factory Word file. A column is omitted only when it duplicates the previous column in every row. Typos named in the notes are corrected. Every other number is unchanged.

Item	As written
—	2400-2500
频率范围(MHz) / Frequency	2400-2500
带宽(MHz) / Bandwidth	100
插入损耗(dB) / Insertion loss	≤1.5
驻波比 / VSWR	≤1.3
带内波动（dB） / Ripple	≤1.3
带外抑制（dB） / Rejection	40@≥2390 40@≥2510 60@≥2380 60@≥2520
平均功率容量(W) / Average power	40
工作温度(℃) / Operating temperature	-40 ~ +85
工作湿度（%） / Humidity	5 ~ 95
接口形式 / Connector	SMA-F
外观 / Finish	黑色油漆

Notes

· Source file: 2400-2500滤波器技术规格书 - - .doc
· Impedance: where the source states 50 Ω, that stands. Where it is silent, N and SMA ports are 50 Ω.
· Indoor aluminum cavity. Tested at 25 °C in a 50 Ω system on a vector network analyzer. A test report ships with the unit.
· The source sheet has no PIM limit. If the order selects the low-PIM option, test PIM3 to ≤ −150 dBc @ 2×43 dBm and put it on the report.

- The source frequency cell is blank; the passband is only in the table header. This page copies it into the frequency row.