5G 合路器（N41 / N78）

KXT-FF-04 • 誉清自工厂 Word 原稿

原稿表格是按列排的项目。本页按行重排为两个端口加共用机械指标，数字没有改写。

项目	端口 1（原稿指标）	端口 2（原稿指标）
名称	5G合路器	
工作频段	2496~2690MHz	2300-2400MHz
带内插入损耗	≤1.2dB	≤1.2dB
带内波动	≤0.8dB	≤0.8dB
输入输出驻波比	≤1.3	≤1.3
隔离度	≥90dB	≥90dB
机械指标（两端口共用）		
外形尺寸	150*105*40mm含调杆	
螺丝固定尺寸	142*97mm	
螺丝固定孔径	4~3.4（mm）	
接头类型	N-F/SMA	

说明

- 来源文件：1_N41N78合路器指标(4)(1).2026.9.11doc(2).doc。相同内容还出现在：2频合路器指标(2026.9.29.doc。
- 特性阻抗：原稿写了 50 Ω 的，以原稿为准；原稿没写的，N 与 SMA 口按 50 Ω。
- 室内型铝合金腔体。测试条件 25 °C、50 Ω、矢量网络分析仪。出货附该件测试报告。
- 原稿没有互调指标。若订单选择低互调档，按 PIM3 ≤ −150 dBc @ 2×43 dBm 测试并写入报告。
- 询价：sales@cavityfilter.com

2-band Cavity Combiner, 2300–2400 / 2496–2690 MHz

KXT-FF-04 • Transcribed from the factory Word file

The source table is laid out with items in columns. It is shown here as two ports plus shared mechanical rows. No number is changed.

Item	Port 1 (as written)	Port 2 (as written)
Name	5G合路器	
Passband / 工作频段	2496~2690MHz	2300-2400MHz
Insertion loss / 带内插入损耗	≤1.2dB	≤1.2dB
Ripple / 带内波动	≤0.8dB	≤0.8dB
VSWR / 输入输出驻波比	≤1.3	≤1.3
Isolation / 隔离度	≥90dB	≥90dB
Mechanical (shared by both ports)		
Outline / 外形尺寸	150*105*40mm含调杆	
Mounting pitch / 螺丝固定尺寸	142*97mm	
Mounting hole / 螺丝固定孔径	4~3.4（mm）	
Connector / 接头类型	N-F/SMA	

Notes

- Source file: 1_N41N78合路器指标(4)(1).2026.9.11doc(2).doc. The same table also appears in: 2频合路器指标(2026.9.29.doc.
- Impedance: where the source states 50 Ω, that stands. Where it is silent, N and SMA ports are 50 Ω.
- Indoor aluminum cavity. Tested at 25 °C in a 50 Ω system on a vector network analyzer. A test report ships with the unit.
- The source sheet has no PIM limit. If the order selects the low-PIM option, PIM3 is tested to ≤ −150 dBc @ 2×43 dBm and reported.
- Enquiries: sales@cavityfilter.com