B3 FDD 1.8G 75M 双工器

KXT-FF-23 · 誉清自工厂 Word 原稿

原稿是一张两通道表。本页按原稿重排为一张表，数字没有改写。

项目	通道 1（原稿指标）	通道 2（原稿指标）
规格型号	SGQ-1.8G-75M-19088-ZTJ	
工作频段	1710-1785MHz	1805-1880MHz
带内插入损耗	≤1.5dB	≤1.7dB
带内波动	≤0.5dB	≤0.8dB
输入输出驻波比	≤1.3	≤1.3
隔离度	≥80dB	≥80dB
模块尺寸	192*88*46.5带螺杆高度	
螺丝固定尺寸	182mm	
螺丝固定孔孔径	4~4.5（mm）	
RF信号输入输出接头	SMA-Female	
外观	无明显划伤，丝印正确	

说明

- 原稿标题与「规格型号」写作 SGQ-1.8G-75M-19088-ZTJ，本页按原稿公开；网站目录型号为 KXT-FF-23。
- 特性阻抗：原稿没写，N 与 SMA 口按 50 Ω。
- 室内型铝合金腔体。测试条件 25 °C、50 Ω、矢量网络分析仪。出货附该件测试报告。
- 原稿没有互调指标。若订单选择低互调档，按 PIM3 ≤ −150 dBc @ 2×43 dBm 测试并写入报告。
- 机械指标在原稿是两通道共用的合并单元格。
- 询价：sales@cavityfilter.com

B3 FDD 1.8 GHz Cavity Duplexer, 1710–1785 / 1805–1880 MHz

KXT-FF-23 • Transcribed from the factory Word file

The source is one two-channel table. It is laid out here as a single table. No number is changed.

Item	Channel 1 (as written)	Channel 2 (as written)
Model / 规格型号	SGQ-1.8G-75M-19088-ZTJ	
Passband / 工作频段	1710-1785MHz	1805-1880MHz
Insertion loss / 带内插入损耗	≤1.5dB	≤1.7dB
Ripple / 带内波动	≤0.5dB	≤0.8dB
VSWR / 输入输出驻波比	≤1.3	≤1.3
Isolation / 隔离度	≥80dB	≥80dB
Outline / 模块尺寸	192*88*46.5带螺杆高度	
Mounting pitch / 螺丝固定尺寸	182mm	
Mounting hole / 螺丝固定孔孔径	4~4.5（mm）	
RF connector / RF信号输入输出接头	SMA-Female	
Finish / 外观	无明显划伤，丝印正确	

Notes

- The source title and “model” cell read SGQ-1.8G-75M-19088-ZTJ and are shown as written; the catalogue number is KXT-FF-23.
- Impedance: not stated on the source; N and SMA ports are 50 Ω.
- Indoor aluminum cavity. Tested at 25 °C in a 50 Ω system on a vector network analyzer. A test report ships with the unit.
- The source sheet has no PIM limit. If the order selects the low-PIM option, PIM3 is tested to ≤ −150 dBc @ 2×43 dBm and reported.
- Mechanical rows are merged cells shared by both channels on the source sheet.
- Enquiries: sales@cavityfilter.com