

https://client-charolf.vercel.app/search






# **Performance**

Values are estimated and may vary. The <u>performance score</u> is calculated directly from these metrics. See calculator.

0-49

50-89

90-100



**METRICS** Expand view

- First Contentful Paint
  - 0.6 s
- Speed Index
  - 0.6 s
- Largest Contentful Paint
  - 0.6 s

- Time to Interactive
  - 0.6 s
- Total Blocking Time
  - 0 ms
- **Cumulative Layout Shift** 
  - 0.015



Show audits relevant to: All FCP TBT LCP CLS

### DIAGNOSTICS

The `unload` event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward

Source

main.js:257

▲ Serve static assets with an efficient cache policy — 7 resources found

Cache. Use 'pagehide' or 'visibilitychange' events instead. Learn more

A long cache lifetime can speed up repeat visits to your page. <u>Learn more</u>.

Show 3rd-party resources (5)

URL	Cache TTL	Transfer Size
js/main.e07a5c93.js (client-charolf.vercel.app)	None	91 KiB
js/angular-1.5.8.min.js (weatherwidget.io)	None	57 KiB
js/iApp.min.js (weatherwidget.io)	None	8 KiB
css/main.b7fa8ddc.css (client-charolf.vercel.app)	None	6 KiB
css/icon-climacons.css (weatherwidget.io)	None	4 KiB
css/if_w.css (weatherwidget.io)	None	3 KiB
/js/widget.min.js (weatherwidget.io)	None	1 KiB

○ Avoid chaining critical requests — 3 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. <u>Learn more</u>. FCP) LCP

Maximum critical path latency: 130 ms

Initial Navigation

/search (client-charolf.vercel.app)

/icon?family=Material+Icons (fonts.googleapis.com) - 70 ms, 0.85 KiB

/FD126C42-.../main.js?attr=OUKsRJhPb... (me.kis.v2.scr.kaspersky-labs.com) - 0 ms, 123.85 KiB

...css/main.b7fa8ddc.css (client-charolf.vercel.app) - 20 ms, 5.69 KiB

○ Keep request counts low and transfer sizes small — 20 requests - 739 KiB

To set budgets for the quantity and size of page resources, add a budget.json file. <u>Learn more</u>.

Resource Type	Requests	Transfer Size
Total	20	739.3 KiB
Script	7	704.5 KiB
Stylesheet	4	12.8 KiB
Other	6	12.7 KiB
Document	3	9.3 KiB
Image	0	0.0 KiB
Media	0	0.0 KiB
Font	0	0.0 KiB
Third-party	15	634.7 KiB


○ Largest Contentful Paint element — 1 element found

This is the largest contentful element painted within the viewport. Learn More (LCP)




O Avoid large layout shifts - 1 element found

These DOM elements contribute most to the CLS of the page. CLS



More information about the performance of your application. These numbers don't directly affect the Performance score.



URL	Transfer Size	Potential Savings
/FD126C42/main.js?attr=0UKsRJhPb (me.kis.v2.scr.kaspersky-labs.com)	123.9 KiB	45.2 KiB

### Reduce unused CSS

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. Learn more. (FCP) (LCP)

● Reduce unused JavaScript — Potential savings of 113 KiB

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. <u>Learn more</u>. <u>LCP</u>

Show 3rd-party resources (1)

URL	Transfer Size	Potential Savings
/FD126C42/main.js?attr=0UKsRJhPb (me.kis.v2.scr.kaspersky-labs.com)	123.9 KiB	75.9 KiB
js/main.e07a5c93.js (client-charolf.vercel.app)	90.9 KiB	37.4 KiB
/node_modules/react-dom/cjs/react-dom.production.min.js	40.9 KiB	15.2 KiB
/node_modules/@auth0/auth0-react/node_modules/@auth0/auth0-spa-js/dist/auth0-spa-js.production.esm.js	33.4 KiB	14.3 KiB
/node_modules/@babel/runtime/helpers/esm/regeneratorRuntime.js	2.0 KiB	1.1 KiB
components/Profile.jsx	1.1 KiB	1.1 KiB
components/Details.jsx	0.9 KiB	0.9 KiB

## Efficiently encode images

Optimized images load faster and consume less cellular data. Learn more.

Serve images in next-gen formats

Image formats like WebP and AVIF often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. <u>Learn more</u>.

• Enable text compression — Potential savings of 101 KiB

Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes.  $\underline{\text{Learn}}$   $\underline{\text{more}}$ .  $\underline{\text{FCP}}$   $\underline{\text{LCP}}$ 

URL	Transfer	Potentia
	Size	Savings
/FD126C42/main.js?attr=0UKsRJhPb (me.kis.v2.scr.kaspersky-labs.com)	123.6 KiB	100.6 KiE
Preconnect to required origins		
Consider adding `preconnect` or `dns-prefetch` resource hints to establish early connectorigins. <u>Learn more</u> . FCP (LCP)	ctions to important th	ird-party
Initial server response time was short — Root document took 30 ms		
Keep the server response time for the main document short because all other requests LCP	depend on it. <u>Learn r</u>	more. FCP
URL		Time Spen
/search (client-charolf.vercel.app)		30 m
Avoid multiple page redirects		
Redirects introduce additional delays before the page can be loaded. <u>Learn more</u> . FCP	LCP	
Preload key requests		
Consider using ` <link rel="preload"/> ` to prioritize fetching resources that are currently reamore. FCP (LCP)	quested later in page	load. <u>Learn</u>
Use HTTP/2		
HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. <u>L</u>	<u>_earn more</u> .	
Use video formats for animated content		

Ramova dunlicata modulas in JavaScrint hundlas

Iveniove authorate modules in savascript panales

Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity. [TBT]

Avoid serving legacy JavaScript to modern browsers — Potential savings of 10 KiB

Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers.

<u>Learn More (TBT)</u>

URL		Potential Savings
js/main.e07a5c93.js (client-charolf.vercel.app)		10.4 KiB
main.e07a5c93.js:2	Array.from	
main.e07a5c93.js:2	Array.prototype.includes	
main.e07a5c93.js:2	@babel/plugin-transform-classes	

Preload Largest Contentful Paint image

Preload the image used by the LCP element in order to improve your LCP time. Learn more. [LCP]

Avoids enormous network payloads — Total size was 752 KiB

Large network payloads cost users real money and are highly correlated with long load times. Learn more. (LCP)


Show 3rd-party resources (6)

URL	Transfer Size
/FD126C42/main.js?attr=0UKsRJhPb (me.kis.v2.scr.kaspersky-labs.com)	247.6 KiB
/FD126C42/main.js?attr=ASS5lHSXC (me.kis.v2.scr.kaspersky-labs.com)	175.6 KiB
/FD126C42/main.js?attr=OUKsRJhPb (me.kis.v2.scr.kaspersky-labs.com)	123.9 KiB
js/main.e07a5c93.js (client-charolf.vercel.app)	90.9 KiB
js/angular-1.5.8.min.js (weatherwidget.io)	57.0 KiB

URL	Transfer Size
/favicon.ico (client-charolf.vercel.app)	12.2 KiB
js/iApp.min.js (weatherwidget.io)	8.2 KiB
css/main.b7fa8ddc.css (client-charolf.vercel.app)	5.7 KiB
/logo192.png (client-charolf.vercel.app)	5.6 KiB
/w/ (weatherwidget.io)	3.9 KiB

● Avoids an excessive DOM size — 39 elements

A large DOM will increase memory usage, cause longer <u>style calculations</u>, and produce costly <u>layout reflows</u>. <u>Learn more</u>.



User Timing marks and measures

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. <u>Learn more</u>.

JavaScript execution time

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. <u>Learn more</u>. (TBT)

● Minimizes main-thread work — 0.2 s

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. <u>Learn more</u> (TBT)

Category	Time Spent
Script Evaluation	73 ms
Other	56 ms
Script Parsing & Compilation	17 ms
Style & Layout	5 ms
Rendering	4 ms
Parse HTML & CSS	3 ms
Garbage Collection	1 ms

All text remains visible during webfont loads

Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. Learn more. [FCP] [LCP]

● Minimize third-party usage — Third-party code blocked the main thread for 0 ms

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. <u>Learn more</u>. (TBT)

Third-Party	Transfer Size	Main-Thread Blocking Time
<u>Auth0</u>	7 KiB	0 ms
Google Fonts	1 KiB	0 ms

O Lazy load third-party resources with facades

to user input. Learn more. (TBT)


Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. Learn more. Largest Contentful Paint image was not lazily loaded Above-the-fold images that are lazily loaded render later in the page lifecycle, which can delay the largest contentful paint. Learn more. Uses passive listeners to improve scrolling performance Consider marking your touch and wheel event listeners as 'passive' to improve your page's scroll performance. Learn more. Avoids document.write() For users on slow connections, external scripts dynamically injected via 'document.write()' can delay page load by tens of seconds. Learn more. Avoid long main-thread tasks Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. Learn more (TBT) Avoid non-composited animations Animations which are not composited can be janky and increase CLS. Learn more (CLS) Image elements have explicit width and height Set an explicit width and height on image elements to reduce layout shifts and improve CLS. Learn more [CLS] Has a <meta name="viewport"> tag with width or initial-scale A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents a 300 millisecond delay



**Accessibility** 


These checks highlight opportunities to improve the accessibility of your web app. Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

### CONTRAST



These are opportunities to improve the legibility of your content.

### **NAVIGATION**



These are opportunities to improve keyboard navigation in your application.

### ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

O The page has a logical tab order

Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. <u>Learn more</u>.

O Interactive controls are keyboard focusable	^
Custom interactive controls are keyboard focusable and display a focus indicator. <u>Learn more</u> .	
O Interactive elements indicate their purpose and state	^
Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. <u>Learn more</u> .	
The user's focus is directed to new content added to the page	^
If new content, such as a dialog, is added to the page, the user's focus is directed to it. <u>Learn more</u> .	
User focus is not accidentally trapped in a region	^
A user can tab into and out of any control or region without accidentally trapping their focus. <u>Learn more</u> .	
Custom controls have associated labels	^
Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. <u>Learn more</u> .	
O Custom controls have ARIA roles	^
Custom interactive controls have appropriate ARIA roles. <u>Learn more</u> .	
O Visual order on the page follows DOM order	^
DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more</u> .	
O Offscreen content is hidden from assistive technology	^
Offscreen content is hidden with display: none or aria-hidden=true. <u>Learn more</u> .	
O HTML5 landmark elements are used to improve navigation	^
Landmark elements ( <main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technolo Learn more.</nav></main>	gy.

These items address areas which an automated testing tool cannot cover. Learn more in our guide on <u>conducting an accessibility</u> <u>review</u>.

PASSED AUDITS (11) Hide

[aria-hidden="true"] is not present on the document <body></body>	^
Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document Learn more.	` <body>`.</body>
Buttons have an accessible name	^
When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for us rely on screen readers. <u>Learn more</u> .	sers who
Form elements have associated labels	^
Labels ensure that form controls are announced properly by assistive technologies, like screen readers. <u>Learn mo</u>	ore.
[user-scalable="no"] is not used in the <meta name="viewport"/> element and the [maximum-scale] attribute is r less than 5.	not
Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the coof a web page. <u>Learn more</u> .	ontents
The page contains a heading, skip link, or landmark region	^
The page contains a heading, skip link, or landmark region  Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more.	^
	^
Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. <u>Learn more</u> .	^ ne if a
Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more.  • Document has a <title> element  The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine&lt;/td&gt;&lt;td&gt;^ ne if a&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. &lt;a href="Learn more"&gt;Learn more&lt;/a&gt;.  Document has a &lt;title&gt; element  The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determin page is relevant to their search. &lt;a href="Learn more"&gt;Learn more&lt;/a&gt;.&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more.  Document has a &lt;title&gt; element  The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determin page is relevant to their search. Learn more.  [id] attributes on active, focusable elements are unique&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more.  Document has a &lt;title&gt; element  The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determin page is relevant to their search. Learn more.  [id] attributes on active, focusable elements are unique  All focusable elements must have a unique 'id' to ensure that they're visible to assistive technologies. Learn more&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more.  Document has a &lt;title&gt; element  The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determin page is relevant to their search. Learn more.  [id] attributes on active, focusable elements are unique  All focusable elements must have a unique `id` to ensure that they're visible to assistive technologies. Learn more&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;/tbody&gt;&lt;/table&gt;</title>	

If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might announce the page's text correctly. <u>Learn more</u> .	
<html> element has a valid value for its [lang] attribute</html>	^
Specifying a valid <u>BCP 47 language</u> helps screen readers announce text properly. <u>Learn more</u> .	

Links have a discernible name

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. <u>Learn more</u>.

NOT APPLICABLE (31)
Hide

O [accesskey] values are unique
Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. <u>Learn</u> more.
O [aria-*] attributes match their roles
Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. <u>Learn more</u> .
O button, link, and menuitem elements have accessible names
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u> .
O [aria-hidden="true"] elements do not contain focusable descendents
Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. <u>Learn more</u> .
ARIA input fields have accessible names
When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u> .
ARIA meter elements have accessible names


When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusal for users who rely on screen readers. <u>Learn more</u> .	ble
ARIA progressbar elements have accessible names	^
When a `progressbar` element doesn't have an accessible name, screen readers announce it with a generic name, ma it unusable for users who rely on screen readers. <u>Learn more</u> .	king
O [role]s have all required [aria-*] attributes	^
Some ARIA roles have required attributes that describe the state of the element to screen readers. <u>Learn more</u> .	
Elements with an ARIA [role] that require children to contain a specific [role] have all required children.	^
Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. <u>Learn mor</u>	<u>e</u> .
[role]s are contained by their required parent element	^
Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. <u>Learn more</u> .	
O [role] values are valid	^
ARIA roles must have valid values in order to perform their intended accessibility functions. <u>Learn more</u> .	
ARIA toggle fields have accessible names	^
When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unus for users who rely on screen readers. <u>Learn more</u> .	sable
ARIA tooltip elements have accessible names	^
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusal for users who rely on screen readers. <u>Learn more</u> .	ble
ARIA treeitem elements have accessible names	^
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusal for users who rely on screen readers. <u>Learn more</u> .	ble
O [aria-*] attributes have valid values	^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. <u>Learn more</u> .
O [aria-*] attributes are valid and not misspelled
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. <u>Learn more</u> .
<dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <div> elements.</td></tr><tr><td>When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. <u>Learn more</u>.</td></tr><tr><td>O Definition list items are wrapped in <dl> elements</td></tr><tr><td>Definition list items ('<dt>' and '<dd>') must be wrapped in a parent '<dl>' element to ensure that screen readers can properly announce them. <u>Learn more</u>.</td></tr><tr><td>O ARIA IDs are unique</td></tr><tr><td>The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. <u>Learn more</u>.</td></tr><tr><td>O No form fields have multiple labels</td></tr><tr><td>Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. <u>Learn more</u>.</td></tr><tr><td>O Image elements have [alt] attributes</td></tr><tr><td>Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <u>Learn more</u>.</td></tr><tr><td><pre>o <input type="image"> elements have [alt] text</pre></td></tr><tr><td>When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. <u>Learn more</u>.</td></tr><tr><td>Lists contain only <li>elements and script supporting elements (<script> and <template>).</td></tr><tr><td>Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. <u>Learn</u> more.</td></tr><tr><td>O List items (<li>) are contained within <ul> or <ol> parent elements</td></tr></tbody></table></script></dd></dt></dl>

Screen readers require list items (` <li>`) to be contained within a parent `<ul>` or `<ol>` to be announced properly. <u>Learn</u> more.</ol></ul></li>	
The document does not use <meta http-equiv="refresh"/>	
Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. <u>Learn more</u> .	
O <object> elements have alternate text</object>	
Screen readers cannot translate non-text content. Adding alternate text to ` <object>` elements helps screen readers convey meaning to users. <u>Learn more</u>.</object>	
No element has a [tabindex] value greater than 0	
A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <u>Learn more</u> .	
Cells in a  element that use the [headers] attribute refer to table cells within the same table.	
Screen readers have features to make navigating tables easier. Ensuring `` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more.	
elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.	
Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. <u>Learn more</u> .	
O [lang] attributes have a valid value	
Specifying a valid <u>BCP 47 language</u> on elements helps ensure that text is pronounced correctly by a screen reader. <u>Learn more</u> .	
<pre>      <video> elements contain a <track/> element with [kind="captions"]</video></pre>	
When a video provides a caption it is easier for deaf and hearing impaired users to access its information. <u>Learn more</u> .	

## **Best Practices**

#### **GENERAL**



### TRUST AND SAFETY



PASSED AUDITS (12) Hide

18/25

**Uses HTTPS** All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding mixed content, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more. Avoids requesting the geolocation permission on page load Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more. Avoids requesting the notification permission on page load Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more. Avoids front-end JavaScript libraries with known security vulnerabilities Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. Learn more. Allows users to paste into password fields Preventing password pasting undermines good security policy. Learn more. Displays images with correct aspect ratio Image display dimensions should match natural aspect ratio. Learn more. Serves images with appropriate resolution Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn more. Page has the HTML doctype ^ Specifying a doctype prevents the browser from switching to quirks-mode. Learn more. Properly defines charset

A character encoding declaration is required. It can be done with a `<meta>` tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. <u>Learn more</u>.

Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. Learn more.

No browser errors logged to the console

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. <u>Learn more</u>

Page has valid source maps

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. <u>Learn more</u>.

URL Map URL

...js/main.e07a5c93.js (client-charolf.vercel.app) ...js/main.e07a5c93.js.map (client-charolf.vercel.app)

NOT APPLICABLE (1) Hide

Fonts with font-display: optional are preloaded

Preload 'optional' fonts so first-time visitors may use them. Learn more



SE<sub>0</sub>

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on Core Web Vitals. Learn more.

^



To appear in search results, crawlers need access to your app.

### ADDITIONAL ITEMS TO MANUALLY CHECK (1)

Hide

Structured data is valid

Run the Structured Data Testing Tool and the Structured Data Linter to validate structured data. Learn more.

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (9) Hide

Has a <meta name="viewport"> tag with width or initial-scale

A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents <u>a 300 millisecond delay</u> to user input. Learn more. (TBT)

Document has a <title> element

^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <u>Learn more</u>.

Document has a meta description

^

Meta descriptions may be included in search results to concisely summarize page content. Learn more.

Page has successful HTTP status code

^

Pages with unsuccessful HTTP status codes may not be indexed properly. Learn more.

Links have descriptive text

Descriptive link text helps search engines understand your content. <u>Learn more</u> .	
Links are crawlable	^
Search engines may use `href` attributes on links to crawl websites. Ensure that the `href` attribute of anchor element links to an appropriate destination, so more pages of the site can be discovered. <u>Learn More</u>	ıts
robots.txt is valid	^
If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled indexed. <u>Learn more</u> .	or
Document has a valid hreflang	^
hreflang links tell search engines what version of a page they should list in search results for a given language or req <u>Learn more</u> .	gion.
Document avoids plugins	^
Search engines can't index plugin content, and many devices restrict plugins or don't support them. <u>Learn more</u> .	
NOT APPLICABLE (4)	Hide
O Image elements have [alt] attributes	^
Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an emalt attribute. <u>Learn more</u> .	pty
O Decument has a valid retranspired	

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more.

Document has a valid rel=canonical

Canonical links suggest which URL to show in search results. Learn more.

Document uses legible font sizes

Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive to have >60% of page text ≥12px. Learn more.

Tap targets are sized appropriately

Alteractive elements like buttons and links should be large enough (48x48px), and have enough space around them, to be easy enough to tap without overlapping onto other elements. Learn more.



### **PWA**

These checks validate the aspects of a Progressive Web App. Learn more.



Web app manifest or service worker do not meet the installability requirements — 1 reason

Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. <u>Learn more</u>.

Failure reason

No matching service worker detected. You may need to reload the page, or check that the scope of the service worker for the current page encloses the scope and start URL from the manifest.

# PWA OPTIMIZED

▲ Does not register a service worker that controls page and start\_url

The service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. <u>Learn more</u>.

Configured for a custom splash screen

A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. <u>Learn</u> <u>more</u>.

Sets a theme color for the address bar.

The browser address bar can be themed to match your site. Learn more.

Content is sized correctly for the viewport

Initial page load

If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. <u>Learn more</u> .	
Has a <meta name="viewport"/> tag with width or initial-scale	^
A ` <meta name="viewport"/> ` not only optimizes your app for mobile screen sizes, but also prevents <u>a 300 millisecond</u> to user input. <u>Learn more</u> . TBT	<u>delay</u>
Provides a valid apple-touch-icon	^
For ideal appearance on iOS when users add a progressive web app to the home screen, define an `apple-touch-icon must point to a non-transparent 192px (or 180px) square PNG. <u>Learn More</u> .	. It
▲ Manifest doesn't have a maskable icon	^
A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. <u>Learn more</u> .	
ADDITIONAL ITEMS TO MANUALLY CHECK (3)	Hide
Site works cross-browser	^
To reach the most number of users, sites should work across every major browser. <u>Learn more</u> .	
Page transitions don't feel like they block on the network	^
Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception performance. <u>Learn more</u> .	on of
O Each page has a URL	^
Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. <u>Learn more</u> .	
These checks are required by the baseline <u>PWA Checklist</u> but are not automatically checked by Lighthouse. They do not aff your score but it's important that you verify them manually.	ect
Captured at Aug 22, 2022, 5:00 Emulated Desktop with Single page load PM PDT Lighthouse 9.6.1	

**Custom throttling** 

Using Chromium 104.0.5112.102

with devtools

Generated by **Lighthouse** 9.6.1 | File an issue