

DATA SCIENCE CAPSTONE PROJECT

PRESENTED BY :
BASKARAN CHARU

OCTOBER 03 / 25

TABLE OF CONTENTS

01 Executive Summary

02 Introduction

03 Methodology

04 Results

05 Conclusion

06 Appendix



EXECUTIVE SUMMARY

Summary of methodologies

- Data collection
- Data wrangling
- Exploratory Data Analysis with Data Visualization
- Exploratory Data Analysis with SQL
- Building an interactive map with Folium
- Building a Dashboard with Plotly Dash
- Predictive analysis (Classification)

Summary of all results

- Exploratory Data Analysis results
- Interactive analytics demo in screenshots
- Predictive analysis results

INTRODUCTION

Project background and context

SpaceX is the most successful company of the commercial space age, making space travel affordable. The company advertises Falcon 9 rocket launches on its website, with a cost of 62 million dollars; other providers cost upward of 165 million dollars each, much of the savings is because SpaceX can reuse the first stage. Therefore, if we can determine if the first stage will land, we can determine the cost of a launch. Based on public information and machine learning models, we are going to predict if SpaceX will reuse the first stage.

Questions to be answered

- How do variables such as payload mass, launch site, number of flights, and orbits affect the success of the first stage landing?
- Does the rate of successful landings increase over the years?
- What is the best algorithm that can be used for binary classification in this case?

METHODOLOGY



Data collection methodology:

- Using SpaceX Rest API
- Using Web Scrapping from Wikipedia

Performed data wrangling

- Filtering the data
- Dealing with missing values
- Using One Hot Encoding to prepare the data to a binary classification

Performed exploratory data analysis (EDA) using visualization and SQL

Performed interactive visual analytics using Folium and Plotly Dash

Performed predictive analysis using classification models

- Building, tuning and evaluation of classification models to ensure the best results

DATA COLLECTION

Data collection process involved a combination of API requests from SpaceX REST API and Web Scraping data from a table in SpaceX's Wikipedia entry.

We had to use both of these data collection methods in order to get complete information about the launches for a more detailed analysis.


Data Columns are obtained by using SpaceX REST API:

FlightNumber, Date, BoosterVersion, PayloadMass, Orbit, LaunchSite, Outcome, Flights, GridFins, Reused, Legs, LandingPad, Block, ReusedCount, Serial, Longitude, Latitude


Data Columns are obtained by using Wikipedia Web Scraping:

Flight No., Launch site, Payload, PayloadMass, Orbit, Customer, Launch outcome, Version Booster, Booster landing, Date, Time

DATA COLLECTION – SPACEX API



DATA COLLECTION – WEB SCRAPING



DATA WRANGLING

In the data set, there are several different cases where the booster did not land successfully. Sometimes a landing was attempted but failed due to an accident; for example, True Ocean means the mission outcome was successfully landed to a specific region of the ocean while False Ocean means the mission outcome was unsuccessfully landed to a specific region of the ocean. True RTLS means the mission outcome was successfully landed to a ground pad False RTLS means the mission outcome was unsuccessfully landed to a ground pad. True ASDS means the mission outcome was successfully landed on a drone ship False ASDS means the mission outcome was unsuccessfully landed on a drone ship. We mainly convert those outcomes into Training Labels with "1" means the booster successfully landed, "0" means it was unsuccessful.

**Perform exploratory Data Analysis
and determine Training Labels**



**Calculate the number of launches
on each site**

**Calculate the number and occurrence
of each orbit**

**Calculate the number and occurrence
of mission outcome per orbit type**

**Create a landing outcome label
from Outcome column**

**Exporting the data
to CSV**

EDA WITH DATA VISUALIZATION

Charts were plotted:

Flight Number vs. Payload Mass, Flight Number vs. Launch Site, Payload Mass vs. Launch Site, Orbit Type vs. Success Rate, Flight Number vs. Orbit Type, Payload Mass vs Orbit Type and Success Rate Yearly Trend

Scatter plots show the relationship between variables. If a relationship exists, they could be used in machine learning model.

Bar charts show comparisons among discrete categories. The goal is to show the relationship between the specific categories being compared and a measured value.

Line charts show trends in data over time (time series).

EDA WITH SQL

Performed SQL queries:

- Displaying the names of the unique launch sites in the space mission
- Displaying 5 records where launch sites begin with the string 'CCA'
- Displaying the total payload mass carried by boosters launched by NASA (CRS)
- Displaying average payload mass carried by booster version F9 v1.1
- Listing the date when the first successful landing outcome in ground pad was achieved
- Listing the names of the boosters which have success in drone ship and have payload mass greater than 4000 but less than 6000
- Listing the total number of successful and failure mission outcomes
- Listing the names of the booster versions which have carried the maximum payload mass
- Listing the failed landing outcomes in drone ship, their booster versions and launch site names for the months in year 2015
- Ranking the count of landing outcomes (such as Failure (drone ship) or Success (ground pad)) between the date 2010-06-04 and 2017-03-20 in descending order

BUILD AN INTERACTIVE MAP WITH FOLIUM

Markers of all Launch Sites:

- Added Marker with Circle, Popup Label and Text Label of NASA Johnson Space Center using its latitude and longitude coordinates as a start location.
- Added Markers with Circle, Popup Label and Text Label of all Launch Sites using their latitude and longitude coordinates to show their geographical locations and proximity to Equator and coasts.

Coloured Markers of the launch outcomes for each Launch Site:

- Added coloured Markers of success (Green) and failed (Red) launches using Marker Cluster to identify which launch sites have relatively high success rates.

Distances between a Launch Site to its proximities:

- Added coloured Lines to show distances between the Launch Site KSC LC-39A (as an example) and its proximities like Railway, Highway, Coastline and Closest City.

[Git hub: Interactive Visual Analytics with Folium](#)

BUILD A DASHBOARD WITH PLOTLY DASH

Launch Sites Dropdown List:

- Added a dropdown list to enable Launch Site selection.

Pie Chart showing Success Launches (All Sites/Certain Site):

- Added a pie chart to show the total successful launches count for all sites and the Success vs. Failed counts for the site, if a specific Launch Site was selected.

Slider of Payload Mass Range:


- Added a slider to select Payload range.

Scatter Chart of Payload Mass vs. Success Rate for the different Booster Versions:

- Added a scatter chart to show the correlation between Payload and Launch Success.

[Git hub: Dashboard with Plotly Dash](#)


PREDICTIVE ANALYSIS (CLASSIFICATION)




RESULTS

Exploratory data analysis results


- Interactive analytics demo in screenshots
- Predictive analysis results



EDA WITH VISUALIZATION




FLIGHT NUMBER VS. LAUNCH SITE



Explanation:

- The earliest flights all failed while the latest flights all succeeded.
- The CCAFS SLC 40 launch site has about a half of all launches.
- VAFB SLC 4E and KSC LC 39A have higher success rates.
- It can be assumed that each new launch has a higher rate of success.

PAYLOAD VS. LAUNCH SITE




Explanation:

- For every launch site the higher the payload mass, the higher the success rate.
- Most of the launches with payload mass over 7000 kg were successful.
- KSC LC 39A has a 100% success rate for payload mass under 5500 kg too.


SUCCESS RATE VS. ORBIT TYPE

Explanation:

- Orbits with 100% success rate:
 - ES-L1, GEO, HEO, SSO
- Orbits with 0% success rate:
 - SO
- Orbits with success rate between 50% and 85%:
 - GTO, ISS, LEO, MEO, PO, VLEO




FLIGHT NUMBER VS. ORBIT TYPE



Explanation:

- In the LEO orbit the Success appears related to the number of flights; on the other hand, there seems to be no relationship between flight number when in GTO orbit.

PAYLOAD MASS VS. ORBIT TYPE




Explanation:

- Heavy payloads have a negative influence on GTO orbits and positive on GTO and Polar LEO (ISS) orbits.


LAUNCH SUCCESS YEARLY TREND

Explanation:

- The success rate since 2013 kept increasing till 2020.



EDA WITH SQL



ALL LAUNCH SITE NAMES

```
[12]: %sql select distinct launch_site from SPACEXTABLE;
```

```
* sqlite:///my_data1.db
```

```
Done.
```

```
[12]: Launch_Site
```

```
CCAFS LC-40
```

```
VAFB SLC-4E
```

```
KSC LC-39A
```

```
CCAFS SLC-40
```

Explanation:

- Displaying the names of the unique launch sites in the space mission

LAUNCH SITE NAMES BEGIN WITH `CCA`

Out[5]:

DATE	time_utc	booster_version	launch_site	payload	payload_mass_kg	orbit	customer	mission_outcome	landing_outcome
2010-06-04	18:45:00	F9 v1.0 B0003	CCAFS LC-40	Dragon Spacecraft Qualification Unit	0	LEO	SpaceX	Success	Failure (parachute)
2010-12-08	15:43:00	F9 v1.0 B0004	CCAFS LC-40	Dragon demo flight C1, two CubeSats, barrel of Brouere cheese	0	LEO (ISS)	NASA (COTS) NRO	Success	Failure (parachute)
2012-05-22	07:44:00	F9 v1.0 B0005	CCAFS LC-40	Dragon demo flight C2	525	LEO (ISS)	NASA (COTS)	Success	No attempt
2012-10-08	00:35:00	F9 v1.0 B0006	CCAFS LC-40	SpaceX CRS-1	500	LEO (ISS)	NASA (CRS)	Success	No attempt
2013-03-01	15:10:00	F9 v1.0 B0007	CCAFS LC-40	SpaceX CRS-2	677	LEO (ISS)	NASA (CRS)	Success	No attempt

Explanation:

- Displaying 5 records where launch sites begin with the string 'CCA'.

TOTAL PAYLOAD MASS

```
[16]: %sql
      SELECT SUM(PAYLOAD_MASS_KG_)
      FROM SPACEXTBL
      WHERE Customer = 'NASA (CRS)';
```

```
* sqlite:///my_data1.db
```

```
Done.
```

```
[16]: SUM(PAYLOAD_MASS_KG_)
      45596
```

Explanation:

- Displaying the total payload mass carried by boosters launched by NASA (CRS)

AVERAGE PAYLOAD MASS BY F9 V1.1

```
[17]: %sql
      SELECT AVG(PAYLOAD_MASS_KG_)
      FROM SPACEXTBL
      WHERE Booster_Version LIKE 'F9 v1.0%';
```

```
* sqlite:///my_data1.db
Done.
```

```
[17]: AVG(PAYLOAD_MASS_KG_)
      340.4
```

Explanation:

- Displaying average payload mass carried by booster version F9 v1.1

FIRST SUCCESSFUL GROUND LANDING DATE

```
[44]: %sql select min(Date) as first_successful_landing from SPACEXTABLE where Landing_Outcome = 'Success (ground pad)';
      * sqlite:///my_data1.db
      Done.
[44]: first_successful_landing
      2015-12-22
```

Explanation:

- Listing the date when the first successful landing outcome in ground pad was achieved

SUCCESSFUL DRONE SHIP LANDING WITH PAYLOAD BETWEEN 4000 AND 6000

```
[43]: %sql select Booster_Version from SPACEXTBL where Landing_Outcome = 'Success (drone ship)' and PAYLOAD_MASS_KG_ between 4000 and 6000;
```

```
* sqlite:///my_data1.db
```

```
Done.
```

```
[43]: Booster_Version
```

```
F9 FT B1022
```

```
F9 FT B1026
```

```
F9 FT B1021.2
```

```
F9 FT B1031.2
```

Explanation:

- Listing the names of the boosters which have success in drone ship and have payload mass greater than 4000 but less than 6000.

TOTAL NUMBER OF SUCCESSFUL AND FAILURE MISSION OUTCOMES

```
[23]: %sql select mission_outcome, count(*) as total_number from SPACEXTBL group by mission_outcome;
```

```
* sqlite:///my_data1.db
```

```
Done.
```

```
[23]:
```

Mission_Outcome	total_number
Failure (in flight)	1
Success	98
Success	1
Success (payload status unclear)	1

Explanation:

- Listing the total number of successful and failure mission outcomes.

BOOSTERS CARRIED MAXIMUM PAYLOAD

```
[27]: %sql select booster_version from SPACEXTBL where payload_mass__kg_ = (select max(payload_mass__kg_) from SPACEXTBL);
```

```
* sqlite:///my_data1.db
```

```
Done.
```

```
[27]: Booster_Version
```

```
F9 B5 B1048.4
```

```
F9 B5 B1049.4
```

```
F9 B5 B1051.3
```

```
F9 B5 B1056.4
```

```
F9 B5 B1048.5
```

```
F9 B5 B1051.4
```

```
F9 B5 B1049.5
```

```
F9 B5 B1060.2
```

```
F9 B5 B1058.3
```

```
F9 B5 B1051.6
```

```
F9 B5 B1060.3
```

```
F9 B5 B1049.7
```

Explanation:

- Listing the names of the booster versions which have carried the maximum payload mass.

2015 LAUNCH RECORDS

```
substr(Date, 0, 5) = '2015' AND 'Landing_Outcome' = 'Failure (drone ship)';  
* sqlite:///my_data1.db  
Done.  
[39]:
```

MonthName	Landing_Outcome	Booster_Version	Launch_Site
January	Failure (drone ship)	F9 v1.1 B1012	CCAFS LC-40
April	Failure (drone ship)	F9 v1.1 B1015	CCAFS LC-40

Explanation:

- Listing the failed landing outcomes in drone ship, their booster versions and launch site names for the months in year 2015.


RANK SUCCESS COUNT BETWEEN 2010-06-04 AND 2017-03-20

```
COUNT / DESC,  
* sqlite:///my_data1.db  
Done.  
[40]: "Landing_Outcome" Events  
      Landing_Outcome      31
```

Explanation:

- Ranking the count of landing outcomes (such as Failure (drone ship) or Success (ground pad)) between the date 2010-06-04 and 2017-03-20 in descending order.

INTERACTIVE MAP WITH FOLIUM



ALL LAUNCH SITES' LOCATION MARKERS ON A GLOBAL MAP —

Explanation:

- Most of Launch sites are in proximity to the Equator line. The land is moving faster at the equator than any other place on the surface of the Earth. Anything on the surface of the Earth at the equator is already moving at 1670 km/hour. If a ship is launched from the equator it goes up into space, and it is also moving around the Earth at the same speed it was moving before launching. This is because of inertia. This speed will help the spacecraft keep up a good enough speed to stay in orbit.

- All launch sites are in very close proximity to the coast, while launching rockets towards the ocean it minimises the risk of having any debris dropping or exploding near people.


ween the date 2010-06-04 and 2017-03-20 in descending order.



COLOUR-LABELED LAUNCH RECORDS ON THE MAP

Explanation:


- From the colour-labeled markers we should be able to easily identify which launch sites have relatively high success rates.
 - Green Marker = Successful Launch
 - Red Marker = Failed Launch
- Launch Site KSC LC-39A has a very high Success Rate.




DISTANCE FROM THE LAUNCH SITE KSC LC-39A TO ITS PROXIMITIES

Explanation:


- From the visual analysis of the launch site KSC LC-39A we can clearly see that it is:
 - relative close to railway (15.23 km)
 - relative close to highway (20.28 km)
 - relative close to coastline (14.99 km)
- Also the launch site KSC LC-39A is relative close to its closest city Titusville (16.32 km).
- Failed rocket with its high speed can cover distances like 15–20 km in few seconds. It could be potentially dangerous to populated areas.



BUILD A DASHBOARD WITH PLOTLY DASH




LAUNCH SUCCESS COUNT FOR ALL SITES



Explanation:

- The chart clearly shows that from all the sites, KSC LC-39A has the most successful launches.

LAUNCH SITE WITH HIGHEST LAUNCH SUCCESS RATIO



Explanation:

- KSC LC-39A has the highest launch success rate (76.9%) with 10 successful and only 3 failed landings.


PAYLOAD MASS VS. LAUNCH OUTCOME FOR ALL SITES

Explanation:

- The charts show that payloads between 2000 and 5500 kg have the highest success rate



PREDICTIVE ANALYSIS (CLASSIFICATION)



CLASSIFICATION ACCURACY

Explanation:

- Based on the scores of the Test Set, we can not confirm which method performs best.
- Same Test Set scores may be due to the small test sample size (18 samples). Therefore, we tested all methods based on the whole Dataset.
- The scores of the whole Dataset confirm that the best model is the Decision Tree Model. This model has not only higher scores, but also the highest accuracy.

	LogReg	SVM	Tree	KNN
Jaccard_Score	0.800000	0.800000	0.800000	0.800000
F1_Score	0.888889	0.888889	0.888889	0.888889
Accuracy	0.833333	0.833333	0.833333	0.833333


	LogReg	SVM	Tree	KNN
Jaccard_Score	0.833333	0.845070	0.882353	0.819444
F1_Score	0.909091	0.916031	0.937500	0.900763
Accuracy	0.866667	0.877778	0.911111	0.855556

CONFUSION MATRIX

Explanation:

- Examining the confusion matrix, we see that logistic regression can distinguish between the different classes. We see that the major problem is false positives

		Predicted Values	
		Negative	Positive
Actual Values	Negative	TN	FP
	Positive	FN	TP



CONCLUSION



Decision Tree Model is the best algorithm for this dataset.

- Launches with a low payload mass show better results than launches with a larger payload mass.
- Most of launch sites are in proximity to the Equator line and all the sites are in very close proximity to the coast.
- The success rate of launches increases over the years.
- KSC LC-39A has the highest success rate of the launches from all the sites.
- Orbits ES-L1, GEO, HEO and SSO have 100% success rate.



APPENDIX

SPECIAL THANKS TO:

INSTRUCTORS

COURSERA

IBM