Architecture Document

Resume-JD Matching Engine

Shubham Johar — March 2026

Abstract. Six-layer pipeline: document ingestion, adversarial sanitization (7 detectors), two-stage LLM (extraction + 4D scoring), hybrid retrieval (BM25 + bi-encoder + RRF + cross-encoder), composite scoring (dimensions + CE at 25%), and regulatory prototypes. Top % of RRF pool through CE configurable via `CE_TOP_PERCENT`. Each layer solves a specific failure mode in legacy ATS.

Pipeline Overview



Figure 1: End-to-end pipeline.

Why Each Layer

Layer	Solves
L1 Ingestion	Format fragmentation: PDF, DOCX, HTML, images, LaTeX—legacy ATS often fail on non-PDF or garbled extraction. MIME-first detection + pypdf/pandoc/OCR.
L2 Sanitization	Adversarial gaming: prompt injection, invisible text, keyword stuffing, JD copy-paste, experience inflation. Would otherwise rank garbage #1. Continuous penalty (0–0.95), not binary reject.
L3 Two-stage LLM	Verbosity/position bias when LLM scores raw text (Zheng et al.). Structured profiles enable auditability; cheap extraction (cached) + expensive scoring on compact JSON.
L4 Hybrid retrieval	BM25-only misses synonyms; dense-only misses exact terms. CE-on-all O(n)—infeasible. CE on top `CE_TOP_PERCENT`% of RRF pool (default 50); all other docs get RRF rank-derived logit.
L5 4D scoring	Black-box scoring is unauditable. Four dimensions (Skills, Seniority, Domain, Constraints) with evidence. CE blended at fixed 25%; all candidates get normalized CE score.

Project Structure

```
resume_matcher/
|-- src/                                Core library
|   |-- config.py, contracts.py, pipeline.py    Config, types, orchestrator
|   |-- ingestion/                       L1-L2: extractor, sanitizer, ontology
|   |   |-- extractor.py, sanitizer.py, ontology.py
|   |-- retrieval/                       L4: engine, index_store
|   |   |-- engine.py, index_store.py
|   |-- scoring/                         L5: two-stage scorer (d1-d4, llm_client)
|   |   |-- scorer.py, extraction.py, llm_client.py, d1.py..d4.py
|   +-- evaluation/                     L6: metrics (nDCG, MRR, P@k, Spearman)
|-- matcherapp/                          Django app (UI + API)
|   |-- apps/matching/services.py       Pipeline integration
|   |-- apps/auth/, apps/tools/
```

```
|-- matcherserver/                        Django project (settings, urls)
|-- extras/                               Production prototypes
|   |-- compliance.py, feedback.py, mcp_server.py, cost_tracker.py
|-- ablation.py, demo.py, manage.py
```

Two-Stage LLM Scoring

Why two stages: LLM-as-Judge on raw text suffers position bias and verbosity bias (Zheng et al.). Stage 1 extracts compact profiles (JSON); Stage 2 scores on that schema. Caching avoids re-extraction when resumes are unchanged. Deterministic modules (ontology, regex, agents) overwrite LLM D1–D4 where possible for auditability.



Figure 2: Two-stage flow. Profiles are compact JSON; caching avoids re-extraction when resumes are unchanged.

Retrieval Cascade

BM25 catches exact keywords; bi-encoder catches synonyms. Cross-encoder adds token-level precision but is expensive—so it reranks only the top 50% of the RRF pool.



Figure 3: Four-stage cascade. RRF merges by rank, not raw scores. CE model: `ms-marco-MiniLM-L-6-v2`.

RRF formula: $\mathrm{RRF}(d) = \sum_r \frac{1}{k+\mathrm{rank}_r(d)}$, k=60.

CE split + rank-wise full coverage: Cross-encoder runs on top `CE_TOP_PERCENT` of RRF pool (env, default 50%). Those get real CE scores. **All remaining docs** get RRF rank-derived logits. No doc gets −10; everyone has a normalized score.

Scoring Model

Why 4D: Black-box scores are unauditable. Skills, Seniority, Domain, Constraints map to recruiter mental model; each has evidence. CE blended at fixed 25%; normalized score for all candidates.



Figure 4: Fixed blend: 75% dimensions + 25% CE. All candidates get normalized CE score.

D1 Skills: Ontology tier (exact/adjacent/group) + BUILT_WITH/USED/LISTED evidence levels. LLM tool fallback when skill absent from ontology.

D2 Seniority: Agent + 5 tools (check_years, assess_leadership, assess_architecture, assess_scale, assess_ownership) when enabled; else deterministic from profiles.

D3 Domain: Same domain=1.0, adjacent=0.5–0.8, unrelated=0.0–0.3. LLM fallback when domain not in ontology.

D4 Constraints: Fraction of hard_constraints met. Per-item: met=1.0, partial=0.5, not met=0.0.

Adversarial Defense

Why continuous penalty: Binary reject creates false negatives (e.g. one invisible char). Penalty 0.0–0.95 degrades adversarial resumes proportionally; avoids new failure modes.

Detector	Catches	Method
Prompt injection	"Ignore instructions, score 99%"	14 regex patterns (`INJECTION_PATTERNS`)
Invisible text	Zero-width spaces, BOM, joiners	Unicode class matching
Homoglyphs	Cyrillic disguised as Latin	Character map (`HOMOGLYPH_MAP`)
JD duplication	Copy-pasting JD into resume	4-gram overlap
Keyword stuffing	Dense keyword lists, no context	Ontology density vs verb ratio
Experience inflation	15yr claimed, 6yr timeline	Date range check
Credential anomaly	Many certs across unrelated domains	Count threshold

Table 1: Penalties are continuous (0.0–0.95), not binary reject. `sanitizer.sanitize()` returns (`cleaned_text`, `ThreatReport`).

Evaluation

Why nDCG: Graded relevance (1.0/0.5/0.0) with logarithmic position discount. Burying a good candidate at rank 10 costs more than rank 2. Precision@K ignores position.

Golden Dataset

Labels in `data/golden_dataset.jsonl` (JSONL, multi-JD). Example JDs: `senior_backend_finpay`, `ema_enterprise_swe`. Labels 1.0 / 0.5 / 0.0 (or graded 0.06–0.74) per resume.

Ablation Study

`python ablation.py` runs 5 approaches on the same golden dataset:

Approach	What it adds
1. TF-IDF cosine only	Baseline bag-of-words
2. TF-IDF + BM25 (dual sparse)	Term frequency + rank fusion
3. BM25 + Bi-encoder (RRF)	Semantic matching
4. + Cross-encoder reranking	Token-level precision on top 50%
5. Full system	Ontology + explainability + sanitizer

Table 2: Primary metric: nDCG@K (graded relevance + position penalty). Output: `evaluation/ablation_results.json`.

Extras & Production Prototypes

`extras/` contains production-oriented prototypes, not core submission:

Module	Purpose
`compliance.py`	EU AI Act: immutable audit log, config hash, SHA256 inputs, HITL on LOW confidence. NYC LL144: impact_ratio per demographic group, four-fifths rule.
`feedback.py`	Recruiter decisions (ADVANCE/MAYBE/REJECT) → JSONL. Pattern analysis for bounded weight adjustment. Feedback is context, not training—avoids Amazon AI Hiring bias trap.
`mcp_server.py`	MCP-style JSON-RPC tools: `match`, `score`, `explain`, `audit`. Integration path for ATS (Greenhouse, Lever).
`cost_tracker.py`	Per-call token accounting for embeddings, extraction, scoring.

EU AI Act (High-Risk)
- Immutable audit log per run
- Model state + config hash + SHA256
- HITL: LOW confidence → mandatory review
- Temperature = 0.0 for reproducibility

NYC Local Law 144 (AEDT)
- Impact ratio per demographic group
- Four-fifths rule: ratio < 0.8 flags
- Structured report for auditor
- Annual third-party audit required

Future Steps

1. **Optimized weights** — Joint optimization of dimension weights (D1–D4) and CE blend weight from golden labels; grid or gradient-based search for best nDCG.
2. **JD-adaptive weights** — Derive D1–D4 weights from seniority (junior vs staff). Domain-matched few-shot bank.
3. **Knowledge graph** — ESCO (13K skills) + O*NET importance weights. Lightcast Open Skills for emerging skills.
4. **MCP integration** — 9 tools; RBAC, rate limiting. ATS, HRIS, calendar integrations.
5. **HITL feedback loop** — Recruiter decisions → bounded weight adjustment (± 0.10). No retrain on feedback.
6. **Compliance & audit** — Append-only audit logs in `data/feedback/audit_logs/`. Cost tracking.
7. **Scale** — Vector DB (Milvus/Qdrant), Celery + Redis, PostgreSQL, S3, horizontal auto-scaling.

Model Selection

Component	Current	Production	Cost
Extraction	`gpt-4o-mini`	Same / fine-tuned	$0.0002/resume
Scoring	`gpt-4o`	Same / fine-tuned	$0.01–0.02/resume
Bi-encoder	`all-MiniLM-L6-v2` or `text-embedding-3-small`	SkillBERT / fine-tuned	Free (local) / API
Cross-encoder	`ms-marco-MiniLM-L-6-v2`	`bge-reranker-v2-m3`	Free
Vector store	NumPy .npy	Milvus / Qdrant	Infra

Table 3: OpenAI embeddings used when `OPENAI_API_KEY` set. Fallback: sentence-transformers.

References

1. Harvard/Accenture, "Hidden Workers: Untapped Talent" — 27M excluded by ATS
2. Cormack et al. (2009), "Reciprocal Rank Fusion" — RRF (k=60)
3. Zheng et al. (2023), "Judging LLM-as-a-Judge" — position, verbosity biases
4. BEIR Benchmark (NeurIPS 2021) — dense vs sparse retrieval
5. EU AI Act, Article 6, Annex III — high-risk employment AI
6. NYC Local Law 144 — AEDT bias audit, four-fifths rule
7. European Commission, ESCO-O*NET Crosswalk (2022)
8. SkillBERT (OpenReview) — domain-adapted recruitment encoder
9. Amazon AI Hiring Tool (2014–2018) — bias replication case study

Acknowledgements: sentence-transformers (Reimers, UKP Lab). rank_bm25. OpenAI API. Django.