

WAYPOINT LAUNCH CHECKLIST

The runway from test-mode to live. Work top to bottom — don't flip Stripe to live until **1–3** are done. As of Sep 6, 2026: feature-complete, Stripe verified in test mode, migrations run through **026**.

ALREADY DONE — Stripe test Tests 1–3 · webhook hardened · join-by-code fix · event dates + duration pricing · ride-type at creation · org white-label + embed · credentials expire with event · rider self-registration with consent.

01 FINISH THE TEST-MODE PASS

STRIPE TEST MODE

☐ Test 4 — entrant-paid

Open the Registration link (or join by code) as a rider on a riders-pay event → Stripe shows the tiered fee (`$10/$12/$15`) → pay with `4242 4242 4242 4242` → rider appears on the public map *only after paying*.

☐ Test 5 — org & white-label

Dashboard shows "Organization plan · active" · set logo + accent at `/dashboard/settings/org` · white-label + linkback show on a public event and its embed · "Manage billing" opens the Stripe portal.

02 LEGAL

BEFORE REAL MONEY

☐ Terms & Conditions — counsel review

Review `terms-and-conditions-draft.md` before collecting payments and handling liability (SOS, tracking).

☐ Privacy policy + consent wording

The in-product consent checkbox exists; the published policy (what's collected, why, retention) does not. Needed before storing real medical data.

03 CONFIG & SECURITY

VERCEL · SUPABASE

☐ Confirm one Supabase project

All three Vercel vars — `NEXT_PUBLIC_SUPABASE_URL`, `NEXT_PUBLIC_SUPABASE_ANON_KEY`, `SUPABASE_SERVICE_ROLE_KEY` — point at the same live project, migrations `017–026` applied there.

☐ No secret under a NEXT_PUBLIC_ name

The service-role key must never sit in a `NEXT_PUBLIC_` var. If it ever did, rotate it in Supabase and redeploy.

☐ Rotate the exposed Mapbox token

Rotate the leaked `sk.` token; set `NEXT_PUBLIC_MAPBOX_TOKEN` to a new URL-restricted token (app.chasingwaypoints.com).

04 FLIP STRIPE TO LIVE

REAL MONEY

☐ Live secret key

Vercel Production `STRIPE_SECRET_KEY` = `sk_live_...` (publishable key is unused by this app).

☐ Live webhook endpoint

Create a LIVE endpoint at `/api/stripe/webhook` for `checkout.session.completed`, `customer.subscription.updated`, `customer.subscription.deleted`; put its `whsec_...` in `STRIPE_WEBHOOK_SECRET`.

☐ Billing Portal (live) + redeploy

Redo the Billing Portal config in LIVE mode (Cancel + Invoice history), then redeploy and wait for Ready.

☐ Smoke test — real charge, then refund

One real \$200 event charge → webhook 200 → event flips Paid → *refund it* in Stripe and delete the throwaway event.

05 OPERATIONAL

AROUND LAUNCH

☐ QStash cron for positions

Add `poll-entrants` in Upstash QStash — every 2 min, `CRON_SECRET` bearer — so beacon positions keep updating in production.

☐ Live SOS test

Trigger a real inReach/SPOT emergency to validate the SOS detection heuristics against a real payload.

☐ Watch webhook error rate

After launch, glance at Stripe → Developers → Webhooks; the hardened handler surfaces real 500s instead of silent failures.

Full detail in `go-live-checklist.md` · Stripe steps in `stripe-test-runbook.md` · data handling in `security-review.md`. Critical path: 01 → 02 → 03 → 04 → smoke test.