

C++ Study Notes

COLLABORATORS

| | | | |
|---------------|-----------------------------------|--------------|------------------|
| | <i>TITLE :</i> C++ Study Notes | | |
| <i>ACTION</i> | <i>NAME</i> | <i>DATE</i> | <i>SIGNATURE</i> |
| WRITTEN BY | Frederick Ollinger | May 28, 2017 | |

REVISION HISTORY

| NUMBER | DATE | DESCRIPTION | NAME |
|--------|------------|-----------------|------|
| 0.0.1 | 2017-05-21 | Initial Version | fko |

Contents

| | | |
|----------|-------------------------------------------------------------|----------|
| 1 | Pointers | 1 |
| 1.1 | Address of Operator | 1 |
| 1.2 | Value At Address Operator | 1 |
| 1.3 | Sending Pointers To Functions | 2 |
| 1.4 | Arrays and Pointers | 3 |
| 1.4.1 | What Are Arrays? | 3 |
| 1.4.2 | How To Use A Pointer To An Array | 4 |
| 1.5 | Dynamically Allocating Memory I (Malloc and Free) | 4 |
| 1.5.1 | malloc() | 4 |
| 1.5.2 | free() | 5 |
| 1.5.3 | Stack vs. Heap | 5 |
| 1.6 | Dynamically Allocating Memory II: New, Delete | 6 |

Chapter 1

Pointers

I got this from: *Pointers in C with examples*.

A pointer is a variable that points to a section of memory. Below is a program that points to a block of memory to show how we can access memory in C.

1.1 Address of Operator

Before we look at pointers, we'll define what we mean by computer memory in address.c.

```
#include <stdio.h>

int var = 1;
int main()
{
    int num = 10;
    printf("Value of var is: %d \n ", num);
    printf("Address of var is: %p \n", &num);
    return 0;
}
```

```
Value of var is: 10
Address of var is: 0x7ffd5d20b56c
```

Thus, in this context the ampersand is the "Address Of" operator.

1.2 Value At Address Operator

Use the asterisk to create a pointer to a variable. The following example shows how pointers work, but it's for demonstration purposes only as we either have an address to a variable or a variable, but usually not both. Here's pointer.c:

```
#include <stdio.h>
int main()
{
    int var = 10;
    int *p;
    p = &var;

    printf ( "\n Address of var is: %p \n", &var);
    printf ( "\n Address of var is: %p \n", p);
}
```

```
printf ( "\n Address of pointer p is: %p \n", &p);

/* Note I have used %p for p's value as it should be an address*/
printf( "\n Value of pointer p is: %p \n", p);

printf ( "\n Value of var is: %d \n", var);
printf ( "\n Value of var is: %d \n", *p);
printf ( "\n Value of var is: %d \n", *( &var));
}
```

Here's the output:

```
Address of var is: 0x7ffda322535c
Address of var is: 0x7ffda322535c
Address of pointer p is: 0x7ffda3225350
Value of pointer p is: 0x7ffda322535c
Value of var is: 10
Value of var is: 10
Value of var is: 10
```

1.3 Sending Pointers To Functions

Here's a classic example which shows how pointers differ from regular variables. Sending a regular variable to a function will yield the same variables when you are done because we pass by value. But if we pass by reference to memory, we can actually allow a function to change a variable.

```
#include <stdio.h>

void swap (int *pa, int *pb) {
    int tmp;
    tmp = *pa;
    *pa = *pb;
    *pb = tmp;
}

int main()
{
    int a = 10;
    int b = 20;

    printf("before swap a: [%i] b: [%i] \n", a, b);

    swap(&a, &b);

    printf("after swap a: [%i] b: [%i] \n", a, b);

    return 0;
}
```

Running the program:

```
before swap a: [10] b: [20]
after swap a: [20] b: [10]
```

Often, you don't want to have your variables modified when they are sent to a function. To show this in an api, use the keyword `const` which allows you to promise that you won't make this change.

```
#include <stdio.h>

void swap (const int *pa, const int *pb) {
    int tmp;
    tmp = *pa;
    *pa = *pb;
    *pb = tmp;
}

int main()
{
    int a = 10;
    int b = 20;

    printf("before swap a: [%i] b: [%i] \n", a, b);

    swap(&a, &b);

    printf("after swap a: [%i] b: [%i] \n", a, b);

    return 0;
}
```

Compiling this gives the following error:

```
cc -Iconst@exe' '-I.' '-I..' '-fdiagnostics-color=always' '-pipe' '-D_FILE_OFFSET_BITS=64' '-Wall' '-Winvalid-pch' '-O0' '-g' '-fuse-ld=gold' '-MMD' '-MQ' 'const@exe/const.c.' 'const@exe/const.c.o.d' -o 'const@exe/const.c.o' -c ../const.c
../const.c: In function 'swap':
../const.c:6:9: error: assignment of read-only location '*pa'
    *pa = *pb;
    ^
../const.c:7:9: error: assignment of read-only location '*pb'
    *pb = tmp;
```

This is a good thing as it can stop us from doing something which we promise not to do.

1.4 Arrays and Pointers

1.4.1 What Are Arrays?

I got this from: *Pointers in C with examples*.

First we'll start by covering arrays. An array is a variable that holds multiple values of the same type. Let's make an array of ints.

```
#include <stdio.h>

int main()
{
    int arr[3] = { 1, 2, 3 };
    printf("arr: [%i] \n", arr[1]);

    return 0;
}
```

Output:

```
arr: [2]
```

Let's make a character array, which is a C string. Note that C will automatically allocate the size of the array for us if we leave the number of elements blank.

```
#include <stdio.h>

int main()
{
    char label[] = "Single";
    printf("label: [%s] \n", label);
    printf("label: [%c] \n", label[2]);

    return 0;
}
```

Output:

```
label: [Single]
printf("label: [%c] \n", label[2]);
```

We also learn that we can access a C string just like a normal array.

NEXT SHOW HOW WE CAN USE A POINTER TO AN ARRAY TO ACCESS CHARACTERS.

1.4.2 How To Use A Pointer To An Array

Here we demonstrate that pointers are merely indexes into arrays. It also shows that the increment operator will automatically increment the size of the type. That is, an int is different from a double, but if you increment a given type of pointer, it will automatically increment properly. Because of this, in order for this to work, you must know the size of the type at compile time.

```
#include <stdio.h>

int main()
{
    int arr[4] = { 1, 2, 3, 4 };
    int *parr = arr;
    printf("parr: [%i] \n", *parr);
    parr++;
    printf("parr: [%i] \n", *parr);

    return 0;
}
```

Output:

```
parr: [1]
parr: [2]
```

1.5 Dynamically Allocating Memory I (Malloc and Free)

1.5.1 malloc()

In C (and in any programming language) each variable uses memory. C is unique in that it's one of the few languages which exposes some of the details of this process.

In this example, we're going to create an array, but we don't know at compile time how large to make it.

```
#include <stdio.h>    // printf()
#include <stdlib.h>    // malloc()
#include <string.h>    // bzero()

#define ARRAY_SIZE 5

int main()
{
    int *pint;
    pint = (int *) malloc(sizeof(int) * ARRAY_SIZE);
    bzero(pint, sizeof(int) * ARRAY_SIZE);

    for (int i = 0; i < ARRAY_SIZE; i++) {
        printf("[%i]: [%i] \n", i, *(pint+i));
    }

    return 0;
}
```

Output:

```
[0]: [0]
[1]: [0]
[2]: [0]
[3]: [0]
[4]: [0]
```

Note, one can modify `ARRAY_SIZE` and allocate and zero different amounts of memory.

1.5.2 free()

Note that each time we call `malloc()` we need to call `free()`. If we don't then we'll create a memory leak. Thus, in the last program, there's a memory leak.

Below is an example of using `free()`.

```
#include <stdio.h>    // printf()
#include <stdlib.h>    // malloc()
#include <string.h>    // bzero()

char* getstr() {
    char *pchar;
    pchar = (char *) malloc(sizeof(char) * 10);
    strcpy(pchar, "my string");
    return pchar;
}

int main()
{
    char *str = getstr();
    printf("[%s] \n", str);
    free(str);
    return 0;
}
```

1.5.3 Stack vs. Heap

I got this from: *Memory : Stack vs Heap*.

Declaring a variable on the stack is:

```
int i;
```

When you use `malloc()`, you are declaring a variable on the heap. Which way you decide to do things depends on a few factors.

"Every time a function declares a new variable, it is "pushed" onto the stack. Then every time a function exits, all of the variables pushed onto the stack by that function, are freed (that is to say, they are deleted)."

Thus, with the stack you don't have to do your own memory management.

"Unlike the stack, variables created on the heap are accessible by any function, anywhere in your program. Heap variables are essentially global in scope."

1.6 Dynamically Allocating Memory II: New, Delete

Now that we understand `malloc/free`, we're going to look at the same concepts in C++. While you can use `malloc/free` in C++, generally, we use `new/delete`.

```
#include <stdio.h>    // printf()
#include <stdlib.h>    // malloc()
#include <string.h>    // bzero()

#define ARRAY_SIZE 5

int main()
{
    int *p = new int();
    *p = 10;

    printf ( "\n Address of var is: %p \n", p);
    printf ( "\n Value of var is: %d \n", *p);

    delete p;
    p = NULL;

    return 0;
}
```

In this example, we have basically made the `pointer.c` example, but we have written it so it uses `new/delete`. Just like `malloc`, `new` will allocate on the heap and thus needs to be freed.