# MAR 30% missing - Generative Adversarial Imputation Nets (GAIN)

```
# sample MCAR dataset from PUMS
source("../../utils/sampleMAR30.R")
n = 10000
missing_col = c(1,3,7,9,10,11)
set.seed(2)
output_list <- sampleMAR30(n)</pre>
df <- output_list[['df']]</pre>
df_observed <- output_list[['df_observed']]</pre>
apply(is.na(df_observed), MARGIN = 2, mean)
##
      VF.H
               MV
                      NP
                            RMSP
                                    ENG MARHT
                                                  SCHL RACNUM
                                                                  AGEP
                                                                           WKL PINCP
```

## 0.3074 0.0000 0.2605 0.0000 0.0000 0.3424 0.0000 0.3227 0.3078 0.3049

#### Generative Adversarial Imputation Nets (GAIN)

reference: https://arxiv.org/abs/1806.02920

```
# Load imputed dataset
d1 = read.csv('../../GAIN/imputed_dataset/MAR_30percent_1.csv', header = FALSE, sep = ',')
d2 = read.csv('../../GAIN/imputed_dataset/MAR_30percent_2.csv', header = FALSE, sep = ',')
d3 = read.csv('../../GAIN/imputed_dataset/MAR_30percent_3.csv', header = FALSE, sep = ',')
d4 = read.csv('../../GAIN/imputed_dataset/MAR_30percent_4.csv', header = FALSE, sep = ',')
d5 = read.csv('../../GAIN/imputed_dataset/MAR_30percent_5.csv', header = FALSE, sep = ',')
colnames(d1) = colnames(df)
colnames(d2) = colnames(df)
colnames(d3) = colnames(df)
colnames(d4) = colnames(df)
colnames(d5) = colnames(df)
imputed_df = rbind(d1, d2, d3, d4, d5)
```

#### Diagnostics

Assess bivariate joint distribution


Assess bivariate joint distribution

```
# calculate rmse
numeric_df = sapply(df, as.numeric)
normalized_df = t(t(numeric_df-1)/(apply(numeric_df, MARGIN = 2, FUN = max)-1))
numeric_impute = sapply(d1, as.numeric)
normalized_impute = t(t(numeric_impute-1)/(apply(numeric_df, MARGIN = 2, FUN = max)-1))
missing_matrix = is.na(df_observed)


rmse = sqrt(sum((normalized_df[missing_matrix] - normalized_impute[missing_matrix])^2)/sum(missing_matrix)
```

## [1] 0.2488675


## MICE: VEH




MICE: NP




### MICE: SCHL




**MICE: AGEP** 




**MICE: WKL** 



### **MICE: PINCP**



## **Bivariate pmf**



# Trivariate pmf

