

Clockwork Language Reference (draft)

Martin Leadbeater

September 14, 2012

1 Preface

Please note that this is a very early draft.

2 Introduction

Clockwork is a language intended to be used to describe systems of interacting components using state machines. The purpose of the language is to provide a platform for monitoring and control and it has been implemented as a control system using the Beckhoff EtherCAT®.

The language provides the programmer with a means to

- define the states of a machine in terms of conditions
- define commands that can be invoked on the machine
- define transition rules that determine what actions can be performed and what state transitions are allowable

Conditions on a machine are generally defined in terms of the state and properties of other machines.

3 Details

3.1 Instances of machines

Clockwork deals primarily with definitions of finite state machines (referred to as MACHINES in the language) and instance of those definitions. There is a common pattern for declaring an instance of a machine; providing the name and then the machine class.

Names can be given for new instances of objects, by first providing the name, then the object and its properties and parameters, i.e.,

```
name machine-class [ '(' property-name ':' property-value ... ')' ] parameters
```

For example, given machine classes called 'MODULE' and 'POINT', an instance can be declared in the following way.

```
Beckhoff_2008 MODULE 2
NG_Output POINT Beckhoff_2008 5
```

define a Module and a point within that module. In the example, the number '2' indicates the position of the module on the bus and the number '5' defines the particular output id of the point that we want to call 'NG_Output'. After the object-class, a list of property key,value pairs may be given., for example

```
NG_Output POINT (tab:Outputs) Beckhoff_2008 5
```

describes the same point but sets a property called 'tab'¹ to the value 'Outputs'.

3.2 Properties and states

We make a distinction between the state of a machine and the properties of the machine, in fact, we regard the state of the machine as one of its properties although more strictly, we should actually include the value of a machine's properties as part of its state. The definitions are

¹The web interface to cw and iod happen to use this property to group various items into tabs on the web page

3.3 Properties and parameters

As shown, the declaration of a machine may have parameters and machines may also have properties. Properties and parameters are distinguished as follows:

- properties have default values and do not have to be predeclared unless they are used in stable state conditions
- parameters generally refer to objects that the machine manipulates and serve to provide an internal alias for a globally defined object. Use of parameters provides for the reuse of machines for different parts of the system.
- when a parameter changes state, the machine receives an event that it may act on to perform an action.
- when a property of a machine or one of its parameters or local variables is changed, the machine reevaluates its stable states.

4 Vocabulary

Within the program text, reserved words are presented in all capitals to distinguish them from user defined values. The language is case sensitive.

4.1 Glossary of Reserved Words

16BIT defines an exported modbus property as a 16bit integer

32BIT defines an exported modbus property as a 32bit integer

ALL used with COPY and EXTRACT to collect all matches from a property

AND (also &&) used to join expressions within a condition

AT used with RESUME to cause execution to resume at a nominated state

BECOMES (also :=) used to assign values to properties

BY used with INC and DEC to change the step size

CATCH marks the beginning of an operation to be performed if any sends a particular message. [not implemented]

COMMAND defined a method that does not change the state of its machine while it is executing.

CONSTANT a predefined machine class that acts like a constant from a syntactic viewpoint

COPY copies substrings matching a pattern from a given property

DEC decrement a property

DEFAULT a stable state that is evaluated last and that always matches

DISABLE

DURING used to define a transitional state that occurs during the execution of a command

EXECUTE extends the definition of a stable state to specify a command that should be executed when a special sub-condition becomes active.

ELSE marks the beginning of the code that is executed when the IF condition evaluates to false

ENABLE

ENTER defines an operation that must be performed during entry to a state. The ENTER function may be restricted to performing functions that are atomic, such as sending message. Currently, these operations are not restricted but cause the machine to enter an invisible substate of the target state.

EXPORT indicates that a property should be exported to modbus

FIND returns a list of objects that are in the given state, options may be added to restrict the range of items found [not implemented]

FOREACH performs an operation for each object within the given list that are in a particular state [not implemented]

GLOBALS lists machines, external to the current class that the current machine is monitoring. State changes on the machines listed as GLOBAL cause a reevaluation of stable states and generate events that can be received.

INC increment a property

IF used within operations (Commands and Enter functions) to provide for conditional behaviour

INIT a predefined state that statemachines enter as soon as they are enabled.

INITIAL defines a state as the state to use for the initial state of the machine.

LOG emit a text string in the log

LOCK provides a way to mark a protected section to prevent, for example, multiple machines simultaneously changing the state of a machine.

MATCHES used in an expression to test for a property matching a given pattern

MACHINE defines a programmed component within the system. All control functionality is implemented within these objects. Machines are based on finite statemachine concept and include both monitoring (automatic state switching) and control (forced state changes to cause actions).

MODULE defines an addressable module that sits on the EtherCAT cabling

NOT (also !)used to invert expressions within a condition

OR (also ||) used to join expressions within a condition

PERSISTENT a property that indicates that state changes on this machine will be published and at startup, this machine will be automatically enabled and initialised from its last known state.

POINT refers to an addressable port within a module

RAISE send a message that any machine may catch. It is an error if a message is raised but not caught. [not implemented]

READONLY used in an EXPORT specification to mark the property as read only

READWRITE used in an EXPORT specification to mark the property as read/write

RESULT the returned value after an expression has been evaluated [not implemented]

RESUME resumes execution of the disabled machine from the beginning of its current state

RECEIVE indicates that a machine should be informed when a specific object sends a particular message. The RECEIVE statement has an associated set of actions that are acted when the event is collected.

REQUIRES indicates that the associated condition must evaluate to True in order that the transition can occur or that a command can be executed [not implemented]

SELF used in expressions to refer

SEND is used to send a message to a machine, this message must be captured by the machine, using a RECEIVE statement

SET causes a machine to move to a given state after executing the optional command associated with the transition

SHUTDOWN cause the clockwork daemon to exit

SOURCE is a variable that holds a reference to the object that send the current message or issued the current command [not implemented]

STATE defines a state name so that this state can be used in a transition or can be set by other machines.

TAG links a FLAG to a sub-condition on a stable state so that the FLAG is automatically turned on and off to track whether the subcondition is true or not.

THEN marks the beginning of the code that is executed when the IF condition evaluates to true

TIMER

TO used within a transition to indicate the destination state, used within a message operation to indicate the target of the message

TRANSITION describes the command that can be used to move the machine from one state to another

UNLOCK reverses the effect of **LOCK**, to permit other instances execute code in a critical section.

USING as part of the transition statement, the Using clause indicates the command that is used for the transition

VARIABLE a predefined machine class that is persistent and acts like a variable from a syntactic viewpoint

WAIT pauses execution of the current method for the set amount of time

WAITFOR pauses execution of the current method until the given machine enters the given state

WHEN defines a set of conditions that indicate a machine is in a particular, stable state. These conditions are not evaluated when the machine is in a transitional state.

4.2 Conditions

Conditions are lists of boolean expressions that are generally used to determine the current state of various parts of the machine. Conditions are implemented by the use of separate state machines. that contain a state (normally called 'true') that indicates the condition is true and a state (normally called 'false') that is the default.

4.3 Notes

An action is a list of steps, such that each step requests that a machine enters a state or waits for a message. Regardless of the action, there are two components: sending a message and waiting for a response. On receipt of the response, the action transitions to the next step in the list.

When a state change request is received, the transitions on the target machine are searched for an action that will satisfy the requested state change. That action causes a further sequence of actions to be queued by having the machine enter a substate with each action sending a message and waiting for a response.

5 Machines

Machines are the processing component of the latproc programming system. They are defined as finite state machines that are interconnected by message passing. A machine will automatically detect its state by polling input conditions that are defined to match certain configurations. By issuing commands, a machine can change the state of other machines and these changes can trigger further state changes.

5.1 Components and scope

The language deals with Finite State Machines, which the language simply calls 'Machines' and their states. The program defines a machine as having certain states and provides conditions and scripts that can identify the current state and change states.

some predefined objects; Modules, Points, Machines, Values, Conditions and States. These objects may have parameters and may also have properties. Properties and parameters are distinguished as follows:

- properties have default values and do not have to be provided
- parameters generally refer to objects that the machine manipulates and serve to provide an internal alias for a globally defined object. Use of parameters provides for the reuse of machines for different parts of the system.

5.2 Parameters

When a machine is instantiated, parameters are resolved by providing either a symbol name or a symbol value. The Machine Instance retains a list of ParameterReferences and for parameters passed by value, a local symbol table allocates a local name

5.3 States

A state is defined by a particular configuration of inputs or execution of an action.

5.4 Actions

An action is a sequence of steps that are executed in response to the receipt of a message, including steps taken within an entry function.

5.5 Transitions

Transitions occur automatically when a machine is idle, when it detects a change of state. When a transition occurs:

- the timer is reset,
- the state variable 'CURRENT' is updated
- a state change message is queued for delivery to interested parties
- the entry function for the state is executed

5.6 Events

An event corresponds to the sending of a message. Examples of events include timers and changes in input levels or analogue or counter values. Timer events are intended to trigger reasonably precisely, based on a fixed time after the message was sent.

5.7 Message Passing

Machines can send and receive messages directly, using the commands SEND and CALL and the handler RECEIVE or it can send messages indirectly by attempting to change the state of the target machine.

5.7.1 RECEIVE and RECEIVE..FROM

Each machine can listen for messages from any entity it knows of. Messages are sent when entities change state or when a script deliberately sends one. To listen for a message, use:

```
RECEIVE objname.message '{' actions '}'
```

or

```
RECEIVE message FROM objname '{' actions '}'
```

This identifies the sending entity from its local name and registers a listener for the *entiyname_statenam_enter* message. In a future release, the current machine will also be registered as a dependant of the sender. Currently, messages are only received from parameters, local instances and machine instances that are specifically listed in GLOBALS.

5.7.2 SEND and SEND..TO

5.8 Exceptions

[Note: not implemented]An exception is a message sent using the 'THROW' command. It is similar to a message sent with 'SEND' except that there is no requirement that there is a machine listening for the message. Messages that are thrown are caught using the 'CATCH' command.

5.9 Statements

5.10 Properties

Machine instances share some standard properties

current the current state of the instance

referers a list of machines that refer to this machine

references a list of machines this one refers to

sends a list of messages this machine sends

receives a list of messages this machine receives

5.11 Builtin classes

Builtin classes such as FLAG and BOOLEAN are readily implemented using the language itself. The POINT class, however is special as it provides an interface to hardware. Integers are currently implemented through properties.

VARIABLE

MODULE

CONSTANT

FLAG two state machine with states 'on' and 'off'

POINT a machine that links to a IO Point

6 Other features

6.1 Expressions

7 Syntax

$$\begin{aligned} \textit{program} &= \textit{definition program} \mid \emptyset \\ \textit{definition} &= \textit{name object parameterlist} \\ \textit{parameters} &= \textit{parameter} \mid \textit{parameter} \textit{' ' parameter} \\ \textit{parameter} &= \textit{value parameter} \mid \emptyset \end{aligned}$$