

TUGIAS MANDIRI Y 2206028932 1) Specification F(A,B,C,D) = C + BC + AD + AB + ABO + ABC + ABCD NAND Gate -> SOP (ii) Formulation ABCOF ABCDF 10000 00000 10011 000010 10100 001011 00110 10110 01000 11001 01010 1011 01101 1 1 1 1 1 01110 (iii) Optimization A 0 0 0 1 8 F = AB + ACD + ACD





2206028931

2206028932

(Ĉ.)	Formulation	


A	B	C	D	F	A	B	C	D	F
0	0	0	0	X	1	0	0	0	×
0	0	0	1	0	1	0	0	1	0
0	0	1	0	1	1	0	1	0	X
0	0	4	1	0	1	0	١	1	0
0	1	0		0	1	1	0	0	1
6	1	O)	0	1	1	0)	0
0	ı)	0	1	1	1	1	0	×
0	l	١	1	×	1	l	l	1	1
_	-	1	1						

A	B	C	0	F	
1	0	0	0	X	
1	0	0	1	D	
1	0	1	0	X	
1	0	١	l	0	
1	1	0	0	١	
1	1	0)	0	
1	1	1	0	×	
1	(l	1	1	

		,	,	_	
<u>~</u>	X	0	0	l	B
A	0	0	X	1	0
۸.	ŧ.	0	1	×	8
n	X	0	0	X	B
	5	T		ō	

$$F = C\overline{D} + BC + A\overline{D}$$
$$= \overline{D}(A+c) + BC$$

Technological 1	lapping
-----------------	---------



4.	0	Specification	:	6-variable	Priority	Encoder	
----	---	---------------	---	------------	----------	---------	--

(i) Formulation

	200000000000000000000000000000000000000								
T ₅	Ty	T3	T ₂	T,	40	Á	В	C	٧
0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	1	0	0	0	١
0	0	.0	0	١	メ	0	0	١	١
0	0	0	١	×	×	0	1	0	١
0	0	1	×	X	×	0	1	1	1
O	1	Χ	X	X	X	ı	0	O	١
1	×	X	X	×	×	ŧ	0	١	1

(iii) Optimization

$$V = T_0 + T_1 + T_2 + T_3 + T_4 + T_5$$
 $A = T_5 + T_5 T_4 = T_5 + T_5 T_4$
 $B = T_5 T_4 T_3 + T_6 T_4 T_3 T_2 = F_1 T_3 + F_1 T_3 T_2$
 $C = T_5 T_4 T_3 T_2 T_1 T_5 + T_5 T_4 T_5 T_5 T_5 T_7 T_7 T_6 + F_1 T_3$
 $F_1 = T_5 T_5 + T_4 T_7 = (T_5 T_4)^2$

0 F,

