



CIML Summer Institute, Day 1

Day 1: Running Jobs

June 27, 2022


Mary Thomas

San Diego Supercomputer Center




Outline

- **Introduction**
- Compiling and Linking Code
- Running Jobs
- Additional Examples
 - MPI Jobs
 - OpenMP Jobs
 - Hybrid MPI-OpenMP Jobs
- Final Comments




Expanse



SDSC SAN DIEGO
SUPERCOMPUTER CENTER
UC San Diego

EXPANSE

COMPUTING WITHOUT BOUNDARIES
5 PETAFL0P/S HPC and DATA RESOURCE





For more details see the Expanse user guide @ https://www.sdsc.edu/support/user_guides/expanse.html
and the "Introduction to Expanse" webinar @ https://www.sdsc.edu/event_items/202006_Introduction_to_Expanse.html



Expanse Heterogeneous Architecture


System Summary

- 13 SDSC Scalable Compute Units (SSCU)
- 728 x 2s Standard Compute Nodes
- 93,184 Compute Cores
- 200 TB DDR4 Memory
- 52x 4-way GPU Nodes w/NVLINK
- 208 V100s
- 4x 2TB Large Memory Nodes
- HDR 100 non-blocking Fabric
- 12 PB Lustre High Performance
- Storage
- 7 PB Ceph Object Storage
- 1.2 PB on-node NVMe
- Dell EMC PowerEdge
- Direct Liquid Cooled




Outline

- Introduction
- **Compiling and Linking Code**
- Running Jobs
- Additional Examples
 - MPI Jobs
 - OpenMP Jobs
 - Hybrid MPI-OpenMP Jobs
- Final Comments



Supported Compilers on Expanse

- CPU nodes
 - GNU, Intel, AOCC (AMD) compilers
 - multiple MPI implementations (OpenMPI, MVAPICH2, and IntelMPI).
 - A majority of applications have been built using gcc/10.2.0 which features AMD Rome specific optimization flags (-march=znver2).
 - Intel, and AOCC compilers all have flags to support Advanced Vector Extensions 2 (AVX2).
- GPU Compiling:
 - Expanse GPU nodes have GNU, Intel, and PGI compilers.
 - Note: Expanse login nodes are not the same as the GPU nodes → all GPU codes must be compiled by requesting an interactive session on the GPU nodes.



AMD AOCC Compilers: CPU Only


| Language | Serial | MPI | OpenMP | MPI + OpenMP |
|----------|---------|----------|---------------|----------------|
| Fortran | flang | mpif90 | ifort -openmp | mpif90 -openmp |
| C | clang | mpiclang | icc -openmp | mpicc -openmp |
| C++ | clang++ | mpiclang | icpc -openmp | mpicxx -openm |

The AMD Optimizing C/C++ Compiler (AOCC) is only available on CPU nodes. AMD compilers can be loaded using the module load command:

```
$ module load aocc
```

For more information on the AMD compilers:

```
$ [flang | clang ] -help
```




Using the AOCC Compilers

- If you have modified your environment, you can change your environment by **swapping modules** or **executing the module purge & load** commands at the Linux prompt
- Place the load commands in your startup file (~/.cshrc or ~/.bashrc) or batch script

```
[user@login02 ~]$ module list
Currently Loaded Modules:
  1) slurm/expanse/21.08.8  2) cpu/0.15.4  3) intel/19.1.1.217  4) openmpi/4.0.4
[user@login02 ~]$ module purge
[user@login02 ~]$ module list
No modules loaded
[user@login02 ~]$ module load slurm
[user@login02 ~]$ module load cpu
[user@login02 ~]$ module load intel
[user@login02 ~]$ module load openmpi/4.0.4
[user@login02 ~]$ module list
Currently Loaded Modules:
  1) slurm/expanse/21.08.8  2) cpu/0.15.4  3) intel/19.1.1.217  4) openmpi/4.0.4
[user@login02 MPI]$ module swap intel aocc
Due to MODULEPATH changes, the following have been reloaded:
  1) openmpi/4.0.4
[user@login02 ~]$ module list
Currently Loaded Modules:
  1) slurm/expanse/20.02.3  2) cpu/1.0  3) aocc/2.2.0  4) openmpi/4.0.4
[user@login02 ~]$ which mpirun
[mthomas@login01 env_info]$ which mpirun
/cm/shared/apps/spack/cpu/opt/spack/linux-centos8-zen/clang-10.0.0/openmpi-4.0.4-nz2g566opuddnwt5ymjorz2cdgb4spfm/bin/mpirun
```

Loaded the wrong module.
Use swap



Intel Compilers: CPU and GPU

Default/Suggested Compilers to used based on programming model and languages:


| | Serial | MPI | OpenMP | MPI + OpenMP |
|---------|--------|--------|---------------|----------------|
| Fortran | ifort | mpif90 | ifort -openmp | mpif90 -openmp |
| C | icc | mpicc | icc -openmp | mpicc -openmp |
| C++ | icpc | mpicxx | icpc -openmp | mpicxx -openmp |

The Intel compilers and the MVAPICH2 MPI compiler wrappers can be loaded by executing the following commands at the Linux prompt:

```
$module load intel mvapich2
```


For more information on the Intel compilers:

```
[$ifort | icc | icpc] -help
```




Using the Intel Compilers

```
[user@login02 ~]$ module list
[user@login02 MPI]$ module list
Currently Loaded Modules:
  1) slurm/expansive/20.02.3  2) cpu/1.0  3) aocc/2.2.0  4) openmpi/4.0.4
[user@login02 ~]$ module purge
[user@login02 ~]$ module list
No modules loaded
[mthomas@login01 env_info]$ which mpirun
/usr/bin/which: no mpirun in (/usr/local/bin:/usr/bin:/usr/local/sbin:/usr/sbin)
[user@login02 ~]$ module load slurm
[user@login02 ~]$ module load cpu
[user@login02 ~]$ module load intel
[user@login02 ~]$ module load openmpi/4.0.4
[user@login02 ~]$ module list
Currently Loaded Modules:
  1) slurm/expansive/20.02.3  2) cpu/0.15.4  3) intel/19.1.1.217  4) openmpi/4.0.4
[user@login02 ~]$ which mpirun
/cm/shared/apps/spack/cpu/opt/spack/linux-centos8-zen2/intel-19.1.1.217/openmpi-4.0.4-f5mc6sg2jtrw7qqdksf6tru4vo4tawrv/bin/mpirun
[mthomas@login01 env_info]$
```



Accessing Intel Compiler Features

- **Advanced Vector Extensions (AVX2):** to enable AVX2 support
 - compile with the `-march=core-avx2` option.
 - https://en.wikipedia.org/wiki/Advanced_Vector_Extensions (128/256bit SIMD, Vector ops (MPI broadcast, gather, ...))
 - Note that `-march=core-avx2` alone does not enable aggressive optimization, so compilation with `-O3` is also suggested.
- **Intel Math Kernal Lib (MKL)** libraries are available as part of the "intel" modules on Expanse.
 - Once this module is loaded, the environment variable `INTEL_MKLHOME` points to the location of the mkl libraries and
 - Use MKL Link Advisor to see what libraries are recommended for your compiler and system configuration:
 - <https://software.intel.com/content/www/us/en/develop/articles/intel-mkl-link-line-advisor.html>




GNU Compilers: CPU & GPU

Table of recommended GNU compilers:

| | Serial | MPI | OpenMP | MPI+OpenMP |
|---------|----------|--------|-------------------|-----------------|
| Fortran | gfortran | mpif90 | gfortran -fopenmp | mpif90 -fopenmp |
| C | gcc | mpicc | gcc -fopenmp | mpicc -fopenmp |
| C++ | g++ | mpicxx | g++ -fopenmp | mpicxx -fopenmp |

- For AVX support, compile with `-march=core-avx2`.
- AVX support only available in version 4.7 or later --> explicitly load the gnu/4.9.2 module
- For more information on the GNU compilers:

`$man [gfortran | gcc | g++]`




GNU Compilers

- The GNU compilers can be loaded by executing the following commands at the Linux prompt or placing in your startup files (~/.cshrc or ~/.bashrc)


```
[user@login02]$ module purge
[user@login02]$ module load slurm
[user@login02]$ module load cpu
[user@login02]$ module load gcc/10.2.0
[user@login02]$ module load openmpi/4.0.4
[user@login02]$ module list
Currently Loaded Modules:

  1) slurm/expense/20.02.3  2) cpu/1.0  3) gcc/10.2.0  4) openmpi/4.0.4
```





Outline

- Introduction
- Compiling and Linking Code
- **Running Jobs**
- Additional Examples
 - MPI Jobs
 - OpenMP Jobs
 - Hybrid MPI-OpenMP Jobs
- Final Comments





Parallel Models: Distributed Memory

- Programs run asynchronously, pass messages for communication and coordination between resources.
- Examples include: SOA-based systems, massively multiplayer online games, peer-to-peer apps.
- Different types of implementations for the message passing mechanism: HTTP, RPC-like connectors, message queues
- HPC historically uses the Message Passing Interface (MPI)




Parallel Models: Shared Memory

- CPUs all share same localized memory (SHMEM);
 - Coordination and communication between tasks via interprocessor communication (IPC) or virtual memory mappings.
- May use uniform or non-uniform memory access (UMA or NUMA); cache-only memory architecture (COMA).
- Most common HPC API's for using SHMEM:
- Portable Operating System Interface (POSIX); Open Multi-Processing (OpenMP) designed for parallel computing – best for multi-core computing.




Running Jobs on Expanse

- “**batch mode**.” you submit jobs to be run on the compute nodes using the **sbatch** command as described below.
- Remember that computationally intensive jobs should be run only on the compute nodes and not the login nodes.
- Expanse places limits on the number of jobs queued and running on a per group (allocation) and partition basis.
- Please note that submitting a large number of jobs (especially very short ones) can impact the overall scheduler response for all users.



Methods for Running Jobs on Expanse


- Batch Jobs: Submit batch scripts to Slurm from the login nodes:
 - Partition (queue)
 - Time limit for the run (maximum of 48 hours)
 - Number of nodes, tasks per node; Memory requirements (if any)
 - Job name, output file location; Email info, configuration
 - Expanse uses the Simple Linux Utility for Resource Management (SLURM) batch environment.
- Interactive Jobs: Use the ***srun*** command to request 'live' nodes from Slurm for command line, interactive access
 - See below




Slurm Resource Manager

Simple Linux Utility for Resource Management

- “Glue” for parallel computer to schedule and execute jobs
- Role: Allocate resources within a cluster
 - Nodes (unique IP address)
 - Interconnect/switches
 - Generic resources (e.g. GPUs)
 - Launch and otherwise manage jobs



- Functionality:
 - Prioritize queue(s) of jobs;
 - decide when and where to start jobs;
 - terminate job when done;
 - Appropriate resources;
 - manage accounts for jobs



<https://slurm.schedmd.com/sbatch.html>

SDSC SAN DIEGO
SUPERCOMPUTER CENTER
UC San Diego

Common Slurm Commands

- Submit jobs using the sbatch command:

```
$ sbatch mycode-slurm.sb
```

```
Submitted batch job 8718049
```

- Check job status using the squeue command:

```
$ squeue -u $USER
```

| JOBID | PARTITION | NAME | USER | ST | TIME | NODES | NODELIST(REASON) |
|---------|-----------|--------|------|----|------|-------|------------------|
| 8718049 | compute | mycode | user | PD | 0:00 | 1 | (Priority) |

- Once the job is running, monitor it's state:


```
$ squeue -u $USER
```

| JOBID | PARTITION | NAME | USER | ST | TIME | NODES | NODELIST(REASON) |
|---------|-----------|--------|------|----|------|-------|------------------|
| 8718049 | debug | mycode | user | R | 0:02 | 1 | expanse-14-01 |

- Cancel a running job:

```
$ scancel 8718049
```

<https://slurm.schedmd.com/sbatch.html>




Slurm Partitions on Expanse

https://www.sdsc.edu/support/user_guides/expanse.html#running

| Partition Name | Max Walltime | Max Nodes/Job | Max Running Jobs | Max Running + Queued Jobs | Charge Factor | Notes |
|----------------|--------------|---------------|------------------|---------------------------|---------------|--|
| compute | 48 hrs | 32 | 32 | 64 | 1 | Used for exclusive access to regular compute nodes; <i>limit applies per group</i> |
| shared | 48 hrs | 1 | 4096 | 4096 | 1 | Single-node jobs using fewer than 128 cores |
| gpu | 48 hrs | 4 | 4 | 8 (32 Tres GPU) | 1 | Used for exclusive access to the GPU nodes |
| gpu-shared | 48 hrs | 1 | 24 | 24 (24 Tres GPU) | 1 | Single-node job using fewer than 4 GPUs |
| large-shared | 48 hrs | 1 | 1 | 4 | 1 | Single-node jobs using large memory up to 2 TB (minimum memory required 256G) |
| debug | 30 min | 2 | 1 | 2 | 1 | Priority access to shared nodes set aside for testing of jobs with short walltime and limited resources |
| gpu-debug | 30 min | 2 | 1 | 2 | 1 | Priority access to gpu-shared nodes set aside for testing of jobs with short walltime and limited resources; <i>max two gpus per job</i> |
| preempt | 7 days | 32 | | 128 | .8 | Non-refundable discounted jobs to run on free nodes that can be pre-empted by jobs submitted to any other queue |
| gpu-preempt | 7 days | 1 | | 24 (24 Tres GPU) | .8 | Non-refundable discounted jobs to run on unallocated nodes that can be pre-empted by higher priority queues |

<https://slurm.schedmd.com/sbatch.html>




Example Batch Script: Show ENV

```
[uswename@login02 calc-prime]$ cat mpi-prime-slurm.sb
#!/bin/bash
#SBATCH --job-name="mpi_prime"
#SBATCH --output="mpi_prime.%j.%N.out"
####SBATCH --partition=compute
#SBATCH --partition=debug
#SBATCH --nodes=1
#SBATCH --ntasks-per-node=1
#SBATCH --export=ALL
#SBATCH -t 00:10:00
#SBATCH -A use300
```

```
## Environment
module purge
module load slurm
module load cpu
module load gcc/10.2.0
module load openmpi/4.0.4
```

```
## echo job name and id:
echo "SLURM_JOB_NAME: $SLURM_JOB_NAME"
echo "SLURM_JOB_ID: $SLURM_JOB_ID"
d=`date`
echo "DATE: $d"
```

```
[mthomas@login02 calc-prime]$ sbatch --export=NLO=1000 mpi-prime-slurm.sb
Submitted batch job 14126259
[mthomas@login02 calc-prime]$ lsq
squeue -u mthomas
JOBID PARTITION NAME USER ST TIME NODES NODELIST(REASON)
14126259 debug mpi_prim mthomas R 0:04 1 exp-9-55
[mthomas@login01 env_info]$ cat envinfo.14126259.exp-4-35.out
SLURM_JOB_NAME: envinfo
SLURM_JOB_ID: 14126259
hostname= exp-4-35
date= Sun Jun 26 22:05:15 PDT 2022
whoami= mthomas
pwd= /home/mthomas/hpctr-examples/env_info
Currently Loaded Modules: 1) slurm/expense/21.08.8 2) cpu/0.15.4
-----
env= LD_LIBRARY_PATH=/cm/shared/apps/slurm/current/lib64/slurm:
[SNIP]
/cm/shared/apps/slurm/current/lib64
SLURM_SUBMIT_DIR=/home/mthomas/hpctr-examples/env_info
HISTCONTROL=ignoredups
DISPLAY=localhost:16.0
HOSTNAME=exp-4-35
[SNIP]
```



SLURM Environment Variables

<https://slurm.schedmd.com/sbatch.html#lBAJ>

Internal ENV vars that exist when job submitted:

INPUT ENVIRONMENT VARS


<https://slurm.schedmd.com/sbatch.html#lBAJ>

- Upon startup, sbatch will read and handle the options set in the following environment variables.
- SBATCH_JOB_NAME
 - Same as -J, --job-name
- SBATCH_ACCOUNT
 - Same as -A, --account
- SBATCH_TIMELIMIT
 - Same as -t, --time

OUTPUT ENVIRONMENT VARS


<https://slurm.schedmd.com/sbatch.html#lBAK>

- The Slurm controller will set the following variables in the environment of the batch script.
- SLURM_EXPORT_ENV
 - Same as --export.
- SLURM_JOB_ID
 - The ID of the job allocation.
- SLURM_JOB_NAME
 - Name of the job.



Passing values into the batch script

- For SLURM: use the **--export** flag.
 - For other schedulers check documentation
- Example: pass the value of two variables x and B into the job script named jobscript.sbatch
 - sbatch --export=x=7,B='mystring' jobscript.sb
 - OR: sbatch --export=ALL,x=7,B= mystring ' jobscript.sbatch
- The first example will replace the user's environment with a new environment containing only values for x and B and the SLURM_* environment variables. The second will add the values for A and b to the existing environment.




Example: Passing Vars to Batch Script

```
[uswername@login02 calc-prime]$ cat mpi-prime-slurm.sb
#!/bin/bash
#SBATCH --job-name="mpi_prime"
#SBATCH --output="mpi_prime.%j.%N.out"
####SBATCH --partition=compute
#SBATCH --partition=debug
#SBATCH --nodes=1
#SBATCH --ntasks-per-node=24
#SBATCH --export=ALL
#SBATCH -t 00:10:00
#SBATCH -A use300
## Environment
module purge
module load slurm
module load cpu
module load gcc/10.2.0
module load openmpi/4.0.4
## echo job name and id:
echo "SLURM_JOB_NAME: $SLURM_JOB_NAME"
echo "SLURM_JOB_ID: $SLURM_JOB_ID"
d=`date`
echo "DATE: $d"
echo "Var NLO: $NLO"
## Use srun to run the job, pass variable to code
srun --mpi=pmi2 -n 24 --cpu-bind=rank ./mpi_prime Y
```


```
[mthomas@login02 calc-prime]$ sbatch --export=NLO=1000 mpi-prime-slurm.sb
Submitted batch job 9113467
[mthomas@login02 calc-prime]$ !sq
squeue -u mthomas
JOBID PARTITION NAME USER ST TIME NODES NODELIST(
9113467 debug mpi_prim mthomas R 0:04 1 exp-9-55
[mthomas@login02 calc-prime]$ cat mpi_prime.9113467.exp-9-55.out
SLURM_JOB_NAME: mpi_prime SLURM_JOB_ID: 9113467
DATE: Fri Jan 28 14:54:54 PST 2022
Var NHI: 250000
The argument supplied is 250000
PRIME_MPI. n_hi= 250000 C/MPI version
N Pi Time
1 0 0.000361
2 1 0.000004
4 2 0.000768
8 4 0.000003
16 6 0.000003
32 11 0.000003
64 18 0.000003
128 31 0.000004
256 54 0.000554
[SNIP]
16384 1900 0.008385
32768 3512 0.030101
65536 6542 0.110856
131072 12251 0.421177
```

Batch
and



What is Interactive HPC-Computing

- In computer science, interactive computing refers to software which accepts input from the user as it runs.
 - commonly used programs, such as word processors or spreadsheet applications.
- Interactive HPC computing involves real-time user inputs to perform tasks on a set of compute node(s) including:
 - Code development, real-time data exploration, and visualizations.
 - Used when applications have large data sets or are too large to download to local device, software is difficult install, etc.
 - User inputs come via command line interface or application GUI (Jupyter Notebooks, Matlab, R-studio).
 - Actions performed on remote compute nodes as a result of user input or program out.
- Expanse supports running applications via command line and Web-based services (Jupyter Notebooks, Matlab, R-studio)




Accessing Interactive Compute Nodes on Expanse

- Connect via terminal using SSH → secure connections
- Use the *srun* command to obtain nodes for 'live,' command line interactive access:

| | |
|-----|--|
| CPU | <code>srun --partition=debug --pty --account=use300 --nodes=1 --ntasks-per-node=4 --mem=8G -t 00:30:00 --wait=0 --export=ALL /bin/bash</code> |
| GPU | <code>srun --partition=gpu-debug --pty --account=use300 --ntasks-per-node=10 --nodes=1 --mem=96G --gpus=1 -t 00:30:00 --wait=0 --export=ALL /bin/bash</code> |

- Note: you don't need an interactive node to launch secure Jupyter notebooks. Use the Portal or the SRPS/galileo



Expanse User Guide: https://www.sdsc.edu/support/user_guides/expanse.html

SDSC SAN DIEGO
SUPERCOMPUTER CENTER
UC San Diego

Using An Interactive mode

```
[user@login02 MPI]$ srun --partition=debug --pty --account=use300 --nodes=1 --ntasks-per-node=4 --  
mem=8G -t 00:10:00 --wait=0 --export=ALL /bin/bash  
srun: job 5825986 queued and waiting for resources  
srun: job 5825986 has been allocated resources  
[user@exp-9-55 MPI]$  
[user@ exp-9-55 MPI]$ module purge  
[user@ exp-9-55 MPI]$ module load slurm  
[user@ exp-9-55 MPI]$ module load cpu  
[user@ exp-9-55 MPI]$ module load gcc/10.2.0  
[user@ exp-9-55 MPI]$ module load openmpi/4.0.4  
[user@exp-9-55 ~]$ hostname  
exp-9-55  
[user @exp-9-55 ~]$ date  
Sun Jun 26 19:02:24 PDT 2022  
[user@exp-9-55 ~]$ module list  
Currently Loaded Modules:  
  1) slurm/expense/20.02.3  2) cpu/0.15.4  3) intel/19.1.1.217  4) openmpi/4.0.4  
[user@exp-9-55 ~]$ module purge  
modul[user@exp-9-55 ~]$ module restore  
Restoring modules from user's default  
[user @exp-9-55 ~]$ module list  
Currently Loaded Modules:  
  1) cpu/0.15.4  2) slurm/expense/20.02.3  3) intel/19.1.1.217  
[user @exp-9-55 ~]$ exit
```

Request
interactive
node for 10
minutes

Update
module
environment
on node


- Exit interactive session when your work is done or you will be charged CPU time.
- Beware of oversubscribing your job: asking for more cores than you have. Intel compiler allows this, but your performance will be degraded.



Running Interactive Jobs - CPU

Obtaining an interactive CPU node with 1 node, 128 cores, and 249GB:

```
[user@login01 ~]$ srun --partition=debug --account=abc123 --pty --nodes=1 --ntasks-per-node=128
--mem=248 -t 00:30:00 --wait=0 --export=ALL /bin/bash
srun: job 5825986 queued and waiting for resources
srun: job 5825986 has been allocated resources
[user@exp-9-55 ~]$ hostname
exp-9-55
[user @exp-9-55 ~]$ date
Sun Jun 26 19:02:24 PDT 2022
[user@exp-9-55 ~]$ module list
Currently Loaded Modules:
  1) slurm/expandse/20.02.3  2) cpu/0.15.4  3) intel/19.1.1.217  4) openmpi/4.0.4
[user@exp-9-55 ~]$ module purge
modul[user@exp-9-55 ~]$ module restore
Restoring modules from user's default
[user @exp-9-55 ~]$ module list
Currently Loaded Modules:
  1) cpu/0.15.4  2) slurm/expandse/20.02.3  3) intel/19.1.1.217
[user @exp-9-55 ~]$ exit
```



Running Interactive Jobs - GPU

The following example will request a GPU node, 10 cores, 1 GPU and 96G in the debug partition for 30 minutes. To ensure the GPU environment is properly loaded, please be sure run both the module purge and module restore commands.


```
[user@login02 ~]$ srun --partition=gpu-debug --pty --account=abc123 --ntasks-per-node=10
--nodes=1 --mem=96G --gpus=1 -t 00:30:00 --wait=0 --export=ALL /bin/bash
srun: job 5826039 queued and waiting for resources
srun: job 5826039 has been allocated resources
[user@exp-7-59 ~]$
[user@exp-7-59 ~]$ hostname
exp-7-59
[user@exp-7-59 ~]$ module purge
[user@exp-7-59 ~]$ module restore
Restoring modules from user's default
[user@exp-7-59 ~]$
```

```
[user@exp-7-59 ~]$ nvidia-smi
Thu Sep 16 00:09:41 2021
```

| NVIDIA-SMI 460.32.03 Driver Version: 460.32.03 CUDA Version: 11.2 | | | | | | | | | |
|---|--------------------|---------------|------------------|-----------------|----------|-------------|--|--|--|
| GPU | Name | Persistence-M | Bus-Id | Disp.A | Volatile | Uncorr. ECC | | | |
| Fan | Temp | Perf | Pwr:Usage/Cap | Memory-Usage | GPU-Util | Compute M. | | | |
| | | | | | MIG | M. | | | |
| 0 | Tesla V100-SXM2... | On | 00000000:18:00.0 | Off | 0% | 0 | | | |
| N/A | 32C | P0 | 41W / 300W | 0MiB / 32510MiB | | Default | | | |
| | | | | | | N/A | | | |


```
Processes:
```

| GPU | GI | CI | PID | Type | Process name | GPU Memory |
|-----|----|----|-----|------|--------------|------------|
| ID | ID | ID | | | | Usage |



General Steps: Compiling/Running Jobs

- Change to your working directory (e.g. hpctr-examples):
- Compile MPI hello world code:

```
[mthomas@login02 ~]$  
[mthomas@login02 ~]$ cd /home/$USER/hpctr-examples/mpl  
[mthomas@login02 mpi]$ ll hello_mpi.f90  
-rw-r--r-- 1 mthomas use300 333 Feb 18 13:42 hello_mpi.f90  
[mthomas@login02 mpi]$
```

- Verify that the correct modules are loaded:

```
[mthomas@login02 ~]$ module list  
Currently Loaded Modules:  
 1) shared 2) cpu/0.15.4 3) slurm/expanse/21.08.8  
 4) sdsc/1.0 5) DefaultModules
```


```
[mthomas@login02 mpi]$  
[mthomas@login02 mpi]$ mpif90 -o hello_mpi hello_mpi.f90  
[mthomas@login02 mpi]$
```

- Verify executable create date:

```
[mthomas@login02 mpi]$  
[mthomas@login02 mpi]$ ls -lt hello_mpi  
-rwxr-xr-x 1 mthomas use300 22440 Jun 26 18:45 hello_mpi  
[mthomas@login02 mpi]$
```


- Submit job

```
[mthomas@login02 mpi]$  
[mthomas@login02 mpi]$ sbatch hellompi-slurm.sb  
Submitted batch job 14124495  
[mthomas@login02 mpi]$
```




Outline

- Introduction
- Compiling and Linking Code
- Running Jobs
- **Additional Examples**
 - MPI Jobs
 - OpenMP Jobs
 - Hybrid MPI-OpenMP Jobs
- Final Comments



Additional Examples

- Copy code examples from:
 - </cm/shared/examples/sdsc/>
 - These are the most recent versions
- Clone examples from
 - <https://github.com/sdsc-hpc-training-org/expanse-101>
- CPU Jobs & GPU Jobs



Outline

- Expanse Overview & Innovative Features
- Compiling and Linking Code
- Running Jobs
- Additional Examples
 - **MPI Jobs**
 - OpenMP Jobs
 - Hybrid MPI-OpenMP Jobs
- Final Comments




MPI Hello World

- Change to the MPI examples directory:

```
[user@login02 MPI]$ cat hello_mpi.f90
! Fortran example
program hello
include 'mpif.h'
integer rank, size, ierror, tag, status(MPI_STATUS_SIZE)

call MPI_INIT(ierror)
call MPI_COMM_SIZE(MPI_COMM_WORLD, size, ierror)
call MPI_COMM_RANK(MPI_COMM_WORLD, rank, ierror)
print*, 'node', rank, ': Hello world!'
call MPI_FINALIZE(ierror)
end
[user@login02 MPI]$
```



MPI Hello World: Compile

Set the environment and
then compile the code

```
[user@login02 MPI]$ cat README.txt  
[1] Compile:
```

```
# Load module environment  
module purge  
module load slurm  
module load cpu  
module load gcc/10.2.0  
module load openmpi/4.0.4
```

```
mpif90 -o hello_mpi hello_mpi.f90
```

[2a] Run using Slurm:

```
sbatch hellompi-slurm.sb
```

[2b] Run using Interactive CPU Node

```
srun --partition=debug --account=sds184 --pty --nodes=1 --ntasks-per-  
node=128 --mem=248 -t 00:30:00 --wait=0 --export=ALL /bin/bash
```

```
[user@login02 MPI]$ module list
```

Currently Loaded Modules:

1) cpu/1.0 2) slurm/expanse/20.02.3

```
[user@login02 MPI]$ module purge
```

```
[user@login02 MPI]$ module load slurm
```

```
[user@login02 MPI]$ module load cpu
```

```
[user@login02 MPI]$ module load gcc/10.2.0
```

```
[user@login02 MPI]$ module load openmpi/4.0.4
```


```
[user@login02 MPI]$ module list
```

Currently Loaded Modules:

1) slurm/expanse/20.02.3 2) cpu/1.0 3) gcc/10.2.0 4) openmpi/4.0.4

```
[user@login02 MPI]$ mpif90 -o hello_mpi hello_mpi.f90
```

```
[user@login02 MPI]$
```



MPI Hello World: Batch Script

- To run the job, use the **batch script submission** command.
- Monitor the job until it is finished using the **squeue** command.

```
[user@login02 MPI]$ cat hellompi-slurm-gnu.sb
#!/bin/bash
#SBATCH --job-name="hellompi-gnu"
#SBATCH --output="hellompi-gnu.%j.%N.out"
#SBATCH --partition=compute
#SBATCH --nodes=2
#SBATCH --ntasks-per-node=128
#SBATCH --export=ALL
#SBATCH -A abc123
#SBATCH -t 00:10:00
squeue -u mthomas
```

#This job runs with 2 nodes,
128 cores per node for a total of 256 cores.

Environment

```
module purge
module load slurm
module load cpu
module load gcc/10.2.0
module load openmpi/4.0.4
```

Use srun to run the job


```
srun --mpi=pmi2 -n 256 --cpu-bind=rank ./hello_mpi_gnu
```

```
[user@login02 MPI]$
```

```
[user@login02 MPI]$ sbatch hellompi-slurm-gnu.sb; squeue -u user
Submitted batch job 108910
      JOBID PARTITION  NAME  USER ST   TIME  NODES NODELIST(REASON)
    108910  compute  hellompi  user PD   0:00    2 (None)
[user@login02 MPI]$ cat hellompi-gnu.108910.exp-12-54.out
node      4 : Hello world!
node      5 : Hello world!
node      7 : Hello world!
node      0 : Hello world!
node      2 : Hello world!
node      3 : Hello world!
node      9 : Hello world!
node     10 : Hello world!

[SNIP]

node    247 : Hello world!
node    248 : Hello world!
node    249 : Hello world!
node    186 : Hello world!
node    220 : Hello world!
node    203 : Hello world!
node    135 : Hello world!
```



Using An Interactive mode

```
[user@login02 MPI]$ srun --partition=debug --pty --account=use300 --nodes=1 --ntasks-per-node=24 --  
mem=8G -t 00:30:00 --wait=0 --export=ALL /bin/bash
```

```
[user@exp-9-55 MPI]$  
[user@exp-9-55 MPI]$ module purge  
[user@exp-9-55 MPI]$ module load slurm  
[user@exp-9-55 MPI]$ module load cpu  
[user@exp-9-55 MPI]$ module load gcc/10.2.0  
[user@exp-9-55 MPI]$ module load openmpi/4.0.4
```


Update
module
environment
on node

Request
interactive
node for 30
minutes

```
[mthomas@exp-9-55 mpi]$ mpirun -np 16 ./hello_mpi
```


```
node      3 : Hello world! F90  
node      8 : Hello world! F90  
node     14 : Hello world! F90  
node      6 : Hello world! F90  
node     13 : Hello world! F90  
node      1 : Hello world! F90  
node      9 : Hello world! F90  
node     10 : Hello world! F90  
node      2 : Hello world! F90  
node      4 : Hello world! F90  
node      0 : Hello world! F90  
node     11 : Hello world! F90  
node     12 : Hello world! F90  
node     15 : Hello world! F90  
node      5 : Hello world! F90  
node      7 : Hello world! F90
```

- Exit interactive session when your work is done or you will be charged CPU time.
- Beware of oversubscribing your job: asking for more cores than you have. Intel compiler allows this, but your performance will be degraded.



Outline

- Introduction
- Compiling and Linking Code
- Running Jobs
- Additional Examples
 - MPI Jobs
 - **OpenMP Jobs**
 - Hybrid MPI-OpenMP Jobs
- Final Comments




OpenMP Hello World

Change to the OPENMP examples directory:

```
[mthomas@login01 examples]$ cd OPENMP/
[mthomas@login01 OPENMP]$ ll
total 89
drwxr-xr-x 2 mthomas use300  7 Oct 7 11:28 .
drwxr-xr-x 7 mthomas use300  7 Oct 8 00:03 ..
-rwxr-xr-x 1 mthomas use300 19640 Oct 7 11:28 hello_openmp
-rw-r--r-- 1 mthomas use300  236 Oct 7 11:28 hello_openmp.f90
-rw-r--r-- 1 mthomas use300  672 Oct 7 11:28 hello_openmp_shared.108737.exp-6-56.out
-rw-r--r-- 1 mthomas use300  442 Oct 7 11:28 openmp-slurm-shared.sb
-rw-r--r-- 1 mthomas use300  168 Oct 7 11:28 README.txt
[mthomas@login01 OPENMP]$ cat hello_openmp.f90
  PROGRAM OMPHELLO
  INTEGER TNUMBER
  INTEGER OMP_GET_THREAD_NUM

  !$OMP PARALLEL DEFAULT(PRIVATE)
    TNUMBER = OMP_GET_THREAD_NUM()
    PRINT *, 'HELLO FROM THREAD NUMBER = ', TNUMBER
  !$OMP END PARALLEL

  END
```



OpenMP Hello World: Compile (using aocc compiler)

Set the environment and
then compile the code

```
[mthomas@login01 OPENMP]$ cat README.txt  
[1] Compile:
```

```
#load module environmentmodule  
module purge  
module load slurm  
module load cpu  
module load aocc
```

```
flang -fopenmp -o hello_openmp hello_openmp.f90
```

```
[2] Run:
```

```
sbatch openmp-slurm-shared.sb
```

```
[mthomas@login01 OPENMP]$
```

```
[mthomas@login01 OPENMP]$ module list
```


```
[mthomas@login01 OPENMP]$ module purge  
[mthomas@login01 OPENMP]$ module load slurm  
[mthomas@login01 OPENMP]$ module load cpu  
[mthomas@login01 OPENMP]$ module load aocc
```

Currently Loaded Modules:

1) slurm/expense/20.02.3 2) cpu/1.0 3) aocc/2.2.0

```
[mthomas@login01 OPENMP]$
```

```
[mthomas@login01 MPI]$ mpif90 -o hello_mpi hello_mpi.f90
```



OpenMP Hello World: Controlling #Threads

A key issue when running OpenMP code is controlling thread behavior.


If you run from command line, it will work, but it is not recommended because you will be using Pthreads, which automatically picks the number of threads - in this case 24.

```
[expanse-ln2:~/expanse1010/PENMP] ./hello_openmp
Hello from Thread Number[      0 ] and Welcome Webinar!
Hello from Thread Number[      2 ] and Welcome Webinar!
.
.
.
Hello from Thread Number[     22 ] and Welcome Webinar!
Hello from Thread Number[     11 ] and Welcome Webinar!
Hello from Thread Number[     23 ] and Welcome Webinar!
```

To control thread behavior, there are several key environment variables: OMP_NUM_THREADS controls the number of threads allowed, and OMP_PROC_BIND binds threads to “places” (e.g. cores) and keeps them from moving around (between cores).

```
[expanse-ln2:~/expanse1010PE/NMP] export OMP_NUM_THREADS=4; ./hello_openmp
HELLO FROM THREAD NUMBER = 3
HELLO FROM THREAD NUMBER = 1
HELLO FROM THREAD NUMBER = 2
HELLO FROM THREAD NUMBER = 0
```

See: https://www.ibm.com/support/knowledgecenter/SSGH2K_13.1.3/com.ibm.xlc1313.aix.doc/compiler_ref/ruomprun.html



OpenMP Hello World: Batch Script

```
[mthomas@login01 OPENMP]$ cat openmp-slurm-  
shared.sb  
#!/bin/bash  
#SBATCH --job-name="hell_openmp_shared"  
#SBATCH --output="hello_openmp_shared.%j.%N.out"  
#SBATCH --partition=shared  
#SBATCH --nodes=1  
#SBATCH --ntasks-per-node=1  
#SBATCH --cpus-per-task=16  
#SBATCH --mem=32G  
#SBATCH --export=ALL  
#SBATCH -t 01:30:00
```

```
# AOCC environment  
module purge  
module load slurm  
module load cpu  
module load aocc
```

```
#SET the number of openmp threads  
export OMP_NUM_THREADS=16
```


```
#Run the openmp job  
./hello_openmp  
[mthomas@login01 OPENMP]$
```

- Note: Expanse supports **shared-node jobs** (more than one job on a single node).
- Many applications are serial or can only scale to a few cores.
- Shared nodes improve job throughput, provide higher overall system utilization, and allow more users to run on nodes.

```
[expanse-ln2:~/expanse101/OPENMP] cat openmp-slurm-  
shared.sb  
#!/bin/bash  
#SBATCH --job-name="hell_openmp_shared"  
#SBATCH --output="hello_openmp_shared.%j.%N.out"  
#SBATCH --partition=shared  
#SBATCH --share  
#SBATCH --nodes=1  
#SBATCH --ntasks-per-node=16  
#SBATCH --mem=80G  
#SBATCH --export=ALL  
#SBATCH -t 01:30:00
```

```
#SET the number of openmp threads  
export OMP_NUM_THREADS=16
```

```
#Run the openmp job  
./hello_openmp
```




OpenMP Hello World: submit job & monitor

To run the job, type the **batch script submission** command:


```
[mthomas@login01 OPENMP]$ sbatch openmp-slurm-shared.sb
Submitted batch job 108911
[mthomas@login01 OPENMP]$ squeue -u mthomas
JOBID PARTITION NAME USER ST TIME NODES NODELIST(REASON)
108911 shared hell_ope mthomas PD 0:00 1 (None)
[mthomas@login01 OPENMP]$ ll
total 98
drwxr-xr-x 2 mthomas use300 8 Oct 8 03:37 .
drwxr-xr-x 7 mthomas use300 7 Oct 8 00:03 ..
-rwxr-xr-x 1 mthomas use300 19640 Oct 7 11:28 hello_openmp
-rw-r--r-- 1 mthomas use300 236 Oct 7 11:28 hello_openmp.f90
-rw-r--r-- 1 mthomas use300 672 Oct 8 03:37 hello_openmp_shared.108911.exp-6-56.out
-rw-r--r-- 1 mthomas use300 442 Oct 7 11:28 openmp-slurm-shared.sb
-rw-r--r-- 1 mthomas use300 168 Oct 7 11:28 README.txt
```

```
[mthomas@login01 OPENMP]$ cat
hello_openmp_shared.108911.exp-6-56.out
HELLO FROM THREAD NUMBER = 7
HELLO FROM THREAD NUMBER = 6
HELLO FROM THREAD NUMBER = 12
HELLO FROM THREAD NUMBER = 10
HELLO FROM THREAD NUMBER = 1
HELLO FROM THREAD NUMBER = 2
HELLO FROM THREAD NUMBER = 5
HELLO FROM THREAD NUMBER = 0
HELLO FROM THREAD NUMBER = 4
HELLO FROM THREAD NUMBER = 3
HELLO FROM THREAD NUMBER = 13
HELLO FROM THREAD NUMBER = 15
HELLO FROM THREAD NUMBER = 14
HELLO FROM THREAD NUMBER = 11
HELLO FROM THREAD NUMBER = 9
HELLO FROM THREAD NUMBER = 8
[mthomas@login01 OPENMP]$
```



Outline

- Introduction
- Compiling and Linking Code
- Running Jobs
- Additional Examples
 - MPI Jobs
 - OpenMP Jobs
 - **Hybrid MPI-OpenMP Jobs**
- Final Comments



Hybrid MPI + OpenMP Hello World


```
#include <stdio.h>
#include "mpi.h"
#include <omp.h>

int main(int argc, char *argv[]) {
    int numprocs, rank, namelen;
    char processor_name[MPI_MAX_PROCESSOR_NAME];
    int iam = 0, np = 1;

    MPI_Init(&argc, &argv);
    MPI_Comm_size(MPI_COMM_WORLD, &numprocs);
    MPI_Comm_rank(MPI_COMM_WORLD, &rank);
    MPI_Get_processor_name(processor_name, &namelen);

    #pragma omp parallel default(shared) private(iam, np)
    {
        np = omp_get_num_threads();
        iam = omp_get_thread_num();
        printf("Hello Webinar participants from thread %d out of %d from process %d out of %d on %s\n",
            iam, np, rank, numprocs, processor_name);
    }

    MPI_Finalize();
}
```



Hybrid MPI + OpenMP Jobs

```
[mthomas@login01 HYBRID]$ cat README.txt
```

[1] Compile:

```
# Load module environment
module purge
module load slurm
module load cpu
module load intel
module load intel-mpi

export I_MPI_CC=icc
mpicc -qopenmp -o hello_hybrid hello_hybrid.c
```

[2] Run:

```
sbatch hybrid-slurm.sb
```

```
[mthomas@login01 HYBRID]$ cat hybrid-slurm.sb
```

```
#!/bin/bash
#SBATCH --job-name="hellohybrid"
#SBATCH --output="hellohybrid.%j.%N.out"
#SBATCH --partition=shared
#SBATCH --nodes=1
#SBATCH --ntasks-per-node=2
#SBATCH --cpus-per-task=16
#SBATCH -B 2:16:1
#SBATCH --export=ALL
#SBATCH -t 01:30:00
```

```
# Load Module Environment
module purge
module load slurm
module load cpu
module load intel
module load intel-mpi
```

```
#Run
```

```
export OMP_NUM_THREADS=16
mpirun -genv I_MPI_PIN_DOMAIN=omp:compact ./hello_hybrid
```

```
[mthomas@login01 HYBRID]$ mpicc -qopenmp -o hello_hybrid hello_hybrid.c
```


```
[mthomas@login01 HYBRID]$ sbatch hybrid-slurm.sb
```

```
Submitted batch job 108875
```

```
[mthomas@login01 HYBRID]$ squeue -u mthomas
```

| JOBID | PARTITION | NAME | USER | ST | TIME | NODES | NODELIST(REASON) |
|--------|-----------|----------|---------|----|------|----------|------------------|
| 108875 | shared | hellohyb | mthomas | PD | 0:00 | 1 (None) | |

```
[mthomas@login01 HYBRID]$
```




Hybrid Hello World: Output

Code ran on:

- 1 node,
- 2 cores per node,
- 16 threads per core


```
[expanse-ln2:~/expanse101/HYBRID] cat hellohybrid. 108875.expanse-06-48.out | sort
```

```
Hello from thread 0 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 0 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 1 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 1 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 2 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 2 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 3 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 3 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 4 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 4 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 5 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 5 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 6 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 6 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 7 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 7 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 8 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 8 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 9 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 9 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 10 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 10 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 11 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 11 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 12 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 12 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 13 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 13 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 14 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 14 out of 16 from process 1 out of 2 on exp-6-56
Hello from thread 15 out of 16 from process 0 out of 2 on exp-6-56
Hello from thread 15 out of 16 from process 1 out of 2 on exp-6-56
```




Outline

- Introduction
- Compiling and Linking Code
- Running Jobs
- Additional Examples
 - MPI Jobs
 - OpenMP Jobs
 - Hybrid MPI-OpenMP Jobs
- **Final Comments**




When Things Go Wrong, Check Your User Environment

- Do you have the right modules loaded?
- What software versions do you need?
- Is your code compiled and updated
 - Did you compile it last year? Have the libraries changed?
- Are you running your job from the right location?
 - \$HOME versus \$WORK?




Run jobs from the right location

- Lustre scratch filesystem:
 - /oasis/scratch/expanse/\$USER/temp_project
 - Preferred: Scalable large block I/O)
- Compute/GPU node local SSD storage:
 - /scratch/\$USER/\$SLURM_JOBID
 - Meta-data intensive jobs, high IOPs)
- Lustre projects filesystem:
 - /oasis/projects/nsf
- /home/\$USER:
 - Only for source files, libraries, binaries.
 - Do not use for I/O intensive jobs.




Useful Links

- Expanse User Guide:
 - https://www.sdsc.edu/support/user_guides/expanse.html
- Expanse Overview:
 - https://education.sdsc.edu/training/interactive/202201_parallel_computing_concepts
- You need to have an Expanse account in order to access the system. There are a few ways to do this:
 - Submit a proposal through the [XSEDE Allocation Request System](#)
 - A PI on an active allocation can add you to their allocation (if you are collaborators working on the same project).
 - Request a trial account: instructions @ <https://portal.xsede.org/allocations/startup>.
- Hands-on/code examples for this tutorial:
 - <https://github.com/sdsc-hpc-training-org/hpctr-examples>
 - <https://github.com/sdsc-hpc-training-org/expanse-101>
 - https://hpc-training.sdsc.edu/expanse-101/Expanse_Tutorial.html



Resources

- Expanse User Guide & Tutorial
 - https://www.sdsc.edu/support/user_guides/expanse.html
 - <https://hpc-training.sdsc.edu/expanse-101/>
- SDSC Training Resources
 - https://www.sdsc.edu/education_and_training/training_hpc.html
- XSEDE Training Resources
 - <https://www.xsede.org/for-users/training>
 - <https://cvw.cac.cornell.edu/expanse/>



Thank You

