133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535, Republic Of Singapore

Tel. +65 6227 6365 - Fax. +65 6225 6286

www.tradeasia.com



# Material Safety Data Sheet Potassium Hydroxide

## **Section 1: Chemical Product and Company Identification**

Product Name : Potassium Hydroxide

Chemical Formula : KOH

Company Identification : Tradeasia International Pte Ltd Email : contact@chemtradeasia.com

# **Section 2: Composition and Information on Ingredients**

Composition:

Name	CAS#	% by Weight
Potassium Hydroxide	1310-58-3	100

Toxicological Data on Ingredients: Potassium Hydroxide: ORAL (LD50): Acute: 273 mg/kg [Rat].

## **Section 3: Hazards Identification**

**Potential Acute Health Effects:** Very hazardous in case of skin contact (corrosive, irritant), of eye contact (irritant, corrosive), of ingestion, of inhalation. The amount of tissue damage depends on length of contact. Eye contact can result in corneal damage or blindness. Skin contact can produce inflammation and blistering. Inhalation of dust will produce irritation to gastro-intestinal or respiratory tract, characterized by burning, sneezing and coughing. Severe over-exposure can produce lung damage, choking, unconsciousness or death. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

#### **Potential Chronic Health Effects:**

CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance may be toxic to upper respiratory tract, skin, eyes. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated skin exposure can produce local skin destruction, or dermatitis. Repeated inhalation of dust can produce varying degree of respiratory irritation or lung damage.

#### **Section 4: First Aid Measures**

# **Eye Contact:**

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention immediately.

## **Skin Contact:**

In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

**Serious Skin Contact:** Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.

133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535, Republic Of Singapore

Tel. +65 6227 6365 - Fax. +65 6225 6286

www.tradeasia.com



**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Serious Inhalation:** Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.

**Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

**Serious Ingestion:** Not available.

#### **Section 5: Fire and Explosion Data**

Flammability of the Product: Non-flammable.

**Auto-Ignition Temperature**: Not applicable.

Flash Points: Not applicable.

Flammable Limits: Not applicable.

**Products of Combustion**: Not available.

Fire Hazards in Presence of Various Substances: Metals, acids.

## **Explosion Hazards in Presence of Various Substances:**

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions: Not applicable.

**Special Remarks on Fire Hazards**: Violent reaction or ignition under appropriate conditions with acids, alcohols, p-bis(1,3-dibromoethyl) benzene, cyclopentadiene, germanium, hyponitrous acid, maleic anhydride, nitroalkanes, 2-nitrophenol, potassium peroxodisulfate, sugars, 2,2,3,3-tetrafluoropropanol, thorium dicarbide. Molten ortho -nitrophenol reacts violently with potassium hydroxide. When potassium hydroxide and tetrachloroethane are heated, a spontaneously flammable gas, chloroacetylene, is formed. When phosphorus is boiled in a solution of potassium hydroxide, phosphine gas is evolved which is spontaneously flammable. 1,2-Dichloroethylene and Potassium hydroxide reaction produces chloroacetylene which is spontaneously flammable in air. Potassium Persulfate and a little Potassium hydroxide and water will ignite. When wet, attacks metals such as aluminum, tin, lead, and zinc, producing flammable hydrogen gas..

**Special Remarks on Explosion Hazards:** Potentially explosive reaction with bromoform + crown ethers, chlorine dioxide, nitrobenzene, nitromethane, nitrogen trichloride, peroxidized tetrahydrofuran, 2,4,6-trinitrotoluene. Reaction with ammonium hexachloroplatiate(2-) + heat forms heat sensitive explosive product. Potassium hydroxide will cause explosive decomposition of maleic anhydride. Detonation will occur when potassiuim hydroxide is mixed with n-methyl-nitroso urea and methylene chloride. Nitrogen trichloride explodes on contact with potassium hydroxide.

#### **Section 6: Accidental Release Measures**

133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535,

Republic Of Singapore

Tel. +65 6227 6365 - Fax. +65 6225 6286

www.tradeasia.com



# **Small Spill:**

Use appropriate tools to put the spilled solid in a convenient waste disposal container. If necessary: Neutralize the residue with a dilute solution of acetic acid.

## **Large Spill:**

Corrosive solid. Stop leak if without risk. Do not get water inside container. Do not touch spilled material. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Neutralize the residue with a dilute solution of acetic acid. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

# **Section 7: Handling and Storage**

**Precautions:** Keep container dry. Do not ingest. Do not breathe dust. Never add water to this product. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as organic materials, metals, acids, moisture.

**Storage:** Keep container tightly closed. Keep container in a cool, well-ventilated area. Do not store above 23° C (73.4°F).

# **Section 8: Exposure Controls/Personal Protection**

## **Engineering Controls:**

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

#### **Personal Protection:**

Splash goggles. Synthetic apron. Vapor and dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

#### Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

**Exposure Limits:** CEIL: 2 (mg/m3) from OSHA (PEL) [United States] CEIL: 2 (mg/m3) from ACGIH (TLV) [United States] Consult local authorities for acceptable exposure limits.

## **Section 9: Physical and Chemical Properties**

Physical state and appearance : Solid
Odor : Odorless
Taste : Not available.
Molecular Weight : 56.11 g/mole

Color : White pH (1% soln./water) : 13 [Basic].

Boiling Point : Decomposition temperature: 1384°C (2523.2°F)

Melting Point : 380°C (716°F)
Critical Temperature : Not available.
Specific Gravity : 2.044 (Water = 1)
Vapor Pressure : Not applicable.

133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535,

Republic Of Singapore

Tel. +65 6227 6365 - Fax. +65 6225 6286

www.tradeasia.com



Vapor Density : Not available.
Volatility : Not available.
Odor Threshold : Not available.
Water/Oil Dist. Coeff. : Not available.
Ionicity (in Water) : Not available.

Dispersion Properties : See solubility in water.

Solubility : Easily soluble in cold water, hot water. Insoluble in diethyl ether.

# Section 10: Stability and Reactivity Data

**Stability:** The product is stable.

**Instability Temperature**: Not available.

Conditions of Instability: Incompatible materials, dust generation, exposure to moist air or water.

Incompatibility with various substances: Highly reactive with acids. Reactive with organic materials, metals,

moisture.

**Corrosivity**: Extremely corrosive in presence of aluminum, brass, and zinc. Slightly corrosive in presence of copper, of stainless steel (304). Non-corrosive in presence of stainless steel (316).

**Special Remarks on Reactivity**: Hygroscopic (absorbs moisture from air). When dissolved in water or alcohol or when the solution is treated with acid, much heat is generated. Reacts violently with acids, halogens, halogenated hydrocarbons, maleic anhydride, organic anhydrides, isocyanates, alkylene oxides, epichlorhydrin, aldehydes, alcohols, gylcols, phenols, cresols, caprolactum solution. Also incompatible with nitro compounds (nitrobenzene, nitromethane, nitrogen trichloride), organic materials, acid anhydrides, acid chlorides, magnesium, peroxidized tetrahydrofuran, chlorine dioxide, maleic dicarbide, sugars. When wet attacks metals such as aluminum, tin, lead, and zinc.

**Special Remarks on Corrosivity**: When wet, attacks metals such as aluminum, tin, lead, and zinc, producing flammable hydrogen gas. Severe corrosive effect on brass and bronze.

Polymerization: Will not occur.

cough, and shortness of breath.

#### **Section 11: Toxicological Information**

Routes of Entry: Absorbed through skin. Eye contact. Inhalation. Ingestion.

**Toxicity to Animals**: Acute oral toxicity (LD50): 273 mg / kg [Rat].

**Chronic Effects on Humans**: MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. May cause damage to the following organs: upper respiratory tract, skin, eyes.

Other Toxic Effects on Humans: Extremely hazardous in case of inhalation (lung corrosive). Very hazardous in case of skin contact (corrosive, irritant), of eye contact (corrosive), of ingestion.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: May affect genetic material based on animal data.

Special Remarks on other Toxic Effects on Humans: Acute Potential Health Effects: Skin: Causes severe skin irritation and burns. Eyes: Causes severe eye irritation and burns. May cause irreversible eye injury. Inhalation: Causes severe irritation and burns of the respiratory tract and mucous membranes. Irritation may lead to chemical pneumonitis. Ingestion: Harmful if swallowed. May cause severe and permanent damage to the digestive tract. Causes severe irritation and burns of the gastrointestinal (digestive) tract with abdominal pain, vomiting and possible death. May cause perforation of the digestive tract. Chronic Potential Health Effects: Chronic contact with dilute solutions of potassium hydroxide can cause dermatitis. Inhalation can produce chronic productive

133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535,

Republic Of Singapore

Tel. +65 6227 6365 - Fax. +65 6225 6286

www.tradeasia.com



## **Section 12: Ecological Information**

Ecotoxicity: Ecotoxicity in water (LC50): 80 mg/l 24 hours [Mosquito Fish].

BOD5 and COD: Not available.

**Products of Biodegradation:** Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

**Toxicity of the Products of Biodegradation**: The products of degradation are less toxic than the product itself. **Special Remarks on the Products of Biodegradation**: Not available.

# **Section 13: Disposal Considerations**

**Waste Disposal:** Waste must be disposed of in accordance with federal, state and local environmental control regulations.

# **Section 14: Transport Information**

**DOT Classification:** Class 8: Corrosive material.

Identification: Potassium hydroxide, solid UNNA: 1813 PG: II

Special Provisions for Transport: Not available.

#### **Section 15: Other Regulatory Information**

**Federal and State Regulations:** New York release reporting list: Potassium hydroxide Pennsylvania RTK: Potassium hydroxide Florida: Potassium hydroxide Minnesota: Potassium hydroxide Massachusetts RTK: Potassium hydroxide New Jersey: Potassium hydroxide California Director's List of Hazardous Substances: Potassium hydroxide TSCA 8(b) inventory: Potassium hydroxide CERCLA: Hazardous substances.: Potassium hydroxide: 1000 lbs. (453.6 kg).

**Other Regulations:** OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

**Other Classifications:** 

**WHMIS** (Canada): CLASS D-1B: Material causing immediate and serious toxic effects (TOXIC). CLASS E: Corrosive solid.

DSCL (EEC): HMIS (U.S.A.): Health Hazard: 3 Fire Hazard: 0 Reactivity: 2

Personal Protection: j

**National Fire Protection Association (U.S.A.):** 

Health: 3

Flammability: 0 Reactivity: 1 Specific hazard:

#### **Protective Equipment:**

Gloves. Synthetic apron. Vapor and dust respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

## **Section 16: Other Information**

133 Cecil Street # 12-03 Keck Seng Tower, Singapore 069535, Republic Of Singapore

Tel. +65 6227 6365 - Fax. +65 6225 6286

www.tradeasia.com



The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall Tradeasia International Pte. Ltd. Be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Tradeasia International Pte. Ltd. has been advised of the possibility of such damages.