

Material Safety Data Sheet

Butyl Acrylate

Section 1 - Product Identification

Synonyms : n-Butyl acrylate, Butyl ester of acrylic acid, Butyl-2-propenoate
Molecular Weight : 128.17 g/mol
Chemical Formula : $C_7H_{12}O_2$
Company Identification : Tradeasia International Pte. Limited
Address : 133 Cecil Street # 12-03 Keck Seng Tower, Singapore
Tel: +65-6227 6365
Fax: +65-6225 6286
Email: contact@chemtradeasia.com

Recommended use of the chemical and restrictions on use:

Laboratory Chemicals, Manufacturing of substances.

Section 2 – Composition/Information on Ingredients

Chemical Name	EC/CAS No	Purity, %
Butyl Acrylate	205-480-7/141-32-2	< 100

Section 3 – Hazards Identification

3.1 Classification of the substance or mixture

Flammable liquids (Category 3), H226

Acute toxicity, Oral (Category 4), H302

Acute toxicity, Inhalation (Category 4), H332

Acute toxicity, Dermal (Category 4), H312

Skin corrosion/irritation (Category 2), H315

Serious eye damage/eye irritation (Category 2), H319

Skin sensitisation (Category 1), H317

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

3.2 Label elements

Hazard statement(s):

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Precautionary statement(s)

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P280 Wear protective gloves/ eye protection/ face protection.

Response

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

3.3 Other hazards

Lachrymator

Section 4 – First-Aid Measures

4.1. Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2. Most important symptoms and effects, both acute and delayed

Most important known symptoms and effects are described in the labelling (section 3.2) and/or in section 11.

4.3. Indication of any immediate medical attention and special treatment needed

N.A.

Section 5 – Fire Fighting Measures

5.1. Suitable Extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2. Specific hazards arising from the chemical

Carbon Oxides

5.3. Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4. Further Information

Use water spray to cool unopened containers.

Section 6 – Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Section 7 – Handling and Storage

7.1. Precautions for safe Handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge. For precautions see section 2.2.

7.2. Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Light sensitive. Do not store under inert atmosphere. Polymerization can occur.

Section 8 – Exposure Controls/Personal Protection

8.1. Control parameters

Component	CAS-No	Value	Control	Basis
Ethyl acrylate	141-32-2	PEL (long term)	10ppm, 52mg/m ³	Singapore. Workplace Safety and Health Act - First Schedule Permissible Exposure Limits of Toxic Substances

8.2. Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0,3 mm

Break through time: 480 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use (US) or type ABEK (EN14387) respirator cartridges as a backup, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.4 Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Section 9 – Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance : Colourless liquid

Odour : N.A.

Odour threshold : N.A.

pH @ 20°C : No data available

Melting point : N.A

Boiling point : 145°C – lit.

Flash point : 36°C – lit.

Evaporation rate : N.A.

Flammability : N.A.

Upper/lower flammability or explosive limits : UFL 9.9%, LFL 1.3% (V)

Vapour pressure : 3.3 mmHg at 20°C

Vapour density : 4.43 (Air = 1.0)

Relative density : 0.894 g/mL at 25°C

Solubility in water : N.A.

Partition coefficient: n-octanol/water : N.A.

Auto-ignition temperature : N.A.

Decomposition temperature : N.A.

Viscosity : N.A.

Explosive properties: N.A.

Oxidizing properties: N.A.

Section 10 – Stability and Reactivity

10.1. Reactivity

N.A.

10.2. Chemical stability

Stable under recommended storage conditions

10.3. Possibility of hazardous reactions

N.A.

10.4. Conditions to avoid:

Oxygen free atmosphere. May polymerize on exposure to light. Heat, flames and sparks

10.5. Incompatible materials

Strong oxidizing agents, strong acids, strong bases

10.6. Hazardous decomposition products

Hazardous decomposition products formed under fire conditions – carbon oxides

In the event of fire, see section 5.

Other decomposition products – No data available.

Section 11 – Toxicological Information

Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 900 mg/kg(Butyl acrylate), LC50 Inhalation - Rat - 4 h - 2730 ppm(Butyl acrylate)

Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste): Olfaction:Other changes. Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Other. Lungs, Thorax, or Respiration:Dyspnea.

LC50 Inhalation - Rat - male - 4 h - 11,2 mg/l(Butyl acrylate) (OECD Test Guideline 403), LD50 Dermal - Rabbit - 1.796 mg/kg(Butyl acrylate)

Skin corrosion/irritation

No data available(Butyl acrylate)

Serious eye damage/eye irritation

No data available(Butyl acrylate)

Respiratory or skin sensitisation

Germ cell mutagenicity

No data available(Butyl acrylate)

Carcinogenicity

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Butyl acrylate)

Reproductive toxicity

Specific target organ toxicity - single exposure

May cause respiratory irritation.(Butyl acrylate)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available(Butyl acrylate)

Additional Information

RTECS: UD3150000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated., Cough, Shortness of breath, Headache, Nausea, Vomiting(Butyl acrylate)

Section 12 – Ecological Information

12.1.Toxicity

Toxicity to fish flow-through test LC50 - Cyprinodon variegatus (sheepshead minnow) – 2.1 mg/l - 96 hours (Butyl acrylate) (OECD Test Guideline 203) Toxicity to daphnia and other aquatic invertebrates static test EC50 - Daphnia magna (Water flea) - 1,3 mg/l - 48 h (Butyl acrylate) (OECD Test Guideline 202)

12.2. Persistence and degradability

Biodegradability aerobic - Exposure time 28 days (Butyl acrylate) Result: 80 - 90 % - Readily biodegradable. (OECD Test Guideline 310)

12.3. Bioaccumulative potential

N.A

12.4. Mobility in soil

N.A

12.5. Other adverse effects

Toxic to aquatic life.

Section 13 – Disposal Considerations

13.1. Disposal methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company

Section 14 – Transport Information

14.1. UN number : ADR/RID: 2348, IMDG: 2348, IATA-DGR: 2348

14.2. UN proper shipping name : N.A

14.3. Transport of hazard classes : ADR/RID: 3, IMDG: 3, IATA-DGR: 3

14.4. Packing group : ADR/RID: III, IMDG: III, IATA-DGR: III

14.5. Environmental hazards : ADR/RID: no, IMDG Marine pollutant: no, IATA-DGR: no

14.6. Special precautions for user : N.A

14.7. Incompatible materials: N.A

Section 15 – Regulatory Information

15.1. Safety, health and environmental regulations for the substance/mixture

N.A

Section 16 : Additional Information

16.1. Full text of H-Statements referred to

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

16.2. Disclaimer of Liability

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its accuracy, reliability or completeness. The conditions or methods of handling, storage use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.