

## Material Safety Data Sheet

### C9 Aromatic Solvent

#### Section 1 - Product Identification

Synonyms	: C9 Solvent
Company Identification	: Tradeasia International Pte. Limited
Address	: 133 Cecil Street # 12-03 Keck Seng Tower, Singapore
Tel	: +65-6227 6365
Fax	: +65-6225 6286
Email	: <a href="mailto:contact@chemtradeasia.com">contact@chemtradeasia.com</a>
Recommended use of the chemical and restriction on use:	manufacture of substances Use as an intermediate Distribution of substance Formulation & (re)packing of substances and mixtures Uses in Coatings Use in Cleaning Agents Use in Oil and Gas field drilling and production operations Lubricants Metal working fluids / rolling oils Use as binders and release agents Use as a fuel Use in laboratories Polymer processing Functional Fluids Water treatment chemicals Use in Agrochemicals Road and construction applications

#### Section 2 – Composition/Information on Ingredients

Chemical Name	EC No/CAS No
C9 Aromatic Solvent	64742-95-6

#### Section 3 – Hazards Identification

##### 3.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard class and category	Hazard statement
--------------	----------	---------------------------	------------------

Flammable liquid	Cat.3	(Flam Liq. 3)	H226
Specific target organ toxicity – single exposure (respiratory tract irritation)	Cat.3	(STOT SE 3)	H335
Specific target organ toxicity – single exposure (narcotic effects, drowsiness)	Cat.3	(STOT SE 3)	H336
Aspiration hazard	Cat.1	(Asp. Tox. 1)	H304
Hazardous to the aquatic environment – chronic hazard	Cat.2	(Aquatic Chronic 2)	H411

#### Remarks

For full text of H-phrases: see SECTION 16.

The classification as a carcinogen or mutagen is not required. The substance contains less than 0,1 % w/w benzene (EINECS No 200753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-P260-P262- P301 + P310-P331 shall apply

#### Supplemental hazard information

Supplemental hazard information.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### The most important adverse physicochemical, human health and environmental effects

May be fatal if swallowed and enters airways.

The product is combustible and can be ignited by potential ignition sources.

#### 3.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008 (CLP)

**Signal word** **Danger**

##### Pictograms

GHS02, GHS07,  
GHS08, GHS09

##### Hazard statements

H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

##### Precautionary statements

##### Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 P241 Use explosion-proof electrical/ventilating/lighting/.../ equipment.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

##### Precautionary statements - response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P331 Do NOT induce vomiting.  
 P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction.

##### Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 Store in a well-ventilated place. Keep cool.

##### Precautionary statements - disposal

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### **Additional labelling requirements**

EUH066 Repeated exposure may cause skin dryness or cracking.

#### **3.3 Other hazards**

According to the results of its assessment, this substance is not a PBT or a vPvB.

Vapour heavier than air, may form an explosive mixture in air: it may be ignited at some distance away from the spill resulting in flashbacks. Flowing product can create electrostatic charge, resulting sparks may ignite or cause an explosion.

### **Section 4 – Composition/ information on ingredients**

#### **4.1 Substances**

Name of substance	Hydrocarbons, C9, aromatics
Registration number (REACH)	01-2119455851-35-0002
EC number	918-668-5
CAS number	64742-95-6
Index No	649-356-00-4
Purity	100 %

### **Section 5 – First-Aid Measures**

#### **5.1 Description of first aid measures**

##### **General advice**

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### **Following inhalation**

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

##### **Following skin contact**

Wash with plenty of soap and water.

##### **Following eye contact**

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. In all cases of doubt, or when symptoms persist, seek medical advice.

##### **Following ingestion**

Do NOT induce vomiting. Rinse mouth with water (only if the person is conscious).

#### **5.2 Most important symptoms and effects, both acute and delayed**

Choking and suffocation risks. Narcotic effects. Deficits in perception and coordination, reaction time, or sleepiness.

#### **5.3 Indication of any immediate medical attention and special treatment needed**

No data available

### **Section 6 – Fire Fighting Measures**

#### **6.1 Extinguishing media**

##### **Suitable extinguishing media**

carbon dioxide (CO<sub>2</sub>), BC-powder, foam, alcohol resistant foam, water mist

##### **Unsuitable extinguishing media**

water jet

#### **6.2 Special hazards arising from the substance or mixture**

Solvent vapours are heavier than air and may spread along floors. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. May produce toxic fumes of carbon monoxide if burning.

#### **Hazardous combustion products**

carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>)

#### **6.3 Advice for firefighters**

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Keep containers cool with water spray.

### **Section 7 – Accidental Release Measures**

#### **7.1 Personal precautions, protective equipment and emergency procedures**

##### **For non-emergency personnel**

Remove persons to safety. Avoid inhaling sprayed product. Wearing of suitable protective equipment (including personal protective equipment referred to under Section 9 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Take off immediately all contaminated clothing and wash it before reuse.

##### **For emergency responders**

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

#### **7.2 Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

#### **7.3 Methods and materials for containment and cleaning up**

##### **Advices on how to contain a spill**

Covering of drains.

##### **Advices on how to clean up a spill**

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

##### **Appropriate containment techniques**

Use of adsorbent materials. - covering of drains

##### **Other information relating to spills and releases**

Place in appropriate containers for disposal. Ventilate affected area.

#### **7.4 Reference to other sections**

Hazardous combustion products: see section 6. Personal protective equipment: see section 9. Incompatible materials: see section 11. Disposal considerations: see section 14.

### **Section 8 – Handling and Storage**

#### **8.1 Precautions for safe handling**

##### **Recommendations**

- **Measures to prevent fire as well as aerosol and dust generation**

Use only in well-ventilated areas. Use local and general ventilation. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- **Warning**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

##### **Advice on general occupational hygiene**

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### **8.2 Conditions for safe storage, including any incompatibilities**

## Managing of associated risks

### • Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

### • Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

### Incompatible substances or mixtures

Observe hints for combined storage.

### Consideration of other advice

#### • Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

#### • Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

Suitable materials and coatings for container/equipment: Carbon Steel, Stainless Steel, Polyester, Polytetrafluoroethylene (PTFE), Polyvinyl Alcohol (PVA)

Unsuitable Materials and Coatings for container/equipment: Butyl Rubber, Natural Rubber, Ethylene-propylene-diene monomer (EPDM), Polystyrene, Polyethylene, Polyacrylonitrile.

## 8.3 Specific end use(s)

See attached exposure scenarios

## Section 9 – Exposure Controls/Personal Protection

### 9.1 Control parameters

#### National limit values

#### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL[ppm]	STEL [mg/m <sup>3</sup> ]	Source
DE	Hydrocarbons, C9, aromatics	64742-95-6	AGW		50		100	TRGS 900

#### Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified).

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified).

#### Relevant DNELs/DMELs/PNECs and other threshold levels

##### • human health values

Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	25 mg/kg	Human, dermal	Worker (industry)	Chronic – systemic effects
DNEL	150 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Chronic – systemic effects
DNEL	11 mg/kg	Human, oral	Consumer (private household)	Chronic – systemic effects
DNEL	11 mg/kg	Human, dermal	Consumer (private household)	Chronic – systemic effects

DNEL	32 mg/m <sup>3</sup>	Human, inhalatory	Consumer (private household)	Chronic – systemic effects
------	----------------------	-------------------	------------------------------	----------------------------

## 9.2 Exposure controls

### Appropriate engineering controls

Technical measures and the appliance of appropriate working methods take priority over the use of personal protective equipment.

Safety and necessary control measures vary according to exposure conditions. Appropriate measures are:

Open windows, door, to allow sufficient ventilation. If this is not possible employ a fan to increase air exchange (see attached exposure scenarios).

### Personal protective equipment

#### Eye/face protection

Use safety goggle with side protection.

#### Skin protection

##### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374.

Short-term contact with the skin: Disposable gloves

Long-term contact with the skin: Gloves with long cuffs

Check leak-tightness/impermeability prior to use.

##### • type of material

NBR: acrylonitrile-butadiene rubber, FKM: fluoro-elastomer

##### • material thickness

0,40 mm.

##### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

##### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Wash hands thoroughly after handling.

Body protection:

Suitable protective clothing: Flame resistant clothing

Suitable safety shoes: Anti static safety shoes according to EN 345 S3

### Respiratory protection

For activities in enclosed areas at elevated temperatures of the substance, local extraction or explosion protected ventilation equipment is recommended. In case this is not sufficient for the intended use, then apply a suitable respiratory protection according to EN 140 type A or better (see exposure scenarios).

### Control of environmental exposure

Do not empty into drains.

## Section 10 – Physical and Chemical Properties

### 10.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid
Colour	colourless
Odour	pungent

#### Other physical and chemical parameters

pH (value)	not determined
Melting point/freezing point	-30 °C at 1,013 mbar (ASTM D 97)

Initial boiling point and boiling range	140 – 200 °C at 1,013 mPa (ASTM D 86)
Flash point	>35 °C at 1,013 mbar
Explosive limits	
• lower explosion limit (LEL)	0.7 vol%
• upper explosion limit (UEL)	7 vol%
Vapour pressure	<1 kPa at 20 °C
Density	0.8 – 0.95 g/cm <sup>3</sup> at 25 °C
Solubility(ies)	not determined
Partition coefficient n-octanol/water (log KOW)	This information is not available.
Auto-ignition temperature	400 °C
Viscosity	
• kinematic viscosity	0.7 – 1.7 mm <sup>2</sup> /s at 20 °C (ASTM D 445)
Explosive properties in use, may form flammable/explosive vapour-air mixture	
Oxidising properties	none

## 10.2 Other safety information

Surface tension	28 – 31 mN/m (25 °C) (Wilhelmy Plate)
-----------------	---------------------------------------

## Section 11 – Stability and Reactivity

### 11.1 Reactivity

risk of ignition

#### • if heated

risk of ignition

### 11.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure (see below "Conditions to avoid").

### 11.3 Possibility of hazardous reactions

No known hazardous reactions.

### 11.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Hints to prevent fire or explosion

Use only non-sparking tools.

### 11.5 Incompatible materials

oxidisers

### 11.6 Hazardous decomposition products

No known hazardous decomposition products.

## Section 12 – Toxicological Information

### 12.1 Information on toxicological effects

Classification according to GHS (1272/2008/EC, CLP)

#### Acute toxicity

Shall not be classified as acutely toxic.

Exposure route	Endpoint	Value	Species
dermal	LD50	>3,160 mg/kg	Rabbit
oral	LD50	3,592 mg/kg	Rat

#### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

#### Specific target organ toxicity (STOT)

##### • Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

##### • Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Information on likely routes of exposure

If on skin. If inhaled.

#### Other information

Repeated exposure may cause skin dryness or cracking.

## Section 13 – Ecological Information

### 13.1 Toxicity

#### Aquatic toxicity (acute)

Endpoint	Value	Species	Exposure time
LL50	9.2 mg/l	rainbow trout ( <i>Oncorhynchus mykiss</i> )	48 h
EL50	3.2 mg/l	daphnia magna	72 h
EL50	2.6 mg/l	algae	96 h

#### Aquatic toxicity (chronic)

May cause long-term adverse effects in the aquatic environment.

Endpoint	Value	Species	Exposure time
NOELR	1.23 mg/l	rainbow trout ( <i>Oncorhynchus mykiss</i> )	28 d
NOELR	2.14 mg/l	daphnia magna	21 d

### 13.2 Persistence and degradability

The substance is readily biodegradable.

Process	Degradation Rate	Time
Oxygen depletion	78 %	28 d

### 13.3 Bioaccumulative potential

No data available

### 13.4 Mobility in soil

No data available

### 13.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.



### 13.6 Other adverse effects

No data available

## Section 14 – Disposal Considerations

### 14.1 Waste treatment methods

#### Waste treatment-relevant information

Solvent reclamation/regeneration.

#### Sewage disposal-relevant information

Do not empty into drains.

#### Waste treatment of containers/packagings

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

#### List of wastes

Proposed waste code(s) for the used product:

07 01 04x Other organic solvents, washing liquids and mother liquors

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## Section 15 – Transport Information

15.1 UN number	1268
15.2 UN proper shipping name	PETROLEUM DISTILLATES, N.O.S.
Technical name	SOLVENT NAPHTHA, Hydrocarbons, C9, aromatics
15.3 Transport hazard class(es)	
Class	3 (flammable liquids)
15.4 Packing group	III (substance presenting low danger)
15.5 Environmental hazards	hazardous to the aquatic environment
15.6 Special precautions for user	

Provisions for dangerous goods (ADR) should be complied within the premises.

### 15.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Note that this product is being carried under the scope of MARPOL Annex I .

#### Information for each of the UN Model Regulations

##### • Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number	1268
Proper shipping name	PETROLEUM DISTILLATES, N.O.S.
Class	3
Classification code	F1
Packing group	III
Danger label(s)	3 + "fish and tree"
Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	664
Excepted quantities (EQ)	E1

Limited quantities (LQ) 5 L  
 Transport category (TC) 3  
 Tunnel restriction code (TRC) D/E  
 Hazard identification No 30  
**Emergency Action Code** 3YE  
**• International Maritime Dangerous Goods Code (IMDG)**  
 Not subject to IMDG.  
 UN number 1268  
 Proper shipping name PETROLEUM DISTILLATES, N.O.S.  
 Class 3  
 Marine pollutant yes (hazardous to the aquatic environment)  
 Packing group III  
 Danger label(s) 3 + "fish and tree"  
 Special provisions (SP) 223, 955  
 Excepted quantities (EQ) E1  
 Limited quantities (LQ) 5 L  
 EmS F-E, S-E  
 Stowage category A

**• International Civil Aviation Organization (ICAO-IATA/DGR)**

UN number 1268  
 Proper shipping name Petroleum distillates, n.o.s.  
 Class 3  
 Environmental hazards yes (hazardous to the aquatic environment)  
 Packing group III  
 Danger label(s) 3

## Section 16 – Regulatory Information

This safety datasheet complies with the requirements of Regulation (EC) No. 453/2010.

### 16.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**• Restrictions according to REACH, Annex XVII**

Name of substance	CAS No	Wt%	Type of registration	No
Hydrocarbons, C9, aromatics		100	1907/2006/EC annex XVII	3
Hydrocarbons, C9, aromatics		100	1907/2006/EC annex XVII	40

**• List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list**  
 not listed

**• 2012/18/EU (Seveso III)**

NO	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements		Notes
E2	environmental hazards (hazardous to the aquatic environment, cat. 2)	200	500	57)

**Notation**

57) Hazardous to the Aquatic Environment in category Chronic 2

**• Limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products (2004/42/EC, Deco-Paint Directive)**

VOC content 100 %

**• Directive on industrial emissions (VOCs, 2010/75/EU)**

VOC content 100 %

• **Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II**

not listed

• **Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)**

not listed

• **Directive 2000/60/EC establishing a framework for Community action in the field of water policy (WFD)**

not listed

#### National inventories

Country	Inventory	Status
AU	AICS	Substance is listed
CA	DSL	Substance is listed
CA	NDSL	Not listed
CN	IECSC	Substance is listed
EU	ECSI	Substance is listed
EU	REACH Reg.	Substance is listed
JP	CSCL-ENCS	Substance is listed
JP	ISHA-ENCS	Substance is listed
KR	KECI	Substance is listed
MX	INSQ	Substance is listed
NZ	NZIoC	Substance is listed
PH	PICCS	Substance is listed
TR	CICR	Substance is listed
TW	TCSI	Substance is listed
US	TSCA	Substance is listed

#### Legend

AICS	Australian Inventory of Chemical Substances.
CICR	Chemical Inventory and Control Regulation.
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS).
DSL	Domestic Substances List (DSL).
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP).
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China.
INSQ	National Inventory of Chemical Substances.
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS).
KECI	Korea Existing Chemicals Inventory.
NDSL	Non-domestic Substances List (NDSL).
NZIoC	New Zealand Inventory of Chemicals.
PICCS	Philippine Inventory of Chemicals and Chemical Substances.
REACH Reg.	REACH registered substances.
TCSI	Taiwan Chemical Substance Inventory.
TSCA	Toxic Substance Control Act

#### 16.2 Chemical Safety Assessment

For this product a chemical safety assessment has been carried out

## Section 17 : Additional Information

### 17.1 Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)
16.1		16.1 National Inventories: change in the listing (table)

#### Abbreviations and acronyms

Abbr	Descriptions of used abbreviations
AND	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
AGW	Workplace exposure limit
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
Index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Reach	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concern-ing the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
SVHC	Substance of Very High Concern
TRGS 900	Arbeitsplatzgrenzwerte (TRGS 900)
TWA	Time-weighted average
VOC	Volatile Organic Compounds

vPvB	Very Persistent and very Bioaccumulative
------	--

**Key literature references and sources for data**

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN).

International Maritime Dangerous Goods Code (IMDG).

International Air Transport Association (IATA).

**List of relevant phrases (code and full text as stated in chapter 3 and 4)**

Code	Text
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product. The information concerning legal regulations can lay no claim to completeness. In addition to this, other provisions may also apply to the product.