

Bounded Model Checking of C++ Programs Based on the Qt Cross-Platform Framework (Journal-First Abstract)

Felipe R. Monteiro*

Federal University of Amazonas
Manaus, Amazonas, Brazil

Lucas C. Cordeiro
University of Manchester
United Kingdom

Mário A. P. Garcia

Federal University of Amazonas
Manaus, Amazonas, Brazil

Eddie B. de Lima Filho
TPV Technology Ltd.
Manaus, Amazonas, Brazil

ABSTRACT

This work proposes an abstraction of the Qt framework, named as Qt Operational Model (QtOM), which is integrated into two different verification approaches: explicit-state model checking and symbolic (bounded) model checking. The proposed methodology is the first one to formally verify Qt-based applications, which has the potential to devise new directions for software verification of portable code. The full version of this paper is published in *Software Testing, Verification and Reliability*, on 02 March 2017 and it is available at <https://doi.org/10.1002/stvr.1632>.

CCS CONCEPTS

• **General and reference** → **Verification**; • **Software and its engineering** → **Model checking**; *Software verification*; Formal software verification;

KEYWORDS

Software Engineering, Qt Framework, Model Checking, Formal Verification, Verification in Industrial Practice

ACM Reference Format:

Felipe R. Monteiro, Mário A. P. Garcia, Lucas C. Cordeiro, and Eddie B. de Lima Filho. 2018. Bounded Model Checking of C++ Programs Based on the Qt Cross-Platform Framework (Journal-First Abstract). In *Proceedings of the 2018 33rd ACM/IEEE International Conference on Automated Software Engineering (ASE '18)*, September 3–7, 2018, Montpellier, France. ACM, New York, NY, USA, 1 page. <https://doi.org/10.1145/3238147.3241981>

1 OVERVIEW

Technology companies, such as AMD, Intel and Amazon, increasingly invest effort and time to develop fast and cheap verification alternatives, in order to check for correctness in their systems and then reduce product recall rates. Among such alternatives, one of the most promising is the model checking approach; however, despite its advantages, there are many systems that could not be automatically verified, due to the restricted support of formal verifiers.

*Corresponding author felipemonteiro@ufam.edu.br

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

ASE '18, September 3–7, 2018, Montpellier, France

© 2018 Copyright held by the owner/author(s).

ACM ISBN 978-1-4503-5937-5/18/09.

<https://doi.org/10.1145/3238147.3241981>

To tackle this problem, Monteiro *et al.* [4] propose a simplified version of the Qt framework, which is integrated into a model checker based on satisfiability modulo theories (SMT), known as the Efficient SMT-based Context-Bounded Model Checker (ESBMC) [2, 5], in order to verify actual Qt-based applications. Importantly, such an approach resulted in a success rate of 89% based on the developed benchmark test suite. Furthermore, the simplified version of the Qt framework, named as Qt Operational Model (QtOM), was also evaluated using other state-of-the-art verifiers for C++ programs. In fact, QtOM was combined with two different verification approaches during the experimental evaluation, i.e., explicit-state model checking and symbolic (bounded) model checking, which highlights its flexibility.

Contributions. Monteiro *et al.* [4] extend a previous published work by Garcia *et al.* [1] and Monteiro *et al.* [3]. QtOM was expanded, in order to include new features from the main Qt modules: QtGUI and QtCore. Indeed, the main contributions here are (i) the support for sequential and associative template-based containers, (ii) the integration of QtOM into the verification process of the state-of-the-art C++ verifiers DIVINE and LLBMC, and (iii) the verification of two Qt-based applications known as *Locomaps* and *GeoMessage*. Furthermore, the employed benchmark suite was extensively revised and expanded, now 13 times bigger than the previous work, and the performance of three SMT solvers (i.e., Z3, Yices, and Boolector) was evaluated, along with the proposed approach.

Availability of Data and Tools. The performed experiments are based on a set of publicly available benchmarks. All benchmarks, tools, and results, associated with the current evaluation, are available at <http://esbmc.org/qtom>.

REFERENCES

- [1] Garcia M. A. P., Monteiro F. R., Cordeiro L. C., and de Lima Filho E. B. 2016. *ESBMC^{QtOM}: A Bounded Model Checking Tool to Verify Qt Applications*. Springer International Publishing, Cham, Chapter 10, 97–103.
- [2] Gadelha M. R., Monteiro F. R., Morse J., Cordeiro L. C., Fischer B., and Nicole D. A. 2018. ESBMC 5.0: An Industrial-Strength C Model Checker. In *33rd ACM/IEEE Int. Conf. on Automated Software Engineering (ASE '18)*. ACM, New York, NY, USA.
- [3] Monteiro F. R., Cordeiro L. C., and de Lima Filho E. B. 2015. Bounded Model Checking of C++ Programs Based on the Qt Framework. In *4th Global Conference on Consumer Electronics*. IEEE, Osaka, Japan.
- [4] Monteiro F. R., Garcia M. A. P., Cordeiro L. C., and de Lima Filho E. B. 2017. Bounded Model Checking of C++ Programs based on the Qt Cross-Platform Framework. *Software Testing, Verification and Reliability* 27, 3 (2017), e1632.
- [5] M. Ramalho, M. Freitas, F. Sousa, H. Marques, L. Cordeiro, and B. Fischer. 2013. SMT-Based Bounded Model Checking of C++ Programs. In *Proceedings of the 20th Annual IEEE Int. Conference and Workshops on the Engineering of Computer Based Systems (ECBS'13)*. IEEE Computer Society, Washington, DC, USA, 147–156.