Comparing GPUs and TPUs on Google Colab

COSC 6385 — Computer Architecture — Experiment A

ChengAo Shen

November 2026

1. Environment

Every run records its own accelerator, `jax.devices()`, library versions and the Colab image tag (the first code cell prints all of these; the raw strings are in the CSVs under `results/`). Three accelerators were used:

Role	Accelerator	`jax.devices()`	Backend / key libs	Python	Image
TPU (required)	**TPU v5e-1** (`TPU v5 lite`, 1 chip, 16 GB HBM)	`[TpuDevice(0)]`, `device_count()==1`	JAX 0.11.2 + XLA, Flax 0.10.6, Keras 3.15.1, KerasHub 0.33.0	3.13.18	RC00 (Nov 6)
GPU (required)	**NVIDIA Tesla T4** (Turing, 15 GB)	`[CudaDevice(0)]`	JAX 0.11.1 + XLA (CUDA), Flax 0.10.6	3.13.16	same
GPU (Part 3 substitute)	**NVIDIA RTX 5070 Ti** (Blackwell `sm_120`, 16 GB), *local*	`torch.cuda` device 0	**Keras 3.15.1 + KerasHub 0.33.0 on the PyTorch 2.11.0+cu128 backend**	3.12.15	local

`jax.device_count()` returns **1** on the TPU — expected, because a Colab TPU is a single v5e chip (not the 8-core pods older tutorials assume).

Why a third machine for Part 3. The assignment's required GPU is the Colab T4, and the T4 completes Parts 1 and 2 fine. For Part 3 (Gemma 3 1B LoRA) the T4 *loads* the model but then **crashes the kernel with a native fault** (not a Python exception, so it cannot be caught) the moment KerasHub runs `generate()` or `fit()` on the JAX-CUDA path; reducing the sequence length to 128 did not help, and an L4 behaved the same way (see §3). To still produce a real GPU-vs-TPU *training* comparison, Part 3's GPU side was reproduced on a local **RTX 5070 Ti** using the **same Keras 3 / KerasHub model and the identical LoRA configuration**, on the PyTorch backend (which is stable on Blackwell). KerasHub and Keras are the *same versions* as the TPU run, so only the compiler backend (XLA vs. `torch`) and the hardware differ — exactly the axes this experiment is about.

2. Method

What is measured. Each part separates **XLA/compiler compilation** (the first call / first epoch) from **steady-state execution**, because the first call takes seconds purely for compilation and must never be counted as throughput.

- *Part 1 (matmul).* For every `n ∈ {1024, 2048, 4096, 8192}` and each precision mode, the first call is timed separately (compilation) and then the kernel is run repeatedly with `block_until_ready()` after each call so asynchronous dispatch cannot hide latency. We report the **median** wall time over the repeats (robust to the occasional scheduling outlier, unlike the mean) and convert to TFLOP/s via `2·n³ / t`.
- *Part 2 (CNN).* A three-block CNN (Flax NNX) trains on CIFAR-10 for 5 epochs. We record compile time (first step), **steady-state epoch and step time**, images/s, and test accuracy, for the cross product of precision {fp32, bf16} × batch {128, 512}. Training data lives on the accelerator and batches are gathered inside the compiled step, so the number isolates the accelerator from Colab's host input pipeline.
- *Part 3 (Gemma LoRA).* `Gemma3CausalLM.from_preset("gemma3_1b")`, LoRA rank 4, sequence length 256, batch 1, 3 epochs on ~400 context-free Databricks-Dolly instructions. We time **each epoch** (a Keras callback), drop epoch 0 (compilation) and report the **median of the steady epochs**, plus peak device memory and sample generations before/after fine-tuning. The same value of every hyper-parameter is used on both devices.

Changes from the defaults (all forced by the current Colab image; see §3): pinned `flax==0.10.6`; re-added `jax.core.get_opaque_trace_state`; a TensorFlow-free CIFAR-10 loader; and, for the model download, `DISABLE_COLAB_CACHE=1` so KerasHub fetches Gemma directly from Kaggle instead of the (unauthenticated, 403-ing) Colab mount proxy. For the Part-3 GPU run, data is passed to `fit()` as the dict `{"prompts": [...], "responses": [...]}` that `Gemma3CausalLMPreprocessor` requires, and the GPU step is compiled (`jit_compile=True`) in `mixed_bfloat16` so the GPU is compared to the TPU on an equally **compiled, bf16** footing.

3. Problems encountered and how they were fixed

#	Symptom (verbatim where useful)	Cause	Fix
1	`ImportError: cannot import name 'mutable_array' from 'jax._src.core' on import flax`	Image ships a Flax too new for its JAX	`pip install --no-deps flax==0.10.6` (protects `jax/jaxlib/libtpu`)
2	`AttributeError: jax.core.get_opaque_trace_state removed in JAX v0.11.0 during NNX init`	Flax NNX calls an API JAX 0.11 removed	shim `jax.core.get_opaque_trace_state = jax.extend.core.get_opaque_trace`
3	`ModuleNotFoundError: tensorflow from keras.datasets.cifar10`	`keras.datasets` needs TF, absent on the image	custom loader: download `cifar-10-python.tar.gz`, unpickle with NumPy
4	Gemma download → `403 Forbidden … /kaggle-hub/models/mount` *although Kaggle shows the licence accepted*	KerasHub used Colab's **mount proxy**, which did not carry our `KAGGLE_API_TOKEN`	set `DISABLE_COLAB_CACHE=1` → direct authenticated download from kaggle.com

#	Symptom (verbatim where useful)	Cause	Fix
5	`TypeError: … got 'prompts' in Gemma3CausalLMPreprocessor.call() on fit()`	Gemma 3 wants a **dict** of prompts/responses, not Gemma-1/2's flat string list	build `data = {"prompts":[…], "responses":[…]}`
6	Chrome blocked the 2nd `files.download()`	browser multi-download guard	read the CSVs straight from `/content` instead of relying on the download
7	**T4 (and L4) kernel crashes** — *"session crashed for an unknown reason"*, native `@0x… (unknown)` trace — right at `generate()`/`fit()` on Gemma 3	the JAX-CUDA path natively faults on this 1 B model/image combo; `seqlen 128` did not help; the model *loads* fine, so it is not a simple capacity OOM	documented as a result; Part 3's GPU number reproduced on a local **RTX 5070 Ti** with the identical Keras/KerasHub model on the **PyTorch** backend

4. Results

Part 1 — Matrix-multiply microbenchmark

Achieved TFLOP/s (and % of the device's precision peak) for `n × n` matmul:

n	TPU bf16	TPU fp32-default	TPU fp32-highest	T4 fp32-default	T4 bf16
1024	9.4 (4.8%)	10.9	6.4	3.8 (47%)	2.5 (3.8%)
2048	58.3 (29.6%)	57.3	21.5	4.9 (60%)	5.0 (7.6%)
4096	138.9 (70.5%)	145.0	28.8	4.6 (56%)	4.7 (7.2%)
8192	**177.7 (90.2%)**	155.1	31.0	4.4 (54%)	4.4 (6.7%)

- The **TPU in bf16 scales to 177.7 TFLOP/s at n = 8192 — 90 % of its ~197 TFLOP/s peak**, and needs a large matrix to get there (only 4.8 % of peak at n = 1024): small matmuls are launch/overhead-bound, large ones saturate the MXU.
- `fp32-default` on the TPU is fast because XLA runs it as a **single bf16 pass** on the MXU (≈ the bf16 curve); `fp32-highest` forces true fp32 (3 bf16 passes) and collapses to ~31 TFLOP/s — a textbook precision/throughput trade.
- The **T4 never clears ~5 TFLOP/s** in any mode. It has **no native bfloat16**, so bf16 is emulated and lands *at fp32 speed* while scoring a tiny "% of (FP16 tensor) peak". Here the TPU's bf16 matmul is **~40× the T4's**.

Part 2 — CNN training on CIFAR-10

5-epoch three-block CNN; steady-state numbers (epoch 0 = compile is excluded):




Figure 1: Part 1 — matmul throughput vs. size

Device	dtype	batch	epoch (s)	step (ms)	images/s	test acc
TPU v5e-1	fp32	128	1.55	3.97	32,280	0.733
TPU v5e-1	bf16	128	1.55	3.96	32,288	0.739
TPU v5e-1	fp32	512	0.54	5.55	92,332	0.668
TPU v5e-1	**bf16**	**512**	**0.45**	4.65	**110,087**	0.666
Tesla T4	fp32	128	1.18	3.03	**42,206**	0.734
Tesla T4	bf16	128	1.16	2.98	**42,895**	0.740
Tesla T4	fp32	512	1.08	11.18	45,810	0.669
Tesla T4	bf16	512	1.14	11.72	43,700	0.667




Figure 2: Part 2 — CNN throughput, bf16

- **At batch 128 the T4 is faster than the TPU** (≈ 43k vs 32k img/s). The CNN is tiny; at

Device	Stack	epoch (s)	peak mem (MB)	epoch times (s)
TPU v5e-1	JAX + XLA (compiled)	**6.14**	6,420	[27.5, 6.1, 6.1]
RTX 5070 Ti	PyTorch + `jit_compile` + bf16	**43.3**	6,553	[165.7, 43.1, 43.5]
RTX 5070 Ti	PyTorch **eager** (no compile)	210.0	6,269	[215.7, 210.5, 209.5]




Figure 3: Part 3 — Gemma 3 1B LoRA, time per epoch (log scale)

Peak memory is ~6.4–6.6 GB on both devices (same 1 B model, same config), so the story is entirely in **time**, not memory. Compilation dominates: on the GPU alone, **eager → compiled is a 4.9× speed-up** (210 → 43 s). LoRA worked (trainable params drop to 652 k / 2.49 MB of the 1 B); loss fell 0.651 → 0.629, and the before/after generations match between the two machines (same base weights), e.g.:

> **Before:** "A TPU is a thermoplastic polyurethane." (then repeats unrelated Q&A)
> **After:** "A TPU is a type of memory that is used in smartphones and tablets…"

The after-tuning answers are shorter and follow the Instruction/Response template better (the point of the run is *training cost*, not answer quality for a 1 B base model given ~40 s of tuning). Full transcripts are in `results/gemma_samples_*.txt`.

5. Analysis

Is the Part-3 speed gap similar to the Part-2 CNN gap? No — it is *much wider*, and for an instructive reason. Relating to Wang, Wei & Brooks (2019) and the **roofline / arithmetic-intensity** framing:

- The **CNN at small batch** sits on the roofline's *memory/latency-bound* side (low arithmetic intensity), so the big systolic MXU gives the TPU no advantage — the T4 even wins.

Raising the batch to 512 moves the CNN toward the *compute-bound* side and the TPU's peak FLOPs finally matter (110k vs 44k img/s).

- The **1 B transformer LoRA** is dominated by **large, high-intensity matmuls** — exactly the regime where Part 1 showed the TPU hitting 90 % of a ~197 TFLOP/s peak while the T4-class GPU is stuck near a few TFLOP/s and must emulate bf16. So on raw compute the TPU *should* dominate, and it does (6.1 vs 43 s/epoch). Two extra factors widen it: **(a) batch = 1 is latency-bound on the GPU** — one short sequence per step cannot fill the SMs, whereas XLA fuses the TPU step so launch overhead is amortised; **(b) compiler maturity** — JAX/XLA fully fuses the training step, while `torch.compile` on the KerasHub graph still takes graph breaks (dynamo warnings in the log), leaving the GPU partly eager. The eager-vs- compiled 4.9× on one GPU is the clearest single illustration of this.

Where the 2019 paper still holds: its central thesis — that the right accelerator depends on the *operator mix and batch size*, read off the roofline, not on a single "peak FLOPs" number — is exactly what Parts 2 and 3 reproduce seven years later. A small/low-intensity workload neutralises the TPU; a large, matmul-heavy, well-batched one lets it win by an order of magnitude.

Where newer hardware changes the picture: (1) **Precision is now first-class.** In 2019, bf16 was a TPU specialty; today bf16 is the default fast path on the TPU *and* on L4/A100/H100/Blackwell GPUs, so the "TPU-only low precision" assumption is gone — except on the **Turing T4**, which predates native bf16 and therefore shows *no* bf16 speed-up (a clean 2019-era artifact still visible in Parts 1–2). (2) **Software maturity is now a hardware-level variable.** The required T4 could not even run the modern KerasHub/JAX Gemma 3 path without crashing, while the TPU ran it cleanly — the "which accelerator is faster" question has partly become "which accelerator's compiler + library stack is mature for this model," a dimension the 2019 FLOPs-and-roofline analysis did not have to consider.

Reproducibility: Parts 1–2 use `notebooks/colab_gpu_tpu_benchmark_FIXED.ipynb`; Part 3 (TPU/T4) uses `notebooks/gemma3_lora_finetune.ipynb`; the Part-3 GPU number uses `notebooks/run_gpu_local.py` (Keras 3 + PyTorch, one command on any CUDA GPU). All raw CSVs and sample transcripts are in `results/`.