

NETWORK SECURITY

Cryptography

- Introduction to Cryptography
- Ciphers
- One-Time Pads
- Two Fundamental Cryptographic Principles


Need for Security

- Some people who cause security problems and why.

Adversary	Goal
Student	To have fun snooping on people's e-mail
Cracker	To test out someone's security system; steal data
Sales rep	To claim to represent all of Europe, not just Andorra
Businessman	To discover a competitor's strategic marketing plan
Ex-employee	To get revenge for being fired
Accountant	To embezzle money from a company
Stockbroker	To deny a promise made to a customer by e-mail
Con man	To steal credit card numbers for sale
Spy	To learn an enemy's military or industrial secrets
Terrorist	To steal germ warfare secrets


An Introduction to Cryptography

□ The encryption model (for a symmetric-key cipher).



Ciphers

- Caesar's Cipher.



One-Time Pads

Message 1: 1001001 0100000 1101100 1101111 1110110 1100101 0100000 1111001 1101111 1110101 0101110

Pad 1: 1010010 1001011 1110010 1010101 1010010 1100011 0001011 0101010 1010111 1100110 0101011


Ciphertext: 0011011 1101011 0011110 0111010 0100100 0000110 0101011 1010011 0111000 0010011 0000101

Pad 2: 1011110 0000111 1101000 1010011 1010111 0100110 1000111 0111010 1001110 1110110 1110110


Plaintext 2: 1000101 1101100 1110110 1101001 1110011 0100000 1101100 1101001 1110110 1100101 1110011

Types of Cryptography

- Symmetric



- Asymmetric



Symmetric-Key Algorithms

- DES – The Data Encryption Standard
- AES – The Advanced Encryption Standard
- Cipher Modes
- Other Ciphers
- Cryptanalysis


Product Ciphers

□ Basic elements of product ciphers.


(a) P-box.

(b) S-box.


(c) Product.



(a)





(b)



(c)

Triple DES

- (a) Triple encryption using DES. (b) Decryption.



AES – The Advanced Encryption Standard

- Rules for AES proposals

1. The algorithm must be a symmetric block cipher.
2. The full design must be public.
3. Key lengths of 128, 192, and 256 bits supported.
4. Both software and hardware implementations required
5. The algorithm must be public or licensed on nondiscriminatory terms.

Cryptanalysis

- Some common symmetric-key cryptographic algorithms.


Cipher	Author	Key length	Comments
Blowfish	Bruce Schneier	1–448 bits	Old and slow
DES	IBM	56 bits	Too weak to use now
IDEA	Massey and Xuejia	128 bits	Good, but patented
RC4	Ronald Rivest	1–2048 bits	Caution: some keys are weak
RC5	Ronald Rivest	128–256 bits	Good, but patented
Rijndael	Daemen and Rijmen	128–256 bits	Best choice
Serpent	Anderson, Biham, Knudsen	128–256 bits	Very strong
Triple DES	IBM	168 bits	Second best choice
Twofish	Bruce Schneier	128–256 bits	Very strong; widely used

Public-Key Algorithms



RSA

Rivest Shamir Adleman Algorithm



RSA Example

- $P = 61$ <= first prime number (destroy this after computing E and D)
- $Q = 53$ <= second prime number (destroy this after computing E and D)
- $PQ = 3233$ <= modulus (give this to others)
- $E = 17$ <= public exponent (give this to others)
- $D = 2753$ <= private exponent (keep this secret!)
- Your public key is (E, PQ) .
- Your private key is D .

RSA Encryption

- The encryption function is:

$$\begin{aligned}\text{encrypt}(T) &= (T^E) \bmod PQ \\ &= (T^{17}) \bmod 3233\end{aligned}$$

$$\text{Encrypt}(123) = (123^{17}) \bmod 3233$$

$$\begin{aligned}&= 337587917446653715596592958817679803 \\&\bmod 3233\end{aligned}$$

$$= 855$$

RSA Decryption

- The decryption function is:

$$\begin{aligned}\text{decrypt}(C) &= (C^D) \bmod P \\ &= (C^{2753}) \bmod 3233\end{aligned}$$

$$\begin{aligned}\text{Decrypt}(855) &= (855^{2753}) \bmod 3233 \\ &= 123\end{aligned}$$


Digital Signatures



- Symmetric-Key Signatures
- Public-Key Signatures
- Message Digests

Public-Key Signatures

- Digital signatures using public-key cryptography.




Hashing

- MD5 Message Digest 5
- SHA1 – Secure Hashing Algorithm 160bit




SHA-1

- Use of SHA-1 and RSA for signing nonsecret messages.



SHA-1 (2)

- (a) A message padded out to a multiple of 512 bits.
- (b) The output variables. (c) The word array.




Management of Public Keys



- Certificates
- X.509
- Public Key Infrastructures

Problems with Public-Key Encryption

- A way for Trudy to subvert public-key encryption.



Certificates

- A possible certificate and its signed hash.

I hereby certify that the public key

19836A8B03030CF83737E3837837FC3s87092827262643FFA82710382828282A
belongs to

Robert John Smith

12345 University Avenue

Berkeley, CA 94702

Birthday: July 4, 1958

Email: bob@superduper.net.com

SHA-1 hash of the above certificate signed with the CA's private key


X.509

□ The basic fields of an X.509 certificate.

Field	Meaning
Version	Which version of X.509
Serial number	This number plus the CA's name uniquely identifies the certificate
Signature algorithm	The algorithm used to sign the certificate
Issuer	X.500 name of the CA
Validity period	The starting and ending times of the validity period
Subject name	The entity whose key is being certified
Public key	The subject's public key and the ID of the algorithm using it
Issuer ID	An optional ID uniquely identifying the certificate's issuer
Subject ID	An optional ID uniquely identifying the certificate's subject
Extensions	Many extensions have been defined
Signature	The certificate's signature (signed by the CA's private key)

Public-Key Infrastructures

- (a) A hierarchical PKI. (b) A chain of certificates.




Communication Security

- IPsec
- Firewalls
- Virtual Private Networks
- Web Security


IPsec

- The IPsec authentication header in transport mode for IPv4.





Firewalls

- A firewall consisting of two packet filters and an application gateway.



Virtual Private Networks

- (a) A leased-line private network.
- (b) A virtual private network.



Web Security

- Threats
- Secure Naming
- SSL – The Secure Sockets Layer
- Mobile Code Security

Secure DNS

Domain name	Time to live	Class	Type	Value
bob.com.	86400	IN	A	36.1.2.3
bob.com.	86400	IN	KEY	3682793A7B73F731029CE2737D...
bob.com.	86400	IN	SIG	86947503A8B848F5272E53930C...

An example RRSet for *bob.com*. The *KEY* record is Bob's public key. The *SIG* record is the top-level *com* server's signed hash of the *A* and *KEY* records to verify their authenticity.

Self-Certifying Names

http://www.bob.com:2g5hd8bfjkc7mf6hg8dgany23xds4pe6/photos/bob.jpg

Server	SHA-1 (Server, Server's Public key)	File name
--------	-------------------------------------	-----------

- A self-certifying URL containing a hash of server's name and public key.

SSL—The Secure Sockets Layer

- Layers (and protocols) for a home user browsing with SSL.

Application (HTTP)
Security (SSL)
Transport (TCP)
Network (IP)
Data link (PPP)
Physical (modem, ADSL, cable TV)

Steganography



- (a) Three zebras and a tree. (b) Three zebras, a tree, and the complete text of five plays by William Shakespeare.