Reddit 内容建议及范例

写作原则

1. 先写具体问题，再写背景。
2. 给出规模、延迟、成本、更新频率、过滤条件或运维限制。
3. 明确区分已观察到的结果、来源支持的事实和仍待验证的判断。
4. 写出失败条件与取舍，不把单次测试包装成普遍结论。
5. 开放问题自然存在时保留；不为了格式强行增加。

真实的短 Discussion 或 Resource Request 使用 short_post；普通技术帖使用 standard_post。短帖不需要为了达到 standard 长度而填充，但仍要有足够背景。

R1/R2 保持匿名，Disclosure 为空。I built 可以使用，但必须有来源支持，且 不得附带身份、雇主、贡献者/维护者角色或 affiliation。标题不得出现 Milvus； 正文最多可出现一次 Milvus，并填写 milvus_mention_basis。

R1 和 R2 都不带链接。标题、正文和任何链接字段都不得出现 URL。

范例 1：RAG Discussion

Title

When does one-hop expansion stop being enough for multi-hop retrieval?

Body

I built a retrieval flow that starts with semantic search, expands one hop through stored entity relationships, reranks the candidates, and then calls the generator. The fixed query path is easier to debug than an agent that decides repeatedly whether to retrieve again.

The weak point is relationship maintenance. Entity deduplication, updates, and high-degree nodes can become more expensive than the query itself. The design still feels reasonable for bounded two-to-four-hop questions, but I am less confident when relationships change frequently or users need exploratory graph queries.

For teams that have tried a similar design, what was the point where a dedicated graph layer became simpler than maintaining references inside the retrieval store?

范例 2：AI Agents Discussion

Title

What belongs in an agent harness instead of the prompt?

Body

Long-running agent failures often look less like prompt failures and more like environment failures: stale documentation, weak validation, missing runtime evidence, or no clear stopping condition.

My current approach is to keep the top-level instructions small, move enforceable rules into tests and linters, and give the agent direct access to logs and browser state. A separate evaluator can help with subjective quality, but it also adds cost and another component that can be wrong.

For longer agent tasks, which improvement changed reliability most in practice: better documentation, stronger runtime checks, richer tools, or a separate evaluator?

范例 3：Vector Database Operations

Title

Should segment count be a first-class production metric?

Body

A compaction test made me rethink how much query cost can come from index fan-out. Merging several sealed segments into one reduced the number of indexes searched per query and improved latency, but the merge also required index rebuild work, memory, and I/O.

That makes aggressive compaction a poor default for collections with steady writes and deletes. A more useful policy may combine segment count, size distribution, time since the last meaningful write, and observed query latency.

Do teams usually trigger compaction from thresholds, schedule it for quiet windows, or require manual approval after checking current write load?

范例 4：LocalLLaMA Question | Help

Title

How do you tell whether a local RAG miss is retrieval or context pressure?

Body

A local RAG answer can fail even when the relevant passage exists in the source. The retriever may have missed it, the chunk may be too broad, or the prompt may be packing enough surrounding text that the useful evidence gets diluted.

I would log the retrieved chunk IDs and scores first, then rerun the same question with the known-good passage inserted directly. If the answer still fails, the next variables are context length, prompt structure, and model choice rather than the index. The harder case is when the answer improves only after removing other retrieved chunks.

What is the smallest diagnostic sequence you use to separate retrieval failure from context-window or model-quality failure on a local setup?

使用提醒

这些范例只展示结构和语气，不能直接当作已验证事实发布。实际草稿必须以来源 为依据，并通过账号、Subreddit、Post Type、匿名、链接和内容校验。