

Stochastic Modeling and Simulations of Car-Following Behaviors

Chengyuan Zhang

Ph.D. Candidate (advised by Prof. Lijun Sun)

Department of Civil Engineering

McGill University

enzocy@gmail.com

Feb. 06, 2025

JTL Research Seminar @ MIT (online)




McGill

About me

- Smart Transportation Lab at McGill University
- Homepage: <https://chengyuan-zhang.github.io/>
- My research focuses on **Bayesian learning, spatiotemporal modeling, traffic flow theory, and multi-agent interaction modeling** within intelligent transportation systems. I aim to bridge the gap between theoretical modeling and practical traffic simulation using advanced statistical techniques. Driven by a passion for understanding human driving behavior, my work seeks to enhance microscopic traffic simulations, ultimately contributing to safer and more efficient transportation systems.


Motivation / background

- How would the vehicle react in response to the leading vehicle?



Motivation / background

- How would the vehicle react in response to the leading vehicle?



- What do we need for simulations?

Motivation / background

- The goal of traffic simulations:
 - **Past** : reproduce traffic phenomenon
 - **Future** : support the development and test of control algorithms
 - Connected and Automated Vehicle
 - Reinforcement learning for traffic control/management
 - Human drivers still involved
 - Safety, predictability, and uncertainty



(How well are the blue cars performing in this simulator?)

Motivation / background

- The goal of traffic simulations:
 - **Past** : reproduce traffic phenomenon
 - **Future** : support the development and test of control algorithms
 - Connected and Automated Vehicle
 - Reinforcement learning for traffic control/management
 - Human drivers still involved
 - Safety, predictability, and uncertainty
- How do we introduce randomness?
 - × Deterministic car-following models
 - ✓ **Probabilistic car-following models with uncertainty quantification**


In this work, we are interested in:

- **How do we model the human-driver car-following behaviors?**
- **How do we simulate human-like car-following behaviors?**

Outline

- Intelligent Driver Model (IDM, as an example)
- Probabilistic Modeling Framework
 - Mean model (IDM/NN) + stochastic processes (GP/AR)
- Stochastic Simulation
- Discussions

Intelligent driver model




- **Intelligent Driver Model (IDM)** (Treiber et al. 2000)

$$a_{\text{IDM}} = \alpha \left(\overset{\text{free-flow}}{\boxed{1 - \left(\frac{v}{v_0}\right)^\delta}} - \overset{\text{interaction}}{\boxed{\left(\frac{s^*(v, \Delta v)}{s}\right)^2}} \right)$$

$$s^*(v, \Delta v) = s_0 + s_1 \sqrt{\frac{v}{v_0}} + vT + \frac{v \Delta v}{2 \sqrt{\alpha \beta}}$$

- v_0 : desired speed;
- s_0 : jam spacing;
- T : time headway;
- α : maximum acceleration;
- β : comfortable deceleration rate.


Intelligent driver model




- Gaussian IDM assumes: $a^{(t)} \approx a_{\text{IDM}}^{(t)}$. \Rightarrow Likelihood: $\mathcal{N}(\hat{a}^{(t)} | a_{\text{IDM}}^{(t)}, \sigma_\epsilon^2)$
- Calibration by MLE: $\max_{\theta} \prod_{t=1}^T \text{likelihood}$ and $\theta = [v_0, s_0, T, \alpha, \beta]$
- Loss function in literature ([Punzo et al. 2021](#)):

$$\min_{\theta} \frac{1}{T} \sum_{t=1}^T (a_{\text{IDM}}^{(t)} - \hat{a}^{(t)})^2 + \frac{\alpha}{T} \sum_{t=1}^T (v_{\text{IDM}}^{(t)} - \hat{v}^{(t)})^2 + \frac{\beta}{T} \sum_{t=1}^T (x_{\text{IDM}}^{(t)} - \hat{x}^{(t)})^2$$


Intelligent driver model




- IDM assumes: $a^{(t)} \approx a_{\text{IDM}}^{(t)}$. Let's visualize the residuals $a^{(t)} - a_{\text{IDM}}^{(t)}$.



**IDM captures much information,
but *some are still left in the residuals!***




The general form of car-following models



- For a human-driver CF model, what do we miss?
 - **Temporally correlated errors / Time delay** (e.g., Wiener process)
 - IDM as a **parsimonious** model can hardly explain all the variation in the data; as a result, the residual terms are **serially correlated**;
 - ...

- Therefore, we assume $a(x, t) \approx \underbrace{f_{\text{CFM}}(x; \theta)}_{\text{mean car-following model}} + \underbrace{\delta(t)}_{\text{temporal correlations}} \quad !!! \quad (\text{Zhang et al. 2025})$

The general form of car-following models



- **We assume:** $a(x, t) \approx \boxed{f_{\text{CFM}}(x; \theta)} + \boxed{\delta(t)}$ (Zhang et al. 2025)
- **IDM assumes:** $a(x, t) \approx \boxed{a_{\text{IDM}}(x; \theta)}$. (Treiber et al. 2000)

Missed the temporal part $\boxed{\delta(t)}$

TO-DO:

- Consider $\delta(t)$ in modeling;
- Model $\delta(t+1)|\delta(t)$ in simulation.

Memory-Augmented IDM (MA-IDM) (Zhang and Sun 2024)

How to model $\delta(t)$ and $\delta(t+1)|\delta(t)$?

- We assume:**

$$a(x, t) = f_{\text{CFM}}(x; \theta) + \delta(t) + \epsilon, \quad \epsilon \stackrel{i.i.d.}{\sim} \mathcal{N}(0, \sigma_{\epsilon}^2)$$

- IDM assumes:**

$$a^{(t)} = a_{\text{IDM}}^{(t)} + \epsilon_t, \quad \epsilon_t \stackrel{i.i.d.}{\sim} \mathcal{N}(0, \sigma_{\epsilon}^2) \Rightarrow a|i, \theta \sim \mathcal{N}(a_{\text{IDM}}, \sigma_{\epsilon}^2 I)$$

- MA-IDM assumes:**

Vector form

$$a^{(t)} = a_{\text{IDM}}^{(t)} + a_{\text{GP}}^{(t)} \Rightarrow a|i, \theta \sim \mathcal{N}(a_{\text{IDM}}, K + \sigma_{\epsilon}^2 I)$$

residuals

where K is a kernel matrix .

[Chengyuan Zhang and Lijun Sun. (2024). Bayesian calibration of the intelligent driver model. *IEEE Transactions on Intelligent Transportation Systems*.]

Memory-Augmented IDM (MA-IDM) (Zhang and Sun 2024)

- IDM assumes:**

$$a^{(t)} = a_{\text{IDM}}^{(t)} + \epsilon_t, \quad \epsilon_t \stackrel{i.i.d.}{\sim} \mathcal{N}(0, \sigma_\epsilon^2) \quad \Rightarrow \mathbf{a} | \mathbf{i}, \boldsymbol{\theta} \sim \mathcal{N}(\mathbf{a}_{\text{IDM}}, \sigma_\epsilon^2 \mathbf{I})$$

Vector form







- MA-IDM assumes:**

$$a^{(t)} = a_{\text{IDM}}^{(t)} + \boxed{a_{\text{GP}}^{(t)}} \quad \Rightarrow \mathbf{a} | \mathbf{i}, \boldsymbol{\theta} \sim \mathcal{N}(\mathbf{a}_{\text{IDM}}, \boxed{\mathbf{K}} + \sigma_\epsilon^2 \mathbf{I})$$

residuals

where \mathbf{K} is a kernel matrix .



- Gaussian processes**



Experiments – Car-Following Data Extraction



- **HighD** dataset:
(Krajewski et al. 2018)
- **20** leader-follower pairs.

<https://levelxdata.com/highd-dataset/>




Experiments – Identified IDM Parameters

Similar posterior distribution shape but **more concentrated**



(a) Hierarchical B-IDM posteriors of truck #211.




(b) Hierarchical MA-IDM posteriors of truck #211.

We can draw samples (IDM parameters) from the posterior distributions!!

Simulations – Deterministic v.s. Stochastic

- **MA-IDM assumes:** $a_d^{(t)} = a_{\text{IDM},d}^{(t)} + a_{\text{GP},d}^{(t)}$
- **Stochastic simulation for step t_0 :**
 - 1) Obtain the first term $a_{\text{IDM},d}^{(t)}$ by feeding θ_d and inputs into the IDM function;
 - 2) Draw a sample $a_{\text{GP},d}^{(t)} | \mathbf{a}_{\text{GP},d}^{(t-T:t-1)}$ at time t from the GP to obtain the temporally correlated information $a_{\text{GP},d}^{(t)}$;

Simulations – Stochastic Simulation (**MA-IDM** v.s. **B-IDM**)




Brief results:


- **Action uncertainty is scenario specific:** When the leading vehicle is braking, all drivers must decelerate; But when the leading vehicle accelerates, actions are more uncertain at their own will.
- **MA-IDM** has a better calibration result than **B-IDM**. Even **B-IDM** is with a large noise variance, it still cannot bridge the **gap** (i.e., with bad uncertainty quantification.)
- But MA-IDM has a much larger variance. **Why?**

What do we miss in the residuals?


Positive correlations
Negative correlations




(a) The Empirical covariance matrix.



(b) The empirical covariance function.



(c) The RBF kernel matrix.



(d) The RBF kernel function.

The length scale is about 1.5 sec → **capture correlations within 4~5 sec**
(3-sigma in Normal distribution).

Dynamic IDM (Zhang et al. 2024)

How to model $\delta(t)$ and $\delta(t+1)|\delta(t)$?

- We assume:**

$$a(x, t) = f_{\text{CFM}}(x; \theta) + \delta(t) + \epsilon, \quad \epsilon \stackrel{i.i.d.}{\sim} \mathcal{N}(0, \sigma_{\epsilon}^2)$$

- Dynamic IDM assumes:**

Autoregressive (AR) processes


$$a_d^{(t)} = \text{IDM}_d^{(t)} + \epsilon_d^{(t)},$$

$$\epsilon_d^{(t)} = \rho_{d,1}\epsilon_d^{(t-1)} + \rho_{d,2}\epsilon_d^{(t-2)} + \cdots + \rho_{d,p}\epsilon_d^{(t-p)} + \eta_d^{(t)},$$


$$\eta_d^{(t)} \stackrel{i.i.d.}{\sim} \mathcal{N}(0, \sigma_{\eta}^2).$$




ADVANTAGE: It involves rich information from **several historical steps** instead of using only one step.




Two random series generated by AR(4)



Experiments – Identified AR Parameters



Positive correlations: up to 5 s
Negative correlations: 5~10 s



(e) The AR(5) covariance matrix.

(f) The AR(5) covariance functions.

$$\rho = [0.874, 0.580, -0.105, -0.315, -0.071]$$

Simulations – Deterministic v.s. Stochastic

How to simulate $\delta(t+1)|\delta(t)$?

- Dynamic IDM:

$$a_d^{(t)} = \text{IDM}_d^{(t)} + \varepsilon_d^{(t)},$$


$$\varepsilon_d^{(t)} = \rho_{d,1}\varepsilon_d^{(t-1)} + \rho_{d,2}\varepsilon_d^{(t-2)} + \dots + \rho_{d,p}\varepsilon_d^{(t-p)} + \eta_d^{(t)},$$

$$\eta_d^{(t)} \stackrel{i.i.d.}{\sim} \mathcal{N}(0, \sigma_\eta^2).$$


- Stochastic simulation for step t_0 :

- generating the mean model by sampling a set of IDM parameters;
- computing the serial correlation term according to the historical information;
- sampling white noise randomly.

Simulations – Stochastic Simulation (Dynamic IDM v.s. MA-IDM)



(a) Truck driver #211.



(b) Car driver #273.


Brief results:

- Dynamic IDM can also obtain accurate parameter estimations;
- Dynamic IDM has much lower variances than MA-IDM;


Simulations – Multi-vehicle scenario: Platoon

OpenACC dataset


<http://data.europa.eu/89h/9702c950-c80f-4d2f-982f-44d06ea0009f>




Simulations – Multi-vehicle scenario: Ring road



(a) Simulation with fixed IDM parameters and random white noise.



(b) Light traffic simulation with dynamic IDM ($p = 4$).



(c) Dense traffic simulation with dynamic IDM ($p = 4$).



Sugiyama experiment

Discussion and takeaway

- ✓ Generate diverse types of drivers. [Bayesian calibration/Hierarchical structure]
 - ✓ Produce good uncertainty for each driver. [GP/AR]
 - ✓ Simulate human-like car-following behaviors. [Stochastic Simulation]
-
- **Importance of probabilistic simulation!**
 - positive correlations (0~5 sec) & negative correlations (5~10 sec)
 - at least 10 sec historical information as input.
 - Provide enough information to calibrate car-following models.
 - IDM is very powerful.

References

- Treiber, M., Hennecke, A., & Helbing, D. (2000). Congested traffic states in empirical observations and microscopic simulations. *Physical Review E*, 62(2), 1805.
- Punzo, V., Zheng, Z., & Montanino, M. (2021). About calibration of car-following dynamics of automated and human-driven vehicles: Methodology, guidelines and codes. *Transportation Research Part C: Emerging Technologies*, 128, 103165.
- Krajewski, R., Bock, J., Kloeker, L., & Eckstein, L. (2018). The highd dataset: A drone dataset of naturalistic vehicle trajectories on german highways for validation of highly automated driving systems. In *2018 21st International Conference on Intelligent Transportation Systems (ITSC)* (pp. 2118-2125). IEEE.
- Anesiadou, A., Makridis, M., Ciuffo, B., & Mattas, K. (2020): Open ACC Database. European Commission, Joint Research Centre (JRC) [Dataset] PID: <http://data.europa.eu/89h/9702c950-c80f-4d2f-982f-44d06ea0009f>
- Treiber, M., Kesting, A., & Helbing, D. (2006). Delays, inaccuracies and anticipation in microscopic traffic models. *Physica A: Statistical Mechanics and its Applications*, 360(1), 71-88.

Read More

➤ Paper:

Zhang, C., & Sun, L. (2024). Bayesian calibration of the intelligent driver model. *IEEE Transactions on Intelligent Transportation Systems*.

Zhang, C., Wang, W., & Sun, L. (2024). Calibrating car-following models via Bayesian dynamic regression. *Transportation Research Part C: Emerging Technologies*, 104719. (ISTTT25 Special Issue).

➤ Code:

https://github.com/Chengyuan-Zhang/IDM_Bayesian_Calibration