

Table 1: Decoder transfer across two forecasting backbones. Each dataset entry is the mean over $H \in \{96, 192, 336, 720\}$. PatchTST-style +ISCF and +ISCF-BSCA use validation-selected, dataset-level decoder profiles shared across all four horizons; the Original Decoder and the complete DLinear-style block reuse the unchanged v1 evidence. Lower is better. Best and second-best results within each backbone are bold and underlined, respectively.

Backbone	Decoder	Weather		ETTM1		ETTM2		ETTh1		ETTh2		Avg.	
		MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE	MSE	MAE
DLinear-style	Original Decoder	0.246	0.274	<u>0.353</u>	<u>0.372</u>	0.311	0.354	0.468	0.465	1.009	0.698	0.478	0.433
	+ISCF	0.229	0.257	0.344	0.370	<u>0.283</u>	<u>0.339</u>	0.460	0.455	<u>0.819</u>	<u>0.611</u>	<u>0.427</u>	<u>0.407</u>
	+ISCF-BSCA	<u>0.232</u>	<u>0.259</u>	0.355	0.376	0.279	0.333	<u>0.465</u>	<u>0.458</u>	0.682	0.562	0.403	0.397
PatchTST-style	Original Decoder	0.229	0.253	0.358	0.375	<u>0.259</u>	0.314	0.394	0.416	0.311	0.361	0.310	0.344
	+ISCF	0.233	0.259	<u>0.354</u>	0.378	0.261	0.315	0.406	0.421	<u>0.318</u>	0.364	0.314	0.347
	+ISCF-BSCA	<u>0.232</u>	<u>0.254</u>	0.351	<u>0.377</u>	0.258	<u>0.315</u>	<u>0.398</u>	<u>0.419</u>	0.319	<u>0.364</u>	<u>0.312</u>	<u>0.346</u>