CS7GV2: Mathematics of Light and Sound

Lecture #7: Intensity

Fergal Shevlin, Ph.D.

School of Computer Science and Statistics,
Trinity College Dublin

November 27, 2020

Intensity

Forces exerted by electric and magnetic fields can move or heat matter and move charges. This means electromagnetic waves have *energy*. (Actually they *transport* energy.)

The energy required to accelerate an object over 1 m distance with 1 N force is,

$$1\,\mathrm{J} = 1\,\mathrm{N\,m} = 1\,\mathrm{kg\,m\,s^{-2}} \cdot 1\,\mathrm{m} = 1\,\mathrm{kg\,m^2\,s^{-2}}.$$

Intensity

EYE ≈ Camera Sensor



Power is energy per unit time, $1\,\mathrm{W} = 1\,\mathrm{J\,s^{-1}}$. Power per unit area, $\mathrm{W\,m^{-2}}$, is energy flux or *intensity*.

Intensity of electromagnetic waves is what what our eyes see; and what is measured by the photo-sensitive elements in cameras.

Photosensitive cells have a surface area and an integration time



Intensity

Electromagnetic wave intensity at a point in space at time t is $\propto$ to the product of field amplitudes,

$$^1/_\mu \|\mathbf{E}(t)\| \, \|\mathbf{B}(t)\|.$$

Average intensity over a wave time period is a more useful quantity,

$$I = \frac{1}{2}\frac{1}{\mu}EB = \frac{E^2}{2\mu c} = \frac{cB^2}{2\mu}$$

where E and B are max. amplitudes.

Intensity

Note that the average of the product of two equal sinusoids is $\propto$ average of $\cos^2$ or $\sin^2$ which is $1/2$.



For simplicity, scaling factors can be ignored and field amplitudes denoted by A to consider avg. intensity $I \propto A^2$.

Intensity

Forces exerted by electric and magnetic fields can move or heat matter and move charges. This means electromagnetic waves have *energy*. (Actually they *transport* energy.)

The energy required to accelerate an object over 1 m distance with 1 N force is,

$$1\,\mathrm{J} = 1\,\mathrm{N\,m} = 1\,\mathrm{kg\,m\,s^{-2}} \cdot 1\,\mathrm{m} = 1\,\mathrm{kg\,m^2\,s^{-2}}.$$

Power is energy per unit time, $1\,\mathrm{W} = 1\,\mathrm{J\,s^{-1}}$. Power per unit area, $\mathrm{W\,m^{-2}}$, is energy flux or *intensity*.

Intensity of electromagnetic waves is what what our eyes see; and what is measured by the photo-sensitive elements in cameras.

Electromagnetic wave intensity at a point in space at time t is $\propto$ to the product of field amplitudes,

$$^1/_\mu \|\mathbf{E}(t)\|\ \|\mathbf{B}(t)\|.$$

Average intensity over a wave time period is a more useful quantity,

$$I = \frac{1}{2}\frac{1}{\mu}EB = \frac{E^2}{2\mu c} = \frac{cB^2}{2\mu}$$

where E and B are max. amplitudes.

Note that the average of the product of two equal sinusoids is $\propto$ average of $\cos^2$ or $\sin^2$ which is ½.



For simplicity, scaling factors can be ignored and field amplitudes denoted by A to consider avg. intensity $I \propto A^2$.

Intensity PDF

$f_A(a)$ for amplitude A of a random phasor sum was found to follow a Rayleigh distribution. The *derived* PDF for intensity $I = A^2$ is,

$$f_I(i) = f_A(\sqrt{i}) \left| \frac{\mathrm{d}\sqrt{i}}{\mathrm{d}i} \right| = f_A(\sqrt{i}) \, \frac{1}{2\sqrt{i}}$$

$$\text{since } \frac{\mathrm{d}i^{\frac{1}{2}}}{\mathrm{d}i} = \frac{1}{2} \, i^{\frac{-1}{2}} = \frac{1}{2} \, \frac{1}{\sqrt{i}} = \frac{1}{2\sqrt{i}}.$$

Intensity PDF

$$f_A(a) = \exp\left\{-\frac{a^2}{2\sigma_A^2}\right\}\frac{a}{\sigma_A^2}.$$

$$f_I(i) = \exp\left\{-\frac{i}{2\sigma_A^2}\right\}\frac{\sqrt{i}}{\sigma_A^2}\frac{1}{2\sqrt{i}}$$

$$= \exp\left\{-\frac{i}{2\sigma_A^2}\right\}\frac{1}{2\sigma_A^2}.$$

So intensity PDF follows an *exponential* distribution, i.e. $f_X(x) = \lambda\, \mathrm{e}^{-\lambda\, x}$.

Intensity PDF



Intensity PDF

Mean intensity $\overline{I}$ can be found as $2\sigma_A^2$ so the PDF can be written,

$$f_I(i) = \exp\left\{-\frac{i}{\overline{I}}\right\}\frac{1}{\overline{I}}.$$

$$\text{Variance } \sigma_I^2 = \overline{I}^{\,2}, \quad \text{Std. dev. } \sigma_I = \overline{I}\,,$$

$$\text{Contrast } C = \sigma_I/\overline{I} = 1.0,$$

$$\text{S/N ratio } = 1/C = \overline{I}\,/\sigma_I = 1.0.$$

Intensity PDF

$f_A(a)$ for amplitude A of a random phasor sum was found to follow a Rayleigh distribution. The *derived* PDF for intensity $I = A^2$ is,

$$f_I(i) = f_A(\sqrt{i}) \left| \frac{\mathrm{d}\sqrt{i}}{\mathrm{d}i} \right| = f_A(\sqrt{i}) \, \frac{1}{2\sqrt{i}}$$

$$\text{since} \quad \frac{\mathrm{d}i^{\frac{1}{2}}}{\mathrm{d}i} = \frac{1}{2}\, i^{\frac{-1}{2}} = \frac{1}{2}\,\frac{1}{\sqrt{i}} = \frac{1}{2\sqrt{i}}.$$

$$f_A(a) = \exp\left\{ -\frac{a^2}{2\sigma_A^2} \right\} \frac{a}{\sigma_A^2}.$$

$$f_I(i) = \exp\left\{ -\frac{i}{2\sigma_A^2} \right\} \frac{\sqrt{i}}{\sigma_A^2} \, \frac{1}{2\sqrt{i}}$$

$$= \exp\left\{ -\frac{i}{2\sigma_A^2} \right\} \frac{1}{2\sigma_A^2}.$$

So intensity PDF follows an *exponential* distribution, i.e. $f_X(x) = \lambda \, \mathrm{e}^{-\lambda x}$.



Mean intensity $\overline{I}$ can be found as $2\sigma_A^2$ so the PDF can be written,

$$f_I(i) = \exp\left\{ -\frac{i}{\overline{I}} \right\} \frac{1}{\overline{I}}.$$

$$\text{Variance } \sigma_I^2 = \overline{I}^{\,2}, \quad \text{Std. dev. } \sigma_I = \overline{I}\,,$$

$$\text{Contrast } C = \sigma_I / \overline{I} = 1.0,$$

$$\text{S/N ratio } = 1/C = \overline{I} / \sigma_I = 1.0.$$

Histogram of simulated intensities

arising from 19,200 random phasor sum amplitudes

~ frequency



intensity

Camera pixel "brightness"

19,200 intensity values chosen randomly in accordance with an exponential PDF with $\overline{I} = 1.0$ and $\sigma_I = 1.0$. These could be many observations over time at a single point in space or many observations over space at a single point in time.

Image of simulated intensities

intensity range

$0 \rightarrow 10$

intensity due to a $\boxed{\text{RPS}}$ at a camera sensor pixel

intensity 10



0.2

intensity 0

Simulated

The same* intensity values i arranged as a 160×120 pixel image.
Contrast $C = \sigma_I / \overline{I} = 1.0$.

Image of actual intensities

Actual data



Material with diffuse reflectance characteristics illuminated evenly with monochromatic light with *no phase or amplitude change* during the observation time period. $C \approx 0.83$.

λ

λ_1

λ_2

$\vdots$

λ_n

20



Averages of simulated intensity images



$N = 16$, $C \approx 0.251 = 1/\sqrt{N}$.

Averages of simulated intensity images



$N = 64$. $C \approx 0.125 = 1/\sqrt{N}$.

Averages of simulated intensity images



$N = 256$. $C \approx 0.061 = 1/\sqrt{N}$.

Averages of simulated intensity images



$N = 256$. $C \approx 0.031 = 1/\sqrt{N}$.

Averages of simulated intensity images



$N = 16.\ C \approx 0.251 = 1/\sqrt{N}.$



$N = 64.\ C \approx 0.125 = 1/\sqrt{N}.$



$N = 256.\ C \approx 0.061 = 1/\sqrt{N}.$



$N = \cancel{256}.\ C \approx 0.031 = 1/\sqrt{N}.$

Averages of simulated intensity images



$N = 4,096$. $C \approx 0.015 = 1/\sqrt{N}$.

Averages of simulated intensity images



$N = 16,384$. $C \approx 0.007 = 1/\sqrt{N}$.

Averages of simulated intensity images



$N = 65,536$. $C \approx 0.003 = 1/\sqrt{N}$.

Averages of simulated intensity images

These simulations show, that with appropriate variation of phase and amplitude over a time period, variation of intensity can reduce* from $C = 1$ to $C = 1/\sqrt{N}$ where N is the number of intensities observed.

Averages of simulated intensity images



$N = 4,096$. $C \approx 0.015 = 1/\sqrt{N}$.



$N = 16,384$. $C \approx 0.007 = 1/\sqrt{N}$.



$N = 65,536$. $C \approx 0.003 = 1/\sqrt{N}$.

These simulations show, that with appropriate variation of phase and amplitude over a time period, variation of intensity can reduce* from $C = 1$ to $C = 1/\sqrt{N}$ where N is the number of intensities observed.