

## Cpt S 515 Homework #2

No late homework!

1. In Lesson 3, we talked about the Tarjan algorithm (SCC algorithm). Now, you are required to find an efficient algorithm to solve the following problem. Let  $G$  be a directed graph where every node is labeled with a color. Many nodes can share the same color. Let  $v_1, v_2, v_3$  be three distinct nodes of the graph (while the graph may have many other nodes besides the three). I want to know whether the following items are all true: there is a walk  $\alpha$  from  $v_1$  to  $v_2$  and a walk  $\beta$  from  $v_1$  to  $v_3$  such that

- $\alpha$  is longer than  $\beta$ ;
- $\alpha$  contains only red nodes (excluding the two end nodes);
- $\beta$  contains only green nodes (excluding the two end nodes).

2. In Lesson 4, we learned network flow. In the problem, capacities on a graph are given constants (which are the algorithm's input, along with the graph itself). Now, suppose that we are interested in two edges  $e_1$  and  $e_2$  whose capacities  $c_1$  and  $c_2$  are not given but we only know these two variables are nonnegative and satisfying  $c_1 + c_2 < K$  where  $K$  is a given positive number (so the  $K$  is part of the algorithm's input). Under this setting, can you think of an efficient algorithm to solve network flow problem? This is a difficult problem.

3. There are a lot of interesting problems concerning graph traversal — noticing that a program in an abstract form can be understood as a directed graph. Let  $G$  be a SCC, where  $v_0$  is a designated initial node. In particular, each node in  $G$  is labeled with a color. I have the following property that I would like to know whether the graph satisfies:

For each infinitely long path  $\alpha$  starting from  $v_0$ ,  $\alpha$  passes a red node from which, there is an infinitely long path that passes a green node and after this green node, does not pass a yellow node.

Please design an algorithm to check whether  $G$  satisfies the property.

4. Path counting forms a class of graph problems. Let  $G$  be a DAG where  $v$  and  $v'$  be two designated nodes. Again, each node is labeled with a color.

(1). Design an algorithm to obtain the number of paths from  $v$  to  $v'$  in  $G$ .

(2). A good path is one where the number of green nodes is greater than the number of yellow nodes. Design an algorithm to obtain the number of good paths from  $v$  to  $v'$  in  $G$ .