EQ2330 – Image and Video Processing

Project 1: Image Enhancement

Students should submit their project reports electronically. Please email your document in PDF format to the course assistant assigned to this project with the subject line "EQ2330 - Project". Your email should also include relevant Matlab source code. You can alternatively submit the project through Canvas. There is a template for the report available at EQ2330 webpage. It also contains some instructions you are expected to follow.

1 Introduction

The goal of this project is to investigate spatial and frequency domain image enhancement techniques. Completion of all tasks in the project description is required to pass the project. Use the "Lena" image 512×512 to demonstrate your results in the report.

2 Spatial domain processing

2.1 Histogram equalization

This task is about the global histogram equalization.

• Plot the histogram (with 8 bits resolution) of the input image using the hist command.

Hint: use im(:) to create an one dimensional vector.

• Simulate a low-contrast image by reducing the dynamic range of the image, e.g.:

$$q(x, y) = \min(\max(|a \cdot f(x, y) + b|, 0), 255),$$

where $\lfloor \cdot \rfloor$ denotes the round operator, 0 < a < 1, 0 < b < 255(1 - a). Use a = 0.2, b = 50. Plot the histogram again and comment on the difference.

Hint: To view the image of lower constrast, you may need to specify the interval for imagesc, e.g., imagesc(im, [0 255]);

- Implement the histogram equalization algorithm from section 3.3.1 in [1]. Apply your algorithm to the contrast-reduced image. Plot the histogram of the enhanced image. *Hint:* Use cumsum to calculate CMF.
- Question: Why is the histogram not flat after the equalization?

2.2 Image denoising

This task is to investigate the denoising effect of spatial smoothing filters and order-statistics filters.

• Use the provided mynoisegen(·) to generate Gaussian (zero-mean and variance 64) and salt & pepper noises (p(0) = p(255) = .05), and apply the noises to the input image. The two noise types should be investigated separately. The Gaussian noise is additive, and for the salt & pepper noise, use

```
im_saltp = im;
n = mynoisegen(saltpepper, 512, 512, .05, .05);
im_saltp(n==0) = 0;
im_saltp(n==1) = 255;
```

Use help mynoisegen for more information. Plot the histograms of the noisy images and compare to the clean image.

• Implement the 3×3 mean filter and apply to the noisy images. Plot and compare the histograms.

Hint: Use the matlab function conv2(·).

- Implement the 3×3 median filter and apply to the noisy image. Again, plot and compare the histograms. Note that conv2(·) cannot be used here anymore.
- Question: Explain the difference between the mean filter and the median filter and their denoising effects on different noise types.

3 Frequency domain filtering

The last task is to investigate the frequency domain filtering. The frequency domain filtering is particularly interesting for the deblurring application, since the convolution corresponds to the multiplication in the frequency domain. The goal of this task is, therefore, to implement a deblurring algorithm which is capable of restoring an out-of-focus image. Before you start working on the task, you should read section 4.6.3 in [1](also [2]) for some common pitfalls in the implementation of the frequency domain filtering.

• The blurred image can be generated using the degradation model

$$q(x, y) = h(x, y) * f(x, y) + \eta(x, y),$$

where the notation and more detailed explanation can be found on page 221 in [1] (and 312 in [2]). The noise term $\eta(x, y)$ is considered to be the quantization noise

introduced by representing (quantizing) the out-of-focus image using the 8-bit resolution,

$$g(x,y) = \min(\max(|h(x,y) * f(x,y)], 0), 255).$$

Plot and compare the Fourier spectra of the image before and after the degradation. *Hint:* The provided h = myblurgen('gaussian', r) can be used to generate h(x, y). For the report, use the Gaussian blur kernel with radius r = 8. The blurred image should be generated using conv2(im, h, same) to ensure that the size of the image preserves.

- Use fftshift(·) to center the spectra. To be specific, the Fourier spectra means the log of the amplitude of the 2-dimensional FFT of the image.
- Design an image deblurring algorithm to enhance the distorted image. The function should take the degraded image g(x,y), the blur function h(x,y) and the noise variance $Var(\eta)$ as the input parameters. Be prepared to demonstrate your function using other input images.

Hint: The enhancement algorithm may assume that the variance of the noise is known, but not the actual realization of the noise (or its spectrum). The noise variance can be evaluated using the difference image between the out-of-focus image and the quantized image.

Hint: Two useful algorithms are described in section 5.8-5.9 in [1] [2]

Hint&question Be careful with the implied periodicity of the DFT, which may cause problems when the input image has sharp edges on the boundaries. Your algorithm may not work if this is not properly treated. Explain why?

Hint Two out-of-focus images are provided for testing purposes. The images are generated using the Gaussian kernel with r = 8, and the noise variance is 0.0833.

References

- [1] R. C. Gonzales and R.E. Woods, *Digital Image Processing*, Prentice Hall, Upper Saddle River, New Jersey, second edition, 2002.
- [2] R. C. Gonzales and R.E. Woods, *Digital Image Processing*, Prentice Hall, Upper Saddle River, New Jersey, third edition, 2008.